



Stormwater Management Study



Northern Pass Transmission, LLC

Transition Station #5

Project No. 58466

RE-ISSUED FOR PERMITTING

January 20, 2017

Stormwater Management Study

prepared for

Northern Pass Transmission, LLC

**Transition Station #5
Main Street, Bethlehem, NH 03574**

Project No. 58466

**RE-ISSUED FOR PERMITTING
January 20, 2017**

prepared by

Burns & McDonnell Engineering Company, Inc.



INDEX AND CERTIFICATION

**Northern Pass Transmission, LLC
Stormwater Management Study
Transition Station #5 – Project No. 58466
RE-ISSUED FOR PERMITTING – January 20, 2017**

Report Index

<u>Section Number</u>	<u>Section Title</u>	<u>Number of Pages</u>
1.0	Project Overview	6
2.0	Hydrology & Hydraulics	7
3.0	Best Management Practices	2
4.0	Conclusion	1
Appendix A	Pre- and Post-Development Watershed Maps	
Appendix B	Hydrology Model (Pondpack)	
Appendix C	Hydraulic and Stability Calculations	
Appendix D	NH DES Worksheets	
Appendix E	Operations and Maintenance Plan	
Appendix J	Pollutant Loading Calculations	

Certification

I hereby certify, as a Professional Engineer in the State of New Hampshire, that the information in this document was assembled under my direct personal charge. This report is not intended or represented to be suitable for reuse by the Northern Pass Transmission, LLC or others without specific verification or adaptation by the Engineer.

Robbyn Reed, P.E.

Date

Additional reference information provided by others and not certified by the above sealing Engineer.

<u>Section Number</u>	<u>Section Title</u>
Appendix F	FEMA Flood Insurance Rate Map
Appendix G	Soil Survey Reports (By Others)
Appendix H	Geotechnical Report (By Others)
Appendix I	Wetlands Delineation Report (By Others)

TABLE OF CONTENTS

	<u>Page No.</u>
1.0 PROJECT OVERVIEW	1-1
1.1 Location and Project Summary.....	1-1
1.2 Existing Conditions Survey Information	1-3
1.3 Geotechnical Investigations	1-3
1.4 Soils.....	1-3
1.5 Wetlands, Rivers, Streams and Vernal Pools.....	1-5
1.6 Floodplain	1-5
1.7 Receiving Surface Waters.....	1-5
1.8 Pre-Development Site Conditions.....	1-5
1.9 Post-Development Site Conditions	1-6
 2.0 HYDROLOGY AND HYDRAULICS	 2-1
2.1 Methodology and Design Criteria.....	2-1
2.1.1 Rainfall Data	2-1
2.1.2 Runoff Data.....	2-1
2.2 Stormwater Modeling Results.....	2-3
2.3 Detention Basin Design	2-4
2.4 Sand Filter	2-4
2.5 Basin Spillway	2-6
2.6 Storm Drainage System	2-6
2.7 Outlet Protection	2-7
 3.0 BEST MANAGEMENT PRACTICES	 3-1
3.1 Groundwater Recharge Volume & Water Quality Volume.....	3-1
3.2 Temporary Erosion Controls.....	3-1
3.3 Permanent Erosion Controls	3-1
3.3.1 Crushed Rock/Paving.....	3-1
3.3.2 Seeding.....	3-1
3.3.3 Outlet Protection	3-2
3.3.4 Flood Protection Analysis.....	3-2
3.4 Antidegradation.....	3-2
 4.0 CONCLUSION	 4-1
 APPENDIX A – PRE- AND POST-DEVELOPMENT WATERSHED MAPS	
APPENDIX B – HYDROLOGY MODEL (PONDPACK)	
APPENDIX C – HYDRAULIC AND STABILITY CALCULATIONS	
APPENDIX D – NH DES WORKSHEETS	
APPENDIX E – OPERATIONS AND MAINTENANCE PLAN	
APPENDIX F – FEMA FLOOD INSURANCE RATE MAP	
APPENDIX G – SOIL SURVEY REPORTS (BY OTHERS)	

APPENDIX H – GEOTECHNICAL REPORT (BY OTHERS)
APPENDIX I – WETLAND DELINEATION REPORT (BY OTHERS)
APPENDIX J – POLLUTANT LOADING CALCULATIONS

LIST OF TABLES

	<u>Page No.</u>
Table 1-1A: Soil Types.....	1-4
Table 1-2B: Soil Types.....	1-5
Table 2-1: 24-Hour Type II Rainfall Data	2-1
Table 2-2: Standard SCS Runoff Curve Numbers.....	2-2
Table 2-3: Pre-Developed Model Data	2-2
Table 2-4: Post-Developed Model Data	2-2
Table 2-5: Manning's Roughness Coefficients	2-2
Table 2-6: Outlet Flow.....	2-3
Table 2-7: Detention Basin Storage Volume	2-4
Table 2-8: Detention Basin Water Surface Elevation.....	2-4
Table 2-9: Underground Sand Filter Storage Volume Within Filter Media.....	2-5
Table 2-10: Underground Sand Filter Storage Volume Above Filter Media	2-5
Table 2-11: Underground Sand Filter Storage Volume In Sediment Chamber.....	2-6
Table 2-12: Underground Sand Filter Water Surface Elevation.....	2-6
Table 2-13: Basin Spillway Summary & Stability	2-6
Table 2-14: Storm Drains.....	2-7
Table 2-15: Outlet Protection	2-7

LIST OF FIGURES

	<u>Page No.</u>
Figure 1-1: USGS Site Location Map	1-2

LIST OF ABBREVIATIONS

<u>Abbreviation</u>	<u>Term/Phrase/Name</u>
BMcD	Burns & McDonnell
BMP	Best Management Practice
CFS	Cubic Feet per Second
E&S	Erosion and Sedimentation Control
FPS	Feet per Second
FT	Feet
LF	Linear Feet
LiDAR	Light Detection and Ranging
NAD	North American Datum
NAVD	North American Vertical Datum
NH DES	New Hampshire Department of Environmental Services
ORW	Outstanding Resource Water
ROW	Right-of-way
TN	Total Nitrogen
TP	Total Phosphorus
TSS	Total Suspended Solids
WQF	Water Quality Flow
WQV	Water Quality Volume

1.0 PROJECT OVERVIEW

1.1 Location and Project Summary

Northern Pass Transmission, LLC (NPT) plans to construct Transition Station #5 (Project), a new transition station located on Eversource owned property at 1071 Main Street (US Highway 302) (N44°16'57.0" latitude and -W71°43'31.5" longitude) in the town of Bethlehem, Grafton County, NH (Site). The site is also known as parcel LL#3140, Bethlehem, NH. Refer to Figure 1-1: USGS Site Location Map.

The Site is bounded by an abandoned motel to the east, shrub and wooded land to the north and west, an existing power line right of way to the west and US Highway 302 to the south. The Site is located within the surface watershed of Bakers Brook, a tributary to the Upper Connecticut River.


Pre-development conditions primarily consist of a developed residential lot with a residential structure and a shed located on site. Stormwater runoff in existing conditions generally sheet flows overland from south to north to wetlands located on the northern half of the site.

The post-development conditions of the Site include construction of a transition station associated with the Northern Pass Transmission (NPT) project. The NPT project is an approximately 200-mile AC and DC transmission line route extending from the United States/Canadian border in Pittsburg, NH to Deerfield, NH. The station development consists of a gravel pad approximately 86-ft by 135-ft with a perimeter fence and access gates. A gravel access drive and turnaround area is also proposed. The post-development conditions will increase the peak stormwater runoff rate and as a result, stormwater attenuation systems will be implemented. Wherever possible, the pre-development drainage and grading patterns were maintained in the post-development conditions.

A hydrologic model was developed to evaluate the pre- and post-development drainage conditions on the Site for the 2-, 10-, and 50-year design frequency storm events. The results of the analysis indicate that there is an increase in peak discharge rates in post-development conditions from pre-development conditions. The analyses summary, results, and model output are located in further sections.

The Project Site property area is 0.93 acres. The Project will result in approximately 0.88-acres of disturbance of which 0.84-acres is on-site and 0.04-acres off-site in roadways. The pre-development impervious cover within the watershed is 0.269 acres and the post-development impervious cover within the watershed is 0.244 acres, therefore, the decrease in impervious cover is 0.025 acres.

Figure 1-1: USGS Site Location Map



1.2 Existing Conditions Survey Information

An Existing Conditions Plan with topography was prepared for the Project and was used as a base throughout the analysis and design of the Site Development Plans and Stormwater Management Study. In the instance where the watershed areas extended outside the survey topography limits, State published LiDAR was obtained from the New Hampshire GRANIT Statewide GIS Clearinghouse and used to determine the watershed limits.

Horizontal Datum: The survey references the New Hampshire State Plane Coordinate System, NAD 83. The Site Development Plans are drawn in the same state plane coordinate system.

Vertical Datum: North American Vertical Datum of 1988 (NAVD88). The proposed elevations referenced within the Site Development Plans refer to the same vertical datum.

1.3 Geotechnical Investigations

A Geotechnical Engineering Report has been prepared for NPT.

- “Geotechnical Engineering Report, Transition Station #5 Project, Northern Pass Transmission Line, Bethlehem, New Hampshire” by Quanta Subsurface.

The geotechnical investigation report can be found in Appendix H.

1.4 Soils

National Resource Conservation Service (NRCS) Web Soil Survey describes the soil at the Project Site as Waumbek loamy sand as well as Monadnock and Hermon soils. The soils on the site were classified as hydrologic soil group B. Four soil types are present on and in the vicinity of the Project Site according to the US Department of Agriculture Soil Conservation Service Soil Survey for Grafton County, New Hampshire. The NRCS Web Soil Survey information is located in Appendix G.

There is also a soil survey report for the site entitled “Northern Pass Transmission Project, Site-Specific Soil Survey Report for the Bethlehem Transition Station (T5A)” by Normandeau Environmental Consultants, dated August 14, 2015, that describes three types of soils that are present at the Project Site.

Peacham and Ossipee soils, and Telos units mapped on-site were derived from glacio-fluvial deposits. Peacham and Ossipee mucky peat is very poorly drained soil and was found north of the Udorthent unit that makes up the area around the house. Telos was found north of the Peacham map unit in the northwest corner of the parcel.

A majority of the lawn area of the parcel as well as the associated driveway were mapped as a sandy Udorthent in a moderately well to well drained condition. A fill layer measuring up to 19 inches over native soil was observed on the west side of the house. On the east side, it appears that some of the native soil was removed and/or reworked. Depths of fill were shallower on the east side, measuring 16 inches at the maximum depth observed. The soil adjacent and north of the house, also mapped as a Udorthent, smoothed, consisted of excavated soil resulting from the house construction.

Beyond the northern edge of the Udorthent Map Unit, there is a steep topographic drop of approximately 2 to 4 feet. At the base of the drop is a Peacham and Ossipee Soils Map Unit that was observed in the wetland in this location. These soils are both organic in nature, very poorly drained, and rated as hydric. Organic matter up to 18 inches was observed in this map unit. The rise in topography along the northern boundary of the parcel contains Telos soils in a somewhat poorly drained condition.

The hydrologic soil group classifications vary and are listed below in Table 1-1B. The soil survey report is located in Appendix G.

Table 1-1A: Soil Types

Map Legend	Soil Type Per NRCS Web Soil Survey	Hydrologic Soil Group
255B	Monodnock and Hermon soils, 3 to 8 percent slopes, very stoney	B
59B	Waumbek loamy sand, 3 to 8 percent slopes, very stoney	B
255E	Monadnock and Hermon soils, 25 to 35 percent slopes, very stoney	B

Table 1-2B: Soil Types

Map Legend	Soil Type Per Normandeau Soil Survey Report	Hydrologic Soil Group
123B	Telos silt loam, 3-8 percent slopes	C
299B/dbcde*	Udorthents, smoothed, 3-8 percent slopes	A/B
299C/dbcde*	Udorthents, smoothed, 8-15 percent slopes	C/A/D
731A	Peacham and Ossipee mucky peat, 0-3 percent slopes	D

* d-drainage class: estimated to be moderately well drained (or drier); b-parent material: glacial-fluvial deposits; c- restrictive/impervious layer: mineral restrictive layer present in the soil profile less than 40 inches; d-estimated ksat: not determined; e-hydrologic group: not determined (likely A/B)

The soils series 299B, 299C and 731A have an erosion factor K that is not rated and soil series 123B has a K-Factor of 0.28. The erosion factor K, with values ranging from 0.02 to 0.69, signifies how susceptible a soil is to erosion. The larger the K value the more susceptible the soil is to erosion by water. The K factor for the Project site indicates that the soils have a moderate susceptibility to erosion by water.

1.5 Wetlands, Rivers, Streams and Vernal Pools

A report entitled “Wetlands, Rivers, Streams and Vernal Pools Resource Report and Impact Analysis” by Normandeau Environmental Consultants, dated October 1, 2015 has been prepared for the NPT Project. Environmentally sensitive areas were found within the Project Site. Refer to Appendix I for a copy of this report.

1.6 Floodplain

According to the Federal Emergency Management Agency (FEMA) Flood Insurance Rate Map (FIRM) Map No.33009C0136E for Grafton County, New Hampshire, Effective Date February 20, 2008, the Project Site is located within Zone X, an area determined to be outside the 0.2% annual chance floodplain. The FIRM Map is located in Appendix F.

1.7 Receiving Surface Waters

The Site is within the Upper Connecticut River Watershed, located east of the Baker Brook Tributary.

1.8 Pre-Development Site Conditions

The Pre-Developed site consists of a developed residential lot with a residential structure and accessory shed. There is a lightly wooded area located along the western side of the property, shrub cover near the

center and east side of the property and wetlands present on the north side of the property. The discharge point is located at the northwest corner of the site where the sheet flow begins to collect; however, channelized flow does not begin until beyond the property limits.

1.9 Post-Development Site Conditions

Pre-developed stormwater drainage patterns are mimicked in post-developed conditions and utilize the same aforementioned Site discharge point as pre-development; however, a point discharge will be utilized to drain a proposed basin, which will be outfitted with outlet protection to minimize any erosion or scouring. Pre- and Post-development watershed maps are located in Appendix B. The post-development peak stormwater discharge rates are the same or below pre-development rates.

No new water or septic/sanitary sewer services are required for the Project.

No proposed improvements are located within a FEMA 100-year flood plain as a result, there are no adverse impacts to properties as a result.

* * * * *

2.0 HYDROLOGY AND HYDRAULICS

The stormwater management for the Project has been developed to minimize the downstream effects of development at the Site. The stormwater requirements set forth by the New Hampshire Department of Environmental Services Stormwater Manual Volumes 1, 2, & 3, dated December 2008 and the New Hampshire Department of Transportation Manual on Design for Highways, Revision Date April 1998 were followed to the maximum extent practical for the design of the Site Development Plans and this Report.

The development of the Site results in the need to attenuate stormwater onsite. One above-ground detention basin is proposed and discussed in further detail below. The following is the data used in the stormwater management analysis.

2.1 Methodology and Design Criteria

2.1.1 Rainfall Data

Type II 24-hour rainfall depths for the site location were obtained from the Northeast Regional Climate Center – <http://precip.eas.cornell.edu/>.

Table 2-1: 24-Hour Type II Rainfall Data

Return Frequency (yr)	24 Hour Depth (in)
2	2.35
10	3.37
50	4.84

2.1.2 Runoff Data

The stormwater runoff calculations were completed using the USDA NRCS/SCS TR-55 runoff curve number method in Bentley's PondPack V8i modeling software. Refer to Appendix B for the inputs and generated outputs. The input values that were used in the PondPack model are shown in the tables below.

Maximum sheet flow length for unpaved areas according to the NH DES Stormwater Manual is 100-ft. Below are the standard SCS runoff curve numbers used in the hydrology modeling and the pre-development and post-development watershed cover data used in the hydrology modeling.

Table 2-2: Standard SCS Runoff Curve Numbers

Land Type	Hydrologic Soil Group	Curve Number
Woods	B	55
Woods	C	70
Woods	D	77
Meadow	B	58
Meadow	C	71
Meadow	D	78
Gravel	B	85
Gravel	D	91
Dirt Roads	B	82
Impervious (Asphalt Pavement, Water, Structures, Foundations)	-	98

Table 2-3: Pre-Developed Model Data

Subarea	Area (ac)	Curve Number	Time of Concentration (Minutes)
1	1.233	72	16.26

Table 2-4: Post-Developed Model Data

Subarea	Area (ac)	Composite Curve Number	Time of Concentration (Minutes)
1	0.679	85	12.06
2	0.554	80	16.08
Total	1.233	-	-

The below table summarizes the Manning's roughness coefficients used in the analysis.

Table 2-5: Manning's Roughness Coefficients

Surface Description	Manning's n
Grass, Dense grasses (sheet)	0.240
Woods, Dense underbrush (sheet)	0.800
Smooth Surface Gravel/Pavement (sheet)	0.100
Woods, Light underbrush (sheet)	0.400
Riprap (D50 = 6") lined channel	0.069
Concrete/RCP	0.013
PVC	0.010
HDPE	0.012
Earth-Straight Channel	0.030
Grass w/ NAG Stabilization	0.045

2.2 Stormwater Modeling Results

For the proposed Project, a new detention basin is proposed to be constructed on the site, located at the north side of the property behind the proposed retaining wall. Runoff from the substation yard and turn around area (Drainage Area: Post 1) will flow southwest to northeast and be collected into a deep sump inlet fitted with a diversion weir located in the northeast corner of the turnaround area. The water quality volume will be conveyed into an underground sand filter and all greater storms will be diverted through drainage line P1 to the detention basin. The detention basin will discharge to a flared end section and riprap outlet protection pad located near the northwest corner of the property. The detention basin includes a concrete outlet control structure to control the runoff rate from the basin and an emergency spillway to manage storm events larger than the 100 year storm event.

The proposed basin was analyzed to mitigate the impacts of stormwater runoff from changes in drainage patterns that would result from the construction of this project. The hydrology model was analyzed assuming no infiltration. The concrete outlet control structure will control the rate of runoff to below the pre-development runoff as shown by the modeling results. The following tables summarize flow conditions for the Project and the reduction of flow achieved by the basin.

There is one analysis point for the site located at Outlet-1 as shown on the Pre-development Watershed Map. The table below summarizes the pre- and post-developed peak discharge runoff rates at the analysis point. Refer to Appendix A for the Pre-Developed and Post-Developed Watershed Maps. Modeling results and output can be found in Appendix B.

Table 2-6: Outlet Flow

Return Frequency (yr)	Pre-Developed Flow (cfs)	Post-Developed Flow (cfs)
2	0.54	0.53
10	2.00	1.32
50	3.73	2.87

2.3 Detention Basin Design

The detention basin, Basin 'DB-1', was designed and analyzed to provide long term stormwater attenuation once the Project has been constructed. The basin has been designed to meet the requirements in the NH DES Stormwater Manual. The detention basin contains storm events up to and including the 50-year design storm with a minimum 1-ft freeboard to the emergency spillway crest elevation. The detention basin has been designed as to not require a State Dam permit. The below tables summarize the detention basin storage volumes and water surface elevations with respect to the design storm events.

Table 2-7: Detention Basin Storage Volume

Elevation (feet-NAVD88)	Surface Area (ac)	Cumulative Storage Volume (Acre-ft)
1,07600	0.019	--
1,077.00	0.025	0.022
1,078.00	0.039	0.054
1,079.00	0.047	0.097
1,080.00	0.057	0.149

Table 2-8: Detention Basin Water Surface Elevation

Return Frequency (yr)	Maximum Water Surface Elevation (ft)
2	1,077.40
10	1,077.79
50	1,078.40

2.4 Sand Filter

An Underground Sand Filter was designed and analyzed to provide long term water quality treatment once the Project has been constructed. To treat the Water Quality event (1 inch rainfall event) an Underground Sand Filter (SF-1) will be constructed in the northeast corner of the gravel access area. The facility will treat impervious surfaces located within post-development drainage area Post-1. The total impervious areas comprised of concrete footings, pads, control building and concrete driveway is 2,159 square feet (0.05 acres). Based on the limited impervious area, the Water Quality Volume (WQV) for this project has been calculated to be 287 cubic feet with a water quality flow (WQF) of 0.065 cubic feet per second.

Stormwater collected from the transition station yard through a deep sump catch basin (CB1) will enter a diversion manhole (MH1) where the Water Quality Flow will be conveyed to the sand filter's pre-

treatment sedimentation chamber through a 2-inch PVC pipe. Greater storms will be allowed to bypass the sand filter through a pipe in the diversion manhole (MH1) set at an invert 6-inches above the 2 inch PVC and be conveyed to the detention basin. The pretreatment sedimentation chamber was sized to contain greater than 25% of the WQV. In the pre-treatment chamber sediment will be given time to settle out before the water continues to the filter chamber through a submerged weir. The filter chamber has been designed to provide a 24-inch thick sand filter layer with 6-inch underdrains located 6 inches below the sand layer and set in a 1- to 2-inch diameter drainage stone layer 12-inches thick. The filter media will be covered with a 3 inch thick gravel debris screen above the sand. The stormwater will enter the filter chamber and flow through the filter media layer. This flow will be collected by the underdrains which will convey the flow to the overflow chamber. The filter chamber was sized to contain 75% of the WQV, with a portion of this volume located within the filter media layer and the rest above but below an overflow weir. The overflow weir has been designed to pass the 10-year storm and is set above the WQV between the filter chamber and the overflow chamber. A maximum ponding depth of 4.5 feet will be maintained in the sedimentation and filter chambers. The Underground Sand Filter was designed to have a maximum drain time of less than 72 hours. The stormwater which enters the overflow chamber will be conveyed into drainage piping to the detention basin DB-1. The tables below summarize the Underground Sand Filter storage and water surface elevations with respect to the Water Quality and 10-year design storm events.

Table 2-9: Underground Sand Filter Storage Volume Within Filter Media

Elevation (feet-NAVD88)	Surface Area (SF)	Cumulative Storage Volume (cf)
1086.65	84.50	-
1087.00	84.50	11.83
1088.00	84.50	45.63
1089.00	84.50	79.43
1089.90	84.50	109.85

Table 2-10: Underground Sand Filter Storage Volume Above Filter Media

Elevation (feet-NAVD88)	Surface Area (SF)	Cumulative Storage Volume (cf)
1089.90	84.50	-
1090.00	84.50	8.45
1091.00	84.50	92.95
1091.15	84.50	105.63

Table 2-11: Underground Sand Filter Storage Volume In Sediment Chamber

Elevation (feet-NAVD88)	Surface Area (SF)	Cumulative Storage Volume (cf)
1086.65	65.00	-
1087.00	65.00	22.75
1088.00	65.00	87.75
1088.65	65.00	130.00
1089.00	52.00	150.43
1090.00	52.00	202.43
1091.00	52.00	254.43
1091.15	52.00	262.23

Table 2-12: Underground Sand Filter Water Surface Elevation

Return Frequency (yr)	Maximum Water Surface Elevation (ft)
WQ Event	1,091.15
10	1,091.75

2.5 Basin Spillway

The detention basin is designed to contain the 100-year storm event without overtopping; the spillway is designed to provide for emergency flow for events higher than the 100-year storm. The spillway was modeled as weir flow using Bentley FlowMaster V8i. The basin spillway will be lined with 12" riprap as specified in the Site Development Plans and the calculation results show the spillway will be stable for storms up to the 100-year flow.

Table 2-13: Basin Spillway Summary & Stability

100 Year Max. Flow (cfs)	100 Year Velocity (ft/s)	Spillway (weir) Width (ft)	Side Slopes (H:V ft)	Downstream Slope (%)	Allowable Shear Stress (psf)	Calculated Shear Stress*
1.75	1.34	5.0	3:1	50	4.8	3.43

*Allowable shear Stress are taken from table 2.3 of FHA HEC 15, Third Edition

Refer to Appendix C for the spillway and shear flow calculations.

2.6 Storm Drainage System

Storm drainage collection system conduit capacity calculations were performed using Bentley FlowMasterV8i. Drainage lines P1, P3 and P5 convey runoff from the station yard and turn around area and outlets into the detention basin. Drainage lines P2 and P4 convey the water quality volume to the underground sand filter which discharges to the detention basin through drainage line P5. The pipe

drainage system is designed to convey the 100-year design storm event. Calculations are provided in Appendix C. Below is a summary of the proposed storm drains and design criteria. Riprap outlet protection is provided at all pipe discharge locations refer to Section 2.7 for further information.

Table 2-14: Storm Drains

Drain	Size	Material	Roughness Coefficient	Length (ft)	Slope (%)	10-Year Design Discharge (cfs)	25-Year Design Discharge (cfs)	100-Year Design Discharge (cfs)
P1	12"	HDPE	0.012	8	2.5	1.68	2.27	3.44
P2	2"	PVC	0.010	5	4.0	0.065	N/A	N/A
P3	12"	HDPE	0.012	17	4.4	1.68	2.27	3.44
P4	8"	PVC	0.010	13	4.6	0.065	N/A	N/A
P5	12"	HDPE	0.012	6	2.5	1.68	2.27	3.44
P6	12"	RCP	0.013	22	5.0	0.57	1.09	1.75
P7	12"	RCP	0.013	6	5.0	0.57	1.09	1.75

*Drain lines P2 and P4 are designed for Water Quality Flow (WQF) = 0.065 cfs

2.7 Outlet Protection

Outlet protection is designed for the 25-year frequency design storm as required by the NH DES Stormwater Manual. Calculations for riprap apron protection are located in Appendix C.

Table 2-15: Outlet Protection

Outlet No.	Length (ft)	Depth (ft)	Width at Culvert (ft)	Width at End of Apron (ft)	Median Stone Size (in)	25-Year Flow (cfs)	25-Year Velocity (fps)
FES-1 (P5)	14	1.5	3	9	6	2.27	7.19
FES-2 (P7)	9	1.5	3	12	6	1.09	7.10

3.0 BEST MANAGEMENT PRACTICES

The proposed Stormwater Management System contains Best Management Practices (BMPs) that will, if maintained properly, provide treatment of Site generated stormwater runoff. The proposed BMPs are described below.

3.1 Groundwater Recharge Volume & Water Quality Volume

Runoff from impervious areas of the site will be treated by an underground sand filter. Impervious areas to be treated by the underground sand filter include a paved driveway, structure footings, structures and pads. The Water Quality Volume (WQV) that is required to be treated from these areas is 287 cubic feet. The underground sand filter has a volume of 477 cubic feet which is above the minimum required.

There is a decrease in impervious cover; therefore, groundwater recharge is not required. The worksheets for the underground sand filter and Groundwater Recharge Volume (GRV) are located in Appendix D.

3.2 Temporary Erosion Controls

During construction of the proposed station, the Contractor will be responsible for installation, implementation, and maintenance of temporary erosion and sedimentation control measures, that if implemented and maintained properly, will help to prevent off-site tracking and conveyance of waterborne loss of sediment and debris. The specific measures proposed are located in the Site Development Plans, which are under separate cover.

Temporary erosion and sedimentation controls shall not be removed until construction is complete and site stabilization is achieved.

3.3 Permanent Erosion Controls

Upon completion of construction, the Site shall be stabilized by one or more of the following measures in accordance with the Site Development Plans (under separate cover):

3.3.1 Crushed Rock/Paving

Crushed rock will be installed on the station pad area and turnaround area. The apron at the site entrance will be paved with asphalt.

3.3.2 Seeding

Any disturbed area not proposed as an impervious or gravel surface will be restored to natural meadow vegetation over 4" of topsoil. Planting and mulching of permanent seed will occur as soon as practical

after final grading, placement of topsoil, and soil preparation has been completed. Seeding should occur during the growing season.

3.3.3 Outlet Protection

Pipe outlets implement riprap outlet protection to help prevent scouring and erosion.

3.3.4 Flood Protection Analysis

Flood protection has been implemented for the detention basin as follows:

- Detention Basin will detain the 2-year through 100-year, 24-hour storm event;
- An emergency spillway will be used to convey storm events larger than the 100-year, 24-hour storm event.

3.4 Antidegradation

There is less than 10% effective impervious cover (EIC) and less than 65% undisturbed cover within the property boundary of the Site, therefore the pollutant loading calculations are required to be performed according to the NHDES 1065 Rule. Refer to the Site Cover Plan located in Appendix A and the pollutant load calculations in Appendix J

The site stormwater runoff discharges to an impaired receiving water according to EPA 2008 Waterbody Report for the Baker Brook. As a result, pollutant loading calculations were performed using NH DES standard Simple Method worksheet to demonstrate that there is no increase in Total Suspended Solids (TSS), Total Phosphorus (TP) and Total Nitrogen (TN) resulting from the project. The pollutant loading calculations and other supporting information are located in Appendix J. Also, an impervious area summary table has been prepared to outline the impervious areas draining to the proposed BMP, refer to Appendix D.

The Simple Method generates pollutant loads based on the pre- and post- drainage areas indicated on the Watershed Maps located in Appendix A. The proposed BMP (underground sand filter) is designed to remove a percentage of the pollutants. The treatment BMP provides water quality and limits post-development pollutant levels to less than pre-development pollutant levels.


The site lies within the NE Regional Mercury Total Maximum Daily Load (TMDL) according to the EPA 2008 Waterbody Report for Baker Brook. The project is not anticipated to produce mercury byproducts; therefore, restrictions from the NE Regional Mercury TMDL are not applicable.

4.0 CONCLUSION

In order to mitigate the impacts of stormwater runoff caused by the addition of the substation, two (2) BMPs were implemented. Those BMPs include the addition of an underground sand filter and detention basin. The underground sand filter will provide filtration for the water quality volume. All greater storm events will bypass the sand filter and be conveyed to the detention basin. The detention basin will reduce the post-developed peak discharge rates below that of the pre-developed flows for the 2-year through the 50-year storm events. The basin utilizes one outlet control structure and emergency spillway. The outlet control structure will control up to and including the 100-year storm event. The storm events larger than the 100-year storm event will discharge through the emergency spillway. The on-site BMPs have been designed in accordance with the New Hampshire Department of Environmental Services Stormwater Manual Volumes 1, 2, & 3.

* * * * *


APPENDIX A – PRE- AND POST-DEVELOPMENT WATERSHED MAPS



SOIL TYPE LEGEND		
Map Legend	Soil Type Per NRCS Web Soil Survey	Hydrologic Soil Group
255B	Monodnock and Hermon soils, 3 to 8 percent slopes, very stoney	B
59B	Waumbek loamy sand, 3 to 8 percent slopes, very stoney	B
255E	Monadnock and Hermon soils, 25 to 35 percent slopes, very stoney	B
123B	Telos silt loam, 3-8 percent slopes	C
299B/dbcde*	Udorthents, smoothed, 3-8 percent slopes	A/B (B)
299C/dbcde*	Udorthents, smoothed, 8-15 percent slopes	C/A/D (B)
731A	Peacham and Ossipee mucky peat, 0-3 percent slopes	D

HSG TOTAL AREA IN ACRES		
HSG	AREA 1	TOTAL
A	-	-
B	0.578	0.578
C	0.048	0.048
D	0.400	0.400
WATER	-	-
IMPERVIOUS	0.207	0.207
TOTAL	1.233	1.233

- LEGEND**
- PRE-DEVELOPMENT SUB-AREA BOUNDARY
 - NRCS WEB SOIL APPROX. SURVEY SOIL BOUNDARY
 - TIME OF CONCENTRATION
 - NRCS SOIL DESIGNATION
 - SPOT ELEVATION



**PROGRESS PRINT
FOR REVIEW ONLY
NOT FOR CONSTRUCTION**

THE NORTHERN PASS


Transmission Business

#

TRANSITION STATION #5
PRE-DEVELOPMENT WATERSHED MAP

DATE: 10/1/2015
SCALE: 1" = 20'

DES: LMP
CHK: RLR
DRW: RP
APR: BSS
TOWN: BETHLEHEM, NH
TRANSMISSION LINE:
MILE NO:
SHEET 1 OF 1
NPT78-WSHED-PRE
REVISION: XXX



SOIL TYPE LEGEND


Map Legend	Soil Type Per NRCS Web Soil Survey	Hydrologic Soil Group
255B	Monadnock and Hermon soils, 3 to 8 percent slopes, very stoney	B
59B	Waumbek loamy sand, 3 to 8 percent slopes, very stoney	B
255E	Monadnock and Hermon soils, 25 to 35 percent slopes, very stoney	B
123B	Telos silt loam, 3-8 percent slopes	C
299B/dbcde*	Udorthents, smoothed, 3-8 percent slopes	A/B (B)
299C/dbcde*	Udorthents, smoothed, 8-15 percent slopes	C/A/D (B)
731A	Peacham and Ossipee mucky peat, 0-3 percent slopes	D

HSG TOTAL AREA IN ACRES

HSG	AREA 1	AREA 2	TOTAL
A	-	-	-
B	0.408	0.175	0.583
C	-	0.035	0.035
D	0.221	0.130	0.351
WATER	-	0.048	0.048
IMPERVIOUS	0.050	0.166	0.216
TOTAL	0.679	0.554	1.233

LEGEND


- POST-DEVELOPMENT SUB-AREA BOUNDARY
- NRCS WEB SOIL APPROX. SURVEY SOIL BOUNDARY
- TIME OF CONCENTRATION
- NRCS SOIL DESIGNATION
- SPOT ELEVATION



0 10' 20' 40'
SCALE IN FEET


PROGRESS PRINT
FOR REVIEW ONLY
NOT FOR CONSTRUCTION

DES: LMP	CHK: RLR	DATE: 10/1/2015
DRW: RP	APR: BSS	SCALE: 1" = 20'
TOWN: BETHLEHEM, NH	TRANSMISSION LINE:	
MILE NO:	SHEET 1 OF 1	
REVISION: XXX		



COVER TYPE TOTAL AREA IN ACRES		
COVER TYPE	AREA 1	TOTAL
WOODS (HSG B)	0.144	0.144
WOODS (HSG C)	0.048	0.048
WOODS (HSG D)	0.144	0.144
MEADOW (HSG B)	0.372	0.372
MEADOW (HSG D)	0.256	0.256
IMPERVIOUS (HSG B)	0.200	0.200
IMPERVIOUS-DIRT DRIVE (HSG B)	0.062	0.062
IMPERVIOUS (HSG D)	0.007	0.007
TOTAL	1.233	1.233

- LEGEND**
- PRE-DEVELOPMENT SUB-AREA BOUNDARY
 - NRCS WEB SOIL APPROX. SURVEY SOIL BOUNDARY
 - TIME OF CONCENTRATION
 - NRCS SOIL DESIGNATION



NOTES:
REFER TO PRE-DEVELOPMENT WATERSHED
MAP DRAWING NPPT8-WSHED-PRE FOR
FURTHER INFORMATION

**PROGRESS PRINT
FOR REVIEW ONLY
NOT FOR CONSTRUCTION**

THE NORTHERN PASS
Transmission
Business

TRANSITION STATION #5
PRE-DEVELOPMENT
COVER TYPE SUMMARY
SCALE: 1" = 20'



DES: XXX CHK:XXX
DRW: XX APR:XXX
TOWN: BETHLEHEM, NH
TRANSMISSION LINE:
MILE NO:
SHEET 1 OF 1
REVISION: XXX

NO.	1	ISSUED FOR PERMITTING	1/13/17	KAM	R/R	CHK	APPROV.
REVISION		DATE		DRWN	CHD		

COVER TYPE TOTAL AREA IN ACRES			
COVER TYPE	AREA 1	AREA 2	TOTAL
WOODS (HSG B)	-	0.017	0.017
WOODS (HSG C)	-	0.010	0.010
WOODS (HSG D)	-	0.046	0.046
MEADOW (HSG B)	0.084	0.130	0.214
MEADOW (HSG C)	-	0.025	0.025
MEADOW (HSG D)	0.0002	0.084	0.084
IMPERVIOUS (HSG B)	0.028	0.166	0.194
IMPERVIOUS-DIRT DRIVE (HSG B)	-	0.028	0.028
IMPERVIOUS (HSG D)	0.022	-	0.022
GRAVEL (HSG B)	0.324	-	0.324
GRAVEL (HSG D)	0.221	-	0.221
WATER (HSG C)	-	0.013	0.013
WATER (HSG D)	-	0.035	0.035
TOTAL	0.679	0.554	1.233

LEGEND

- POST-DEVELOPMENT SUB-AREA BOUNDARY
- NRCS WEB SOIL APPROX. SURVEY SOIL BOUNDARY
- TIME OF CONCENTRATION
- NRCS SOIL DESIGNATION
- SPOT ELEVATION



NOTES:
REFER TO POST-DEVELOPMENT WATERSHED
MAP DRAWING NPPTT8-WSHD-POST FOR
FURTHER INFORMATION

PROGRESS PRINT
FOR REVIEW ONLY
NOT FOR CONSTRUCTION

THE NORTHERN PASS
Transmission Business

TRANSITION STATION #5
POST-DEVELOPMENT
COVER TYPE SUMMARY

DES: XXX CHK:XXX
DRW: XX APR:XXX
TOWN: BETHLEHEM, NH
TRANSMISSION LINE:
MILE NO:
SHEET 1 OF 1
NPPTT8-WSHD-POST-COVER
REVISION: XXX

NO.	DATE	REVISION	CHK	APPV.
1	1/3/17	ISSUED FOR PERMITTING	KAM	R/P



LEGEND

- EI - EXISTING IMPERVIOUS AREA
- UDC - UNDISTURBED COVER
- PI - PROPOSED IMPERVIOUS AREA
- DIA - PROPOSED DISCONNECTED IMPERVIOUS AREA
- EXISTING PARCEL LINE
- LOD

PROPOSED LIMIT OF DISTURBANCE LINE (LOD)


SITE COVER AREA			
ITEM	DESCRIPTION	AREA (SF)	AREA (AC)
PS	PARCEL SIZE	40,305	0.93
EI	EXISTING IMPERVIOUS	3,170	0.07
PI	PROPOSED IMPERVIOUS	3,505	0.08
PDA	PROPOSED DISTURBED AREA (WITHIN PROPERTY LINE)	36,561	0.84
UDC	UNDISTURBED COVER	3,700	0.08
DIA	DISCONNECTED AREA	0	0.00

SITE COVER TABULATION			
ITEM	DESCRIPTION	FORMULA	TOTAL
TIC	TOTAL IMPERVIOUS COVER (ACRES)	EI + PI	0.03
EIC	EFFECTIVE IMPERVIOUS COVER (ACRES)	TIC - DIA	0.03
EIC %	EIC PERCENTAGE	EIC / PS	3.2%
UDC %	UDC PERCENTAGE	UDC / PS	9.2%

MAP REFERENCES:

- 2011 ORTHOIMAGERY OBTAINED IN .SID FORMAT FROM NH STATEWIDE GIS CLEARINGHOUSE WEBSITE AT www.granit.unh.edu.
TILES USED: 0965006450 & 09650065500

- NOTES:
- THE TOTAL IMPERVIOUS COVER (TIC) AS A RESULT OF THIS PROJECT ACCOUNTS FOR THE SUM OF THE PROPOSED IMPERVIOUS AREA (PI) AND THE DISCONNECTED IMPERVIOUS AREA (DIA) MINUS THE EXISTING IMPERVIOUS AREA (EI) TO BE DEMOLISHED.
 - NPDES/LIMIT OF DISTURBANCE (LOD) AREA TOTAL = 0.884 ACRES, OF WHICH 0.839 ACRES IS ON-SITE DISTURBANCE AND 0.045 ACRES IS OFF-SITE DISTURBANCE.



FOR PERMITTING
PURPOSES ONLY
NOT FOR CONSTRUCTION

THE NORTHERN PASS

Transmission Business

TRANSITION STATION #5
SITE COVER PLAN

DES: LMP | CHK:RLR
DRW: FP | APR: BSS
TOWN: BETHLEHEM, NH
TRANSMISSION LINE:
MILE NO:
SHEET 1 OF 1
NPTT8-SCP

DATE: 10/1/2015
SCALE: 1" = 100'

NO.	DATE	BY	CHK	APP
1	10/1/15	FP	RLR	BSS
2	1/20/17	KAM	RLR	BSS
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15				
16				
17				
18				
19				
20				
21				
22				
23				
24				
25				
26				
27				
28				
29				
30				
31				
32				
33				
34				
35				
36				
37				
38				
39				
40				
41				
42				
43				
44				
45				
46				
47				
48				
49				
50				
51				
52				
53				
54				
55				
56				
57				
58				
59				
60				
61				
62				
63				
64				
65				
66				
67				
68				
69				
70				
71				
72				
73				
74				
75				
76				
77				
78				
79				
80				
81				
82				
83				
84				
85				
86				
87				
88				
89				
90				
91				
92				
93				
94				
95				
96				
97				
98				
99				
100				

APPENDIX B – HYDROLOGY MODEL (PONDPACK)

Extreme Precipitation Tables

Northeast Regional Climate Center

Data represents point estimates calculated from partial duration series. All precipitation amounts are displayed in inches.

Smoothing	Yes
State	New Hampshire
Location	
Longitude	71.726 degrees West
Latitude	44.282 degrees North
Elevation	0 feet
Date/Time	Wed, 15 Jul 2015 10:38:20 -0400

Extreme Precipitation Estimates

	5min	10min	15min	30min	60min	120min		1hr	2hr	3hr	6hr	12hr	24hr	48hr		1day	2day	4day	7day	10day	
1yr	0.26	0.39	0.49	0.64	0.80	0.99	1yr	0.69	0.95	1.13	1.38	1.67	2.01	2.30	1yr	1.78	2.21	2.58	3.22	3.72	1yr
2yr	0.30	0.46	0.57	0.76	0.95	1.18	2yr	0.82	1.09	1.35	1.63	1.96	2.35	2.68	2yr	2.08	2.58	3.02	3.70	4.26	2yr
5yr	0.35	0.55	0.69	0.92	1.18	1.47	5yr	1.02	1.35	1.68	2.04	2.43	2.88	3.31	5yr	2.55	3.18	3.68	4.47	5.10	5yr
10yr	0.40	0.62	0.79	1.07	1.39	1.75	10yr	1.20	1.59	2.00	2.42	2.87	3.37	3.88	10yr	2.98	3.73	4.27	5.15	5.85	10yr
25yr	0.47	0.74	0.95	1.30	1.73	2.19	25yr	1.50	1.96	2.50	3.01	3.56	4.14	4.80	25yr	3.66	4.61	5.21	6.23	7.02	25yr
50yr	0.53	0.85	1.09	1.52	2.05	2.60	50yr	1.77	2.31	2.97	3.57	4.19	4.84	5.64	50yr	4.28	5.42	6.07	7.19	8.05	50yr
100yr	0.60	0.97	1.25	1.77	2.42	3.09	100yr	2.09	2.71	3.54	4.23	4.93	5.65	6.62	100yr	5.00	6.37	7.06	8.30	9.24	100yr
200yr	0.69	1.12	1.45	2.08	2.87	3.66	200yr	2.47	3.19	4.20	5.00	5.80	6.61	7.79	200yr	5.85	7.49	8.22	9.59	10.61	200yr
500yr	0.82	1.35	1.76	2.55	3.59	4.60	500yr	3.09	3.97	5.26	6.24	7.20	8.14	9.67	500yr	7.21	9.30	10.07	11.62	12.75	500yr


Lower Confidence Limits

	5min	10min	15min	30min	60min	120min		1hr	2hr	3hr	6hr	12hr	24hr	48hr		1day	2day	4day	7day	10day	
1yr	0.22	0.34	0.41	0.55	0.68	0.81	1yr	0.59	0.79	0.94	1.20	1.48	1.84	2.17	1yr	1.63	2.09	2.32	2.68	3.08	1yr
2yr	0.29	0.44	0.54	0.74	0.91	1.08	2yr	0.79	1.05	1.24	1.57	1.96	2.30	2.62	2yr	2.04	2.52	2.95	3.63	4.19	2yr
5yr	0.32	0.50	0.62	0.85	1.08	1.27	5yr	0.93	1.24	1.43	1.82	2.34	2.72	3.11	5yr	2.41	2.99	3.50	4.26	4.88	5yr
10yr	0.35	0.54	0.67	0.94	1.21	1.42	10yr	1.05	1.39	1.58	2.02	2.50	3.06	3.54	10yr	2.71	3.41	3.96	4.82	5.46	10yr
25yr	0.40	0.60	0.75	1.07	1.41	1.64	25yr	1.22	1.60	1.79	2.32	2.85	3.59	4.20	25yr	3.18	4.04	4.70	5.66	6.33	25yr
50yr	0.42	0.64	0.80	1.15	1.55	1.82	50yr	1.34	1.78	1.95	2.55	3.14	4.03	4.77	50yr	3.56	4.59	5.33	6.38	7.11	50yr
100yr	0.46	0.69	0.87	1.25	1.72	2.01	100yr	1.48	1.96	2.13	2.80	3.46	4.53	5.41	100yr	4.01	5.20	6.07	7.23	7.97	100yr
200yr	0.50	0.75	0.95	1.37	1.91	2.21	200yr	1.65	2.16	2.32	3.09	3.79	5.09	6.27	200yr	4.51	6.03	6.91	8.18	8.94	200yr
500yr	0.55	0.83	1.06	1.54	2.19	2.53	500yr	1.89	2.47	2.58	3.49	4.28	5.95	7.48	500yr	5.27	7.20	8.22	9.66	10.43	500yr

Upper Confidence Limits

	5min	10min	15min	30min	60min	120min		1hr	2hr	3hr	6hr	12hr	24hr	48hr		1day	2day	4day	7day	10day	
1yr	0.28	0.43	0.53	0.71	0.87	1.08	1yr	0.75	1.05	1.23	1.61	1.94	2.14	2.46	1yr	1.90	2.36	2.73	3.41	3.95	1yr
2yr	0.32	0.49	0.61	0.82	1.01	1.19	2yr	0.87	1.16	1.35	1.73	2.14	2.42	2.74	2yr	2.14	2.64	3.09	3.78	4.35	2yr
5yr	0.39	0.60	0.74	1.02	1.29	1.50	5yr	1.12	1.47	1.68	2.15	2.62	3.04	3.49	5yr	2.69	3.36	3.87	4.68	5.32	5yr
10yr	0.46	0.70	0.87	1.22	1.57	1.83	10yr	1.36	1.79	1.99	2.57	3.21	3.63	4.21	10yr	3.22	4.05	4.60	5.51	6.19	10yr
25yr	0.58	0.88	1.10	1.57	2.06	2.39	25yr	1.78	2.33	2.53	3.29	4.11	4.64	5.41	25yr	4.10	5.20	5.79	6.85	7.59	25yr
50yr	0.69	1.06	1.32	1.89	2.55	2.91	50yr	2.20	2.85	3.05	3.96	4.97	5.56	6.53	50yr	4.92	6.28	6.88	8.05	8.85	50yr
100yr	0.84	1.26	1.58	2.29	3.14	3.57	100yr	2.71	3.49	3.66	4.77	6.03	6.70	7.91	100yr	5.93	7.61	8.19	9.49	10.33	100yr
200yr	1.00	1.51	1.91	2.77	3.86	4.37	200yr	3.33	4.27	4.43	5.78	7.32	8.07	9.45	200yr	7.14	9.09	9.74	11.18	12.06	200yr
500yr	1.29	1.92	2.47	3.59	5.11	5.71	500yr	4.41	5.58	5.70	7.45	9.50	10.34	12.10	500yr	9.15	11.64	12.27	13.89	14.82	500yr

Scenario: Post-Development 25 year



Project Summary

Title	Northern Pass Transition Station #5a Stormwater Model
Engineer	R. Reed
Company	Burns & McDonnell
Date	1/17/2017

Notes

Catchments Summary

Label	Scenario	Return Event (years)	Hydrograph Volume (ac-ft)	Time to Peak (hours)	Peak Flow (ft ³ /s)
PRE-1	Pre-Development 2 year	2	0.046	12.083	0.54
PRE-1	Pre-Development 10 year	10	0.143	12.050	2.00
PRE-1	Pre-Development 50 year	50	0.264	12.050	3.73
PRE-1	Pre-Development 100 year	100	0.277	12.050	3.91
POST-1	Post-Development 2 year	2	0.060	12.017	0.94
POST-1	Post-Development 10 year	10	0.107	12.017	1.68
POST-1	Post-Development 50 year	50	0.182	12.000	2.81
POST-1	Post-Development 100 year	100	0.224	12.000	3.44
POST-2	Post-Development 2 year	2	0.036	12.067	0.50
POST-2	Post-Development 10 year	10	0.071	12.067	1.00
POST-2	Post-Development 50 year	50	0.127	12.050	1.79
POST-2	Post-Development 100 year	100	0.160	12.050	2.25

Node Summary

Label	Scenario	Return Event (years)	Hydrograph Volume (ac-ft)	Time to Peak (hours)	Peak Flow (ft ³ /s)
O-1 (PRE)	Pre-Development 2 year	2	0.046	12.083	0.54
O-1 (PRE)	Pre-Development 10 year	10	0.143	12.050	2.00
O-1 (PRE)	Pre-Development 50 year	50	0.264	12.050	3.73
O-1 (PRE)	Pre-Development 100 year	100	0.277	12.050	3.91
O-1 (POST)	Post-Development 2 year	2	0.079	12.067	0.53
O-1 (POST)	Post-Development 10 year	10	0.155	12.117	1.32
O-1 (POST)	Post-Development 50 year	50	0.279	12.067	2.87
O-1 (POST)	Post-Development 100 year	100	0.352	12.067	3.58

Pond Summary

Label	Scenario	Return Event (years)	Hydrograph Volume (ac-ft)	Time to Peak (hours)	Peak Flow (ft ³ /s)	Maximum Water Surface Elevation (ft)	Maximum Pond Storage (ac-ft)
DB-1 (IN)	Post-Development 2 year	2	0.060	12.017	0.94	(N/A)	(N/A)

Pond Summary

Label	Scenario	Return Event (years)	Hydrograph Volume (ac-ft)	Time to Peak (hours)	Peak Flow (ft ³ /s)	Maximum Water Surface Elevation (ft)	Maximum Pond Storage (ac-ft)
DB-1 (OUT)	Post-Development 2 year	2	0.043	13.900	0.05	1,077.40	0.033
DB-1 (IN)	Post-Development 10 year	10	0.107	12.017	1.68	(N/A)	(N/A)
DB-1 (OUT)	Post-Development 10 year	10	0.084	12.233	0.55	1,077.79	0.046
DB-1 (IN)	Post-Development 50 year	50	0.182	12.000	2.81	(N/A)	(N/A)
DB-1 (OUT)	Post-Development 50 year	50	0.152	12.183	1.22	1,078.40	0.070
DB-1 (IN)	Post-Development 100 year	100	0.224	12.000	3.44	(N/A)	(N/A)
DB-1 (OUT)	Post-Development 100 year	100	0.192	12.183	1.47	1,078.74	0.085

Time-Depth Curve: 10 year

Label	10 year
Start Time	0.000 hours
Increment	0.100 hours
End Time	24.000 hours
Return Event	10 years

CUMULATIVE RAINFALL (in)**Output Time Increment = 0.100 hours****Time on left represents time for first value in each row.**

Time (hours)	Depth (in)	Depth (in)	Depth (in)	Depth (in)	Depth (in)
0.000	0.0	0.0	0.0	0.0	0.0
0.500	0.0	0.0	0.0	0.0	0.0
1.000	0.0	0.0	0.0	0.0	0.1
1.500	0.1	0.1	0.1	0.1	0.1
2.000	0.1	0.1	0.1	0.1	0.1
2.500	0.1	0.1	0.1	0.1	0.1
3.000	0.1	0.1	0.1	0.1	0.1
3.500	0.1	0.1	0.1	0.2	0.2
4.000	0.2	0.2	0.2	0.2	0.2
4.500	0.2	0.2	0.2	0.2	0.2
5.000	0.2	0.2	0.2	0.2	0.2
5.500	0.2	0.2	0.3	0.3	0.3
6.000	0.3	0.3	0.3	0.3	0.3
6.500	0.3	0.3	0.3	0.3	0.3
7.000	0.3	0.3	0.3	0.4	0.4
7.500	0.4	0.4	0.4	0.4	0.4
8.000	0.4	0.4	0.4	0.4	0.4
8.500	0.4	0.5	0.5	0.5	0.5
9.000	0.5	0.5	0.5	0.5	0.5
9.500	0.5	0.6	0.6	0.6	0.6
10.000	0.6	0.6	0.6	0.7	0.7
10.500	0.7	0.7	0.7	0.7	0.8
11.000	0.8	0.8	0.8	0.9	0.9
11.500	1.0	1.0	1.2	1.5	1.9
12.000	2.2	2.3	2.4	2.4	2.4
12.500	2.5	2.5	2.5	2.6	2.6
13.000	2.6	2.6	2.6	2.7	2.7
13.500	2.7	2.7	2.7	2.7	2.8
14.000	2.8	2.8	2.8	2.8	2.8
14.500	2.8	2.8	2.8	2.9	2.9
15.000	2.9	2.9	2.9	2.9	2.9
15.500	2.9	2.9	2.9	2.9	3.0
16.000	3.0	3.0	3.0	3.0	3.0
16.500	3.0	3.0	3.0	3.0	3.0
17.000	3.0	3.0	3.1	3.1	3.1
17.500	3.1	3.1	3.1	3.1	3.1
18.000	3.1	3.1	3.1	3.1	3.1
18.500	3.1	3.1	3.1	3.1	3.2
19.000	3.2	3.2	3.2	3.2	3.2
19.500	3.2	3.2	3.2	3.2	3.2
20.000	3.2	3.2	3.2	3.2	3.2
20.500	3.2	3.2	3.2	3.2	3.2
21.000	3.3	3.3	3.3	3.3	3.3
21.500	3.3	3.3	3.3	3.3	3.3

CUMULATIVE RAINFALL (in)
Output Time Increment = 0.100 hours
Time on left represents time for first value in each row.

Time (hours)	Depth (in)	Depth (in)	Depth (in)	Depth (in)	Depth (in)
22.000	3.3	3.3	3.3	3.3	3.3
22.500	3.3	3.3	3.3	3.3	3.3
23.000	3.3	3.3	3.3	3.3	3.3
23.500	3.4	3.4	3.4	3.4	3.4
24.000	3.4	(N/A)	(N/A)	(N/A)	(N/A)

Time-Depth Curve: 100 year

Label	100 year
Start Time	0.000 hours
Increment	0.100 hours
End Time	24.000 hours
Return Event	100 years

CUMULATIVE RAINFALL (in)**Output Time Increment = 0.100 hours****Time on left represents time for first value in each row.**

Time (hours)	Depth (in)	Depth (in)	Depth (in)	Depth (in)	Depth (in)
0.000	0.0	0.0	0.0	0.0	0.0
0.500	0.0	0.0	0.0	0.0	0.1
1.000	0.1	0.1	0.1	0.1	0.1
1.500	0.1	0.1	0.1	0.1	0.1
2.000	0.1	0.1	0.1	0.1	0.2
2.500	0.2	0.2	0.2	0.2	0.2
3.000	0.2	0.2	0.2	0.2	0.2
3.500	0.2	0.2	0.2	0.3	0.3
4.000	0.3	0.3	0.3	0.3	0.3
4.500	0.3	0.3	0.3	0.3	0.3
5.000	0.4	0.4	0.4	0.4	0.4
5.500	0.4	0.4	0.4	0.4	0.4
6.000	0.5	0.5	0.5	0.5	0.5
6.500	0.5	0.5	0.5	0.5	0.5
7.000	0.6	0.6	0.6	0.6	0.6
7.500	0.6	0.6	0.6	0.7	0.7
8.000	0.7	0.7	0.7	0.7	0.7
8.500	0.7	0.8	0.8	0.8	0.8
9.000	0.8	0.8	0.9	0.9	0.9
9.500	0.9	0.9	1.0	1.0	1.0
10.000	1.0	1.0	1.1	1.1	1.1
10.500	1.2	1.2	1.2	1.3	1.3
11.000	1.3	1.4	1.4	1.5	1.5
11.500	1.6	1.7	2.0	2.4	3.2
12.000	3.7	3.9	3.9	4.0	4.1
12.500	4.2	4.2	4.2	4.3	4.3
13.000	4.4	4.4	4.4	4.5	4.5
13.500	4.5	4.5	4.6	4.6	4.6
14.000	4.6	4.7	4.7	4.7	4.7
14.500	4.7	4.8	4.8	4.8	4.8
15.000	4.8	4.8	4.9	4.9	4.9
15.500	4.9	4.9	4.9	4.9	5.0
16.000	5.0	5.0	5.0	5.0	5.0
16.500	5.0	5.0	5.1	5.1	5.1
17.000	5.1	5.1	5.1	5.1	5.1
17.500	5.2	5.2	5.2	5.2	5.2
18.000	5.2	5.2	5.2	5.2	5.2
18.500	5.3	5.3	5.3	5.3	5.3
19.000	5.3	5.3	5.3	5.3	5.3
19.500	5.3	5.3	5.4	5.4	5.4
20.000	5.4	5.4	5.4	5.4	5.4
20.500	5.4	5.4	5.4	5.4	5.4
21.000	5.5	5.5	5.5	5.5	5.5
21.500	5.5	5.5	5.5	5.5	5.5

CUMULATIVE RAINFALL (in)
Output Time Increment = 0.100 hours
Time on left represents time for first value in each row.

Time (hours)	Depth (in)	Depth (in)	Depth (in)	Depth (in)	Depth (in)
22.000	5.5	5.5	5.5	5.5	5.5
22.500	5.6	5.6	5.6	5.6	5.6
23.000	5.6	5.6	5.6	5.6	5.6
23.500	5.6	5.6	5.6	5.6	5.6
24.000	5.7	(N/A)	(N/A)	(N/A)	(N/A)

Time-Depth Curve: 2 year

Label	2 year
Start Time	0.000 hours
Increment	0.100 hours
End Time	24.000 hours
Return Event	2 years

CUMULATIVE RAINFALL (in)**Output Time Increment = 0.100 hours****Time on left represents time for first value in each row.**

Time (hours)	Depth (in)	Depth (in)	Depth (in)	Depth (in)	Depth (in)
0.000	0.0	0.0	0.0	0.0	0.0
0.500	0.0	0.0	0.0	0.0	0.0
1.000	0.0	0.0	0.0	0.0	0.0
1.500	0.0	0.0	0.0	0.0	0.0
2.000	0.1	0.1	0.1	0.1	0.1
2.500	0.1	0.1	0.1	0.1	0.1
3.000	0.1	0.1	0.1	0.1	0.1
3.500	0.1	0.1	0.1	0.1	0.1
4.000	0.1	0.1	0.1	0.1	0.1
4.500	0.1	0.1	0.1	0.1	0.1
5.000	0.1	0.2	0.2	0.2	0.2
5.500	0.2	0.2	0.2	0.2	0.2
6.000	0.2	0.2	0.2	0.2	0.2
6.500	0.2	0.2	0.2	0.2	0.2
7.000	0.2	0.2	0.2	0.2	0.3
7.500	0.3	0.3	0.3	0.3	0.3
8.000	0.3	0.3	0.3	0.3	0.3
8.500	0.3	0.3	0.3	0.3	0.3
9.000	0.3	0.4	0.4	0.4	0.4
9.500	0.4	0.4	0.4	0.4	0.4
10.000	0.4	0.4	0.4	0.5	0.5
10.500	0.5	0.5	0.5	0.5	0.5
11.000	0.6	0.6	0.6	0.6	0.6
11.500	0.7	0.7	0.8	1.0	1.3
12.000	1.6	1.6	1.6	1.7	1.7
12.500	1.7	1.7	1.8	1.8	1.8
13.000	1.8	1.8	1.8	1.9	1.9
13.500	1.9	1.9	1.9	1.9	1.9
14.000	1.9	1.9	1.9	2.0	2.0
14.500	2.0	2.0	2.0	2.0	2.0
15.000	2.0	2.0	2.0	2.0	2.0
15.500	2.0	2.0	2.1	2.1	2.1
16.000	2.1	2.1	2.1	2.1	2.1
16.500	2.1	2.1	2.1	2.1	2.1
17.000	2.1	2.1	2.1	2.1	2.1
17.500	2.1	2.1	2.2	2.2	2.2
18.000	2.2	2.2	2.2	2.2	2.2
18.500	2.2	2.2	2.2	2.2	2.2
19.000	2.2	2.2	2.2	2.2	2.2
19.500	2.2	2.2	2.2	2.2	2.2
20.000	2.2	2.2	2.2	2.2	2.2
20.500	2.3	2.3	2.3	2.3	2.3
21.000	2.3	2.3	2.3	2.3	2.3
21.500	2.3	2.3	2.3	2.3	2.3

CUMULATIVE RAINFALL (in)
Output Time Increment = 0.100 hours
Time on left represents time for first value in each row.

Time (hours)	Depth (in)	Depth (in)	Depth (in)	Depth (in)	Depth (in)
22.000	2.3	2.3	2.3	2.3	2.3
22.500	2.3	2.3	2.3	2.3	2.3
23.000	2.3	2.3	2.3	2.3	2.3
23.500	2.3	2.3	2.3	2.3	2.3
24.000	2.4	(N/A)	(N/A)	(N/A)	(N/A)

Subsection: Time-Depth Curve
 Label: Bethlehem NH

Return Event: 50 years
 Storm Event: 50 year

Time-Depth Curve: 50 year	
Label	50 year
Start Time	0.000 hours
Increment	0.100 hours
End Time	24.000 hours
Return Event	50 years

CUMULATIVE RAINFALL (in)
Output Time Increment = 0.100 hours
Time on left represents time for first value in each row.

Time (hours)	Depth (in)	Depth (in)	Depth (in)	Depth (in)	Depth (in)
0.000	0.0	0.0	0.0	0.0	0.0
0.500	0.0	0.0	0.0	0.0	0.0
1.000	0.1	0.1	0.1	0.1	0.1
1.500	0.1	0.1	0.1	0.1	0.1
2.000	0.1	0.1	0.1	0.1	0.1
2.500	0.1	0.1	0.1	0.2	0.2
3.000	0.2	0.2	0.2	0.2	0.2
3.500	0.2	0.2	0.2	0.2	0.2
4.000	0.2	0.2	0.2	0.3	0.3
4.500	0.3	0.3	0.3	0.3	0.3
5.000	0.3	0.3	0.3	0.3	0.3
5.500	0.3	0.4	0.4	0.4	0.4
6.000	0.4	0.4	0.4	0.4	0.4
6.500	0.4	0.4	0.5	0.5	0.5
7.000	0.5	0.5	0.5	0.5	0.5
7.500	0.5	0.5	0.5	0.6	0.6
8.000	0.6	0.6	0.6	0.6	0.6
8.500	0.6	0.7	0.7	0.7	0.7
9.000	0.7	0.7	0.7	0.8	0.8
9.500	0.8	0.8	0.8	0.8	0.9
10.000	0.9	0.9	0.9	0.9	1.0
10.500	1.0	1.0	1.0	1.1	1.1
11.000	1.1	1.2	1.2	1.3	1.3
11.500	1.4	1.5	1.7	2.1	2.7
12.000	3.2	3.3	3.4	3.5	3.5
12.500	3.6	3.6	3.6	3.7	3.7
13.000	3.7	3.8	3.8	3.8	3.8
13.500	3.9	3.9	3.9	3.9	4.0
14.000	4.0	4.0	4.0	4.0	4.0
14.500	4.1	4.1	4.1	4.1	4.1
15.000	4.1	4.1	4.2	4.2	4.2
15.500	4.2	4.2	4.2	4.2	4.2
16.000	4.3	4.3	4.3	4.3	4.3
16.500	4.3	4.3	4.3	4.3	4.4
17.000	4.4	4.4	4.4	4.4	4.4
17.500	4.4	4.4	4.4	4.4	4.4
18.000	4.5	4.5	4.5	4.5	4.5
18.500	4.5	4.5	4.5	4.5	4.5
19.000	4.5	4.5	4.6	4.6	4.6
19.500	4.6	4.6	4.6	4.6	4.6
20.000	4.6	4.6	4.6	4.6	4.6
20.500	4.6	4.6	4.7	4.7	4.7
21.000	4.7	4.7	4.7	4.7	4.7
21.500	4.7	4.7	4.7	4.7	4.7

CUMULATIVE RAINFALL (in)
Output Time Increment = 0.100 hours
Time on left represents time for first value in each row.

Time (hours)	Depth (in)	Depth (in)	Depth (in)	Depth (in)	Depth (in)
22.000	4.7	4.7	4.7	4.7	4.8
22.500	4.8	4.8	4.8	4.8	4.8
23.000	4.8	4.8	4.8	4.8	4.8
23.500	4.8	4.8	4.8	4.8	4.8
24.000	4.8	(N/A)	(N/A)	(N/A)	(N/A)

Time of Concentration Results

Segment #1: TR-55 Sheet Flow	
Hydraulic Length	18.00 ft
Manning's n	0.240
Slope	0.178 ft/ft
2 Year 24 Hour Depth	2.4 in
Average Velocity	0.17 ft/s
Segment Time of Concentration	0.029 hours
Segment #2: TR-55 Sheet Flow	
Hydraulic Length	79.00 ft
Manning's n	0.100
Slope	0.010 ft/ft
2 Year 24 Hour Depth	2.4 in
Average Velocity	0.15 ft/s
Segment Time of Concentration	0.151 hours
Segment #3: TR-55 Shallow Concentrated Flow	
Hydraulic Length	73.00 ft
Is Paved?	True
Slope	0.011 ft/ft
Average Velocity	2.13 ft/s
Segment Time of Concentration	0.010 hours
Segment #4: TR-55 Shallow Concentrated Flow	
Hydraulic Length	99.00 ft
Is Paved?	True
Slope	0.014 ft/ft
Average Velocity	2.41 ft/s
Segment Time of Concentration	0.011 hours
Time of Concentration (Composite)	
Time of Concentration (Composite)	0.201 hours

==== SCS Channel Flow

$$R = Q_a / W_p$$
$$T_c = \frac{V = (1.49 * (R^{2/3}) * (S_f^{0.5})) / n}{(L_f / V) / 3600}$$

Where:

R = Hydraulic radius
 A_q = Flow area, square feet
 W_p = Wetted perimeter, feet
 V = Velocity, ft/sec
 S_f = Slope, ft/ft
 n = Manning's n
 T_c = Time of concentration, hours
 L_f = Flow length, feet

==== SCS TR-55 Shallow Concentration Flow

Unpaved surface:

$$V = 16.1345 * (S_f^{0.5})$$

Paved Surface:

$$V = 20.3282 * (S_f^{0.5})$$
$$T_c = \frac{(L_f / V) / 3600}{V = \text{Velocity, ft/sec}}$$

Where:

S_f = Slope, ft/ft
 T_c = Time of concentration, hours
 L_f = Flow length, feet

Time of Concentration Results

Segment #1: TR-55 Sheet Flow	
Hydraulic Length	100.00 ft
Manning's n	0.240
Slope	0.030 ft/ft
2 Year 24 Hour Depth	2.4 in
Average Velocity	0.12 ft/s
Segment Time of Concentration	0.236 hours
Segment #2: TR-55 Shallow Concentrated Flow	
Hydraulic Length	95.00 ft
Is Paved?	False
Slope	0.015 ft/ft
Average Velocity	1.98 ft/s
Segment Time of Concentration	0.013 hours
Segment #3: TR-55 Shallow Concentrated Flow	
Hydraulic Length	133.00 ft
Is Paved?	False
Slope	0.053 ft/ft
Average Velocity	3.71 ft/s
Segment Time of Concentration	0.010 hours
Segment #4: TR-55 Shallow Concentrated Flow	
Hydraulic Length	17.00 ft
Is Paved?	False
Slope	0.353 ft/ft
Average Velocity	9.59 ft/s
Segment Time of Concentration	0.000 hours
Segment #5: TR-55 Shallow Concentrated Flow	
Hydraulic Length	68.00 ft
Is Paved?	False
Slope	0.059 ft/ft
Average Velocity	3.92 ft/s
Segment Time of Concentration	0.005 hours
Segment #6: TR-55 Shallow Concentrated Flow	
Hydraulic Length	36.00 ft
Is Paved?	False
Slope	0.063 ft/ft
Average Velocity	4.05 ft/s
Segment Time of Concentration	0.002 hours
Segment #7: TR-55 Shallow Concentrated Flow	
Hydraulic Length	14.00 ft

Subsection: Time of Concentration Calculations
Label: POST-2

Return Event: 2 years
Storm Event: 2 year

Segment #7: TR-55 Shallow Concentrated Flow

Is Paved?	False
Slope	0.089 ft/ft
Average Velocity	4.81 ft/s
Segment Time of Concentration	0.001 hours

Time of Concentration (Composite)

Time of Concentration (Composite)	0.268 hours
-----------------------------------	-------------

==== SCS Channel Flow

$$R = Q_a / W_p$$

$$T_c = \frac{V = (1.49 * (R^{2/3}) * (S_f^{0.5})) / n}{(L_f / V) / 3600}$$

Where:

R = Hydraulic radius
 A_q = Flow area, square feet
 W_p = Wetted perimeter, feet
 V = Velocity, ft/sec
 S_f = Slope, ft/ft
 n = Manning's n
 T_c = Time of concentration, hours
 L_f = Flow length, feet

==== SCS TR-55 Shallow Concentration Flow

Unpaved surface:

$$V = 16.1345 * (S_f^{0.5})$$

Paved Surface:

$$V = 20.3282 * (S_f^{0.5})$$

$$T_c = \frac{(L_f / V) / 3600}{V = \text{Velocity, ft/sec}}$$

Where:

S_f = Slope, ft/ft
 T_c = Time of concentration, hours
 L_f = Flow length, feet

Time of Concentration Results

Segment #1: TR-55 Sheet Flow	
Hydraulic Length	100.00 ft
Manning's n	0.240
Slope	0.030 ft/ft
2 Year 24 Hour Depth	2.4 in
Average Velocity	0.12 ft/s
Segment Time of Concentration	0.236 hours
Segment #2: TR-55 Shallow Concentrated Flow	
Hydraulic Length	95.00 ft
Is Paved?	False
Slope	0.015 ft/ft
Average Velocity	1.98 ft/s
Segment Time of Concentration	0.013 hours
Segment #3: TR-55 Shallow Concentrated Flow	
Hydraulic Length	181.00 ft
Is Paved?	True
Slope	0.055 ft/ft
Average Velocity	4.77 ft/s
Segment Time of Concentration	0.011 hours
Segment #4: TR-55 Shallow Concentrated Flow	
Hydraulic Length	10.00 ft
Is Paved?	False
Slope	0.400 ft/ft
Average Velocity	10.20 ft/s
Segment Time of Concentration	0.000 hours
Segment #5: TR-55 Shallow Concentrated Flow	
Hydraulic Length	172.00 ft
Is Paved?	False
Slope	0.070 ft/ft
Average Velocity	4.27 ft/s
Segment Time of Concentration	0.011 hours
Time of Concentration (Composite)	
Time of Concentration (Composite)	0.271 hours

==== SCS Channel Flow

$$R = Q_a / W_p$$

$$T_c = \frac{V = (1.49 * (R^{2/3}) * (S_f^{0.5})) / n}{(L_f / V) / 3600}$$

Where:

R = Hydraulic radius
 A_q = Flow area, square feet
 W_p = Wetted perimeter, feet
 V = Velocity, ft/sec
 S_f = Slope, ft/ft
 n = Manning's n
 T_c = Time of concentration, hours
 L_f = Flow length, feet

==== SCS TR-55 Shallow Concentration Flow

Unpaved surface:

$$V = 16.1345 * (S_f^{0.5})$$

Paved Surface:

$$V = 20.3282 * (S_f^{0.5})$$

$$T_c = \frac{(L_f / V) / 3600}{V = \text{Velocity, ft/sec}}$$

Where:

S_f = Slope, ft/ft
 T_c = Time of concentration, hours
 L_f = Flow length, feet

Subsection: Runoff CN-Area
Label: POST-1

Return Event: 2 years
Storm Event: 2 year

Runoff Curve Number Data

Soil/Surface Description	CN	Area (acres)	C (%)	UC (%)	Adjusted CN
Meadow - cont. grass (non grazed) - ---- - Soil B	58.000	0.084	0.0	0.0	58.000
Meadow - cont. grass (non grazed) - ---- - Soil D	78.000	0.000	0.0	0.0	78.000
Impervious Areas - Paved parking lots, roofs, driveways, Streets and roads - Soil B	98.000	0.028	0.0	0.0	98.000
Impervious Areas - Paved parking lots, roofs, driveways, Streets and roads - Soil D	98.000	0.022	0.0	0.0	98.000
Impervious Areas - Gravel (w/ right-of- way) - Soil B	85.000	0.324	0.0	0.0	85.000
Impervious Areas - Gravel (w/ right-of- way) - Soil D	91.000	0.221	0.0	0.0	91.000
COMPOSITE AREA & WEIGHTED CN --->	(N/A)	0.679	(N/A)	(N/A)	84.568

Subsection: Runoff CN-Area
Label: POST-2

Return Event: 2 years
Storm Event: 2 year

Runoff Curve Number Data

Soil/Surface Description	CN	Area (acres)	C (%)	UC (%)	Adjusted CN
Woods - good - Soil B	55.000	0.017	0.0	0.0	55.000
Woods - good - Soil C	70.000	0.010	0.0	0.0	70.000
Woods - good - Soil D	77.000	0.046	0.0	0.0	77.000
Meadow - cont. grass (non grazed) - ---- - Soil B	58.000	0.130	0.0	0.0	58.000
Meadow - cont. grass (non grazed) - ---- - Soil C	71.000	0.025	0.0	0.0	71.000
Meadow - cont. grass (non grazed) - ---- - Soil D	78.000	0.084	0.0	0.0	78.000
Impervious Areas - Paved parking lots, roofs, driveways, Streets and roads - Soil B	98.000	0.166	0.0	0.0	98.000
Impervious Areas - Dirt (w/ right-of-way) - Soil B	82.000	0.028	0.0	0.0	82.000
Impervious Areas - Paved parking lots, roofs, driveways, Streets and roads - Soil C	98.000	0.013	0.0	0.0	98.000
Water/Pond - Soil D	98.000	0.035	0.0	0.0	98.000
COMPOSITE AREA & WEIGHTED CN --->	(N/A)	0.554	(N/A)	(N/A)	79.986

Subsection: Runoff CN-Area
Label: PRE-1

Return Event: 2 years
Storm Event: 2 year

Runoff Curve Number Data

Soil/Surface Description	CN	Area (acres)	C (%)	UC (%)	Adjusted CN
Woods - good - Soil B	55.000	0.144	0.0	0.0	55.000
Woods - good - Soil C	70.000	0.048	0.0	0.0	70.000
Woods - good - Soil D	77.000	0.144	0.0	0.0	77.000
Meadow - cont. grass (non grazed) - ---- - Soil B	58.000	0.372	0.0	0.0	58.000
Meadow - cont. grass (non grazed) - ---- - Soil D	78.000	0.256	0.0	0.0	78.000
Impervious Areas - Paved parking lots, roofs, driveways, Streets and roads - Soil B	98.000	0.200	0.0	0.0	98.000
Impervious Areas - Paved parking lots, roofs, driveways, Streets and roads - Soil D	98.000	0.007	0.0	0.0	98.000
Impervious Areas - Dirt (w/ right-of-way) - Soil B	82.000	0.062	0.0	0.0	82.000
COMPOSITE AREA & WEIGHTED CN --->	(N/A)	1.233	(N/A)	(N/A)	72.410

Storm Event	2 year
Return Event	2 years
Duration	24.000 hours
Depth	2.4 in
Time of Concentration (Composite)	0.201 hours
Area (User Defined)	0.679 acres
Computational Time Increment	0.027 hours
Time to Peak (Computed)	12.024 hours
Flow (Peak, Computed)	0.94 ft ³ /s
Output Increment	0.017 hours
Time to Flow (Peak Interpolated Output)	12.017 hours
Flow (Peak Interpolated Output)	0.94 ft ³ /s
Drainage Area	
SCS CN (Composite)	85.000
Area (User Defined)	0.679 acres
Maximum Retention (Pervious)	1.8 in
Maximum Retention (Pervious, 20 percent)	0.4 in
Cumulative Runoff	
Cumulative Runoff Depth (Pervious)	1.1 in
Runoff Volume (Pervious)	0.060 ac-ft
Hydrograph Volume (Area under Hydrograph curve)	
Volume	0.060 ac-ft
SCS Unit Hydrograph Parameters	
Time of Concentration (Composite)	0.201 hours
Computational Time Increment	0.027 hours
Unit Hydrograph Shape Factor	483.432
K Factor	0.749
Receding/Rising, Tr/Tp	1.670
Unit peak, qp	3.83 ft ³ /s
Unit peak time, Tp	0.134 hours
Unit receding limb, Tr	0.536 hours
Total unit time, Tb	0.670 hours

Storm Event	2 year
Return Event	2 years
Duration	24.000 hours
Depth	2.4 in
Time of Concentration (Composite)	0.201 hours
Area (User Defined)	0.679 acres

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
9.500	0.00	0.00	0.00	0.00	0.00
9.583	0.00	0.00	0.00	0.00	0.00
9.667	0.00	0.00	0.00	0.00	0.00
9.750	0.00	0.00	0.00	0.00	0.00
9.833	0.00	0.00	0.00	0.00	0.00
9.917	0.00	0.00	0.00	0.00	0.00
10.000	0.00	0.00	0.00	0.00	0.00
10.083	0.00	0.00	0.00	0.00	0.00
10.167	0.01	0.01	0.01	0.01	0.01
10.250	0.01	0.01	0.01	0.01	0.01
10.333	0.01	0.01	0.01	0.01	0.01
10.417	0.01	0.01	0.01	0.01	0.01
10.500	0.01	0.01	0.01	0.01	0.01
10.583	0.01	0.01	0.01	0.01	0.01
10.667	0.01	0.01	0.01	0.01	0.01
10.750	0.01	0.01	0.01	0.01	0.01
10.833	0.01	0.01	0.02	0.02	0.02
10.917	0.02	0.02	0.02	0.02	0.02
11.000	0.02	0.02	0.02	0.02	0.02
11.083	0.02	0.02	0.02	0.02	0.02
11.167	0.02	0.02	0.02	0.03	0.03
11.250	0.03	0.03	0.03	0.03	0.03
11.333	0.03	0.03	0.03	0.03	0.04
11.417	0.04	0.04	0.04	0.04	0.04
11.500	0.04	0.04	0.05	0.05	0.05
11.583	0.06	0.06	0.07	0.08	0.09
11.667	0.10	0.12	0.14	0.15	0.18
11.750	0.20	0.23	0.26	0.29	0.33
11.833	0.37	0.42	0.47	0.54	0.61
11.917	0.68	0.75	0.81	0.86	0.90
12.000	0.93	0.94	0.93	0.92	0.88
12.083	0.82	0.76	0.69	0.62	0.55
12.167	0.49	0.43	0.39	0.35	0.32
12.250	0.29	0.27	0.25	0.23	0.22
12.333	0.21	0.20	0.19	0.18	0.17
12.417	0.17	0.16	0.15	0.15	0.14
12.500	0.14	0.13	0.13	0.12	0.12
12.583	0.12	0.11	0.11	0.11	0.10
12.667	0.10	0.10	0.10	0.10	0.09
12.750	0.09	0.09	0.09	0.09	0.09
12.833	0.09	0.09	0.09	0.08	0.08
12.917	0.08	0.08	0.08	0.08	0.08
13.000	0.08	0.08	0.08	0.07	0.07

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**


Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
13.083	0.07	0.07	0.07	0.07	0.07
13.167	0.07	0.07	0.07	0.07	0.07
13.250	0.07	0.07	0.07	0.06	0.06
13.333	0.06	0.06	0.06	0.06	0.06
13.417	0.06	0.06	0.06	0.06	0.06
13.500	0.06	0.06	0.06	0.06	0.06
13.583	0.06	0.06	0.06	0.05	0.05
13.667	0.05	0.05	0.05	0.05	0.05
13.750	0.05	0.05	0.05	0.05	0.05
13.833	0.05	0.05	0.05	0.05	0.05
13.917	0.05	0.05	0.05	0.05	0.05
14.000	0.05	0.05	0.05	0.05	0.05
14.083	0.04	0.04	0.04	0.04	0.04
14.167	0.04	0.04	0.04	0.04	0.04
14.250	0.04	0.04	0.04	0.04	0.04
14.333	0.04	0.04	0.04	0.04	0.04
14.417	0.04	0.04	0.04	0.04	0.04
14.500	0.04	0.04	0.04	0.04	0.04
14.583	0.04	0.04	0.04	0.04	0.04
14.667	0.04	0.04	0.04	0.04	0.04
14.750	0.04	0.04	0.04	0.04	0.04
14.833	0.04	0.04	0.04	0.04	0.04
14.917	0.04	0.04	0.04	0.04	0.04
15.000	0.04	0.04	0.04	0.04	0.04
15.083	0.04	0.04	0.04	0.04	0.04
15.167	0.04	0.04	0.04	0.03	0.03
15.250	0.03	0.03	0.03	0.03	0.03
15.333	0.03	0.03	0.03	0.03	0.03
15.417	0.03	0.03	0.03	0.03	0.03
15.500	0.03	0.03	0.03	0.03	0.03
15.583	0.03	0.03	0.03	0.03	0.03
15.667	0.03	0.03	0.03	0.03	0.03
15.750	0.03	0.03	0.03	0.03	0.03
15.833	0.03	0.03	0.03	0.03	0.03
15.917	0.03	0.03	0.03	0.03	0.03
16.000	0.03	0.03	0.03	0.03	0.03
16.083	0.03	0.03	0.03	0.03	0.03
16.167	0.03	0.03	0.03	0.03	0.03
16.250	0.03	0.03	0.03	0.03	0.03
16.333	0.03	0.03	0.03	0.03	0.03
16.417	0.03	0.03	0.03	0.03	0.03
16.500	0.03	0.03	0.03	0.03	0.03
16.583	0.03	0.03	0.03	0.03	0.03
16.667	0.03	0.03	0.03	0.03	0.03
16.750	0.03	0.03	0.03	0.03	0.03
16.833	0.03	0.03	0.03	0.03	0.03
16.917	0.03	0.03	0.03	0.03	0.03
17.000	0.03	0.03	0.03	0.03	0.03
17.083	0.02	0.02	0.02	0.02	0.02
17.167	0.02	0.02	0.02	0.02	0.02
17.250	0.02	0.02	0.02	0.02	0.02
17.333	0.02	0.02	0.02	0.02	0.02

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
17.417	0.02	0.02	0.02	0.02	0.02
17.500	0.02	0.02	0.02	0.02	0.02
17.583	0.02	0.02	0.02	0.02	0.02
17.667	0.02	0.02	0.02	0.02	0.02
17.750	0.02	0.02	0.02	0.02	0.02
17.833	0.02	0.02	0.02	0.02	0.02
17.917	0.02	0.02	0.02	0.02	0.02
18.000	0.02	0.02	0.02	0.02	0.02
18.083	0.02	0.02	0.02	0.02	0.02
18.167	0.02	0.02	0.02	0.02	0.02
18.250	0.02	0.02	0.02	0.02	0.02
18.333	0.02	0.02	0.02	0.02	0.02
18.417	0.02	0.02	0.02	0.02	0.02
18.500	0.02	0.02	0.02	0.02	0.02
18.583	0.02	0.02	0.02	0.02	0.02
18.667	0.02	0.02	0.02	0.02	0.02
18.750	0.02	0.02	0.02	0.02	0.02
18.833	0.02	0.02	0.02	0.02	0.02
18.917	0.02	0.02	0.02	0.02	0.02
19.000	0.02	0.02	0.02	0.02	0.02
19.083	0.02	0.02	0.02	0.02	0.02
19.167	0.02	0.02	0.02	0.02	0.02
19.250	0.02	0.02	0.02	0.02	0.02
19.333	0.02	0.02	0.02	0.02	0.02
19.417	0.02	0.02	0.02	0.02	0.02
19.500	0.02	0.02	0.02	0.02	0.02
19.583	0.02	0.02	0.02	0.02	0.02
19.667	0.02	0.02	0.02	0.02	0.02
19.750	0.02	0.02	0.02	0.02	0.02
19.833	0.02	0.02	0.02	0.02	0.02
19.917	0.02	0.02	0.02	0.02	0.02
20.000	0.02	0.02	0.02	0.02	0.02
20.083	0.02	0.02	0.02	0.02	0.02
20.167	0.02	0.02	0.02	0.02	0.02
20.250	0.02	0.02	0.02	0.02	0.02
20.333	0.02	0.02	0.02	0.02	0.02
20.417	0.02	0.02	0.02	0.02	0.02
20.500	0.02	0.02	0.02	0.02	0.02
20.583	0.02	0.02	0.02	0.02	0.02
20.667	0.02	0.02	0.02	0.02	0.02
20.750	0.02	0.02	0.02	0.02	0.02
20.833	0.02	0.02	0.02	0.02	0.02
20.917	0.02	0.02	0.02	0.02	0.02
21.000	0.02	0.02	0.02	0.02	0.02
21.083	0.02	0.02	0.02	0.02	0.02
21.167	0.02	0.02	0.02	0.02	0.02
21.250	0.02	0.02	0.02	0.02	0.02
21.333	0.02	0.02	0.02	0.02	0.02
21.417	0.02	0.02	0.02	0.02	0.02
21.500	0.02	0.02	0.02	0.02	0.02
21.583	0.02	0.02	0.02	0.02	0.02
21.667	0.02	0.02	0.02	0.02	0.02

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
21.750	0.02	0.02	0.02	0.02	0.02
21.833	0.02	0.02	0.02	0.02	0.02
21.917	0.02	0.02	0.02	0.02	0.02
22.000	0.02	0.02	0.02	0.01	0.01
22.083	0.01	0.01	0.01	0.01	0.01
22.167	0.01	0.01	0.01	0.01	0.01
22.250	0.01	0.01	0.01	0.01	0.01
22.333	0.01	0.01	0.01	0.01	0.01
22.417	0.01	0.01	0.01	0.01	0.01
22.500	0.01	0.01	0.01	0.01	0.01
22.583	0.01	0.01	0.01	0.01	0.01
22.667	0.01	0.01	0.01	0.01	0.01
22.750	0.01	0.01	0.01	0.01	0.01
22.833	0.01	0.01	0.01	0.01	0.01
22.917	0.01	0.01	0.01	0.01	0.01
23.000	0.01	0.01	0.01	0.01	0.01
23.083	0.01	0.01	0.01	0.01	0.01
23.167	0.01	0.01	0.01	0.01	0.01
23.250	0.01	0.01	0.01	0.01	0.01
23.333	0.01	0.01	0.01	0.01	0.01
23.417	0.01	0.01	0.01	0.01	0.01
23.500	0.01	0.01	0.01	0.01	0.01
23.583	0.01	0.01	0.01	0.01	0.01
23.667	0.01	0.01	0.01	0.01	0.01
23.750	0.01	0.01	0.01	0.01	0.01
23.833	0.01	0.01	0.01	0.01	0.01
23.917	0.01	0.01	0.01	0.01	0.01
24.000	0.01	(N/A)	(N/A)	(N/A)	(N/A)



Storm Event	10 year
Return Event	10 years
Duration	24.000 hours
Depth	3.4 in
Time of Concentration (Composite)	0.201 hours
Area (User Defined)	0.679 acres
Computational Time Increment	0.027 hours
Time to Peak (Computed)	12.024 hours
Flow (Peak, Computed)	1.68 ft ³ /s
Output Increment	0.017 hours
Time to Flow (Peak Interpolated Output)	12.017 hours
Flow (Peak Interpolated Output)	1.68 ft ³ /s
Drainage Area	
SCS CN (Composite)	85.000
Area (User Defined)	0.679 acres
Maximum Retention (Pervious)	1.8 in
Maximum Retention (Pervious, 20 percent)	0.4 in
Cumulative Runoff	
Cumulative Runoff Depth (Pervious)	1.9 in
Runoff Volume (Pervious)	0.108 ac-ft
Hydrograph Volume (Area under Hydrograph curve)	
Volume	0.107 ac-ft
SCS Unit Hydrograph Parameters	
Time of Concentration (Composite)	0.201 hours
Computational Time Increment	0.027 hours
Unit Hydrograph Shape Factor	483.432
K Factor	0.749
Receding/Rising, Tr/Tp	1.670
Unit peak, qp	3.83 ft ³ /s
Unit peak time, Tp	0.134 hours
Unit receding limb, Tr	0.536 hours
Total unit time, Tb	0.670 hours

Storm Event	10 year
Return Event	10 years
Duration	24.000 hours
Depth	3.4 in
Time of Concentration (Composite)	0.201 hours
Area (User Defined)	0.679 acres

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
7.700	0.00	0.00	0.00	0.00	0.00
7.783	0.00	0.00	0.00	0.00	0.00
7.867	0.00	0.00	0.00	0.00	0.00
7.950	0.00	0.00	0.00	0.00	0.00
8.033	0.00	0.00	0.00	0.00	0.00
8.117	0.00	0.00	0.00	0.00	0.00
8.200	0.00	0.00	0.00	0.00	0.00
8.283	0.00	0.00	0.00	0.00	0.00
8.367	0.00	0.00	0.00	0.00	0.00
8.450	0.00	0.00	0.00	0.00	0.01
8.533	0.01	0.01	0.01	0.01	0.01
8.617	0.01	0.01	0.01	0.01	0.01
8.700	0.01	0.01	0.01	0.01	0.01
8.783	0.01	0.01	0.01	0.01	0.01
8.867	0.01	0.01	0.01	0.01	0.01
8.950	0.01	0.01	0.01	0.01	0.01
9.033	0.01	0.01	0.01	0.01	0.01
9.117	0.01	0.01	0.01	0.01	0.01
9.200	0.01	0.01	0.01	0.01	0.01
9.283	0.01	0.01	0.01	0.01	0.01
9.367	0.01	0.01	0.01	0.01	0.01
9.450	0.01	0.01	0.01	0.01	0.01
9.533	0.01	0.01	0.01	0.01	0.01
9.617	0.01	0.01	0.01	0.01	0.01
9.700	0.01	0.02	0.02	0.02	0.02
9.783	0.02	0.02	0.02	0.02	0.02
9.867	0.02	0.02	0.02	0.02	0.02
9.950	0.02	0.02	0.02	0.02	0.02
10.033	0.02	0.02	0.02	0.02	0.02
10.117	0.02	0.02	0.02	0.02	0.02
10.200	0.02	0.02	0.02	0.02	0.02
10.283	0.02	0.03	0.03	0.03	0.03
10.367	0.03	0.03	0.03	0.03	0.03
10.450	0.03	0.03	0.03	0.03	0.03
10.533	0.03	0.03	0.03	0.03	0.03
10.617	0.03	0.03	0.04	0.04	0.04
10.700	0.04	0.04	0.04	0.04	0.04
10.783	0.04	0.04	0.04	0.04	0.04
10.867	0.04	0.05	0.05	0.05	0.05
10.950	0.05	0.05	0.05	0.05	0.05
11.033	0.05	0.05	0.05	0.06	0.06
11.117	0.06	0.06	0.06	0.06	0.06
11.200	0.07	0.07	0.07	0.07	0.07

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**


Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
11.283	0.07	0.08	0.08	0.08	0.08
11.367	0.08	0.09	0.09	0.09	0.09
11.450	0.09	0.10	0.10	0.10	0.10
11.533	0.11	0.11	0.12	0.13	0.15
11.617	0.16	0.18	0.20	0.23	0.26
11.700	0.30	0.33	0.38	0.42	0.47
11.783	0.53	0.59	0.66	0.74	0.83
11.867	0.92	1.04	1.16	1.29	1.40
11.950	1.50	1.58	1.64	1.68	1.68
12.033	1.66	1.63	1.55	1.45	1.33
12.117	1.21	1.08	0.96	0.85	0.75
12.200	0.67	0.60	0.55	0.50	0.46
12.283	0.43	0.40	0.38	0.36	0.34
12.367	0.32	0.31	0.29	0.28	0.27
12.450	0.26	0.25	0.24	0.23	0.22
12.533	0.22	0.21	0.20	0.19	0.19
12.617	0.18	0.18	0.17	0.17	0.17
12.700	0.16	0.16	0.16	0.16	0.15
12.783	0.15	0.15	0.15	0.15	0.14
12.867	0.14	0.14	0.14	0.14	0.13
12.950	0.13	0.13	0.13	0.13	0.13
13.033	0.13	0.12	0.12	0.12	0.12
13.117	0.12	0.12	0.12	0.11	0.11
13.200	0.11	0.11	0.11	0.11	0.11
13.283	0.11	0.11	0.11	0.11	0.10
13.367	0.10	0.10	0.10	0.10	0.10
13.450	0.10	0.10	0.10	0.10	0.10
13.533	0.09	0.09	0.09	0.09	0.09
13.617	0.09	0.09	0.09	0.09	0.09
13.700	0.09	0.09	0.09	0.09	0.08
13.783	0.08	0.08	0.08	0.08	0.08
13.867	0.08	0.08	0.08	0.08	0.08
13.950	0.08	0.08	0.08	0.08	0.08
14.033	0.07	0.07	0.07	0.07	0.07
14.117	0.07	0.07	0.07	0.07	0.07
14.200	0.07	0.07	0.07	0.07	0.07
14.283	0.07	0.07	0.07	0.07	0.07
14.367	0.07	0.07	0.07	0.07	0.07
14.450	0.07	0.07	0.07	0.07	0.07
14.533	0.07	0.07	0.07	0.06	0.06
14.617	0.06	0.06	0.06	0.06	0.06
14.700	0.06	0.06	0.06	0.06	0.06
14.783	0.06	0.06	0.06	0.06	0.06
14.867	0.06	0.06	0.06	0.06	0.06
14.950	0.06	0.06	0.06	0.06	0.06
15.033	0.06	0.06	0.06	0.06	0.06
15.117	0.06	0.06	0.06	0.06	0.06
15.200	0.06	0.06	0.06	0.06	0.06
15.283	0.06	0.06	0.06	0.06	0.06
15.367	0.05	0.05	0.05	0.05	0.05
15.450	0.05	0.05	0.05	0.05	0.05
15.533	0.05	0.05	0.05	0.05	0.05

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
15.617	0.05	0.05	0.05	0.05	0.05
15.700	0.05	0.05	0.05	0.05	0.05
15.783	0.05	0.05	0.05	0.05	0.05
15.867	0.05	0.05	0.05	0.05	0.05
15.950	0.05	0.05	0.05	0.05	0.05
16.033	0.05	0.05	0.05	0.05	0.05
16.117	0.05	0.05	0.04	0.04	0.04
16.200	0.04	0.04	0.04	0.04	0.04
16.283	0.04	0.04	0.04	0.04	0.04
16.367	0.04	0.04	0.04	0.04	0.04
16.450	0.04	0.04	0.04	0.04	0.04
16.533	0.04	0.04	0.04	0.04	0.04
16.617	0.04	0.04	0.04	0.04	0.04
16.700	0.04	0.04	0.04	0.04	0.04
16.783	0.04	0.04	0.04	0.04	0.04
16.867	0.04	0.04	0.04	0.04	0.04
16.950	0.04	0.04	0.04	0.04	0.04
17.033	0.04	0.04	0.04	0.04	0.04
17.117	0.04	0.04	0.04	0.04	0.04
17.200	0.04	0.04	0.04	0.04	0.04
17.283	0.04	0.04	0.04	0.04	0.04
17.367	0.04	0.04	0.04	0.04	0.04
17.450	0.04	0.04	0.04	0.04	0.04
17.533	0.04	0.04	0.04	0.04	0.04
17.617	0.04	0.04	0.04	0.04	0.04
17.700	0.04	0.04	0.04	0.04	0.04
17.783	0.04	0.04	0.04	0.04	0.04
17.867	0.04	0.04	0.04	0.04	0.04
17.950	0.04	0.04	0.04	0.04	0.04
18.033	0.04	0.04	0.04	0.04	0.04
18.117	0.04	0.04	0.04	0.04	0.04
18.200	0.04	0.03	0.03	0.03	0.03
18.283	0.03	0.03	0.03	0.03	0.03
18.367	0.03	0.03	0.03	0.03	0.03
18.450	0.03	0.03	0.03	0.03	0.03
18.533	0.03	0.03	0.03	0.03	0.03
18.617	0.03	0.03	0.03	0.03	0.03
18.700	0.03	0.03	0.03	0.03	0.03
18.783	0.03	0.03	0.03	0.03	0.03
18.867	0.03	0.03	0.03	0.03	0.03
18.950	0.03	0.03	0.03	0.03	0.03
19.033	0.03	0.03	0.03	0.03	0.03
19.117	0.03	0.03	0.03	0.03	0.03
19.200	0.03	0.03	0.03	0.03	0.03
19.283	0.03	0.03	0.03	0.03	0.03
19.367	0.03	0.03	0.03	0.03	0.03
19.450	0.03	0.03	0.03	0.03	0.03
19.533	0.03	0.03	0.03	0.03	0.03
19.617	0.03	0.03	0.03	0.03	0.03
19.700	0.03	0.03	0.03	0.03	0.03
19.783	0.03	0.03	0.03	0.03	0.03
19.867	0.03	0.03	0.03	0.03	0.03

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
19.950	0.03	0.03	0.03	0.03	0.03
20.033	0.03	0.03	0.03	0.03	0.03
20.117	0.03	0.03	0.03	0.03	0.03
20.200	0.03	0.03	0.03	0.03	0.03
20.283	0.03	0.03	0.03	0.03	0.03
20.367	0.03	0.03	0.03	0.03	0.03
20.450	0.03	0.03	0.03	0.03	0.03
20.533	0.03	0.03	0.03	0.03	0.03
20.617	0.03	0.03	0.03	0.03	0.03
20.700	0.03	0.03	0.03	0.03	0.03
20.783	0.03	0.03	0.03	0.03	0.02
20.867	0.02	0.02	0.02	0.02	0.02
20.950	0.02	0.02	0.02	0.02	0.02
21.033	0.02	0.02	0.02	0.02	0.02
21.117	0.02	0.02	0.02	0.02	0.02
21.200	0.02	0.02	0.02	0.02	0.02
21.283	0.02	0.02	0.02	0.02	0.02
21.367	0.02	0.02	0.02	0.02	0.02
21.450	0.02	0.02	0.02	0.02	0.02
21.533	0.02	0.02	0.02	0.02	0.02
21.617	0.02	0.02	0.02	0.02	0.02
21.700	0.02	0.02	0.02	0.02	0.02
21.783	0.02	0.02	0.02	0.02	0.02
21.867	0.02	0.02	0.02	0.02	0.02
21.950	0.02	0.02	0.02	0.02	0.02
22.033	0.02	0.02	0.02	0.02	0.02
22.117	0.02	0.02	0.02	0.02	0.02
22.200	0.02	0.02	0.02	0.02	0.02
22.283	0.02	0.02	0.02	0.02	0.02
22.367	0.02	0.02	0.02	0.02	0.02
22.450	0.02	0.02	0.02	0.02	0.02
22.533	0.02	0.02	0.02	0.02	0.02
22.617	0.02	0.02	0.02	0.02	0.02
22.700	0.02	0.02	0.02	0.02	0.02
22.783	0.02	0.02	0.02	0.02	0.02
22.867	0.02	0.02	0.02	0.02	0.02
22.950	0.02	0.02	0.02	0.02	0.02
23.033	0.02	0.02	0.02	0.02	0.02
23.117	0.02	0.02	0.02	0.02	0.02
23.200	0.02	0.02	0.02	0.02	0.02
23.283	0.02	0.02	0.02	0.02	0.02
23.367	0.02	0.02	0.02	0.02	0.02
23.450	0.02	0.02	0.02	0.02	0.02
23.533	0.02	0.02	0.02	0.02	0.02
23.617	0.02	0.02	0.02	0.02	0.02
23.700	0.02	0.02	0.02	0.02	0.02
23.783	0.02	0.02	0.02	0.02	0.02
23.867	0.02	0.02	0.02	0.02	0.02
23.950	0.02	0.02	0.02	0.02	(N/A)



Storm Event	50 year
Return Event	50 years
Duration	24.000 hours
Depth	4.8 in
Time of Concentration (Composite)	0.201 hours
Area (User Defined)	0.679 acres
Computational Time Increment	0.027 hours
Time to Peak (Computed)	11.997 hours
Flow (Peak, Computed)	2.81 ft ³ /s
Output Increment	0.017 hours
Time to Flow (Peak Interpolated Output)	12.000 hours
Flow (Peak Interpolated Output)	2.81 ft ³ /s
Drainage Area	
SCS CN (Composite)	85.000
Area (User Defined)	0.679 acres
Maximum Retention (Pervious)	1.8 in
Maximum Retention (Pervious, 20 percent)	0.4 in
Cumulative Runoff	
Cumulative Runoff Depth (Pervious)	3.2 in
Runoff Volume (Pervious)	0.182 ac-ft
Hydrograph Volume (Area under Hydrograph curve)	
Volume	0.182 ac-ft
SCS Unit Hydrograph Parameters	
Time of Concentration (Composite)	0.201 hours
Computational Time Increment	0.027 hours
Unit Hydrograph Shape Factor	483.432
K Factor	0.749
Receding/Rising, Tr/Tp	1.670
Unit peak, qp	3.83 ft ³ /s
Unit peak time, Tp	0.134 hours
Unit receding limb, Tr	0.536 hours
Total unit time, Tb	0.670 hours

Storm Event	50 year
Return Event	50 years
Duration	24.000 hours
Depth	4.8 in
Time of Concentration (Composite)	0.201 hours
Area (User Defined)	0.679 acres

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
5.933	0.00	0.00	0.00	0.00	0.00
6.017	0.00	0.00	0.00	0.00	0.00
6.100	0.00	0.00	0.00	0.00	0.00
6.183	0.00	0.00	0.00	0.00	0.00
6.267	0.00	0.00	0.00	0.00	0.00
6.350	0.00	0.00	0.00	0.00	0.00
6.433	0.00	0.00	0.00	0.00	0.00
6.517	0.00	0.00	0.00	0.00	0.00
6.600	0.00	0.01	0.01	0.01	0.01
6.683	0.01	0.01	0.01	0.01	0.01
6.767	0.01	0.01	0.01	0.01	0.01
6.850	0.01	0.01	0.01	0.01	0.01
6.933	0.01	0.01	0.01	0.01	0.01
7.017	0.01	0.01	0.01	0.01	0.01
7.100	0.01	0.01	0.01	0.01	0.01
7.183	0.01	0.01	0.01	0.01	0.01
7.267	0.01	0.01	0.01	0.01	0.01
7.350	0.01	0.01	0.01	0.01	0.01
7.433	0.01	0.01	0.01	0.01	0.01
7.517	0.01	0.01	0.01	0.01	0.01
7.600	0.01	0.01	0.01	0.01	0.01
7.683	0.01	0.01	0.01	0.01	0.01
7.767	0.01	0.01	0.01	0.01	0.01
7.850	0.01	0.01	0.01	0.01	0.01
7.933	0.01	0.01	0.01	0.01	0.01
8.017	0.01	0.01	0.01	0.02	0.02
8.100	0.02	0.02	0.02	0.02	0.02
8.183	0.02	0.02	0.02	0.02	0.02
8.267	0.02	0.02	0.02	0.02	0.02
8.350	0.02	0.02	0.02	0.02	0.02
8.433	0.02	0.02	0.02	0.02	0.02
8.517	0.02	0.02	0.02	0.02	0.02
8.600	0.02	0.02	0.02	0.02	0.02
8.683	0.02	0.02	0.02	0.02	0.02
8.767	0.03	0.03	0.03	0.03	0.03
8.850	0.03	0.03	0.03	0.03	0.03
8.933	0.03	0.03	0.03	0.03	0.03
9.017	0.03	0.03	0.03	0.03	0.03
9.100	0.03	0.03	0.03	0.03	0.03
9.183	0.03	0.03	0.03	0.03	0.03
9.267	0.03	0.03	0.03	0.03	0.03
9.350	0.03	0.03	0.04	0.04	0.04
9.433	0.04	0.04	0.04	0.04	0.04

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
9.517	0.04	0.04	0.04	0.04	0.04
9.600	0.04	0.04	0.04	0.04	0.04
9.683	0.04	0.04	0.04	0.04	0.04
9.767	0.04	0.04	0.04	0.04	0.04
9.850	0.04	0.04	0.04	0.05	0.05
9.933	0.05	0.05	0.05	0.05	0.05
10.017	0.05	0.05	0.05	0.05	0.05
10.100	0.05	0.05	0.05	0.05	0.05
10.183	0.06	0.06	0.06	0.06	0.06
10.267	0.06	0.06	0.06	0.06	0.06
10.350	0.06	0.06	0.06	0.07	0.07
10.433	0.07	0.07	0.07	0.07	0.07
10.517	0.07	0.07	0.07	0.07	0.08
10.600	0.08	0.08	0.08	0.08	0.08
10.683	0.08	0.08	0.08	0.09	0.09
10.767	0.09	0.09	0.09	0.09	0.09
10.850	0.10	0.10	0.10	0.10	0.10
10.933	0.10	0.10	0.11	0.11	0.11
11.017	0.11	0.11	0.11	0.12	0.12
11.100	0.12	0.12	0.12	0.13	0.13
11.183	0.13	0.14	0.14	0.14	0.14
11.267	0.15	0.15	0.15	0.16	0.16
11.350	0.16	0.17	0.17	0.18	0.18
11.433	0.18	0.19	0.19	0.19	0.20
11.517	0.21	0.21	0.23	0.24	0.26
11.600	0.29	0.31	0.35	0.39	0.44
11.683	0.50	0.56	0.63	0.70	0.78
11.767	0.87	0.97	1.08	1.19	1.32
11.850	1.47	1.63	1.82	2.02	2.22
11.933	2.40	2.55	2.68	2.76	2.81
12.017	2.80	2.76	2.69	2.55	2.38
12.100	2.18	1.98	1.77	1.57	1.39
12.183	1.22	1.09	0.98	0.89	0.81
12.267	0.74	0.69	0.64	0.60	0.57
12.350	0.54	0.51	0.49	0.47	0.45
12.433	0.43	0.41	0.40	0.38	0.37
12.517	0.35	0.34	0.33	0.32	0.31
12.600	0.30	0.29	0.28	0.27	0.27
12.683	0.26	0.26	0.25	0.25	0.25
12.767	0.24	0.24	0.23	0.23	0.23
12.850	0.23	0.22	0.22	0.22	0.22
12.933	0.21	0.21	0.21	0.20	0.20
13.017	0.20	0.20	0.20	0.19	0.19
13.100	0.19	0.19	0.18	0.18	0.18
13.183	0.18	0.18	0.18	0.17	0.17
13.267	0.17	0.17	0.17	0.17	0.16
13.350	0.16	0.16	0.16	0.16	0.16
13.433	0.16	0.16	0.15	0.15	0.15
13.517	0.15	0.15	0.15	0.15	0.14
13.600	0.14	0.14	0.14	0.14	0.14
13.683	0.14	0.14	0.14	0.13	0.13
13.767	0.13	0.13	0.13	0.13	0.13

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**


Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
13.850	0.13	0.13	0.13	0.12	0.12
13.933	0.12	0.12	0.12	0.12	0.12
14.017	0.12	0.12	0.12	0.12	0.11
14.100	0.11	0.11	0.11	0.11	0.11
14.183	0.11	0.11	0.11	0.11	0.11
14.267	0.11	0.11	0.11	0.11	0.11
14.350	0.11	0.11	0.11	0.10	0.10
14.433	0.10	0.10	0.10	0.10	0.10
14.517	0.10	0.10	0.10	0.10	0.10
14.600	0.10	0.10	0.10	0.10	0.10
14.683	0.10	0.10	0.10	0.10	0.10
14.767	0.10	0.10	0.10	0.10	0.10
14.850	0.10	0.10	0.09	0.09	0.09
14.933	0.09	0.09	0.09	0.09	0.09
15.017	0.09	0.09	0.09	0.09	0.09
15.100	0.09	0.09	0.09	0.09	0.09
15.183	0.09	0.09	0.09	0.09	0.09
15.267	0.09	0.09	0.09	0.09	0.09
15.350	0.09	0.09	0.08	0.08	0.08
15.433	0.08	0.08	0.08	0.08	0.08
15.517	0.08	0.08	0.08	0.08	0.08
15.600	0.08	0.08	0.08	0.08	0.08
15.683	0.08	0.08	0.08	0.08	0.08
15.767	0.08	0.08	0.08	0.08	0.08
15.850	0.08	0.07	0.07	0.07	0.07
15.933	0.07	0.07	0.07	0.07	0.07
16.017	0.07	0.07	0.07	0.07	0.07
16.100	0.07	0.07	0.07	0.07	0.07
16.183	0.07	0.07	0.07	0.07	0.07
16.267	0.07	0.07	0.07	0.07	0.07
16.350	0.07	0.07	0.07	0.07	0.07
16.433	0.07	0.07	0.07	0.07	0.07
16.517	0.07	0.07	0.07	0.07	0.07
16.600	0.07	0.07	0.07	0.07	0.07
16.683	0.07	0.06	0.06	0.06	0.06
16.767	0.06	0.06	0.06	0.06	0.06
16.850	0.06	0.06	0.06	0.06	0.06
16.933	0.06	0.06	0.06	0.06	0.06
17.017	0.06	0.06	0.06	0.06	0.06
17.100	0.06	0.06	0.06	0.06	0.06
17.183	0.06	0.06	0.06	0.06	0.06
17.267	0.06	0.06	0.06	0.06	0.06
17.350	0.06	0.06	0.06	0.06	0.06
17.433	0.06	0.06	0.06	0.06	0.06
17.517	0.06	0.06	0.06	0.06	0.06
17.600	0.06	0.06	0.06	0.06	0.06
17.683	0.06	0.06	0.06	0.06	0.06
17.767	0.06	0.06	0.06	0.06	0.06
17.850	0.06	0.06	0.06	0.06	0.06
17.933	0.06	0.06	0.06	0.06	0.06
18.017	0.06	0.06	0.06	0.05	0.05
18.100	0.05	0.05	0.05	0.05	0.05

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
18.183	0.05	0.05	0.05	0.05	0.05
18.267	0.05	0.05	0.05	0.05	0.05
18.350	0.05	0.05	0.05	0.05	0.05
18.433	0.05	0.05	0.05	0.05	0.05
18.517	0.05	0.05	0.05	0.05	0.05
18.600	0.05	0.05	0.05	0.05	0.05
18.683	0.05	0.05	0.05	0.05	0.05
18.767	0.05	0.05	0.05	0.05	0.05
18.850	0.05	0.05	0.05	0.05	0.05
18.933	0.05	0.05	0.05	0.05	0.05
19.017	0.05	0.05	0.05	0.05	0.05
19.100	0.05	0.05	0.05	0.05	0.05
19.183	0.05	0.05	0.05	0.05	0.05
19.267	0.05	0.05	0.05	0.05	0.05
19.350	0.05	0.05	0.05	0.05	0.04
19.433	0.04	0.04	0.04	0.04	0.04
19.517	0.04	0.04	0.04	0.04	0.04
19.600	0.04	0.04	0.04	0.04	0.04
19.683	0.04	0.04	0.04	0.04	0.04
19.767	0.04	0.04	0.04	0.04	0.04
19.850	0.04	0.04	0.04	0.04	0.04
19.933	0.04	0.04	0.04	0.04	0.04
20.017	0.04	0.04	0.04	0.04	0.04
20.100	0.04	0.04	0.04	0.04	0.04
20.183	0.04	0.04	0.04	0.04	0.04
20.267	0.04	0.04	0.04	0.04	0.04
20.350	0.04	0.04	0.04	0.04	0.04
20.433	0.04	0.04	0.04	0.04	0.04
20.517	0.04	0.04	0.04	0.04	0.04
20.600	0.04	0.04	0.04	0.04	0.04
20.683	0.04	0.04	0.04	0.04	0.04
20.767	0.04	0.04	0.04	0.04	0.04
20.850	0.04	0.04	0.04	0.04	0.04
20.933	0.04	0.04	0.04	0.04	0.04
21.017	0.04	0.04	0.04	0.04	0.04
21.100	0.04	0.04	0.04	0.04	0.04
21.183	0.04	0.04	0.04	0.04	0.04
21.267	0.04	0.04	0.04	0.04	0.04
21.350	0.04	0.04	0.04	0.04	0.04
21.433	0.04	0.04	0.04	0.04	0.04
21.517	0.04	0.04	0.04	0.04	0.04
21.600	0.04	0.04	0.04	0.04	0.04
21.683	0.04	0.04	0.04	0.04	0.04
21.767	0.04	0.04	0.04	0.04	0.04
21.850	0.04	0.04	0.04	0.04	0.04
21.933	0.04	0.04	0.04	0.04	0.04
22.017	0.04	0.04	0.04	0.04	0.04
22.100	0.04	0.04	0.04	0.04	0.04
22.183	0.04	0.04	0.04	0.04	0.04
22.267	0.04	0.04	0.04	0.04	0.04
22.350	0.04	0.04	0.04	0.04	0.04
22.433	0.04	0.04	0.04	0.04	0.04

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
22.517	0.04	0.04	0.04	0.04	0.04
22.600	0.04	0.04	0.04	0.04	0.04
22.683	0.04	0.04	0.04	0.04	0.04
22.767	0.04	0.04	0.04	0.04	0.04
22.850	0.04	0.04	0.04	0.04	0.04
22.933	0.04	0.04	0.04	0.04	0.04
23.017	0.04	0.04	0.04	0.04	0.04
23.100	0.04	0.04	0.04	0.04	0.04
23.183	0.04	0.03	0.03	0.03	0.03
23.267	0.03	0.03	0.03	0.03	0.03
23.350	0.03	0.03	0.03	0.03	0.03
23.433	0.03	0.03	0.03	0.03	0.03
23.517	0.03	0.03	0.03	0.03	0.03
23.600	0.03	0.03	0.03	0.03	0.03
23.683	0.03	0.03	0.03	0.03	0.03
23.767	0.03	0.03	0.03	0.03	0.03
23.850	0.03	0.03	0.03	0.03	0.03
23.933	0.03	0.03	0.03	0.03	0.03



Storm Event	100 year
Return Event	100 years
Duration	24.000 hours
Depth	5.7 in
Time of Concentration (Composite)	0.201 hours
Area (User Defined)	0.679 acres
Computational Time Increment	0.027 hours
Time to Peak (Computed)	11.997 hours
Flow (Peak, Computed)	3.44 ft ³ /s
Output Increment	0.017 hours
Time to Flow (Peak Interpolated Output)	12.000 hours
Flow (Peak Interpolated Output)	3.44 ft ³ /s
Drainage Area	
SCS CN (Composite)	85.000
Area (User Defined)	0.679 acres
Maximum Retention (Pervious)	1.8 in
Maximum Retention (Pervious, 20 percent)	0.4 in
Cumulative Runoff	
Cumulative Runoff Depth (Pervious)	4.0 in
Runoff Volume (Pervious)	0.225 ac-ft
Hydrograph Volume (Area under Hydrograph curve)	
Volume	0.224 ac-ft
SCS Unit Hydrograph Parameters	
Time of Concentration (Composite)	0.201 hours
Computational Time Increment	0.027 hours
Unit Hydrograph Shape Factor	483.432
K Factor	0.749
Receding/Rising, Tr/Tp	1.670
Unit peak, qp	3.83 ft ³ /s
Unit peak time, Tp	0.134 hours
Unit receding limb, Tr	0.536 hours
Total unit time, Tb	0.670 hours

Storm Event	100 year
Return Event	100 years
Duration	24.000 hours
Depth	5.7 in
Time of Concentration (Composite)	0.201 hours
Area (User Defined)	0.679 acres

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
5.283	0.00	0.00	0.00	0.00	0.00
5.367	0.00	0.00	0.00	0.00	0.00
5.450	0.00	0.00	0.00	0.00	0.00
5.533	0.00	0.00	0.00	0.00	0.00
5.617	0.00	0.00	0.00	0.00	0.00
5.700	0.00	0.00	0.00	0.00	0.00
5.783	0.00	0.00	0.00	0.00	0.00
5.867	0.01	0.01	0.01	0.01	0.01
5.950	0.01	0.01	0.01	0.01	0.01
6.033	0.01	0.01	0.01	0.01	0.01
6.117	0.01	0.01	0.01	0.01	0.01
6.200	0.01	0.01	0.01	0.01	0.01
6.283	0.01	0.01	0.01	0.01	0.01
6.367	0.01	0.01	0.01	0.01	0.01
6.450	0.01	0.01	0.01	0.01	0.01
6.533	0.01	0.01	0.01	0.01	0.01
6.617	0.01	0.01	0.01	0.01	0.01
6.700	0.01	0.01	0.01	0.01	0.01
6.783	0.01	0.01	0.01	0.01	0.01
6.867	0.01	0.01	0.01	0.01	0.01
6.950	0.01	0.01	0.01	0.01	0.01
7.033	0.01	0.01	0.01	0.01	0.01
7.117	0.01	0.02	0.02	0.02	0.02
7.200	0.02	0.02	0.02	0.02	0.02
7.283	0.02	0.02	0.02	0.02	0.02
7.367	0.02	0.02	0.02	0.02	0.02
7.450	0.02	0.02	0.02	0.02	0.02
7.533	0.02	0.02	0.02	0.02	0.02
7.617	0.02	0.02	0.02	0.02	0.02
7.700	0.02	0.02	0.02	0.02	0.02
7.783	0.02	0.02	0.02	0.02	0.02
7.867	0.02	0.02	0.02	0.02	0.02
7.950	0.02	0.02	0.02	0.02	0.02
8.033	0.02	0.02	0.02	0.02	0.02
8.117	0.02	0.02	0.02	0.02	0.03
8.200	0.03	0.03	0.03	0.03	0.03
8.283	0.03	0.03	0.03	0.03	0.03
8.367	0.03	0.03	0.03	0.03	0.03
8.450	0.03	0.03	0.03	0.03	0.03
8.533	0.03	0.03	0.03	0.03	0.03
8.617	0.03	0.03	0.03	0.03	0.04
8.700	0.04	0.04	0.04	0.04	0.04
8.783	0.04	0.04	0.04	0.04	0.04

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
8.867	0.04	0.04	0.04	0.04	0.04
8.950	0.04	0.04	0.04	0.04	0.04
9.033	0.04	0.04	0.04	0.04	0.05
9.117	0.05	0.05	0.05	0.05	0.05
9.200	0.05	0.05	0.05	0.05	0.05
9.283	0.05	0.05	0.05	0.05	0.05
9.367	0.05	0.05	0.05	0.05	0.05
9.450	0.05	0.05	0.05	0.05	0.05
9.533	0.05	0.05	0.05	0.05	0.05
9.617	0.05	0.05	0.05	0.05	0.05
9.700	0.06	0.06	0.06	0.06	0.06
9.783	0.06	0.06	0.06	0.06	0.06
9.867	0.06	0.06	0.06	0.06	0.06
9.950	0.06	0.07	0.07	0.07	0.07
10.033	0.07	0.07	0.07	0.07	0.07
10.117	0.07	0.07	0.07	0.07	0.08
10.200	0.08	0.08	0.08	0.08	0.08
10.283	0.08	0.08	0.08	0.08	0.09
10.367	0.09	0.09	0.09	0.09	0.09
10.450	0.09	0.09	0.09	0.10	0.10
10.533	0.10	0.10	0.10	0.10	0.10
10.617	0.10	0.11	0.11	0.11	0.11
10.700	0.11	0.11	0.11	0.12	0.12
10.783	0.12	0.12	0.12	0.12	0.13
10.867	0.13	0.13	0.13	0.13	0.14
10.950	0.14	0.14	0.14	0.14	0.15
11.033	0.15	0.15	0.15	0.15	0.16
11.117	0.16	0.16	0.17	0.17	0.17
11.200	0.18	0.18	0.18	0.19	0.19
11.283	0.20	0.20	0.21	0.21	0.21
11.367	0.22	0.22	0.23	0.23	0.24
11.450	0.24	0.25	0.25	0.26	0.26
11.533	0.28	0.29	0.31	0.34	0.37
11.617	0.40	0.45	0.50	0.56	0.63
11.700	0.71	0.80	0.89	0.99	1.10
11.783	1.22	1.36	1.50	1.65	1.83
11.867	2.03	2.26	2.50	2.74	2.95
11.950	3.14	3.29	3.38	3.44	3.43
12.033	3.37	3.28	3.10	2.90	2.66
12.117	2.40	2.15	1.91	1.69	1.48
12.200	1.32	1.18	1.07	0.98	0.90
12.283	0.83	0.78	0.73	0.69	0.65
12.367	0.62	0.59	0.56	0.54	0.52
12.450	0.50	0.48	0.46	0.44	0.43
12.533	0.41	0.40	0.38	0.37	0.36
12.617	0.35	0.34	0.33	0.32	0.32
12.700	0.31	0.30	0.30	0.29	0.29
12.783	0.29	0.28	0.28	0.27	0.27
12.867	0.27	0.26	0.26	0.26	0.26
12.950	0.25	0.25	0.25	0.24	0.24
13.033	0.24	0.23	0.23	0.23	0.23
13.117	0.22	0.22	0.22	0.22	0.21

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**


Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
13.200	0.21	0.21	0.21	0.21	0.20
13.283	0.20	0.20	0.20	0.20	0.20
13.367	0.19	0.19	0.19	0.19	0.19
13.450	0.19	0.18	0.18	0.18	0.18
13.533	0.18	0.18	0.17	0.17	0.17
13.617	0.17	0.17	0.17	0.17	0.16
13.700	0.16	0.16	0.16	0.16	0.16
13.783	0.16	0.16	0.15	0.15	0.15
13.867	0.15	0.15	0.15	0.15	0.15
13.950	0.15	0.14	0.14	0.14	0.14
14.033	0.14	0.14	0.14	0.14	0.14
14.117	0.13	0.13	0.13	0.13	0.13
14.200	0.13	0.13	0.13	0.13	0.13
14.283	0.13	0.13	0.13	0.13	0.13
14.367	0.13	0.13	0.13	0.12	0.12
14.450	0.12	0.12	0.12	0.12	0.12
14.533	0.12	0.12	0.12	0.12	0.12
14.617	0.12	0.12	0.12	0.12	0.12
14.700	0.12	0.12	0.12	0.12	0.12
14.783	0.12	0.12	0.12	0.11	0.11
14.867	0.11	0.11	0.11	0.11	0.11
14.950	0.11	0.11	0.11	0.11	0.11
15.033	0.11	0.11	0.11	0.11	0.11
15.117	0.11	0.11	0.11	0.11	0.11
15.200	0.11	0.11	0.10	0.10	0.10
15.283	0.10	0.10	0.10	0.10	0.10
15.367	0.10	0.10	0.10	0.10	0.10
15.450	0.10	0.10	0.10	0.10	0.10
15.533	0.10	0.10	0.10	0.10	0.10
15.617	0.10	0.10	0.09	0.09	0.09
15.700	0.09	0.09	0.09	0.09	0.09
15.783	0.09	0.09	0.09	0.09	0.09
15.867	0.09	0.09	0.09	0.09	0.09
15.950	0.09	0.09	0.09	0.09	0.09
16.033	0.09	0.08	0.08	0.08	0.08
16.117	0.08	0.08	0.08	0.08	0.08
16.200	0.08	0.08	0.08	0.08	0.08
16.283	0.08	0.08	0.08	0.08	0.08
16.367	0.08	0.08	0.08	0.08	0.08
16.450	0.08	0.08	0.08	0.08	0.08
16.533	0.08	0.08	0.08	0.08	0.08
16.617	0.08	0.08	0.08	0.08	0.08
16.700	0.08	0.08	0.08	0.08	0.08
16.783	0.08	0.08	0.08	0.08	0.08
16.867	0.08	0.08	0.08	0.08	0.08
16.950	0.08	0.08	0.08	0.07	0.07
17.033	0.07	0.07	0.07	0.07	0.07
17.117	0.07	0.07	0.07	0.07	0.07
17.200	0.07	0.07	0.07	0.07	0.07
17.283	0.07	0.07	0.07	0.07	0.07
17.367	0.07	0.07	0.07	0.07	0.07
17.450	0.07	0.07	0.07	0.07	0.07

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
17.533	0.07	0.07	0.07	0.07	0.07
17.617	0.07	0.07	0.07	0.07	0.07
17.700	0.07	0.07	0.07	0.07	0.07
17.783	0.07	0.07	0.07	0.07	0.07
17.867	0.07	0.07	0.07	0.07	0.07
17.950	0.07	0.07	0.07	0.07	0.07
18.033	0.07	0.07	0.07	0.07	0.07
18.117	0.07	0.06	0.06	0.06	0.06
18.200	0.06	0.06	0.06	0.06	0.06
18.283	0.06	0.06	0.06	0.06	0.06
18.367	0.06	0.06	0.06	0.06	0.06
18.450	0.06	0.06	0.06	0.06	0.06
18.533	0.06	0.06	0.06	0.06	0.06
18.617	0.06	0.06	0.06	0.06	0.06
18.700	0.06	0.06	0.06	0.06	0.06
18.783	0.06	0.06	0.06	0.06	0.06
18.867	0.06	0.06	0.06	0.06	0.06
18.950	0.06	0.06	0.06	0.06	0.06
19.033	0.06	0.06	0.06	0.06	0.06
19.117	0.06	0.06	0.06	0.06	0.06
19.200	0.06	0.06	0.06	0.06	0.05
19.283	0.05	0.05	0.05	0.05	0.05
19.367	0.05	0.05	0.05	0.05	0.05
19.450	0.05	0.05	0.05	0.05	0.05
19.533	0.05	0.05	0.05	0.05	0.05
19.617	0.05	0.05	0.05	0.05	0.05
19.700	0.05	0.05	0.05	0.05	0.05
19.783	0.05	0.05	0.05	0.05	0.05
19.867	0.05	0.05	0.05	0.05	0.05
19.950	0.05	0.05	0.05	0.05	0.05
20.033	0.05	0.05	0.05	0.05	0.05
20.117	0.05	0.05	0.05	0.05	0.05
20.200	0.05	0.05	0.05	0.05	0.05
20.283	0.05	0.05	0.05	0.05	0.05
20.367	0.05	0.05	0.05	0.05	0.05
20.450	0.05	0.05	0.05	0.05	0.05
20.533	0.05	0.05	0.05	0.05	0.05
20.617	0.05	0.05	0.05	0.05	0.05
20.700	0.05	0.05	0.05	0.05	0.05
20.783	0.05	0.05	0.05	0.05	0.05
20.867	0.05	0.05	0.05	0.05	0.05
20.950	0.05	0.05	0.05	0.05	0.05
21.033	0.05	0.05	0.05	0.05	0.05
21.117	0.05	0.05	0.05	0.05	0.05
21.200	0.05	0.05	0.05	0.04	0.04
21.283	0.04	0.04	0.04	0.04	0.04
21.367	0.04	0.04	0.04	0.04	0.04
21.450	0.04	0.04	0.04	0.04	0.04
21.533	0.04	0.04	0.04	0.04	0.04
21.617	0.04	0.04	0.04	0.04	0.04
21.700	0.04	0.04	0.04	0.04	0.04
21.783	0.04	0.04	0.04	0.04	0.04

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
21.867	0.04	0.04	0.04	0.04	0.04
21.950	0.04	0.04	0.04	0.04	0.04
22.033	0.04	0.04	0.04	0.04	0.04
22.117	0.04	0.04	0.04	0.04	0.04
22.200	0.04	0.04	0.04	0.04	0.04
22.283	0.04	0.04	0.04	0.04	0.04
22.367	0.04	0.04	0.04	0.04	0.04
22.450	0.04	0.04	0.04	0.04	0.04
22.533	0.04	0.04	0.04	0.04	0.04
22.617	0.04	0.04	0.04	0.04	0.04
22.700	0.04	0.04	0.04	0.04	0.04
22.783	0.04	0.04	0.04	0.04	0.04
22.867	0.04	0.04	0.04	0.04	0.04
22.950	0.04	0.04	0.04	0.04	0.04
23.033	0.04	0.04	0.04	0.04	0.04
23.117	0.04	0.04	0.04	0.04	0.04
23.200	0.04	0.04	0.04	0.04	0.04
23.283	0.04	0.04	0.04	0.04	0.04
23.367	0.04	0.04	0.04	0.04	0.04
23.450	0.04	0.04	0.04	0.04	0.04
23.533	0.04	0.04	0.04	0.04	0.04
23.617	0.04	0.04	0.04	0.04	0.04
23.700	0.04	0.04	0.04	0.04	0.04
23.783	0.04	0.04	0.04	0.04	0.04
23.867	0.04	0.04	0.04	0.04	0.04
23.950	0.04	0.04	0.04	0.04	(N/A)



Storm Event	2 year
Return Event	2 years
Duration	24.000 hours
Depth	2.4 in
Time of Concentration (Composite)	0.268 hours
Area (User Defined)	0.554 acres
Computational Time	
Increment	0.036 hours
Time to Peak (Computed)	12.072 hours
Flow (Peak, Computed)	0.50 ft ³ /s
Output Increment	0.017 hours
Time to Flow (Peak Interpolated Output)	12.067 hours
Flow (Peak Interpolated Output)	0.50 ft ³ /s
Drainage Area	
SCS CN (Composite)	80.000
Area (User Defined)	0.554 acres
Maximum Retention (Pervious)	2.5 in
Maximum Retention (Pervious, 20 percent)	0.5 in
Cumulative Runoff	
Cumulative Runoff Depth (Pervious)	0.8 in
Runoff Volume (Pervious)	0.036 ac-ft
Hydrograph Volume (Area under Hydrograph curve)	
Volume	0.036 ac-ft
SCS Unit Hydrograph Parameters	
Time of Concentration (Composite)	0.268 hours
Computational Time Increment	0.036 hours
Unit Hydrograph Shape Factor	483.432
K Factor	0.749
Receding/Rising, Tr/Tp	1.670
Unit peak, qp	2.34 ft ³ /s
Unit peak time, Tp	0.179 hours
Unit receding limb, Tr	0.714 hours
Total unit time, Tb	0.893 hours

Storm Event	2 year
Return Event	2 years
Duration	24.000 hours
Depth	2.4 in
Time of Concentration (Composite)	0.268 hours
Area (User Defined)	0.554 acres

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
10.950	0.00	0.00	0.00	0.00	0.00
11.033	0.00	0.00	0.00	0.00	0.00
11.117	0.00	0.00	0.00	0.00	0.00
11.200	0.00	0.00	0.00	0.00	0.01
11.283	0.01	0.01	0.01	0.01	0.01
11.367	0.01	0.01	0.01	0.01	0.01
11.450	0.01	0.01	0.01	0.01	0.01
11.533	0.01	0.01	0.01	0.02	0.02
11.617	0.02	0.02	0.03	0.03	0.03
11.700	0.04	0.05	0.05	0.06	0.07
11.783	0.08	0.10	0.11	0.13	0.15
11.867	0.18	0.21	0.24	0.27	0.31
11.950	0.34	0.38	0.41	0.44	0.46
12.033	0.48	0.49	0.50	0.49	0.48
12.117	0.46	0.44	0.41	0.38	0.35
12.200	0.33	0.30	0.27	0.25	0.23
12.283	0.21	0.20	0.19	0.17	0.16
12.367	0.16	0.15	0.14	0.13	0.13
12.450	0.12	0.12	0.11	0.11	0.10
12.533	0.10	0.10	0.09	0.09	0.09
12.617	0.08	0.08	0.08	0.08	0.07
12.700	0.07	0.07	0.07	0.07	0.07
12.783	0.06	0.06	0.06	0.06	0.06
12.867	0.06	0.06	0.06	0.06	0.06
12.950	0.06	0.05	0.05	0.05	0.05
13.033	0.05	0.05	0.05	0.05	0.05
13.117	0.05	0.05	0.05	0.05	0.05
13.200	0.05	0.05	0.05	0.05	0.05
13.283	0.04	0.04	0.04	0.04	0.04
13.367	0.04	0.04	0.04	0.04	0.04
13.450	0.04	0.04	0.04	0.04	0.04
13.533	0.04	0.04	0.04	0.04	0.04
13.617	0.04	0.04	0.04	0.04	0.04
13.700	0.04	0.04	0.04	0.04	0.04
13.783	0.04	0.03	0.03	0.03	0.03
13.867	0.03	0.03	0.03	0.03	0.03
13.950	0.03	0.03	0.03	0.03	0.03
14.033	0.03	0.03	0.03	0.03	0.03
14.117	0.03	0.03	0.03	0.03	0.03
14.200	0.03	0.03	0.03	0.03	0.03
14.283	0.03	0.03	0.03	0.03	0.03
14.367	0.03	0.03	0.03	0.03	0.03
14.450	0.03	0.03	0.03	0.03	0.03

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**


Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
14.533	0.03	0.03	0.03	0.03	0.03
14.617	0.03	0.03	0.03	0.03	0.03
14.700	0.03	0.03	0.03	0.03	0.03
14.783	0.03	0.03	0.03	0.03	0.03
14.867	0.03	0.03	0.03	0.03	0.03
14.950	0.03	0.03	0.03	0.03	0.03
15.033	0.02	0.02	0.02	0.02	0.02
15.117	0.02	0.02	0.02	0.02	0.02
15.200	0.02	0.02	0.02	0.02	0.02
15.283	0.02	0.02	0.02	0.02	0.02
15.367	0.02	0.02	0.02	0.02	0.02
15.450	0.02	0.02	0.02	0.02	0.02
15.533	0.02	0.02	0.02	0.02	0.02
15.617	0.02	0.02	0.02	0.02	0.02
15.700	0.02	0.02	0.02	0.02	0.02
15.783	0.02	0.02	0.02	0.02	0.02
15.867	0.02	0.02	0.02	0.02	0.02
15.950	0.02	0.02	0.02	0.02	0.02
16.033	0.02	0.02	0.02	0.02	0.02
16.117	0.02	0.02	0.02	0.02	0.02
16.200	0.02	0.02	0.02	0.02	0.02
16.283	0.02	0.02	0.02	0.02	0.02
16.367	0.02	0.02	0.02	0.02	0.02
16.450	0.02	0.02	0.02	0.02	0.02
16.533	0.02	0.02	0.02	0.02	0.02
16.617	0.02	0.02	0.02	0.02	0.02
16.700	0.02	0.02	0.02	0.02	0.02
16.783	0.02	0.02	0.02	0.02	0.02
16.867	0.02	0.02	0.02	0.02	0.02
16.950	0.02	0.02	0.02	0.02	0.02
17.033	0.02	0.02	0.02	0.02	0.02
17.117	0.02	0.02	0.02	0.02	0.02
17.200	0.02	0.02	0.02	0.02	0.02
17.283	0.02	0.02	0.02	0.02	0.02
17.367	0.02	0.02	0.02	0.02	0.02
17.450	0.02	0.02	0.02	0.02	0.02
17.533	0.02	0.02	0.02	0.02	0.02
17.617	0.02	0.02	0.02	0.02	0.02
17.700	0.02	0.02	0.02	0.02	0.02
17.783	0.02	0.02	0.02	0.02	0.02
17.867	0.02	0.02	0.02	0.02	0.02
17.950	0.02	0.02	0.02	0.02	0.02
18.033	0.02	0.02	0.02	0.02	0.02
18.117	0.02	0.02	0.02	0.02	0.02
18.200	0.02	0.02	0.02	0.02	0.02
18.283	0.01	0.01	0.01	0.01	0.01
18.367	0.01	0.01	0.01	0.01	0.01
18.450	0.01	0.01	0.01	0.01	0.01
18.533	0.01	0.01	0.01	0.01	0.01
18.617	0.01	0.01	0.01	0.01	0.01
18.700	0.01	0.01	0.01	0.01	0.01
18.783	0.01	0.01	0.01	0.01	0.01

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
18.867	0.01	0.01	0.01	0.01	0.01
18.950	0.01	0.01	0.01	0.01	0.01
19.033	0.01	0.01	0.01	0.01	0.01
19.117	0.01	0.01	0.01	0.01	0.01
19.200	0.01	0.01	0.01	0.01	0.01
19.283	0.01	0.01	0.01	0.01	0.01
19.367	0.01	0.01	0.01	0.01	0.01
19.450	0.01	0.01	0.01	0.01	0.01
19.533	0.01	0.01	0.01	0.01	0.01
19.617	0.01	0.01	0.01	0.01	0.01
19.700	0.01	0.01	0.01	0.01	0.01
19.783	0.01	0.01	0.01	0.01	0.01
19.867	0.01	0.01	0.01	0.01	0.01
19.950	0.01	0.01	0.01	0.01	0.01
20.033	0.01	0.01	0.01	0.01	0.01
20.117	0.01	0.01	0.01	0.01	0.01
20.200	0.01	0.01	0.01	0.01	0.01
20.283	0.01	0.01	0.01	0.01	0.01
20.367	0.01	0.01	0.01	0.01	0.01
20.450	0.01	0.01	0.01	0.01	0.01
20.533	0.01	0.01	0.01	0.01	0.01
20.617	0.01	0.01	0.01	0.01	0.01
20.700	0.01	0.01	0.01	0.01	0.01
20.783	0.01	0.01	0.01	0.01	0.01
20.867	0.01	0.01	0.01	0.01	0.01
20.950	0.01	0.01	0.01	0.01	0.01
21.033	0.01	0.01	0.01	0.01	0.01
21.117	0.01	0.01	0.01	0.01	0.01
21.200	0.01	0.01	0.01	0.01	0.01
21.283	0.01	0.01	0.01	0.01	0.01
21.367	0.01	0.01	0.01	0.01	0.01
21.450	0.01	0.01	0.01	0.01	0.01
21.533	0.01	0.01	0.01	0.01	0.01
21.617	0.01	0.01	0.01	0.01	0.01
21.700	0.01	0.01	0.01	0.01	0.01
21.783	0.01	0.01	0.01	0.01	0.01
21.867	0.01	0.01	0.01	0.01	0.01
21.950	0.01	0.01	0.01	0.01	0.01
22.033	0.01	0.01	0.01	0.01	0.01
22.117	0.01	0.01	0.01	0.01	0.01
22.200	0.01	0.01	0.01	0.01	0.01
22.283	0.01	0.01	0.01	0.01	0.01
22.367	0.01	0.01	0.01	0.01	0.01
22.450	0.01	0.01	0.01	0.01	0.01
22.533	0.01	0.01	0.01	0.01	0.01
22.617	0.01	0.01	0.01	0.01	0.01
22.700	0.01	0.01	0.01	0.01	0.01
22.783	0.01	0.01	0.01	0.01	0.01
22.867	0.01	0.01	0.01	0.01	0.01
22.950	0.01	0.01	0.01	0.01	0.01
23.033	0.01	0.01	0.01	0.01	0.01
23.117	0.01	0.01	0.01	0.01	0.01

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
23.200	0.01	0.01	0.01	0.01	0.01
23.283	0.01	0.01	0.01	0.01	0.01
23.367	0.01	0.01	0.01	0.01	0.01
23.450	0.01	0.01	0.01	0.01	0.01
23.533	0.01	0.01	0.01	0.01	0.01
23.617	0.01	0.01	0.01	0.01	0.01
23.700	0.01	0.01	0.01	0.01	0.01
23.783	0.01	0.01	0.01	0.01	0.01
23.867	0.01	0.01	0.01	0.01	0.01
23.950	0.01	0.01	0.01	0.01	(N/A)



Storm Event	10 year
Return Event	10 years
Duration	24.000 hours
Depth	3.4 in
Time of Concentration (Composite)	0.268 hours
Area (User Defined)	0.554 acres
Computational Time Increment	0.036 hours
Time to Peak (Computed)	12.072 hours
Flow (Peak, Computed)	1.00 ft ³ /s
Output Increment	0.017 hours
Time to Flow (Peak Interpolated Output)	12.067 hours
Flow (Peak Interpolated Output)	1.00 ft ³ /s
Drainage Area	
SCS CN (Composite)	80.000
Area (User Defined)	0.554 acres
Maximum Retention (Pervious)	2.5 in
Maximum Retention (Pervious, 20 percent)	0.5 in
Cumulative Runoff	
Cumulative Runoff Depth (Pervious)	1.5 in
Runoff Volume (Pervious)	0.071 ac-ft
Hydrograph Volume (Area under Hydrograph curve)	
Volume	0.071 ac-ft
SCS Unit Hydrograph Parameters	
Time of Concentration (Composite)	0.268 hours
Computational Time Increment	0.036 hours
Unit Hydrograph Shape Factor	483.432
K Factor	0.749
Receding/Rising, Tr/Tp	1.670
Unit peak, qp	2.34 ft ³ /s
Unit peak time, Tp	0.179 hours
Unit receding limb, Tr	0.714 hours
Total unit time, Tb	0.893 hours

Storm Event	10 year
Return Event	10 years
Duration	24.000 hours
Depth	3.4 in
Time of Concentration (Composite)	0.268 hours
Area (User Defined)	0.554 acres

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
9.450	0.00	0.00	0.00	0.00	0.00
9.533	0.00	0.00	0.00	0.00	0.00
9.617	0.00	0.00	0.00	0.00	0.00
9.700	0.00	0.00	0.00	0.00	0.00
9.783	0.00	0.00	0.00	0.00	0.00
9.867	0.00	0.00	0.00	0.00	0.00
9.950	0.00	0.00	0.00	0.00	0.00
10.033	0.00	0.00	0.00	0.01	0.01
10.117	0.01	0.01	0.01	0.01	0.01
10.200	0.01	0.01	0.01	0.01	0.01
10.283	0.01	0.01	0.01	0.01	0.01
10.367	0.01	0.01	0.01	0.01	0.01
10.450	0.01	0.01	0.01	0.01	0.01
10.533	0.01	0.01	0.01	0.01	0.01
10.617	0.01	0.01	0.01	0.01	0.01
10.700	0.01	0.01	0.01	0.01	0.01
10.783	0.01	0.02	0.02	0.02	0.02
10.867	0.02	0.02	0.02	0.02	0.02
10.950	0.02	0.02	0.02	0.02	0.02
11.033	0.02	0.02	0.02	0.02	0.02
11.117	0.02	0.02	0.03	0.03	0.03
11.200	0.03	0.03	0.03	0.03	0.03
11.283	0.03	0.03	0.03	0.03	0.04
11.367	0.04	0.04	0.04	0.04	0.04
11.450	0.04	0.04	0.05	0.05	0.05
11.533	0.05	0.05	0.06	0.06	0.06
11.617	0.07	0.08	0.09	0.10	0.11
11.700	0.12	0.14	0.16	0.18	0.20
11.783	0.23	0.26	0.29	0.33	0.38
11.867	0.43	0.48	0.54	0.61	0.68
11.950	0.74	0.81	0.86	0.92	0.95
12.033	0.98	0.99	1.00	0.98	0.95
12.117	0.91	0.86	0.80	0.74	0.69
12.200	0.63	0.57	0.53	0.48	0.44
12.283	0.41	0.38	0.35	0.33	0.31
12.367	0.29	0.27	0.26	0.25	0.24
12.450	0.22	0.21	0.21	0.20	0.19
12.533	0.18	0.17	0.17	0.16	0.16
12.617	0.15	0.15	0.14	0.14	0.13
12.700	0.13	0.13	0.12	0.12	0.12
12.783	0.11	0.11	0.11	0.11	0.11
12.867	0.11	0.10	0.10	0.10	0.10
12.950	0.10	0.10	0.10	0.10	0.09

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**


Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
13.033	0.09	0.09	0.09	0.09	0.09
13.117	0.09	0.09	0.09	0.08	0.08
13.200	0.08	0.08	0.08	0.08	0.08
13.283	0.08	0.08	0.08	0.08	0.08
13.367	0.08	0.08	0.07	0.07	0.07
13.450	0.07	0.07	0.07	0.07	0.07
13.533	0.07	0.07	0.07	0.07	0.07
13.617	0.07	0.07	0.07	0.07	0.06
13.700	0.06	0.06	0.06	0.06	0.06
13.783	0.06	0.06	0.06	0.06	0.06
13.867	0.06	0.06	0.06	0.06	0.06
13.950	0.06	0.06	0.06	0.06	0.06
14.033	0.06	0.05	0.05	0.05	0.05
14.117	0.05	0.05	0.05	0.05	0.05
14.200	0.05	0.05	0.05	0.05	0.05
14.283	0.05	0.05	0.05	0.05	0.05
14.367	0.05	0.05	0.05	0.05	0.05
14.450	0.05	0.05	0.05	0.05	0.05
14.533	0.05	0.05	0.05	0.05	0.05
14.617	0.05	0.05	0.05	0.05	0.05
14.700	0.05	0.05	0.05	0.05	0.05
14.783	0.05	0.05	0.05	0.05	0.04
14.867	0.04	0.04	0.04	0.04	0.04
14.950	0.04	0.04	0.04	0.04	0.04
15.033	0.04	0.04	0.04	0.04	0.04
15.117	0.04	0.04	0.04	0.04	0.04
15.200	0.04	0.04	0.04	0.04	0.04
15.283	0.04	0.04	0.04	0.04	0.04
15.367	0.04	0.04	0.04	0.04	0.04
15.450	0.04	0.04	0.04	0.04	0.04
15.533	0.04	0.04	0.04	0.04	0.04
15.617	0.04	0.04	0.04	0.04	0.04
15.700	0.04	0.04	0.04	0.04	0.04
15.783	0.04	0.04	0.04	0.04	0.04
15.867	0.04	0.04	0.04	0.04	0.03
15.950	0.03	0.03	0.03	0.03	0.03
16.033	0.03	0.03	0.03	0.03	0.03
16.117	0.03	0.03	0.03	0.03	0.03
16.200	0.03	0.03	0.03	0.03	0.03
16.283	0.03	0.03	0.03	0.03	0.03
16.367	0.03	0.03	0.03	0.03	0.03
16.450	0.03	0.03	0.03	0.03	0.03
16.533	0.03	0.03	0.03	0.03	0.03
16.617	0.03	0.03	0.03	0.03	0.03
16.700	0.03	0.03	0.03	0.03	0.03
16.783	0.03	0.03	0.03	0.03	0.03
16.867	0.03	0.03	0.03	0.03	0.03
16.950	0.03	0.03	0.03	0.03	0.03
17.033	0.03	0.03	0.03	0.03	0.03
17.117	0.03	0.03	0.03	0.03	0.03
17.200	0.03	0.03	0.03	0.03	0.03
17.283	0.03	0.03	0.03	0.03	0.03

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
17.367	0.03	0.03	0.03	0.03	0.03
17.450	0.03	0.03	0.03	0.03	0.03
17.533	0.03	0.03	0.03	0.03	0.03
17.617	0.03	0.03	0.03	0.03	0.03
17.700	0.03	0.03	0.03	0.03	0.03
17.783	0.03	0.03	0.03	0.03	0.03
17.867	0.03	0.03	0.03	0.03	0.03
17.950	0.03	0.03	0.03	0.03	0.03
18.033	0.03	0.03	0.03	0.03	0.03
18.117	0.03	0.03	0.03	0.03	0.03
18.200	0.03	0.03	0.03	0.03	0.03
18.283	0.03	0.03	0.03	0.03	0.03
18.367	0.03	0.03	0.03	0.03	0.03
18.450	0.02	0.02	0.02	0.02	0.02
18.533	0.02	0.02	0.02	0.02	0.02
18.617	0.02	0.02	0.02	0.02	0.02
18.700	0.02	0.02	0.02	0.02	0.02
18.783	0.02	0.02	0.02	0.02	0.02
18.867	0.02	0.02	0.02	0.02	0.02
18.950	0.02	0.02	0.02	0.02	0.02
19.033	0.02	0.02	0.02	0.02	0.02
19.117	0.02	0.02	0.02	0.02	0.02
19.200	0.02	0.02	0.02	0.02	0.02
19.283	0.02	0.02	0.02	0.02	0.02
19.367	0.02	0.02	0.02	0.02	0.02
19.450	0.02	0.02	0.02	0.02	0.02
19.533	0.02	0.02	0.02	0.02	0.02
19.617	0.02	0.02	0.02	0.02	0.02
19.700	0.02	0.02	0.02	0.02	0.02
19.783	0.02	0.02	0.02	0.02	0.02
19.867	0.02	0.02	0.02	0.02	0.02
19.950	0.02	0.02	0.02	0.02	0.02
20.033	0.02	0.02	0.02	0.02	0.02
20.117	0.02	0.02	0.02	0.02	0.02
20.200	0.02	0.02	0.02	0.02	0.02
20.283	0.02	0.02	0.02	0.02	0.02
20.367	0.02	0.02	0.02	0.02	0.02
20.450	0.02	0.02	0.02	0.02	0.02
20.533	0.02	0.02	0.02	0.02	0.02
20.617	0.02	0.02	0.02	0.02	0.02
20.700	0.02	0.02	0.02	0.02	0.02
20.783	0.02	0.02	0.02	0.02	0.02
20.867	0.02	0.02	0.02	0.02	0.02
20.950	0.02	0.02	0.02	0.02	0.02
21.033	0.02	0.02	0.02	0.02	0.02
21.117	0.02	0.02	0.02	0.02	0.02
21.200	0.02	0.02	0.02	0.02	0.02
21.283	0.02	0.02	0.02	0.02	0.02
21.367	0.02	0.02	0.02	0.02	0.02
21.450	0.02	0.02	0.02	0.02	0.02
21.533	0.02	0.02	0.02	0.02	0.02
21.617	0.02	0.02	0.02	0.02	0.02

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
21.700	0.02	0.02	0.02	0.02	0.02
21.783	0.02	0.02	0.02	0.02	0.02
21.867	0.02	0.02	0.02	0.02	0.02
21.950	0.02	0.02	0.02	0.02	0.02
22.033	0.02	0.02	0.02	0.02	0.02
22.117	0.02	0.02	0.02	0.02	0.02
22.200	0.02	0.02	0.02	0.02	0.02
22.283	0.02	0.02	0.02	0.02	0.02
22.367	0.02	0.02	0.02	0.02	0.02
22.450	0.02	0.02	0.02	0.02	0.02
22.533	0.02	0.02	0.02	0.02	0.02
22.617	0.02	0.02	0.02	0.02	0.02
22.700	0.02	0.02	0.02	0.02	0.02
22.783	0.02	0.02	0.02	0.02	0.02
22.867	0.02	0.02	0.02	0.02	0.02
22.950	0.02	0.02	0.02	0.02	0.02
23.033	0.02	0.02	0.02	0.02	0.02
23.117	0.02	0.02	0.02	0.02	0.02
23.200	0.02	0.02	0.02	0.02	0.02
23.283	0.02	0.02	0.02	0.02	0.02
23.367	0.02	0.02	0.02	0.02	0.02
23.450	0.02	0.02	0.02	0.02	0.02
23.533	0.02	0.02	0.02	0.02	0.02
23.617	0.02	0.02	0.02	0.02	0.02
23.700	0.02	0.02	0.02	0.02	0.02
23.783	0.02	0.02	0.02	0.02	0.02
23.867	0.02	0.02	0.02	0.02	0.02
23.950	0.02	0.02	0.02	0.02	(N/A)



Storm Event	50 year
Return Event	50 years
Duration	24.000 hours
Depth	4.8 in
Time of Concentration (Composite)	0.268 hours
Area (User Defined)	0.554 acres
Computational Time Increment	0.036 hours
Time to Peak (Computed)	12.037 hours
Flow (Peak, Computed)	1.79 ft ³ /s
Output Increment	0.017 hours
Time to Flow (Peak Interpolated Output)	12.050 hours
Flow (Peak Interpolated Output)	1.79 ft ³ /s
Drainage Area	
SCS CN (Composite)	80.000
Area (User Defined)	0.554 acres
Maximum Retention (Pervious)	2.5 in
Maximum Retention (Pervious, 20 percent)	0.5 in
Cumulative Runoff	
Cumulative Runoff Depth (Pervious)	2.8 in
Runoff Volume (Pervious)	0.127 ac-ft
Hydrograph Volume (Area under Hydrograph curve)	
Volume	0.127 ac-ft
SCS Unit Hydrograph Parameters	
Time of Concentration (Composite)	0.268 hours
Computational Time Increment	0.036 hours
Unit Hydrograph Shape Factor	483.432
K Factor	0.749
Receding/Rising, Tr/Tp	1.670
Unit peak, qp	2.34 ft ³ /s
Unit peak time, Tp	0.179 hours
Unit receding limb, Tr	0.714 hours
Total unit time, Tb	0.893 hours

Storm Event	50 year
Return Event	50 years
Duration	24.000 hours
Depth	4.8 in
Time of Concentration (Composite)	0.268 hours
Area (User Defined)	0.554 acres

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
7.650	0.00	0.00	0.00	0.00	0.00
7.733	0.00	0.00	0.00	0.00	0.00
7.817	0.00	0.00	0.00	0.00	0.00
7.900	0.00	0.00	0.00	0.00	0.00
7.983	0.00	0.00	0.00	0.00	0.00
8.067	0.00	0.00	0.00	0.00	0.00
8.150	0.00	0.00	0.00	0.00	0.00
8.233	0.00	0.00	0.00	0.00	0.00
8.317	0.00	0.00	0.00	0.00	0.00
8.400	0.00	0.01	0.01	0.01	0.01
8.483	0.01	0.01	0.01	0.01	0.01
8.567	0.01	0.01	0.01	0.01	0.01
8.650	0.01	0.01	0.01	0.01	0.01
8.733	0.01	0.01	0.01	0.01	0.01
8.817	0.01	0.01	0.01	0.01	0.01
8.900	0.01	0.01	0.01	0.01	0.01
8.983	0.01	0.01	0.01	0.01	0.01
9.067	0.01	0.01	0.01	0.01	0.01
9.150	0.01	0.01	0.01	0.01	0.01
9.233	0.01	0.01	0.01	0.01	0.01
9.317	0.01	0.01	0.01	0.01	0.01
9.400	0.01	0.01	0.01	0.01	0.02
9.483	0.02	0.02	0.02	0.02	0.02
9.567	0.02	0.02	0.02	0.02	0.02
9.650	0.02	0.02	0.02	0.02	0.02
9.733	0.02	0.02	0.02	0.02	0.02
9.817	0.02	0.02	0.02	0.02	0.02
9.900	0.02	0.02	0.02	0.02	0.02
9.983	0.02	0.02	0.02	0.02	0.02
10.067	0.02	0.02	0.02	0.02	0.02
10.150	0.03	0.03	0.03	0.03	0.03
10.233	0.03	0.03	0.03	0.03	0.03
10.317	0.03	0.03	0.03	0.03	0.03
10.400	0.03	0.03	0.03	0.03	0.03
10.483	0.03	0.04	0.04	0.04	0.04
10.567	0.04	0.04	0.04	0.04	0.04
10.650	0.04	0.04	0.04	0.04	0.04
10.733	0.04	0.04	0.05	0.05	0.05
10.817	0.05	0.05	0.05	0.05	0.05
10.900	0.05	0.05	0.05	0.06	0.06
10.983	0.06	0.06	0.06	0.06	0.06
11.067	0.06	0.06	0.06	0.07	0.07
11.150	0.07	0.07	0.07	0.07	0.07

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**


Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
11.233	0.08	0.08	0.08	0.08	0.08
11.317	0.09	0.09	0.09	0.09	0.09
11.400	0.10	0.10	0.10	0.10	0.11
11.483	0.11	0.11	0.12	0.12	0.12
11.567	0.13	0.14	0.15	0.16	0.18
11.650	0.20	0.22	0.24	0.27	0.30
11.733	0.34	0.39	0.43	0.48	0.54
11.817	0.61	0.68	0.76	0.85	0.95
11.900	1.05	1.17	1.29	1.40	1.51
11.983	1.60	1.69	1.74	1.78	1.79
12.067	1.79	1.75	1.69	1.61	1.51
12.150	1.41	1.31	1.20	1.10	1.00
12.233	0.92	0.83	0.77	0.70	0.65
12.317	0.60	0.57	0.53	0.50	0.47
12.400	0.44	0.42	0.40	0.38	0.36
12.483	0.35	0.33	0.32	0.31	0.29
12.567	0.28	0.27	0.26	0.25	0.24
12.650	0.24	0.23	0.22	0.21	0.21
12.733	0.20	0.20	0.19	0.19	0.19
12.817	0.18	0.18	0.18	0.18	0.17
12.900	0.17	0.17	0.17	0.16	0.16
12.983	0.16	0.16	0.16	0.15	0.15
13.067	0.15	0.15	0.15	0.15	0.14
13.150	0.14	0.14	0.14	0.14	0.14
13.233	0.13	0.13	0.13	0.13	0.13
13.317	0.13	0.13	0.13	0.13	0.12
13.400	0.12	0.12	0.12	0.12	0.12
13.483	0.12	0.12	0.12	0.11	0.11
13.567	0.11	0.11	0.11	0.11	0.11
13.650	0.11	0.11	0.11	0.11	0.10
13.733	0.10	0.10	0.10	0.10	0.10
13.817	0.10	0.10	0.10	0.10	0.10
13.900	0.10	0.10	0.09	0.09	0.09
13.983	0.09	0.09	0.09	0.09	0.09
14.067	0.09	0.09	0.09	0.09	0.09
14.150	0.09	0.09	0.08	0.08	0.08
14.233	0.08	0.08	0.08	0.08	0.08
14.317	0.08	0.08	0.08	0.08	0.08
14.400	0.08	0.08	0.08	0.08	0.08
14.483	0.08	0.08	0.08	0.08	0.08
14.567	0.08	0.08	0.08	0.08	0.08
14.650	0.08	0.08	0.08	0.08	0.08
14.733	0.07	0.07	0.07	0.07	0.07
14.817	0.07	0.07	0.07	0.07	0.07
14.900	0.07	0.07	0.07	0.07	0.07
14.983	0.07	0.07	0.07	0.07	0.07
15.067	0.07	0.07	0.07	0.07	0.07
15.150	0.07	0.07	0.07	0.07	0.07
15.233	0.07	0.07	0.07	0.07	0.07
15.317	0.07	0.07	0.07	0.07	0.07
15.400	0.06	0.06	0.06	0.06	0.06
15.483	0.06	0.06	0.06	0.06	0.06

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
15.567	0.06	0.06	0.06	0.06	0.06
15.650	0.06	0.06	0.06	0.06	0.06
15.733	0.06	0.06	0.06	0.06	0.06
15.817	0.06	0.06	0.06	0.06	0.06
15.900	0.06	0.06	0.06	0.06	0.06
15.983	0.06	0.06	0.06	0.06	0.05
16.067	0.05	0.05	0.05	0.05	0.05
16.150	0.05	0.05	0.05	0.05	0.05
16.233	0.05	0.05	0.05	0.05	0.05
16.317	0.05	0.05	0.05	0.05	0.05
16.400	0.05	0.05	0.05	0.05	0.05
16.483	0.05	0.05	0.05	0.05	0.05
16.567	0.05	0.05	0.05	0.05	0.05
16.650	0.05	0.05	0.05	0.05	0.05
16.733	0.05	0.05	0.05	0.05	0.05
16.817	0.05	0.05	0.05	0.05	0.05
16.900	0.05	0.05	0.05	0.05	0.05
16.983	0.05	0.05	0.05	0.05	0.05
17.067	0.05	0.05	0.05	0.05	0.05
17.150	0.05	0.05	0.05	0.05	0.05
17.233	0.05	0.05	0.05	0.05	0.05
17.317	0.05	0.05	0.05	0.05	0.05
17.400	0.05	0.05	0.05	0.05	0.05
17.483	0.05	0.05	0.05	0.05	0.05
17.567	0.04	0.04	0.04	0.04	0.04
17.650	0.04	0.04	0.04	0.04	0.04
17.733	0.04	0.04	0.04	0.04	0.04
17.817	0.04	0.04	0.04	0.04	0.04
17.900	0.04	0.04	0.04	0.04	0.04
17.983	0.04	0.04	0.04	0.04	0.04
18.067	0.04	0.04	0.04	0.04	0.04
18.150	0.04	0.04	0.04	0.04	0.04
18.233	0.04	0.04	0.04	0.04	0.04
18.317	0.04	0.04	0.04	0.04	0.04
18.400	0.04	0.04	0.04	0.04	0.04
18.483	0.04	0.04	0.04	0.04	0.04
18.567	0.04	0.04	0.04	0.04	0.04
18.650	0.04	0.04	0.04	0.04	0.04
18.733	0.04	0.04	0.04	0.04	0.04
18.817	0.04	0.04	0.04	0.04	0.04
18.900	0.04	0.04	0.04	0.04	0.04
18.983	0.04	0.04	0.04	0.04	0.04
19.067	0.04	0.04	0.04	0.04	0.04
19.150	0.04	0.04	0.04	0.04	0.04
19.233	0.04	0.04	0.04	0.04	0.04
19.317	0.04	0.04	0.04	0.03	0.03
19.400	0.03	0.03	0.03	0.03	0.03
19.483	0.03	0.03	0.03	0.03	0.03
19.567	0.03	0.03	0.03	0.03	0.03
19.650	0.03	0.03	0.03	0.03	0.03
19.733	0.03	0.03	0.03	0.03	0.03
19.817	0.03	0.03	0.03	0.03	0.03

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
19.900	0.03	0.03	0.03	0.03	0.03
19.983	0.03	0.03	0.03	0.03	0.03
20.067	0.03	0.03	0.03	0.03	0.03
20.150	0.03	0.03	0.03	0.03	0.03
20.233	0.03	0.03	0.03	0.03	0.03
20.317	0.03	0.03	0.03	0.03	0.03
20.400	0.03	0.03	0.03	0.03	0.03
20.483	0.03	0.03	0.03	0.03	0.03
20.567	0.03	0.03	0.03	0.03	0.03
20.650	0.03	0.03	0.03	0.03	0.03
20.733	0.03	0.03	0.03	0.03	0.03
20.817	0.03	0.03	0.03	0.03	0.03
20.900	0.03	0.03	0.03	0.03	0.03
20.983	0.03	0.03	0.03	0.03	0.03
21.067	0.03	0.03	0.03	0.03	0.03
21.150	0.03	0.03	0.03	0.03	0.03
21.233	0.03	0.03	0.03	0.03	0.03
21.317	0.03	0.03	0.03	0.03	0.03
21.400	0.03	0.03	0.03	0.03	0.03
21.483	0.03	0.03	0.03	0.03	0.03
21.567	0.03	0.03	0.03	0.03	0.03
21.650	0.03	0.03	0.03	0.03	0.03
21.733	0.03	0.03	0.03	0.03	0.03
21.817	0.03	0.03	0.03	0.03	0.03
21.900	0.03	0.03	0.03	0.03	0.03
21.983	0.03	0.03	0.03	0.03	0.03
22.067	0.03	0.03	0.03	0.03	0.03
22.150	0.03	0.03	0.03	0.03	0.03
22.233	0.03	0.03	0.03	0.03	0.03
22.317	0.03	0.03	0.03	0.03	0.03
22.400	0.03	0.03	0.03	0.03	0.03
22.483	0.03	0.03	0.03	0.03	0.03
22.567	0.03	0.03	0.03	0.03	0.03
22.650	0.03	0.03	0.03	0.03	0.03
22.733	0.03	0.03	0.03	0.03	0.03
22.817	0.03	0.03	0.03	0.03	0.03
22.900	0.03	0.03	0.03	0.03	0.03
22.983	0.03	0.03	0.03	0.03	0.03
23.067	0.03	0.03	0.03	0.03	0.03
23.150	0.03	0.03	0.03	0.03	0.03
23.233	0.03	0.03	0.03	0.03	0.03
23.317	0.03	0.03	0.03	0.03	0.03
23.400	0.03	0.03	0.03	0.03	0.03
23.483	0.03	0.03	0.03	0.03	0.03
23.567	0.03	0.03	0.03	0.03	0.03
23.650	0.03	0.03	0.03	0.03	0.03
23.733	0.03	0.03	0.03	0.03	0.03
23.817	0.03	0.03	0.03	0.03	0.03
23.900	0.03	0.03	0.03	0.03	0.03
23.983	0.03	0.03	(N/A)	(N/A)	(N/A)



Storm Event	100 year
Return Event	100 years
Duration	24.000 hours
Depth	5.7 in
Time of Concentration (Composite)	0.268 hours
Area (User Defined)	0.554 acres
Computational Time Increment	0.036 hours
Time to Peak (Computed)	12.037 hours
Flow (Peak, Computed)	2.25 ft ³ /s
Output Increment	0.017 hours
Time to Flow (Peak Interpolated Output)	12.050 hours
Flow (Peak Interpolated Output)	2.25 ft ³ /s
Drainage Area	
SCS CN (Composite)	80.000
Area (User Defined)	0.554 acres
Maximum Retention (Pervious)	2.5 in
Maximum Retention (Pervious, 20 percent)	0.5 in
Cumulative Runoff	
Cumulative Runoff Depth (Pervious)	3.5 in
Runoff Volume (Pervious)	0.160 ac-ft
Hydrograph Volume (Area under Hydrograph curve)	
Volume	0.160 ac-ft
SCS Unit Hydrograph Parameters	
Time of Concentration (Composite)	0.268 hours
Computational Time Increment	0.036 hours
Unit Hydrograph Shape Factor	483.432
K Factor	0.749
Receding/Rising, Tr/Tp	1.670
Unit peak, qp	2.34 ft ³ /s
Unit peak time, Tp	0.179 hours
Unit receding limb, Tr	0.714 hours
Total unit time, Tb	0.893 hours

Storm Event	100 year
Return Event	100 years
Duration	24.000 hours
Depth	5.7 in
Time of Concentration (Composite)	0.268 hours
Area (User Defined)	0.554 acres

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
6.850	0.00	0.00	0.00	0.00	0.00
6.933	0.00	0.00	0.00	0.00	0.00
7.017	0.00	0.00	0.00	0.00	0.00
7.100	0.00	0.00	0.00	0.00	0.00
7.183	0.00	0.00	0.00	0.00	0.00
7.267	0.00	0.00	0.00	0.00	0.00
7.350	0.00	0.00	0.00	0.00	0.00
7.433	0.00	0.00	0.00	0.00	0.00
7.517	0.00	0.00	0.00	0.00	0.01
7.600	0.01	0.01	0.01	0.01	0.01
7.683	0.01	0.01	0.01	0.01	0.01
7.767	0.01	0.01	0.01	0.01	0.01
7.850	0.01	0.01	0.01	0.01	0.01
7.933	0.01	0.01	0.01	0.01	0.01
8.017	0.01	0.01	0.01	0.01	0.01
8.100	0.01	0.01	0.01	0.01	0.01
8.183	0.01	0.01	0.01	0.01	0.01
8.267	0.01	0.01	0.01	0.01	0.01
8.350	0.01	0.01	0.01	0.01	0.01
8.433	0.01	0.01	0.01	0.01	0.01
8.517	0.01	0.01	0.01	0.01	0.01
8.600	0.01	0.01	0.01	0.01	0.01
8.683	0.01	0.01	0.01	0.01	0.02
8.767	0.02	0.02	0.02	0.02	0.02
8.850	0.02	0.02	0.02	0.02	0.02
8.933	0.02	0.02	0.02	0.02	0.02
9.017	0.02	0.02	0.02	0.02	0.02
9.100	0.02	0.02	0.02	0.02	0.02
9.183	0.02	0.02	0.02	0.02	0.02
9.267	0.02	0.02	0.02	0.02	0.02
9.350	0.02	0.02	0.02	0.02	0.02
9.433	0.02	0.02	0.02	0.02	0.02
9.517	0.03	0.03	0.03	0.03	0.03
9.600	0.03	0.03	0.03	0.03	0.03
9.683	0.03	0.03	0.03	0.03	0.03
9.767	0.03	0.03	0.03	0.03	0.03
9.850	0.03	0.03	0.03	0.03	0.03
9.933	0.03	0.03	0.03	0.03	0.03
10.017	0.03	0.04	0.04	0.04	0.04
10.100	0.04	0.04	0.04	0.04	0.04
10.183	0.04	0.04	0.04	0.04	0.04
10.267	0.04	0.04	0.04	0.04	0.04
10.350	0.05	0.05	0.05	0.05	0.05

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
10.433	0.05	0.05	0.05	0.05	0.05
10.517	0.05	0.05	0.05	0.05	0.06
10.600	0.06	0.06	0.06	0.06	0.06
10.683	0.06	0.06	0.06	0.06	0.06
10.767	0.07	0.07	0.07	0.07	0.07
10.850	0.07	0.07	0.07	0.07	0.08
10.933	0.08	0.08	0.08	0.08	0.08
11.017	0.08	0.08	0.09	0.09	0.09
11.100	0.09	0.09	0.09	0.10	0.10
11.183	0.10	0.10	0.10	0.11	0.11
11.267	0.11	0.11	0.12	0.12	0.12
11.350	0.12	0.13	0.13	0.13	0.14
11.433	0.14	0.14	0.15	0.15	0.15
11.517	0.16	0.16	0.17	0.18	0.19
11.600	0.20	0.22	0.24	0.26	0.29
11.683	0.32	0.36	0.40	0.46	0.51
11.767	0.57	0.64	0.71	0.79	0.88
11.850	0.98	1.10	1.22	1.36	1.50
11.933	1.64	1.78	1.92	2.02	2.13
12.017	2.19	2.24	2.25	2.24	2.19
12.100	2.11	2.01	1.89	1.76	1.63
12.183	1.49	1.37	1.24	1.14	1.03
12.267	0.95	0.87	0.81	0.75	0.70
12.350	0.65	0.61	0.58	0.55	0.52
12.433	0.49	0.47	0.45	0.43	0.41
12.517	0.39	0.37	0.36	0.35	0.33
12.600	0.32	0.31	0.30	0.29	0.28
12.683	0.27	0.26	0.26	0.25	0.24
12.767	0.24	0.23	0.23	0.22	0.22
12.850	0.22	0.21	0.21	0.21	0.21
12.933	0.20	0.20	0.20	0.20	0.19
13.017	0.19	0.19	0.19	0.18	0.18
13.100	0.18	0.18	0.17	0.17	0.17
13.183	0.17	0.17	0.17	0.16	0.16
13.267	0.16	0.16	0.16	0.16	0.16
13.350	0.15	0.15	0.15	0.15	0.15
13.433	0.15	0.15	0.14	0.14	0.14
13.517	0.14	0.14	0.14	0.14	0.14
13.600	0.13	0.13	0.13	0.13	0.13
13.683	0.13	0.13	0.13	0.13	0.13
13.767	0.12	0.12	0.12	0.12	0.12
13.850	0.12	0.12	0.12	0.12	0.12
13.933	0.12	0.11	0.11	0.11	0.11
14.017	0.11	0.11	0.11	0.11	0.11
14.100	0.11	0.11	0.10	0.10	0.10
14.183	0.10	0.10	0.10	0.10	0.10
14.267	0.10	0.10	0.10	0.10	0.10
14.350	0.10	0.10	0.10	0.10	0.10
14.433	0.10	0.10	0.10	0.10	0.10
14.517	0.09	0.09	0.09	0.09	0.09
14.600	0.09	0.09	0.09	0.09	0.09
14.683	0.09	0.09	0.09	0.09	0.09

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.


Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
14.767	0.09	0.09	0.09	0.09	0.09
14.850	0.09	0.09	0.09	0.09	0.09
14.933	0.09	0.09	0.09	0.09	0.09
15.017	0.09	0.09	0.08	0.08	0.08
15.100	0.08	0.08	0.08	0.08	0.08
15.183	0.08	0.08	0.08	0.08	0.08
15.267	0.08	0.08	0.08	0.08	0.08
15.350	0.08	0.08	0.08	0.08	0.08
15.433	0.08	0.08	0.08	0.08	0.08
15.517	0.08	0.08	0.08	0.08	0.08
15.600	0.07	0.07	0.07	0.07	0.07
15.683	0.07	0.07	0.07	0.07	0.07
15.767	0.07	0.07	0.07	0.07	0.07
15.850	0.07	0.07	0.07	0.07	0.07
15.933	0.07	0.07	0.07	0.07	0.07
16.017	0.07	0.07	0.07	0.07	0.07
16.100	0.07	0.07	0.06	0.06	0.06
16.183	0.06	0.06	0.06	0.06	0.06
16.267	0.06	0.06	0.06	0.06	0.06
16.350	0.06	0.06	0.06	0.06	0.06
16.433	0.06	0.06	0.06	0.06	0.06
16.517	0.06	0.06	0.06	0.06	0.06
16.600	0.06	0.06	0.06	0.06	0.06
16.683	0.06	0.06	0.06	0.06	0.06
16.767	0.06	0.06	0.06	0.06	0.06
16.850	0.06	0.06	0.06	0.06	0.06
16.933	0.06	0.06	0.06	0.06	0.06
17.017	0.06	0.06	0.06	0.06	0.06
17.100	0.06	0.06	0.06	0.06	0.06
17.183	0.06	0.06	0.06	0.06	0.06
17.267	0.06	0.06	0.06	0.06	0.06
17.350	0.06	0.06	0.06	0.06	0.06
17.433	0.06	0.06	0.05	0.05	0.05
17.517	0.05	0.05	0.05	0.05	0.05
17.600	0.05	0.05	0.05	0.05	0.05
17.683	0.05	0.05	0.05	0.05	0.05
17.767	0.05	0.05	0.05	0.05	0.05
17.850	0.05	0.05	0.05	0.05	0.05
17.933	0.05	0.05	0.05	0.05	0.05
18.017	0.05	0.05	0.05	0.05	0.05
18.100	0.05	0.05	0.05	0.05	0.05
18.183	0.05	0.05	0.05	0.05	0.05
18.267	0.05	0.05	0.05	0.05	0.05
18.350	0.05	0.05	0.05	0.05	0.05
18.433	0.05	0.05	0.05	0.05	0.05
18.517	0.05	0.05	0.05	0.05	0.05
18.600	0.05	0.05	0.05	0.05	0.05
18.683	0.05	0.05	0.05	0.05	0.05
18.767	0.05	0.05	0.05	0.05	0.05
18.850	0.05	0.05	0.05	0.05	0.05
18.933	0.05	0.04	0.04	0.04	0.04
19.017	0.04	0.04	0.04	0.04	0.04

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
19.100	0.04	0.04	0.04	0.04	0.04
19.183	0.04	0.04	0.04	0.04	0.04
19.267	0.04	0.04	0.04	0.04	0.04
19.350	0.04	0.04	0.04	0.04	0.04
19.433	0.04	0.04	0.04	0.04	0.04
19.517	0.04	0.04	0.04	0.04	0.04
19.600	0.04	0.04	0.04	0.04	0.04
19.683	0.04	0.04	0.04	0.04	0.04
19.767	0.04	0.04	0.04	0.04	0.04
19.850	0.04	0.04	0.04	0.04	0.04
19.933	0.04	0.04	0.04	0.04	0.04
20.017	0.04	0.04	0.04	0.04	0.04
20.100	0.04	0.04	0.04	0.04	0.04
20.183	0.04	0.04	0.04	0.04	0.04
20.267	0.04	0.04	0.04	0.04	0.04
20.350	0.04	0.04	0.04	0.04	0.04
20.433	0.04	0.04	0.04	0.04	0.04
20.517	0.04	0.04	0.04	0.04	0.04
20.600	0.04	0.04	0.04	0.04	0.04
20.683	0.04	0.04	0.04	0.04	0.04
20.767	0.04	0.04	0.04	0.04	0.04
20.850	0.04	0.04	0.04	0.04	0.04
20.933	0.04	0.04	0.04	0.04	0.04
21.017	0.04	0.04	0.04	0.04	0.04
21.100	0.04	0.04	0.04	0.04	0.04
21.183	0.04	0.04	0.04	0.03	0.03
21.267	0.03	0.03	0.03	0.03	0.03
21.350	0.03	0.03	0.03	0.03	0.03
21.433	0.03	0.03	0.03	0.03	0.03
21.517	0.03	0.03	0.03	0.03	0.03
21.600	0.03	0.03	0.03	0.03	0.03
21.683	0.03	0.03	0.03	0.03	0.03
21.767	0.03	0.03	0.03	0.03	0.03
21.850	0.03	0.03	0.03	0.03	0.03
21.933	0.03	0.03	0.03	0.03	0.03
22.017	0.03	0.03	0.03	0.03	0.03
22.100	0.03	0.03	0.03	0.03	0.03
22.183	0.03	0.03	0.03	0.03	0.03
22.267	0.03	0.03	0.03	0.03	0.03
22.350	0.03	0.03	0.03	0.03	0.03
22.433	0.03	0.03	0.03	0.03	0.03
22.517	0.03	0.03	0.03	0.03	0.03
22.600	0.03	0.03	0.03	0.03	0.03
22.683	0.03	0.03	0.03	0.03	0.03
22.767	0.03	0.03	0.03	0.03	0.03
22.850	0.03	0.03	0.03	0.03	0.03
22.933	0.03	0.03	0.03	0.03	0.03
23.017	0.03	0.03	0.03	0.03	0.03
23.100	0.03	0.03	0.03	0.03	0.03
23.183	0.03	0.03	0.03	0.03	0.03
23.267	0.03	0.03	0.03	0.03	0.03
23.350	0.03	0.03	0.03	0.03	0.03

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
23.433	0.03	0.03	0.03	0.03	0.03
23.517	0.03	0.03	0.03	0.03	0.03
23.600	0.03	0.03	0.03	0.03	0.03
23.683	0.03	0.03	0.03	0.03	0.03
23.767	0.03	0.03	0.03	0.03	0.03
23.850	0.03	0.03	0.03	0.03	0.03
23.933	0.03	0.03	0.03	0.03	0.03



Storm Event	2 year
Return Event	2 years
Duration	24.000 hours
Depth	2.4 in
Time of Concentration (Composite)	0.271 hours
Area (User Defined)	1.233 acres
Computational Time	
Increment	0.036 hours
Time to Peak (Computed)	12.084 hours
Flow (Peak, Computed)	0.54 ft ³ /s
Output Increment	0.017 hours
Time to Flow (Peak Interpolated Output)	12.083 hours
Flow (Peak Interpolated Output)	0.54 ft ³ /s
Drainage Area	
SCS CN (Composite)	72.000
Area (User Defined)	1.233 acres
Maximum Retention (Pervious)	3.9 in
Maximum Retention (Pervious, 20 percent)	0.8 in
Cumulative Runoff	
Cumulative Runoff Depth (Pervious)	0.5 in
Runoff Volume (Pervious)	0.047 ac-ft
Hydrograph Volume (Area under Hydrograph curve)	
Volume	0.046 ac-ft
SCS Unit Hydrograph Parameters	
Time of Concentration (Composite)	0.271 hours
Computational Time Increment	0.036 hours
Unit Hydrograph Shape Factor	483.432
K Factor	0.749
Receding/Rising, Tr/Tp	1.670
Unit peak, qp	5.15 ft ³ /s
Unit peak time, Tp	0.181 hours
Unit receding limb, Tr	0.724 hours
Total unit time, Tb	0.905 hours

Storm Event	2 year
Return Event	2 years
Duration	24.000 hours
Depth	2.4 in
Time of Concentration (Composite)	0.271 hours
Area (User Defined)	1.233 acres

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
11.700	0.00	0.00	0.00	0.01	0.01
11.783	0.01	0.02	0.03	0.04	0.06
11.867	0.08	0.12	0.15	0.19	0.23
11.950	0.28	0.32	0.37	0.41	0.45
12.033	0.49	0.52	0.53	0.54	0.54
12.117	0.53	0.51	0.48	0.46	0.43
12.200	0.40	0.37	0.34	0.32	0.29
12.283	0.27	0.26	0.24	0.23	0.22
12.367	0.21	0.20	0.19	0.18	0.17
12.450	0.17	0.16	0.15	0.15	0.14
12.533	0.14	0.13	0.13	0.13	0.12
12.617	0.12	0.11	0.11	0.11	0.10
12.700	0.10	0.10	0.10	0.10	0.09
12.783	0.09	0.09	0.09	0.09	0.09
12.867	0.09	0.08	0.08	0.08	0.08
12.950	0.08	0.08	0.08	0.08	0.08
13.033	0.08	0.08	0.07	0.07	0.07
13.117	0.07	0.07	0.07	0.07	0.07
13.200	0.07	0.07	0.07	0.07	0.07
13.283	0.07	0.07	0.07	0.06	0.06
13.367	0.06	0.06	0.06	0.06	0.06
13.450	0.06	0.06	0.06	0.06	0.06
13.533	0.06	0.06	0.06	0.06	0.06
13.617	0.06	0.06	0.06	0.06	0.06
13.700	0.05	0.05	0.05	0.05	0.05
13.783	0.05	0.05	0.05	0.05	0.05
13.867	0.05	0.05	0.05	0.05	0.05
13.950	0.05	0.05	0.05	0.05	0.05
14.033	0.05	0.05	0.05	0.05	0.05
14.117	0.05	0.05	0.05	0.05	0.04
14.200	0.04	0.04	0.04	0.04	0.04
14.283	0.04	0.04	0.04	0.04	0.04
14.367	0.04	0.04	0.04	0.04	0.04
14.450	0.04	0.04	0.04	0.04	0.04
14.533	0.04	0.04	0.04	0.04	0.04
14.617	0.04	0.04	0.04	0.04	0.04
14.700	0.04	0.04	0.04	0.04	0.04
14.783	0.04	0.04	0.04	0.04	0.04
14.867	0.04	0.04	0.04	0.04	0.04
14.950	0.04	0.04	0.04	0.04	0.04
15.033	0.04	0.04	0.04	0.04	0.04
15.117	0.04	0.04	0.04	0.04	0.04
15.200	0.04	0.04	0.04	0.04	0.04

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**


Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
15.283	0.04	0.04	0.04	0.04	0.04
15.367	0.04	0.04	0.04	0.04	0.04
15.450	0.04	0.04	0.04	0.03	0.03
15.533	0.03	0.03	0.03	0.03	0.03
15.617	0.03	0.03	0.03	0.03	0.03
15.700	0.03	0.03	0.03	0.03	0.03
15.783	0.03	0.03	0.03	0.03	0.03
15.867	0.03	0.03	0.03	0.03	0.03
15.950	0.03	0.03	0.03	0.03	0.03
16.033	0.03	0.03	0.03	0.03	0.03
16.117	0.03	0.03	0.03	0.03	0.03
16.200	0.03	0.03	0.03	0.03	0.03
16.283	0.03	0.03	0.03	0.03	0.03
16.367	0.03	0.03	0.03	0.03	0.03
16.450	0.03	0.03	0.03	0.03	0.03
16.533	0.03	0.03	0.03	0.03	0.03
16.617	0.03	0.03	0.03	0.03	0.03
16.700	0.03	0.03	0.03	0.03	0.03
16.783	0.03	0.03	0.03	0.03	0.03
16.867	0.03	0.03	0.03	0.03	0.03
16.950	0.03	0.03	0.03	0.03	0.03
17.033	0.03	0.03	0.03	0.03	0.03
17.117	0.03	0.03	0.03	0.03	0.03
17.200	0.03	0.03	0.03	0.03	0.03
17.283	0.03	0.03	0.03	0.03	0.03
17.367	0.03	0.03	0.03	0.03	0.03
17.450	0.03	0.03	0.03	0.03	0.03
17.533	0.03	0.03	0.03	0.03	0.03
17.617	0.03	0.03	0.03	0.03	0.03
17.700	0.03	0.03	0.03	0.03	0.03
17.783	0.03	0.03	0.03	0.03	0.03
17.867	0.03	0.02	0.02	0.02	0.02
17.950	0.02	0.02	0.02	0.02	0.02
18.033	0.02	0.02	0.02	0.02	0.02
18.117	0.02	0.02	0.02	0.02	0.02
18.200	0.02	0.02	0.02	0.02	0.02
18.283	0.02	0.02	0.02	0.02	0.02
18.367	0.02	0.02	0.02	0.02	0.02
18.450	0.02	0.02	0.02	0.02	0.02
18.533	0.02	0.02	0.02	0.02	0.02
18.617	0.02	0.02	0.02	0.02	0.02
18.700	0.02	0.02	0.02	0.02	0.02
18.783	0.02	0.02	0.02	0.02	0.02
18.867	0.02	0.02	0.02	0.02	0.02
18.950	0.02	0.02	0.02	0.02	0.02
19.033	0.02	0.02	0.02	0.02	0.02
19.117	0.02	0.02	0.02	0.02	0.02
19.200	0.02	0.02	0.02	0.02	0.02
19.283	0.02	0.02	0.02	0.02	0.02
19.367	0.02	0.02	0.02	0.02	0.02
19.450	0.02	0.02	0.02	0.02	0.02
19.533	0.02	0.02	0.02	0.02	0.02

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
19.617	0.02	0.02	0.02	0.02	0.02
19.700	0.02	0.02	0.02	0.02	0.02
19.783	0.02	0.02	0.02	0.02	0.02
19.867	0.02	0.02	0.02	0.02	0.02
19.950	0.02	0.02	0.02	0.02	0.02
20.033	0.02	0.02	0.02	0.02	0.02
20.117	0.02	0.02	0.02	0.02	0.02
20.200	0.02	0.02	0.02	0.02	0.02
20.283	0.02	0.02	0.02	0.02	0.02
20.367	0.02	0.02	0.02	0.02	0.02
20.450	0.02	0.02	0.02	0.02	0.02
20.533	0.02	0.02	0.02	0.02	0.02
20.617	0.02	0.02	0.02	0.02	0.02
20.700	0.02	0.02	0.02	0.02	0.02
20.783	0.02	0.02	0.02	0.02	0.02
20.867	0.02	0.02	0.02	0.02	0.02
20.950	0.02	0.02	0.02	0.02	0.02
21.033	0.02	0.02	0.02	0.02	0.02
21.117	0.02	0.02	0.02	0.02	0.02
21.200	0.02	0.02	0.02	0.02	0.02
21.283	0.02	0.02	0.02	0.02	0.02
21.367	0.02	0.02	0.02	0.02	0.02
21.450	0.02	0.02	0.02	0.02	0.02
21.533	0.02	0.02	0.02	0.02	0.02
21.617	0.02	0.02	0.02	0.02	0.02
21.700	0.02	0.02	0.02	0.02	0.02
21.783	0.02	0.02	0.02	0.02	0.02
21.867	0.02	0.02	0.02	0.02	0.02
21.950	0.02	0.02	0.02	0.02	0.02
22.033	0.02	0.02	0.02	0.02	0.02
22.117	0.02	0.02	0.02	0.02	0.02
22.200	0.02	0.02	0.02	0.02	0.02
22.283	0.02	0.02	0.02	0.02	0.02
22.367	0.02	0.02	0.02	0.02	0.02
22.450	0.02	0.02	0.02	0.02	0.02
22.533	0.02	0.02	0.02	0.02	0.02
22.617	0.02	0.02	0.02	0.02	0.02
22.700	0.02	0.02	0.02	0.02	0.02
22.783	0.02	0.02	0.02	0.02	0.02
22.867	0.02	0.02	0.02	0.02	0.02
22.950	0.02	0.02	0.02	0.02	0.02
23.033	0.02	0.02	0.02	0.02	0.02
23.117	0.02	0.02	0.02	0.02	0.02
23.200	0.02	0.02	0.02	0.02	0.02
23.283	0.02	0.02	0.02	0.02	0.02
23.367	0.02	0.02	0.02	0.02	0.02
23.450	0.02	0.02	0.02	0.02	0.02
23.533	0.02	0.02	0.02	0.02	0.02
23.617	0.02	0.02	0.02	0.02	0.02
23.700	0.02	0.02	0.02	0.02	0.02
23.783	0.02	0.02	0.02	0.02	0.02
23.867	0.02	0.02	0.02	0.02	0.02

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
23.950	0.02	0.02	0.02	0.02	(N/A)



Storm Event	10 year
Return Event	10 years
Duration	24.000 hours
Depth	3.4 in
Time of Concentration (Composite)	0.271 hours
Area (User Defined)	1.233 acres
Computational Time Increment	0.036 hours
Time to Peak (Computed)	12.048 hours
Flow (Peak, Computed)	2.00 ft ³ /s
Output Increment	0.017 hours
Time to Flow (Peak Interpolated Output)	12.050 hours
Flow (Peak Interpolated Output)	2.00 ft ³ /s
Drainage Area	
SCS CN (Composite)	72.000
Area (User Defined)	1.233 acres
Maximum Retention (Pervious)	3.9 in
Maximum Retention (Pervious, 20 percent)	0.8 in
Cumulative Runoff	
Cumulative Runoff Depth (Pervious)	1.4 in
Runoff Volume (Pervious)	0.144 ac-ft
Hydrograph Volume (Area under Hydrograph curve)	
Volume	0.143 ac-ft
SCS Unit Hydrograph Parameters	
Time of Concentration (Composite)	0.271 hours
Computational Time Increment	0.036 hours
Unit Hydrograph Shape Factor	483.432
K Factor	0.749
Receding/Rising, Tr/Tp	1.670
Unit peak, qp	5.15 ft ³ /s
Unit peak time, Tp	0.181 hours
Unit receding limb, Tr	0.724 hours
Total unit time, Tb	0.905 hours

Storm Event	10 year
Return Event	10 years
Duration	24.000 hours
Depth	3.4 in
Time of Concentration (Composite)	0.271 hours
Area (User Defined)	1.233 acres

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
9.900	0.00	0.00	0.00	0.00	0.00
9.983	0.00	0.00	0.00	0.00	0.00
10.067	0.00	0.00	0.00	0.00	0.00
10.150	0.00	0.00	0.00	0.01	0.01
10.233	0.01	0.01	0.01	0.01	0.01
10.317	0.01	0.01	0.01	0.01	0.01
10.400	0.01	0.01	0.01	0.01	0.01
10.483	0.01	0.01	0.01	0.01	0.01
10.567	0.01	0.01	0.01	0.02	0.02
10.650	0.02	0.02	0.02	0.02	0.02
10.733	0.02	0.02	0.02	0.02	0.02
10.817	0.02	0.02	0.02	0.02	0.03
10.900	0.03	0.03	0.03	0.03	0.03
10.983	0.03	0.03	0.03	0.03	0.03
11.067	0.03	0.04	0.04	0.04	0.04
11.150	0.04	0.04	0.04	0.04	0.05
11.233	0.05	0.05	0.05	0.05	0.05
11.317	0.06	0.06	0.06	0.06	0.06
11.400	0.07	0.07	0.07	0.07	0.07
11.483	0.08	0.08	0.08	0.09	0.09
11.567	0.10	0.10	0.11	0.12	0.14
11.650	0.15	0.17	0.19	0.22	0.25
11.733	0.29	0.33	0.37	0.43	0.48
11.817	0.55	0.62	0.71	0.80	0.92
11.900	1.04	1.17	1.31	1.45	1.58
11.983	1.70	1.81	1.89	1.95	2.00
12.067	1.99	1.98	1.92	1.85	1.75
12.150	1.64	1.53	1.41	1.30	1.19
12.233	1.09	1.00	0.92	0.85	0.79
12.317	0.74	0.69	0.65	0.61	0.58
12.400	0.55	0.52	0.49	0.47	0.45
12.483	0.43	0.41	0.40	0.38	0.37
12.567	0.35	0.34	0.33	0.32	0.31
12.650	0.30	0.29	0.28	0.27	0.26
12.733	0.26	0.25	0.25	0.24	0.24
12.817	0.23	0.23	0.22	0.22	0.22
12.900	0.22	0.21	0.21	0.21	0.20
12.983	0.20	0.20	0.20	0.19	0.19
13.067	0.19	0.19	0.19	0.18	0.18
13.150	0.18	0.18	0.18	0.17	0.17
13.233	0.17	0.17	0.17	0.17	0.16
13.317	0.16	0.16	0.16	0.16	0.16
13.400	0.16	0.16	0.15	0.15	0.15

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**


Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
13.483	0.15	0.15	0.15	0.15	0.15
13.567	0.14	0.14	0.14	0.14	0.14
13.650	0.14	0.14	0.14	0.14	0.13
13.733	0.13	0.13	0.13	0.13	0.13
13.817	0.13	0.13	0.13	0.13	0.12
13.900	0.12	0.12	0.12	0.12	0.12
13.983	0.12	0.12	0.12	0.12	0.12
14.067	0.11	0.11	0.11	0.11	0.11
14.150	0.11	0.11	0.11	0.11	0.11
14.233	0.11	0.11	0.11	0.11	0.11
14.317	0.10	0.10	0.10	0.10	0.10
14.400	0.10	0.10	0.10	0.10	0.10
14.483	0.10	0.10	0.10	0.10	0.10
14.567	0.10	0.10	0.10	0.10	0.10
14.650	0.10	0.10	0.10	0.10	0.10
14.733	0.10	0.10	0.10	0.10	0.10
14.817	0.10	0.09	0.09	0.09	0.09
14.900	0.09	0.09	0.09	0.09	0.09
14.983	0.09	0.09	0.09	0.09	0.09
15.067	0.09	0.09	0.09	0.09	0.09
15.150	0.09	0.09	0.09	0.09	0.09
15.233	0.09	0.09	0.09	0.09	0.09
15.317	0.09	0.09	0.09	0.08	0.08
15.400	0.08	0.08	0.08	0.08	0.08
15.483	0.08	0.08	0.08	0.08	0.08
15.567	0.08	0.08	0.08	0.08	0.08
15.650	0.08	0.08	0.08	0.08	0.08
15.733	0.08	0.08	0.08	0.08	0.08
15.817	0.08	0.08	0.08	0.08	0.07
15.900	0.07	0.07	0.07	0.07	0.07
15.983	0.07	0.07	0.07	0.07	0.07
16.067	0.07	0.07	0.07	0.07	0.07
16.150	0.07	0.07	0.07	0.07	0.07
16.233	0.07	0.07	0.07	0.07	0.07
16.317	0.07	0.07	0.07	0.07	0.07
16.400	0.07	0.07	0.07	0.07	0.07
16.483	0.07	0.07	0.07	0.07	0.07
16.567	0.07	0.07	0.07	0.07	0.07
16.650	0.07	0.07	0.07	0.07	0.06
16.733	0.06	0.06	0.06	0.06	0.06
16.817	0.06	0.06	0.06	0.06	0.06
16.900	0.06	0.06	0.06	0.06	0.06
16.983	0.06	0.06	0.06	0.06	0.06
17.067	0.06	0.06	0.06	0.06	0.06
17.150	0.06	0.06	0.06	0.06	0.06
17.233	0.06	0.06	0.06	0.06	0.06
17.317	0.06	0.06	0.06	0.06	0.06
17.400	0.06	0.06	0.06	0.06	0.06
17.483	0.06	0.06	0.06	0.06	0.06
17.567	0.06	0.06	0.06	0.06	0.06
17.650	0.06	0.06	0.06	0.06	0.06
17.733	0.06	0.06	0.06	0.06	0.06

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
17.817	0.06	0.06	0.06	0.06	0.06
17.900	0.06	0.06	0.06	0.06	0.06
17.983	0.06	0.06	0.06	0.06	0.06
18.067	0.06	0.06	0.06	0.06	0.06
18.150	0.05	0.05	0.05	0.05	0.05
18.233	0.05	0.05	0.05	0.05	0.05
18.317	0.05	0.05	0.05	0.05	0.05
18.400	0.05	0.05	0.05	0.05	0.05
18.483	0.05	0.05	0.05	0.05	0.05
18.567	0.05	0.05	0.05	0.05	0.05
18.650	0.05	0.05	0.05	0.05	0.05
18.733	0.05	0.05	0.05	0.05	0.05
18.817	0.05	0.05	0.05	0.05	0.05
18.900	0.05	0.05	0.05	0.05	0.05
18.983	0.05	0.05	0.05	0.05	0.05
19.067	0.05	0.05	0.05	0.05	0.05
19.150	0.05	0.05	0.05	0.05	0.05
19.233	0.05	0.05	0.05	0.05	0.05
19.317	0.05	0.05	0.05	0.05	0.05
19.400	0.05	0.05	0.05	0.05	0.05
19.483	0.05	0.05	0.05	0.05	0.04
19.567	0.04	0.04	0.04	0.04	0.04
19.650	0.04	0.04	0.04	0.04	0.04
19.733	0.04	0.04	0.04	0.04	0.04
19.817	0.04	0.04	0.04	0.04	0.04
19.900	0.04	0.04	0.04	0.04	0.04
19.983	0.04	0.04	0.04	0.04	0.04
20.067	0.04	0.04	0.04	0.04	0.04
20.150	0.04	0.04	0.04	0.04	0.04
20.233	0.04	0.04	0.04	0.04	0.04
20.317	0.04	0.04	0.04	0.04	0.04
20.400	0.04	0.04	0.04	0.04	0.04
20.483	0.04	0.04	0.04	0.04	0.04
20.567	0.04	0.04	0.04	0.04	0.04
20.650	0.04	0.04	0.04	0.04	0.04
20.733	0.04	0.04	0.04	0.04	0.04
20.817	0.04	0.04	0.04	0.04	0.04
20.900	0.04	0.04	0.04	0.04	0.04
20.983	0.04	0.04	0.04	0.04	0.04
21.067	0.04	0.04	0.04	0.04	0.04
21.150	0.04	0.04	0.04	0.04	0.04
21.233	0.04	0.04	0.04	0.04	0.04
21.317	0.04	0.04	0.04	0.04	0.04
21.400	0.04	0.04	0.04	0.04	0.04
21.483	0.04	0.04	0.04	0.04	0.04
21.567	0.04	0.04	0.04	0.04	0.04
21.650	0.04	0.04	0.04	0.04	0.04
21.733	0.04	0.04	0.04	0.04	0.04
21.817	0.04	0.04	0.04	0.04	0.04
21.900	0.04	0.04	0.04	0.04	0.04
21.983	0.04	0.04	0.04	0.04	0.04
22.067	0.04	0.04	0.04	0.04	0.04

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
22.150	0.04	0.04	0.04	0.04	0.04
22.233	0.04	0.04	0.04	0.04	0.04
22.317	0.04	0.04	0.04	0.04	0.04
22.400	0.04	0.04	0.04	0.04	0.04
22.483	0.04	0.04	0.04	0.04	0.04
22.567	0.04	0.04	0.04	0.04	0.04
22.650	0.04	0.04	0.04	0.04	0.04
22.733	0.04	0.04	0.04	0.04	0.04
22.817	0.04	0.04	0.04	0.04	0.04
22.900	0.04	0.04	0.04	0.04	0.04
22.983	0.04	0.04	0.04	0.04	0.04
23.067	0.04	0.04	0.04	0.04	0.04
23.150	0.04	0.04	0.04	0.04	0.04
23.233	0.04	0.04	0.04	0.04	0.04
23.317	0.04	0.04	0.04	0.04	0.04
23.400	0.04	0.04	0.04	0.04	0.04
23.483	0.04	0.04	0.04	0.04	0.04
23.567	0.04	0.04	0.04	0.04	0.04
23.650	0.04	0.04	0.04	0.04	0.04
23.733	0.04	0.04	0.04	0.04	0.04
23.817	0.04	0.04	0.04	0.03	0.03
23.900	0.03	0.03	0.03	0.03	0.03
23.983	0.03	0.03	(N/A)	(N/A)	(N/A)



Storm Event	50 year
Return Event	50 years
Duration	24.000 hours
Depth	4.8 in
Time of Concentration (Composite)	0.271 hours
Area (User Defined)	1.233 acres
Computational Time Increment	0.036 hours
Time to Peak (Computed)	12.048 hours
Flow (Peak, Computed)	3.73 ft ³ /s
Output Increment	0.017 hours
Time to Flow (Peak Interpolated Output)	12.050 hours
Flow (Peak Interpolated Output)	3.73 ft ³ /s
Drainage Area	
SCS CN (Composite)	72.000
Area (User Defined)	1.233 acres
Maximum Retention (Pervious)	3.9 in
Maximum Retention (Pervious, 20 percent)	0.8 in
Cumulative Runoff	
Cumulative Runoff Depth (Pervious)	2.6 in
Runoff Volume (Pervious)	0.265 ac-ft
Hydrograph Volume (Area under Hydrograph curve)	
Volume	0.264 ac-ft
SCS Unit Hydrograph Parameters	
Time of Concentration (Composite)	0.271 hours
Computational Time Increment	0.036 hours
Unit Hydrograph Shape Factor	483.432
K Factor	0.749
Receding/Rising, Tr/Tp	1.670
Unit peak, qp	5.15 ft ³ /s
Unit peak time, Tp	0.181 hours
Unit receding limb, Tr	0.724 hours
Total unit time, Tb	0.905 hours

Storm Event	50 year
Return Event	50 years
Duration	24.000 hours
Depth	4.8 in
Time of Concentration (Composite)	0.271 hours
Area (User Defined)	1.233 acres

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
8.133	0.00	0.00	0.00	0.00	0.00
8.217	0.00	0.00	0.00	0.00	0.00
8.300	0.00	0.00	0.00	0.00	0.00
8.383	0.00	0.00	0.00	0.00	0.00
8.467	0.00	0.00	0.01	0.01	0.01
8.550	0.01	0.01	0.01	0.01	0.01
8.633	0.01	0.01	0.01	0.01	0.01
8.717	0.01	0.01	0.01	0.01	0.01
8.800	0.01	0.01	0.01	0.01	0.01
8.883	0.01	0.01	0.01	0.01	0.01
8.967	0.01	0.01	0.01	0.01	0.01
9.050	0.01	0.02	0.02	0.02	0.02
9.133	0.02	0.02	0.02	0.02	0.02
9.217	0.02	0.02	0.02	0.02	0.02
9.300	0.02	0.02	0.02	0.02	0.02
9.383	0.02	0.02	0.02	0.02	0.02
9.467	0.02	0.02	0.02	0.02	0.02
9.550	0.02	0.02	0.03	0.03	0.03
9.633	0.03	0.03	0.03	0.03	0.03
9.717	0.03	0.03	0.03	0.03	0.03
9.800	0.03	0.03	0.03	0.03	0.03
9.883	0.03	0.03	0.03	0.03	0.04
9.967	0.04	0.04	0.04	0.04	0.04
10.050	0.04	0.04	0.04	0.04	0.04
10.133	0.04	0.04	0.04	0.04	0.05
10.217	0.05	0.05	0.05	0.05	0.05
10.300	0.05	0.05	0.05	0.05	0.05
10.383	0.06	0.06	0.06	0.06	0.06
10.467	0.06	0.06	0.06	0.06	0.06
10.550	0.07	0.07	0.07	0.07	0.07
10.633	0.07	0.07	0.07	0.08	0.08
10.717	0.08	0.08	0.08	0.08	0.08
10.800	0.09	0.09	0.09	0.09	0.09
10.883	0.09	0.10	0.10	0.10	0.10
10.967	0.10	0.11	0.11	0.11	0.11
11.050	0.11	0.12	0.12	0.12	0.12
11.133	0.13	0.13	0.13	0.13	0.14
11.217	0.14	0.14	0.15	0.15	0.16
11.300	0.16	0.16	0.17	0.17	0.18
11.383	0.18	0.19	0.19	0.19	0.20
11.467	0.20	0.21	0.21	0.22	0.23
11.550	0.24	0.25	0.27	0.29	0.31
11.633	0.34	0.38	0.42	0.47	0.53

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**


Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
11.717	0.60	0.67	0.76	0.85	0.95
11.800	1.07	1.20	1.34	1.51	1.68
11.883	1.90	2.12	2.36	2.61	2.84
11.967	3.08	3.28	3.45	3.59	3.66
12.050	3.73	3.69	3.66	3.52	3.38
12.133	3.19	2.98	2.77	2.55	2.34
12.217	2.15	1.96	1.80	1.64	1.52
12.300	1.40	1.30	1.22	1.14	1.07
12.383	1.01	0.96	0.91	0.86	0.82
12.467	0.78	0.75	0.72	0.68	0.66
12.550	0.63	0.61	0.58	0.56	0.54
12.633	0.52	0.51	0.49	0.48	0.46
12.717	0.45	0.44	0.43	0.42	0.41
12.800	0.40	0.39	0.39	0.38	0.38
12.883	0.37	0.37	0.36	0.36	0.35
12.967	0.35	0.34	0.34	0.33	0.33
13.050	0.33	0.32	0.32	0.31	0.31
13.133	0.31	0.30	0.30	0.30	0.29
13.217	0.29	0.29	0.29	0.28	0.28
13.300	0.28	0.28	0.27	0.27	0.27
13.383	0.27	0.26	0.26	0.26	0.26
13.467	0.25	0.25	0.25	0.25	0.25
13.550	0.24	0.24	0.24	0.24	0.24
13.633	0.23	0.23	0.23	0.23	0.23
13.717	0.22	0.22	0.22	0.22	0.22
13.800	0.22	0.21	0.21	0.21	0.21
13.883	0.21	0.21	0.20	0.20	0.20
13.967	0.20	0.20	0.20	0.20	0.19
14.050	0.19	0.19	0.19	0.19	0.19
14.133	0.19	0.18	0.18	0.18	0.18
14.217	0.18	0.18	0.18	0.18	0.18
14.300	0.18	0.17	0.17	0.17	0.17
14.383	0.17	0.17	0.17	0.17	0.17
14.467	0.17	0.17	0.17	0.17	0.17
14.550	0.17	0.17	0.17	0.17	0.16
14.633	0.16	0.16	0.16	0.16	0.16
14.717	0.16	0.16	0.16	0.16	0.16
14.800	0.16	0.16	0.16	0.16	0.16
14.883	0.16	0.16	0.15	0.15	0.15
14.967	0.15	0.15	0.15	0.15	0.15
15.050	0.15	0.15	0.15	0.15	0.15
15.133	0.15	0.15	0.15	0.15	0.15
15.217	0.15	0.14	0.14	0.14	0.14
15.300	0.14	0.14	0.14	0.14	0.14
15.383	0.14	0.14	0.14	0.14	0.14
15.467	0.14	0.14	0.14	0.14	0.13
15.550	0.13	0.13	0.13	0.13	0.13
15.633	0.13	0.13	0.13	0.13	0.13
15.717	0.13	0.13	0.13	0.13	0.13
15.800	0.13	0.13	0.13	0.12	0.12
15.883	0.12	0.12	0.12	0.12	0.12
15.967	0.12	0.12	0.12	0.12	0.12

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
16.050	0.12	0.12	0.12	0.12	0.12
16.133	0.12	0.12	0.11	0.11	0.11
16.217	0.11	0.11	0.11	0.11	0.11
16.300	0.11	0.11	0.11	0.11	0.11
16.383	0.11	0.11	0.11	0.11	0.11
16.467	0.11	0.11	0.11	0.11	0.11
16.550	0.11	0.11	0.11	0.11	0.11
16.633	0.11	0.11	0.11	0.11	0.11
16.717	0.11	0.11	0.11	0.11	0.11
16.800	0.11	0.11	0.11	0.11	0.11
16.883	0.10	0.10	0.10	0.10	0.10
16.967	0.10	0.10	0.10	0.10	0.10
17.050	0.10	0.10	0.10	0.10	0.10
17.133	0.10	0.10	0.10	0.10	0.10
17.217	0.10	0.10	0.10	0.10	0.10
17.300	0.10	0.10	0.10	0.10	0.10
17.383	0.10	0.10	0.10	0.10	0.10
17.467	0.10	0.10	0.10	0.10	0.10
17.550	0.10	0.10	0.10	0.10	0.10
17.633	0.10	0.10	0.10	0.10	0.10
17.717	0.10	0.09	0.09	0.09	0.09
17.800	0.09	0.09	0.09	0.09	0.09
17.883	0.09	0.09	0.09	0.09	0.09
17.967	0.09	0.09	0.09	0.09	0.09
18.050	0.09	0.09	0.09	0.09	0.09
18.133	0.09	0.09	0.09	0.09	0.09
18.217	0.09	0.09	0.09	0.09	0.09
18.300	0.09	0.09	0.09	0.09	0.09
18.383	0.09	0.09	0.09	0.09	0.09
18.467	0.09	0.09	0.09	0.09	0.09
18.550	0.09	0.09	0.08	0.08	0.08
18.633	0.08	0.08	0.08	0.08	0.08
18.717	0.08	0.08	0.08	0.08	0.08
18.800	0.08	0.08	0.08	0.08	0.08
18.883	0.08	0.08	0.08	0.08	0.08
18.967	0.08	0.08	0.08	0.08	0.08
19.050	0.08	0.08	0.08	0.08	0.08
19.133	0.08	0.08	0.08	0.08	0.08
19.217	0.08	0.08	0.08	0.08	0.08
19.300	0.08	0.08	0.08	0.08	0.08
19.383	0.08	0.07	0.07	0.07	0.07
19.467	0.07	0.07	0.07	0.07	0.07
19.550	0.07	0.07	0.07	0.07	0.07
19.633	0.07	0.07	0.07	0.07	0.07
19.717	0.07	0.07	0.07	0.07	0.07
19.800	0.07	0.07	0.07	0.07	0.07
19.883	0.07	0.07	0.07	0.07	0.07
19.967	0.07	0.07	0.07	0.07	0.07
20.050	0.07	0.07	0.07	0.07	0.07
20.133	0.07	0.07	0.07	0.07	0.07
20.217	0.07	0.07	0.07	0.07	0.07
20.300	0.07	0.06	0.06	0.06	0.06

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
20.383	0.06	0.06	0.06	0.06	0.06
20.467	0.06	0.06	0.06	0.06	0.06
20.550	0.06	0.06	0.06	0.06	0.06
20.633	0.06	0.06	0.06	0.06	0.06
20.717	0.06	0.06	0.06	0.06	0.06
20.800	0.06	0.06	0.06	0.06	0.06
20.883	0.06	0.06	0.06	0.06	0.06
20.967	0.06	0.06	0.06	0.06	0.06
21.050	0.06	0.06	0.06	0.06	0.06
21.133	0.06	0.06	0.06	0.06	0.06
21.217	0.06	0.06	0.06	0.06	0.06
21.300	0.06	0.06	0.06	0.06	0.06
21.383	0.06	0.06	0.06	0.06	0.06
21.467	0.06	0.06	0.06	0.06	0.06
21.550	0.06	0.06	0.06	0.06	0.06
21.633	0.06	0.06	0.06	0.06	0.06
21.717	0.06	0.06	0.06	0.06	0.06
21.800	0.06	0.06	0.06	0.06	0.06
21.883	0.06	0.06	0.06	0.06	0.06
21.967	0.06	0.06	0.06	0.06	0.06
22.050	0.06	0.06	0.06	0.06	0.06
22.133	0.06	0.06	0.06	0.06	0.06
22.217	0.06	0.06	0.06	0.06	0.06
22.300	0.06	0.06	0.06	0.06	0.06
22.383	0.06	0.06	0.06	0.06	0.06
22.467	0.06	0.06	0.06	0.06	0.06
22.550	0.06	0.06	0.06	0.06	0.06
22.633	0.06	0.06	0.06	0.06	0.06
22.717	0.06	0.06	0.06	0.06	0.06
22.800	0.06	0.06	0.06	0.06	0.06
22.883	0.06	0.06	0.06	0.06	0.06
22.967	0.06	0.06	0.06	0.06	0.06
23.050	0.06	0.06	0.06	0.06	0.06
23.133	0.06	0.06	0.06	0.06	0.06
23.217	0.06	0.06	0.06	0.06	0.06
23.300	0.06	0.06	0.06	0.06	0.06
23.383	0.06	0.06	0.06	0.06	0.06
23.467	0.06	0.06	0.06	0.06	0.06
23.550	0.06	0.06	0.06	0.06	0.06
23.633	0.06	0.06	0.06	0.06	0.06
23.717	0.06	0.06	0.06	0.06	0.06
23.800	0.06	0.06	0.06	0.06	0.06
23.883	0.06	0.06	0.06	0.06	0.06
23.967	0.06	0.06	0.06	(N/A)	(N/A)



Storm Event	100 year
Return Event	100 years
Duration	24.000 hours
Depth	5.7 in
Time of Concentration (Composite)	0.271 hours
Area (User Defined)	1.233 acres
Computational Time Increment	0.036 hours
Time to Peak (Computed)	12.048 hours
Flow (Peak, Computed)	3.91 ft ³ /s
Output Increment	0.017 hours
Time to Flow (Peak Interpolated Output)	12.050 hours
Flow (Peak Interpolated Output)	3.91 ft ³ /s
Drainage Area	
SCS CN (Composite)	72.000
Area (User Defined)	1.233 acres
Maximum Retention (Pervious)	3.9 in
Maximum Retention (Pervious, 20 percent)	0.8 in
Cumulative Runoff	
Cumulative Runoff Depth (Pervious)	2.7 in
Runoff Volume (Pervious)	0.278 ac-ft
Hydrograph Volume (Area under Hydrograph curve)	
Volume	0.277 ac-ft
SCS Unit Hydrograph Parameters	
Time of Concentration (Composite)	0.271 hours
Computational Time Increment	0.036 hours
Unit Hydrograph Shape Factor	483.432
K Factor	0.749
Receding/Rising, Tr/Tp	1.670
Unit peak, qp	5.15 ft ³ /s
Unit peak time, Tp	0.181 hours
Unit receding limb, Tr	0.724 hours
Total unit time, Tb	0.905 hours

Storm Event	100 year
Return Event	100 years
Duration	24.000 hours
Depth	5.7 in
Time of Concentration (Composite)	0.271 hours
Area (User Defined)	1.233 acres

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
8.917	0.00	0.00	0.00	0.00	0.00
9.000	0.00	0.00	0.00	0.00	0.00
9.083	0.00	0.00	0.00	0.00	0.00
9.167	0.01	0.01	0.01	0.01	0.01
9.250	0.01	0.01	0.01	0.01	0.01
9.333	0.01	0.01	0.01	0.01	0.01
9.417	0.01	0.01	0.01	0.01	0.01
9.500	0.01	0.01	0.01	0.01	0.01
9.583	0.01	0.01	0.01	0.01	0.01
9.667	0.01	0.02	0.02	0.02	0.02
9.750	0.02	0.02	0.02	0.02	0.02
9.833	0.02	0.02	0.02	0.02	0.02
9.917	0.02	0.02	0.02	0.02	0.02
10.000	0.02	0.03	0.03	0.03	0.03
10.083	0.03	0.03	0.03	0.03	0.03
10.167	0.03	0.03	0.03	0.03	0.03
10.250	0.03	0.04	0.04	0.04	0.04
10.333	0.04	0.04	0.04	0.04	0.04
10.417	0.04	0.04	0.04	0.05	0.05
10.500	0.05	0.05	0.05	0.05	0.05
10.583	0.05	0.05	0.06	0.06	0.06
10.667	0.06	0.06	0.06	0.06	0.06
10.750	0.07	0.07	0.07	0.07	0.07
10.833	0.07	0.08	0.08	0.08	0.08
10.917	0.08	0.08	0.09	0.09	0.09
11.000	0.09	0.09	0.10	0.10	0.10
11.083	0.10	0.10	0.11	0.11	0.11
11.167	0.11	0.12	0.12	0.12	0.13
11.250	0.13	0.13	0.14	0.14	0.15
11.333	0.15	0.15	0.16	0.16	0.17
11.417	0.17	0.18	0.18	0.19	0.19
11.500	0.20	0.20	0.21	0.22	0.23
11.583	0.25	0.27	0.29	0.32	0.36
11.667	0.40	0.45	0.51	0.57	0.65
11.750	0.73	0.83	0.93	1.05	1.18
11.833	1.33	1.51	1.68	1.91	2.15
11.917	2.40	2.67	2.92	3.17	3.39
12.000	3.58	3.74	3.83	3.91	3.88
12.083	3.85	3.71	3.57	3.37	3.16
12.167	2.94	2.71	2.49	2.29	2.09
12.250	1.92	1.75	1.62	1.49	1.40
12.333	1.30	1.22	1.15	1.09	1.03
12.417	0.98	0.93	0.88	0.84	0.81

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**


Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
12.500	0.77	0.74	0.71	0.68	0.66
12.583	0.63	0.61	0.59	0.57	0.55
12.667	0.53	0.52	0.50	0.49	0.48
12.750	0.47	0.46	0.45	0.44	0.43
12.833	0.42	0.42	0.41	0.40	0.40
12.917	0.39	0.39	0.38	0.38	0.37
13.000	0.37	0.36	0.36	0.36	0.35
13.083	0.35	0.34	0.34	0.34	0.33
13.167	0.33	0.32	0.32	0.32	0.32
13.250	0.31	0.31	0.31	0.30	0.30
13.333	0.30	0.30	0.29	0.29	0.29
13.417	0.29	0.28	0.28	0.28	0.28
13.500	0.27	0.27	0.27	0.27	0.27
13.583	0.26	0.26	0.26	0.26	0.25
13.667	0.25	0.25	0.25	0.25	0.24
13.750	0.24	0.24	0.24	0.24	0.24
13.833	0.23	0.23	0.23	0.23	0.23
13.917	0.22	0.22	0.22	0.22	0.22
14.000	0.22	0.21	0.21	0.21	0.21
14.083	0.21	0.21	0.21	0.20	0.20
14.167	0.20	0.20	0.20	0.20	0.20
14.250	0.20	0.19	0.19	0.19	0.19
14.333	0.19	0.19	0.19	0.19	0.19
14.417	0.19	0.19	0.19	0.19	0.19
14.500	0.19	0.18	0.18	0.18	0.18
14.583	0.18	0.18	0.18	0.18	0.18
14.667	0.18	0.18	0.18	0.18	0.18
14.750	0.18	0.18	0.18	0.17	0.17
14.833	0.17	0.17	0.17	0.17	0.17
14.917	0.17	0.17	0.17	0.17	0.17
15.000	0.17	0.17	0.17	0.17	0.17
15.083	0.16	0.16	0.16	0.16	0.16
15.167	0.16	0.16	0.16	0.16	0.16
15.250	0.16	0.16	0.16	0.16	0.16
15.333	0.16	0.16	0.15	0.15	0.15
15.417	0.15	0.15	0.15	0.15	0.15
15.500	0.15	0.15	0.15	0.15	0.15
15.583	0.15	0.15	0.15	0.15	0.14
15.667	0.14	0.14	0.14	0.14	0.14
15.750	0.14	0.14	0.14	0.14	0.14
15.833	0.14	0.14	0.14	0.14	0.14
15.917	0.14	0.13	0.13	0.13	0.13
16.000	0.13	0.13	0.13	0.13	0.13
16.083	0.13	0.13	0.13	0.13	0.13
16.167	0.13	0.13	0.13	0.13	0.12
16.250	0.12	0.12	0.12	0.12	0.12
16.333	0.12	0.12	0.12	0.12	0.12
16.417	0.12	0.12	0.12	0.12	0.12
16.500	0.12	0.12	0.12	0.12	0.12
16.583	0.12	0.12	0.12	0.12	0.12
16.667	0.12	0.12	0.12	0.12	0.12
16.750	0.12	0.12	0.12	0.12	0.12

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
16.833	0.12	0.12	0.12	0.12	0.12
16.917	0.12	0.12	0.12	0.11	0.11
17.000	0.11	0.11	0.11	0.11	0.11
17.083	0.11	0.11	0.11	0.11	0.11
17.167	0.11	0.11	0.11	0.11	0.11
17.250	0.11	0.11	0.11	0.11	0.11
17.333	0.11	0.11	0.11	0.11	0.11
17.417	0.11	0.11	0.11	0.11	0.11
17.500	0.11	0.11	0.11	0.11	0.11
17.583	0.11	0.11	0.11	0.11	0.11
17.667	0.11	0.11	0.11	0.11	0.11
17.750	0.10	0.10	0.10	0.10	0.10
17.833	0.10	0.10	0.10	0.10	0.10
17.917	0.10	0.10	0.10	0.10	0.10
18.000	0.10	0.10	0.10	0.10	0.10
18.083	0.10	0.10	0.10	0.10	0.10
18.167	0.10	0.10	0.10	0.10	0.10
18.250	0.10	0.10	0.10	0.10	0.10
18.333	0.10	0.10	0.10	0.10	0.10
18.417	0.10	0.10	0.10	0.10	0.10
18.500	0.10	0.09	0.09	0.09	0.09
18.583	0.09	0.09	0.09	0.09	0.09
18.667	0.09	0.09	0.09	0.09	0.09
18.750	0.09	0.09	0.09	0.09	0.09
18.833	0.09	0.09	0.09	0.09	0.09
18.917	0.09	0.09	0.09	0.09	0.09
19.000	0.09	0.09	0.09	0.09	0.09
19.083	0.09	0.09	0.09	0.09	0.09
19.167	0.09	0.09	0.09	0.09	0.09
19.250	0.09	0.08	0.08	0.08	0.08
19.333	0.08	0.08	0.08	0.08	0.08
19.417	0.08	0.08	0.08	0.08	0.08
19.500	0.08	0.08	0.08	0.08	0.08
19.583	0.08	0.08	0.08	0.08	0.08
19.667	0.08	0.08	0.08	0.08	0.08
19.750	0.08	0.08	0.08	0.08	0.08
19.833	0.08	0.08	0.08	0.08	0.08
19.917	0.08	0.08	0.08	0.08	0.08
20.000	0.08	0.07	0.07	0.07	0.07
20.083	0.07	0.07	0.07	0.07	0.07
20.167	0.07	0.07	0.07	0.07	0.07
20.250	0.07	0.07	0.07	0.07	0.07
20.333	0.07	0.07	0.07	0.07	0.07
20.417	0.07	0.07	0.07	0.07	0.07
20.500	0.07	0.07	0.07	0.07	0.07
20.583	0.07	0.07	0.07	0.07	0.07
20.667	0.07	0.07	0.07	0.07	0.07
20.750	0.07	0.07	0.07	0.07	0.07
20.833	0.07	0.07	0.07	0.07	0.07
20.917	0.07	0.07	0.07	0.07	0.07
21.000	0.07	0.07	0.07	0.07	0.07
21.083	0.07	0.07	0.07	0.07	0.07

HYDROGRAPH ORDINATES (ft³/s)**Output Time Increment = 0.017 hours****Time on left represents time for first value in each row.**

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
21.167	0.07	0.07	0.07	0.07	0.07
21.250	0.07	0.07	0.07	0.07	0.07
21.333	0.07	0.07	0.07	0.07	0.07
21.417	0.07	0.07	0.07	0.07	0.07
21.500	0.07	0.07	0.07	0.07	0.07
21.583	0.07	0.07	0.07	0.07	0.07
21.667	0.07	0.07	0.07	0.07	0.07
21.750	0.07	0.07	0.07	0.07	0.07
21.833	0.07	0.07	0.07	0.07	0.07
21.917	0.07	0.07	0.07	0.07	0.07
22.000	0.07	0.07	0.07	0.07	0.07
22.083	0.07	0.07	0.07	0.07	0.07
22.167	0.07	0.07	0.07	0.07	0.07
22.250	0.07	0.07	0.07	0.07	0.07
22.333	0.07	0.07	0.07	0.07	0.07
22.417	0.07	0.07	0.07	0.07	0.07
22.500	0.07	0.07	0.07	0.07	0.07
22.583	0.07	0.07	0.07	0.07	0.07
22.667	0.07	0.07	0.07	0.07	0.07
22.750	0.07	0.07	0.07	0.07	0.07
22.833	0.07	0.07	0.07	0.07	0.07
22.917	0.07	0.07	0.07	0.07	0.07
23.000	0.07	0.07	0.07	0.07	0.07
23.083	0.06	0.06	0.06	0.06	0.06
23.167	0.06	0.06	0.06	0.06	0.06
23.250	0.06	0.06	0.06	0.06	0.06
23.333	0.06	0.06	0.06	0.06	0.06
23.417	0.06	0.06	0.06	0.06	0.06
23.500	0.06	0.06	0.06	0.06	0.06
23.583	0.06	0.06	0.06	0.06	0.06
23.667	0.06	0.06	0.06	0.06	0.06
23.750	0.06	0.06	0.06	0.06	0.06
23.833	0.06	0.06	0.06	0.06	0.06
23.917	0.06	0.06	0.06	0.06	0.06
24.000	0.06	(N/A)	(N/A)	(N/A)	(N/A)



Subsection: Addition Summary
Label: O-1 (POST)

Return Event: 2 years
Storm Event: 2 year

Summary for Hydrograph Addition at 'O-1 (POST)'

Upstream Link	Upstream Node
Outlet-1	DB-1
<Catchment to Outflow Node>	POST-2

Node Inflows

Inflow Type	Element	Volume (ac-ft)	Time to Peak (hours)	Flow (Peak) (ft ³ /s)
Flow (From)	Outlet-1	0.043	13.900	0.05
Flow (From)	POST-2	0.036	12.067	0.50
Flow (In)	O-1 (POST)	0.079	12.067	0.53

Subsection: Addition Summary
Label: O-1 (POST)

Return Event: 10 years
Storm Event: 10 year

Summary for Hydrograph Addition at 'O-1 (POST)'

Upstream Link	Upstream Node
Outlet-1	DB-1
<Catchment to Outflow Node>	POST-2

Node Inflows

Inflow Type	Element	Volume (ac-ft)	Time to Peak (hours)	Flow (Peak) (ft ³ /s)
Flow (From)	Outlet-1	0.084	12.233	0.55
Flow (From)	POST-2	0.071	12.067	1.00
Flow (In)	O-1 (POST)	0.155	12.117	1.32

Subsection: Addition Summary
Label: O-1 (POST)

Return Event: 50 years
Storm Event: 50 year

Summary for Hydrograph Addition at 'O-1 (POST)'

Upstream Link	Upstream Node
Outlet-1	DB-1
<Catchment to Outflow Node>	POST-2

Node Inflows

Inflow Type	Element	Volume (ac-ft)	Time to Peak (hours)	Flow (Peak) (ft ³ /s)
Flow (From)	Outlet-1	0.152	12.183	1.22
Flow (From)	POST-2	0.127	12.050	1.79
Flow (In)	O-1 (POST)	0.279	12.067	2.87

Subsection: Addition Summary
Label: O-1 (POST)

Return Event: 100 years
Storm Event: 100 year

Summary for Hydrograph Addition at 'O-1 (POST)'

Upstream Link	Upstream Node
Outlet-1	DB-1
<Catchment to Outflow Node>	POST-2

Node Inflows

Inflow Type	Element	Volume (ac-ft)	Time to Peak (hours)	Flow (Peak) (ft ³ /s)
Flow (From)	Outlet-1	0.192	12.183	1.47
Flow (From)	POST-2	0.160	12.050	2.25
Flow (In)	O-1 (POST)	0.352	12.067	3.58

Subsection: Addition Summary
Label: O-1 (PRE)

Return Event: 2 years
Storm Event: 2 year

Summary for Hydrograph Addition at 'O-1 (PRE)'

Upstream Link	Upstream Node
<Catchment to Outflow Node>	PRE-1

Node Inflows

Inflow Type	Element	Volume (ac-ft)	Time to Peak (hours)	Flow (Peak) (ft ³ /s)
Flow (From)	PRE-1	0.046	12.083	0.54
Flow (In)	O-1 (PRE)	0.046	12.083	0.54

Subsection: Addition Summary
Label: O-1 (PRE)

Return Event: 10 years
Storm Event: 10 year

Summary for Hydrograph Addition at 'O-1 (PRE)'

Upstream Link	Upstream Node
<Catchment to Outflow Node>	PRE-1

Node Inflows

Inflow Type	Element	Volume (ac-ft)	Time to Peak (hours)	Flow (Peak) (ft ³ /s)
Flow (From)	PRE-1	0.143	12.050	2.00
Flow (In)	O-1 (PRE)	0.143	12.050	2.00

Subsection: Addition Summary
Label: O-1 (PRE)

Return Event: 50 years
Storm Event: 50 year

Summary for Hydrograph Addition at 'O-1 (PRE)'

Upstream Link	Upstream Node
<Catchment to Outflow Node>	PRE-1

Node Inflows

Inflow Type	Element	Volume (ac-ft)	Time to Peak (hours)	Flow (Peak) (ft ³ /s)
Flow (From)	PRE-1	0.264	12.050	3.73
Flow (In)	O-1 (PRE)	0.264	12.050	3.73

Subsection: Addition Summary
Label: O-1 (PRE)

Return Event: 100 years
Storm Event: 100 year

Summary for Hydrograph Addition at 'O-1 (PRE)'

Upstream Link	Upstream Node
<Catchment to Outflow Node>	PRE-1

Node Inflows

Inflow Type	Element	Volume (ac-ft)	Time to Peak (hours)	Flow (Peak) (ft ³ /s)
Flow (From)	PRE-1	0.277	12.050	3.91
Flow (In)	O-1 (PRE)	0.277	12.050	3.91

Elevation (ft)	Planimeter (ft ²)	Area (acres)	A1 + A2 + sq (A1*A2) (acres)	Volume (ac-ft)	Volume (Total) (ac-ft)
1,076.00	0.0	0.019	0.000	0.000	0.000
1,077.00	0.0	0.025	0.066	0.022	0.022
1,078.00	0.0	0.039	0.095	0.032	0.054
1,079.00	0.0	0.047	0.129	0.043	0.097
1,080.00	0.0	0.057	0.156	0.052	0.149

Requested Pond Water Surface Elevations	
Minimum (Headwater)	1,076.00 ft
Increment (Headwater)	0.50 ft
Maximum (Headwater)	1,080.00 ft

Outlet Connectivity

Structure Type	Outlet ID	Direction	Outfall	E1 (ft)	E2 (ft)
Orifice-Circular	Orifice - 2	Forward	TW	1,077.40	1,080.00
Inlet Box	Riser - 1	Forward	TW	1,078.75	1,080.00
Orifice-Circular	Orifice - 1	Forward	TW	1,076.00	1,080.00
Tailwater Settings	Tailwater			(N/A)	(N/A)

Structure ID: Riser - 1	
Structure Type: Inlet Box	
Number of Openings	1
Elevation	1,078.75 ft
Orifice Area	16.0 ft ²
Orifice Coefficient	0.600
Weir Length	4.00 ft
Weir Coefficient	2.80 (ft ^{0.5})/s
K Reverse	1.000
Manning's n	0.000
Kev, Charged Riser	0.000
Weir Submergence	False
Orifice H to crest	True
Structure ID: Orifice - 1	
Structure Type: Orifice-Circular	
Number of Openings	1
Elevation	1,076.00 ft
Orifice Diameter	1.3 in
Orifice Coefficient	0.600
Structure ID: Orifice - 2	
Structure Type: Orifice-Circular	
Number of Openings	2
Elevation	1,077.40 ft
Orifice Diameter	5.0 in
Orifice Coefficient	0.600
Structure ID: TW	
Structure Type: TW Setup, DS Channel	
Tailwater Type	Free Outfall
Convergence Tolerances	
Maximum Iterations	30
Tailwater Tolerance (Minimum)	0.01 ft
Tailwater Tolerance (Maximum)	0.50 ft
Headwater Tolerance (Minimum)	0.01 ft
Headwater Tolerance (Maximum)	0.50 ft
Flow Tolerance (Minimum)	0.001 ft ³ /s
Flow Tolerance (Maximum)	10.000 ft ³ /s

Infiltration			
Infiltration Method (Computed)		No Infiltration	
Initial Conditions			
Elevation (Water Surface, Initial)		1,076.00 ft	
Volume (Initial)		0.000 ac-ft	
Flow (Initial Outlet)		0.00 ft³/s	
Flow (Initial Infiltration)		0.00 ft³/s	
Flow (Initial, Total)		0.00 ft³/s	
Time Increment		0.017 hours	
Inflow/Outflow Hydrograph Summary			
Flow (Peak In)		0.94 ft³/s	Time to Peak (Flow, In)
Flow (Peak Outlet)		0.05 ft³/s	Time to Peak (Flow, Outlet)
			12.017 hours
			13.900 hours
Peak Conditions			
Elevation (Water Surface, Peak)		1,077.40 ft	
Volume (Peak)		0.033 ac-ft	
Mass Balance (ac-ft)			
Volume (Initial)		0.000 ac-ft	
Volume (Total Inflow)		0.060 ac-ft	
Volume (Total Infiltration)		0.000 ac-ft	
Volume (Total Outlet Outflow)		0.043 ac-ft	
Volume (Retained)		0.016 ac-ft	
Volume (Unrouted)		0.000 ac-ft	
Error (Mass Balance)		0.4 %	

Infiltration	
Infiltration Method (Computed)	No Infiltration
Initial Conditions	
Elevation (Water Surface, Initial)	1,076.00 ft
Volume (Initial)	0.000 ac-ft
Flow (Initial Outlet)	0.00 ft ³ /s
Flow (Initial Infiltration)	0.00 ft ³ /s
Flow (Initial, Total)	0.00 ft ³ /s
Time Increment	0.017 hours

Inflow/Outflow Hydrograph Summary			
Flow (Peak In)	1.68 ft ³ /s	Time to Peak (Flow, In)	12.017 hours
Flow (Peak Outlet)	0.55 ft ³ /s	Time to Peak (Flow, Outlet)	12.233 hours

Elevation (Water Surface, Peak)	1,077.79 ft
Volume (Peak)	0.046 ac-ft

Mass Balance (ac-ft)	
Volume (Initial)	0.000 ac-ft
Volume (Total Inflow)	0.107 ac-ft
Volume (Total Infiltration)	0.000 ac-ft
Volume (Total Outlet Outflow)	0.084 ac-ft
Volume (Retained)	0.023 ac-ft
Volume (Unrouted)	0.000 ac-ft
Error (Mass Balance)	0.2 %

Infiltration	
Infiltration Method (Computed)	No Infiltration
Initial Conditions	
Elevation (Water Surface, Initial)	1,076.00 ft
Volume (Initial)	0.000 ac-ft
Flow (Initial Outlet)	0.00 ft ³ /s
Flow (Initial Infiltration)	0.00 ft ³ /s
Flow (Initial, Total)	0.00 ft ³ /s
Time Increment	0.017 hours

Inflow/Outflow Hydrograph Summary			
Flow (Peak In)	2.81 ft ³ /s	Time to Peak (Flow, In)	12.000 hours
Flow (Peak Outlet)	1.22 ft ³ /s	Time to Peak (Flow, Outlet)	12.183 hours

Elevation (Water Surface, Peak)	1,078.40 ft
Volume (Peak)	0.070 ac-ft

Mass Balance (ac-ft)	
Volume (Initial)	0.000 ac-ft
Volume (Total Inflow)	0.182 ac-ft
Volume (Total Infiltration)	0.000 ac-ft
Volume (Total Outlet Outflow)	0.152 ac-ft
Volume (Retained)	0.029 ac-ft
Volume (Unrouted)	0.000 ac-ft
Error (Mass Balance)	0.2 %

Infiltration	
Infiltration Method (Computed)	No Infiltration
Initial Conditions	
Elevation (Water Surface, Initial)	1,076.00 ft
Volume (Initial)	0.000 ac-ft
Flow (Initial Outlet)	0.00 ft ³ /s
Flow (Initial Infiltration)	0.00 ft ³ /s
Flow (Initial, Total)	0.00 ft ³ /s
Time Increment	0.017 hours

Inflow/Outflow Hydrograph Summary			
Flow (Peak In)	3.44 ft ³ /s	Time to Peak (Flow, In)	12.000 hours
Flow (Peak Outlet)	1.47 ft ³ /s	Time to Peak (Flow, Outlet)	12.183 hours

Elevation (Water Surface, Peak)	1,078.74 ft
Volume (Peak)	0.085 ac-ft

Mass Balance (ac-ft)	
Volume (Initial)	0.000 ac-ft
Volume (Total Inflow)	0.224 ac-ft
Volume (Total Infiltration)	0.000 ac-ft
Volume (Total Outlet Outflow)	0.192 ac-ft
Volume (Retained)	0.032 ac-ft
Volume (Unrouted)	0.000 ac-ft
Error (Mass Balance)	0.1 %

Subsection: Pond Routed Hydrograph (total out)
Label: DB-1 (OUT)

Return Event: 2 years
Storm Event: 2 year

Peak Discharge	0.05 ft ³ /s
Time to Peak	13.900 hours
Hydrograph Volume	0.043 ac-ft

HYDROGRAPH ORDINATES (ft³/s)

Output Time Increment = 0.017 hours

Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
10.583	0.00	0.00	0.00	0.00	0.00
10.667	0.00	0.00	0.00	0.00	0.00
10.750	0.00	0.00	0.00	0.00	0.00
10.833	0.00	0.00	0.00	0.00	0.00
10.917	0.00	0.00	0.00	0.00	0.00
11.000	0.00	0.00	0.00	0.00	0.00
11.083	0.00	0.00	0.00	0.00	0.00
11.167	0.00	0.00	0.00	0.00	0.00
11.250	0.00	0.00	0.00	0.00	0.00
11.333	0.00	0.00	0.00	0.00	0.00
11.417	0.00	0.00	0.00	0.00	0.00
11.500	0.00	0.01	0.01	0.01	0.01
11.583	0.01	0.01	0.01	0.01	0.01
11.667	0.01	0.01	0.01	0.01	0.01
11.750	0.01	0.01	0.01	0.01	0.01
11.833	0.01	0.02	0.02	0.02	0.02
11.917	0.02	0.03	0.03	0.03	0.03
12.000	0.03	0.03	0.03	0.04	0.04
12.083	0.04	0.04	0.04	0.04	0.04
12.167	0.04	0.04	0.04	0.04	0.04
12.250	0.04	0.04	0.04	0.04	0.04
12.333	0.04	0.04	0.04	0.04	0.04
12.417	0.04	0.05	0.05	0.05	0.05
12.500	0.05	0.05	0.05	0.05	0.05
12.583	0.05	0.05	0.05	0.05	0.05
12.667	0.05	0.05	0.05	0.05	0.05
12.750	0.05	0.05	0.05	0.05	0.05
12.833	0.05	0.05	0.05	0.05	0.05
12.917	0.05	0.05	0.05	0.05	0.05
13.000	0.05	0.05	0.05	0.05	0.05
13.083	0.05	0.05	0.05	0.05	0.05
13.167	0.05	0.05	0.05	0.05	0.05
13.250	0.05	0.05	0.05	0.05	0.05
13.333	0.05	0.05	0.05	0.05	0.05
13.417	0.05	0.05	0.05	0.05	0.05
13.500	0.05	0.05	0.05	0.05	0.05
13.583	0.05	0.05	0.05	0.05	0.05
13.667	0.05	0.05	0.05	0.05	0.05
13.750	0.05	0.05	0.05	0.05	0.05
13.833	0.05	0.05	0.05	0.05	0.05
13.917	0.05	0.05	0.05	0.05	0.05
14.000	0.05	0.05	0.05	0.05	0.05
14.083	0.05	0.05	0.05	0.05	0.05
14.167	0.05	0.05	0.05	0.05	0.05
14.250	0.05	0.05	0.05	0.05	0.05
14.333	0.05	0.05	0.05	0.05	0.05
14.417	0.05	0.05	0.05	0.05	0.05
14.500	0.05	0.05	0.05	0.05	0.05

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
14.583	0.05	0.05	0.05	0.05	0.05
14.667	0.05	0.05	0.05	0.05	0.05
14.750	0.05	0.05	0.05	0.05	0.05
14.833	0.05	0.05	0.05	0.05	0.05
14.917	0.05	0.05	0.05	0.05	0.05
15.000	0.05	0.05	0.05	0.05	0.05
15.083	0.05	0.05	0.05	0.05	0.05
15.167	0.05	0.05	0.05	0.05	0.05
15.250	0.05	0.05	0.05	0.05	0.05
15.333	0.05	0.05	0.05	0.05	0.05
15.417	0.05	0.05	0.05	0.05	0.05
15.500	0.05	0.05	0.05	0.05	0.05
15.583	0.05	0.05	0.05	0.05	0.05
15.667	0.05	0.05	0.05	0.05	0.05
15.750	0.05	0.05	0.05	0.05	0.05
15.833	0.05	0.05	0.05	0.05	0.05
15.917	0.05	0.05	0.05	0.05	0.05
16.000	0.05	0.05	0.05	0.05	0.05
16.083	0.05	0.05	0.05	0.05	0.05
16.167	0.05	0.05	0.05	0.05	0.05
16.250	0.05	0.05	0.05	0.05	0.05
16.333	0.05	0.05	0.05	0.05	0.05
16.417	0.05	0.05	0.05	0.05	0.05
16.500	0.05	0.05	0.05	0.05	0.05
16.583	0.05	0.05	0.05	0.05	0.05
16.667	0.05	0.05	0.05	0.05	0.05
16.750	0.05	0.05	0.05	0.05	0.05
16.833	0.05	0.05	0.05	0.05	0.05
16.917	0.05	0.05	0.05	0.05	0.05
17.000	0.05	0.05	0.05	0.05	0.05
17.083	0.05	0.05	0.05	0.05	0.05
17.167	0.05	0.05	0.05	0.05	0.05
17.250	0.05	0.05	0.05	0.04	0.04
17.333	0.04	0.04	0.04	0.04	0.04
17.417	0.04	0.04	0.04	0.04	0.04
17.500	0.04	0.04	0.04	0.04	0.04
17.583	0.04	0.04	0.04	0.04	0.04
17.667	0.04	0.04	0.04	0.04	0.04
17.750	0.04	0.04	0.04	0.04	0.04
17.833	0.04	0.04	0.04	0.04	0.04
17.917	0.04	0.04	0.04	0.04	0.04
18.000	0.04	0.04	0.04	0.04	0.04
18.083	0.04	0.04	0.04	0.04	0.04
18.167	0.04	0.04	0.04	0.04	0.04
18.250	0.04	0.04	0.04	0.04	0.04
18.333	0.04	0.04	0.04	0.04	0.04
18.417	0.04	0.04	0.04	0.04	0.04
18.500	0.04	0.04	0.04	0.04	0.04
18.583	0.04	0.04	0.04	0.04	0.04
18.667	0.04	0.04	0.04	0.04	0.04
18.750	0.04	0.04	0.04	0.04	0.04
18.833	0.04	0.04	0.04	0.04	0.04

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.


Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
18.917	0.04	0.04	0.04	0.04	0.04
19.000	0.04	0.04	0.04	0.04	0.04
19.083	0.04	0.04	0.04	0.04	0.04
19.167	0.04	0.04	0.04	0.04	0.04
19.250	0.04	0.04	0.04	0.04	0.04
19.333	0.04	0.04	0.04	0.04	0.04
19.417	0.04	0.04	0.04	0.04	0.04
19.500	0.04	0.04	0.04	0.04	0.04
19.583	0.04	0.04	0.04	0.04	0.04
19.667	0.04	0.04	0.04	0.04	0.04
19.750	0.04	0.04	0.04	0.04	0.04
19.833	0.04	0.04	0.04	0.04	0.04
19.917	0.04	0.04	0.04	0.04	0.04
20.000	0.04	0.04	0.04	0.04	0.04
20.083	0.04	0.04	0.04	0.04	0.04
20.167	0.04	0.04	0.04	0.04	0.04
20.250	0.04	0.04	0.04	0.04	0.04
20.333	0.04	0.04	0.04	0.04	0.04
20.417	0.04	0.04	0.04	0.04	0.04
20.500	0.04	0.04	0.04	0.04	0.04
20.583	0.04	0.04	0.04	0.04	0.04
20.667	0.04	0.04	0.04	0.04	0.04
20.750	0.04	0.04	0.04	0.04	0.04
20.833	0.04	0.04	0.04	0.04	0.04
20.917	0.04	0.04	0.04	0.04	0.04
21.000	0.04	0.04	0.04	0.04	0.04
21.083	0.04	0.04	0.04	0.04	0.04
21.167	0.04	0.04	0.04	0.04	0.04
21.250	0.04	0.04	0.04	0.04	0.04
21.333	0.04	0.04	0.04	0.04	0.04
21.417	0.04	0.04	0.04	0.04	0.04
21.500	0.04	0.04	0.04	0.04	0.04
21.583	0.04	0.04	0.04	0.04	0.04
21.667	0.04	0.04	0.04	0.04	0.04
21.750	0.04	0.04	0.04	0.04	0.04
21.833	0.04	0.04	0.04	0.04	0.04
21.917	0.04	0.04	0.04	0.04	0.04
22.000	0.04	0.04	0.04	0.04	0.04
22.083	0.04	0.04	0.04	0.04	0.04
22.167	0.04	0.04	0.04	0.04	0.04
22.250	0.04	0.04	0.04	0.04	0.04
22.333	0.04	0.04	0.04	0.04	0.04
22.417	0.04	0.04	0.04	0.04	0.04
22.500	0.04	0.04	0.04	0.04	0.04
22.583	0.04	0.04	0.04	0.04	0.04
22.667	0.04	0.04	0.04	0.04	0.04
22.750	0.04	0.04	0.04	0.04	0.04
22.833	0.04	0.04	0.04	0.04	0.04
22.917	0.04	0.04	0.04	0.04	0.04
23.000	0.04	0.04	0.04	0.04	0.04
23.083	0.04	0.04	0.04	0.04	0.04
23.167	0.04	0.04	0.04	0.04	0.04

Subsection: Pond Routed Hydrograph (total out)
 Label: DB-1 (OUT)

Return Event: 2 years
 Storm Event: 2 year

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
23.250	0.04	0.04	0.04	0.04	0.04
23.333	0.04	0.04	0.04	0.04	0.04
23.417	0.04	0.04	0.04	0.04	0.04
23.500	0.04	0.04	0.04	0.03	0.03
23.583	0.03	0.03	0.03	0.03	0.03
23.667	0.03	0.03	0.03	0.03	0.03
23.750	0.03	0.03	0.03	0.03	0.03
23.833	0.03	0.03	0.03	0.03	0.03
23.917	0.03	0.03	0.03	0.03	0.03
24.000	0.03	(N/A)	(N/A)	(N/A)	(N/A)



Subsection: Pond Routed Hydrograph (total out)
Label: DB-1 (OUT)

Return Event: 10 years
Storm Event: 10 year

Peak Discharge	0.55 ft ³ /s
Time to Peak	12.233 hours
Hydrograph Volume	0.084 ac-ft

HYDROGRAPH ORDINATES (ft³/s)

Output Time Increment = 0.017 hours

Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
8.933	0.00	0.00	0.00	0.00	0.00
9.017	0.00	0.00	0.00	0.00	0.00
9.100	0.00	0.00	0.00	0.00	0.00
9.183	0.00	0.00	0.00	0.00	0.00
9.267	0.00	0.00	0.00	0.00	0.00
9.350	0.00	0.00	0.00	0.00	0.00
9.433	0.00	0.00	0.00	0.00	0.00
9.517	0.00	0.00	0.00	0.00	0.00
9.600	0.00	0.00	0.00	0.00	0.00
9.683	0.00	0.00	0.00	0.00	0.00
9.767	0.00	0.00	0.00	0.00	0.00
9.850	0.00	0.00	0.00	0.00	0.00
9.933	0.00	0.00	0.00	0.00	0.00
10.017	0.00	0.00	0.00	0.00	0.00
10.100	0.00	0.00	0.00	0.00	0.00
10.183	0.00	0.00	0.00	0.00	0.00
10.267	0.00	0.00	0.00	0.00	0.00
10.350	0.01	0.01	0.01	0.01	0.01
10.433	0.01	0.01	0.01	0.01	0.01
10.517	0.01	0.01	0.01	0.01	0.01
10.600	0.01	0.01	0.01	0.01	0.01
10.683	0.01	0.01	0.01	0.01	0.01
10.767	0.01	0.01	0.01	0.01	0.01
10.850	0.01	0.01	0.01	0.01	0.01
10.933	0.01	0.01	0.01	0.01	0.01
11.017	0.01	0.01	0.01	0.01	0.01
11.100	0.01	0.01	0.01	0.01	0.01
11.183	0.01	0.01	0.01	0.01	0.01
11.267	0.01	0.01	0.01	0.01	0.01
11.350	0.01	0.01	0.01	0.01	0.01
11.433	0.01	0.02	0.02	0.02	0.02
11.517	0.02	0.02	0.02	0.02	0.02
11.600	0.02	0.02	0.02	0.02	0.02
11.683	0.02	0.02	0.02	0.02	0.03
11.767	0.03	0.03	0.03	0.03	0.03
11.850	0.03	0.03	0.03	0.04	0.04
11.933	0.04	0.04	0.04	0.04	0.05
12.017	0.05	0.07	0.13	0.21	0.29
12.100	0.36	0.41	0.45	0.49	0.51
12.183	0.53	0.54	0.55	0.55	0.55
12.267	0.54	0.54	0.53	0.52	0.51
12.350	0.50	0.49	0.48	0.47	0.46
12.433	0.45	0.44	0.43	0.42	0.41
12.517	0.39	0.38	0.37	0.36	0.35
12.600	0.34	0.33	0.33	0.32	0.31
12.683	0.30	0.29	0.28	0.28	0.27
12.767	0.26	0.26	0.25	0.24	0.24
12.850	0.23	0.23	0.22	0.22	0.21

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
12.933	0.21	0.20	0.20	0.19	0.19
13.017	0.19	0.18	0.18	0.18	0.17
13.100	0.17	0.17	0.16	0.16	0.16
13.183	0.16	0.15	0.15	0.15	0.15
13.267	0.14	0.14	0.14	0.14	0.14
13.350	0.13	0.13	0.13	0.13	0.13
13.433	0.13	0.12	0.12	0.12	0.12
13.517	0.12	0.12	0.12	0.11	0.11
13.600	0.11	0.11	0.11	0.11	0.11
13.683	0.11	0.10	0.10	0.10	0.10
13.767	0.10	0.10	0.10	0.10	0.10
13.850	0.10	0.10	0.09	0.09	0.09
13.933	0.09	0.09	0.09	0.09	0.09
14.017	0.09	0.09	0.09	0.09	0.09
14.100	0.09	0.09	0.09	0.09	0.09
14.183	0.09	0.09	0.09	0.09	0.09
14.267	0.09	0.09	0.08	0.08	0.08
14.350	0.08	0.08	0.08	0.08	0.08
14.433	0.08	0.08	0.08	0.08	0.08
14.517	0.08	0.08	0.08	0.08	0.08
14.600	0.08	0.08	0.08	0.08	0.08
14.683	0.08	0.08	0.08	0.08	0.08
14.767	0.08	0.08	0.08	0.08	0.08
14.850	0.08	0.07	0.07	0.07	0.07
14.933	0.07	0.07	0.07	0.07	0.07
15.017	0.07	0.07	0.07	0.07	0.07
15.100	0.07	0.07	0.07	0.07	0.07
15.183	0.07	0.07	0.07	0.07	0.07
15.267	0.07	0.07	0.07	0.07	0.07
15.350	0.07	0.07	0.07	0.07	0.07
15.433	0.07	0.07	0.07	0.07	0.07
15.517	0.07	0.06	0.06	0.06	0.06
15.600	0.06	0.06	0.06	0.06	0.06
15.683	0.06	0.06	0.06	0.06	0.06
15.767	0.06	0.06	0.06	0.06	0.06
15.850	0.06	0.06	0.06	0.06	0.06
15.933	0.06	0.06	0.06	0.06	0.06
16.017	0.06	0.06	0.06	0.06	0.06
16.100	0.06	0.06	0.06	0.06	0.06
16.183	0.06	0.06	0.06	0.06	0.05
16.267	0.05	0.05	0.05	0.05	0.05
16.350	0.05	0.05	0.05	0.05	0.05
16.433	0.05	0.05	0.05	0.05	0.05
16.517	0.05	0.05	0.05	0.05	0.05
16.600	0.05	0.05	0.05	0.05	0.05
16.683	0.05	0.05	0.05	0.05	0.05
16.767	0.05	0.05	0.05	0.05	0.05
16.850	0.05	0.05	0.05	0.05	0.05
16.933	0.05	0.05	0.05	0.05	0.05
17.017	0.05	0.05	0.05	0.05	0.05
17.100	0.05	0.05	0.05	0.05	0.05
17.183	0.05	0.05	0.05	0.05	0.05

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.


Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
17.267	0.05	0.05	0.05	0.05	0.05
17.350	0.05	0.05	0.05	0.05	0.05
17.433	0.05	0.05	0.05	0.05	0.05
17.517	0.05	0.05	0.05	0.05	0.05
17.600	0.05	0.05	0.05	0.05	0.05
17.683	0.05	0.05	0.05	0.05	0.05
17.767	0.05	0.05	0.05	0.05	0.05
17.850	0.05	0.05	0.05	0.05	0.05
17.933	0.05	0.05	0.05	0.05	0.05
18.017	0.05	0.05	0.05	0.05	0.05
18.100	0.05	0.05	0.05	0.05	0.05
18.183	0.05	0.05	0.05	0.05	0.05
18.267	0.05	0.05	0.05	0.05	0.05
18.350	0.05	0.05	0.05	0.05	0.05
18.433	0.05	0.05	0.05	0.05	0.05
18.517	0.05	0.05	0.05	0.05	0.05
18.600	0.05	0.05	0.05	0.05	0.05
18.683	0.05	0.05	0.05	0.05	0.05
18.767	0.05	0.05	0.05	0.05	0.05
18.850	0.05	0.05	0.05	0.05	0.05
18.933	0.05	0.05	0.05	0.05	0.05
19.017	0.05	0.05	0.05	0.05	0.05
19.100	0.05	0.05	0.05	0.05	0.05
19.183	0.05	0.05	0.05	0.05	0.05
19.267	0.05	0.05	0.05	0.05	0.05
19.350	0.05	0.05	0.05	0.05	0.05
19.433	0.05	0.05	0.05	0.05	0.05
19.517	0.05	0.05	0.05	0.05	0.05
19.600	0.05	0.05	0.05	0.05	0.05
19.683	0.05	0.05	0.05	0.05	0.05
19.767	0.05	0.05	0.05	0.05	0.05
19.850	0.05	0.05	0.05	0.05	0.05
19.933	0.05	0.05	0.05	0.05	0.05
20.017	0.05	0.05	0.05	0.05	0.05
20.100	0.05	0.05	0.05	0.05	0.05
20.183	0.05	0.05	0.05	0.05	0.05
20.267	0.05	0.05	0.05	0.04	0.04
20.350	0.04	0.04	0.04	0.04	0.04
20.433	0.04	0.04	0.04	0.04	0.04
20.517	0.04	0.04	0.04	0.04	0.04
20.600	0.04	0.04	0.04	0.04	0.04
20.683	0.04	0.04	0.04	0.04	0.04
20.767	0.04	0.04	0.04	0.04	0.04
20.850	0.04	0.04	0.04	0.04	0.04
20.933	0.04	0.04	0.04	0.04	0.04
21.017	0.04	0.04	0.04	0.04	0.04
21.100	0.04	0.04	0.04	0.04	0.04
21.183	0.04	0.04	0.04	0.04	0.04
21.267	0.04	0.04	0.04	0.04	0.04
21.350	0.04	0.04	0.04	0.04	0.04
21.433	0.04	0.04	0.04	0.04	0.04
21.517	0.04	0.04	0.04	0.04	0.04

Subsection: Pond Routed Hydrograph (total out)
 Label: DB-1 (OUT)

Return Event: 10 years
 Storm Event: 10 year

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
21.600	0.04	0.04	0.04	0.04	0.04
21.683	0.04	0.04	0.04	0.04	0.04
21.767	0.04	0.04	0.04	0.04	0.04
21.850	0.04	0.04	0.04	0.04	0.04
21.933	0.04	0.04	0.04	0.04	0.04
22.017	0.04	0.04	0.04	0.04	0.04
22.100	0.04	0.04	0.04	0.04	0.04
22.183	0.04	0.04	0.04	0.04	0.04
22.267	0.04	0.04	0.04	0.04	0.04
22.350	0.04	0.04	0.04	0.04	0.04
22.433	0.04	0.04	0.04	0.04	0.04
22.517	0.04	0.04	0.04	0.04	0.04
22.600	0.04	0.04	0.04	0.04	0.04
22.683	0.04	0.04	0.04	0.04	0.04
22.767	0.04	0.04	0.04	0.04	0.04
22.850	0.04	0.04	0.04	0.04	0.04
22.933	0.04	0.04	0.04	0.04	0.04
23.017	0.04	0.04	0.04	0.04	0.04
23.100	0.04	0.04	0.04	0.04	0.04
23.183	0.04	0.04	0.04	0.04	0.04
23.267	0.04	0.04	0.04	0.04	0.04
23.350	0.04	0.04	0.04	0.04	0.04
23.433	0.04	0.04	0.04	0.04	0.04
23.517	0.04	0.04	0.04	0.04	0.04
23.600	0.04	0.04	0.04	0.04	0.04
23.683	0.04	0.04	0.04	0.04	0.04
23.767	0.04	0.04	0.04	0.04	0.04
23.850	0.04	0.04	0.04	0.04	0.04
23.933	0.04	0.04	0.04	0.04	0.04



Subsection: Pond Routed Hydrograph (total out)
Label: DB-1 (OUT)

Return Event: 50 years
Storm Event: 50 year

Peak Discharge	1.22 ft ³ /s
Time to Peak	12.183 hours
Hydrograph Volume	0.152 ac-ft

HYDROGRAPH ORDINATES (ft³/s)

Output Time Increment = 0.017 hours

Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
7.083	0.00	0.00	0.00	0.00	0.00
7.167	0.00	0.00	0.00	0.00	0.00
7.250	0.00	0.00	0.00	0.00	0.00
7.333	0.00	0.00	0.00	0.00	0.00
7.417	0.00	0.00	0.00	0.00	0.00
7.500	0.00	0.00	0.00	0.00	0.00
7.583	0.00	0.00	0.00	0.00	0.00
7.667	0.00	0.00	0.00	0.00	0.00
7.750	0.00	0.00	0.00	0.00	0.00
7.833	0.00	0.00	0.00	0.00	0.00
7.917	0.00	0.00	0.00	0.00	0.00
8.000	0.00	0.00	0.00	0.00	0.00
8.083	0.00	0.00	0.00	0.00	0.00
8.167	0.00	0.00	0.00	0.00	0.00
8.250	0.00	0.00	0.00	0.00	0.00
8.333	0.00	0.00	0.00	0.00	0.00
8.417	0.00	0.00	0.00	0.00	0.00
8.500	0.00	0.00	0.00	0.00	0.00
8.583	0.00	0.00	0.00	0.00	0.01
8.667	0.01	0.01	0.01	0.01	0.01
8.750	0.01	0.01	0.01	0.01	0.01
8.833	0.01	0.01	0.01	0.01	0.01
8.917	0.01	0.01	0.01	0.01	0.01
9.000	0.01	0.01	0.01	0.01	0.01
9.083	0.01	0.01	0.01	0.01	0.01
9.167	0.01	0.01	0.01	0.01	0.01
9.250	0.01	0.01	0.01	0.01	0.01
9.333	0.01	0.01	0.01	0.01	0.01
9.417	0.01	0.01	0.01	0.01	0.01
9.500	0.01	0.01	0.01	0.01	0.01
9.583	0.01	0.01	0.01	0.01	0.01
9.667	0.01	0.01	0.01	0.01	0.01
9.750	0.01	0.01	0.01	0.01	0.01
9.833	0.01	0.01	0.01	0.01	0.01
9.917	0.01	0.01	0.01	0.01	0.01
10.000	0.01	0.01	0.01	0.01	0.01
10.083	0.01	0.01	0.01	0.01	0.01
10.167	0.01	0.01	0.01	0.01	0.01
10.250	0.01	0.02	0.02	0.02	0.02
10.333	0.02	0.02	0.02	0.02	0.02
10.417	0.02	0.02	0.02	0.02	0.02
10.500	0.02	0.02	0.02	0.02	0.02
10.583	0.02	0.02	0.02	0.02	0.02
10.667	0.02	0.02	0.02	0.02	0.02
10.750	0.02	0.02	0.02	0.02	0.02
10.833	0.02	0.02	0.02	0.02	0.02
10.917	0.02	0.02	0.02	0.02	0.02
11.000	0.03	0.03	0.03	0.03	0.03

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
11.083	0.03	0.03	0.03	0.03	0.03
11.167	0.03	0.03	0.03	0.03	0.03
11.250	0.03	0.03	0.03	0.03	0.03
11.333	0.03	0.03	0.03	0.03	0.03
11.417	0.03	0.03	0.03	0.03	0.03
11.500	0.03	0.03	0.03	0.03	0.03
11.583	0.03	0.03	0.03	0.03	0.03
11.667	0.04	0.04	0.04	0.04	0.04
11.750	0.04	0.04	0.04	0.04	0.04
11.833	0.04	0.05	0.05	0.07	0.14
11.917	0.25	0.38	0.50	0.63	0.75
12.000	0.87	0.93	0.98	1.03	1.08
12.083	1.12	1.15	1.18	1.20	1.21
12.167	1.22	1.22	1.22	1.21	1.20
12.250	1.19	1.18	1.17	1.15	1.14
12.333	1.12	1.11	1.09	1.07	1.06
12.417	1.04	1.02	1.01	0.99	0.97
12.500	0.96	0.94	0.92	0.91	0.89
12.583	0.87	0.83	0.80	0.77	0.74
12.667	0.71	0.69	0.66	0.64	0.61
12.750	0.59	0.57	0.55	0.53	0.51
12.833	0.50	0.48	0.47	0.45	0.44
12.917	0.42	0.41	0.40	0.39	0.38
13.000	0.37	0.36	0.35	0.34	0.33
13.083	0.32	0.31	0.31	0.30	0.29
13.167	0.29	0.28	0.27	0.27	0.26
13.250	0.26	0.25	0.25	0.24	0.24
13.333	0.23	0.23	0.23	0.22	0.22
13.417	0.21	0.21	0.21	0.20	0.20
13.500	0.20	0.20	0.19	0.19	0.19
13.583	0.18	0.18	0.18	0.18	0.18
13.667	0.17	0.17	0.17	0.17	0.17
13.750	0.16	0.16	0.16	0.16	0.16
13.833	0.15	0.15	0.15	0.15	0.15
13.917	0.15	0.15	0.14	0.14	0.14
14.000	0.14	0.14	0.14	0.14	0.14
14.083	0.13	0.13	0.13	0.13	0.13
14.167	0.13	0.13	0.13	0.13	0.12
14.250	0.12	0.12	0.12	0.12	0.12
14.333	0.12	0.12	0.12	0.12	0.12
14.417	0.12	0.11	0.11	0.11	0.11
14.500	0.11	0.11	0.11	0.11	0.11
14.583	0.11	0.11	0.11	0.11	0.11
14.667	0.11	0.11	0.11	0.11	0.11
14.750	0.10	0.10	0.10	0.10	0.10
14.833	0.10	0.10	0.10	0.10	0.10
14.917	0.10	0.10	0.10	0.10	0.10
15.000	0.10	0.10	0.10	0.10	0.10
15.083	0.10	0.10	0.10	0.10	0.10
15.167	0.10	0.09	0.09	0.09	0.09
15.250	0.09	0.09	0.09	0.09	0.09
15.333	0.09	0.09	0.09	0.09	0.09

Subsection: Pond Routed Hydrograph (total out)
Label: DB-1 (OUT)


Return Event: 50 years
Storm Event: 50 year

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
15.417	0.09	0.09	0.09	0.09	0.09
15.500	0.09	0.09	0.09	0.09	0.09
15.583	0.09	0.09	0.09	0.09	0.09
15.667	0.09	0.09	0.09	0.09	0.09
15.750	0.09	0.09	0.09	0.09	0.09
15.833	0.09	0.09	0.09	0.09	0.09
15.917	0.09	0.09	0.08	0.08	0.08
16.000	0.08	0.08	0.08	0.08	0.08
16.083	0.08	0.08	0.08	0.08	0.08
16.167	0.08	0.08	0.08	0.08	0.08
16.250	0.08	0.08	0.08	0.08	0.08
16.333	0.08	0.08	0.08	0.08	0.08
16.417	0.08	0.08	0.08	0.08	0.08
16.500	0.08	0.08	0.08	0.08	0.08
16.583	0.08	0.08	0.08	0.08	0.08
16.667	0.08	0.07	0.07	0.07	0.07
16.750	0.07	0.07	0.07	0.07	0.07
16.833	0.07	0.07	0.07	0.07	0.07
16.917	0.07	0.07	0.07	0.07	0.07
17.000	0.07	0.07	0.07	0.07	0.07
17.083	0.07	0.07	0.07	0.07	0.07
17.167	0.07	0.07	0.07	0.07	0.07
17.250	0.07	0.07	0.07	0.07	0.07
17.333	0.07	0.07	0.07	0.07	0.07
17.417	0.07	0.07	0.07	0.07	0.07
17.500	0.07	0.07	0.07	0.07	0.07
17.583	0.07	0.07	0.07	0.07	0.07
17.667	0.07	0.07	0.07	0.06	0.06
17.750	0.06	0.06	0.06	0.06	0.06
17.833	0.06	0.06	0.06	0.06	0.06
17.917	0.06	0.06	0.06	0.06	0.06
18.000	0.06	0.06	0.06	0.06	0.06
18.083	0.06	0.06	0.06	0.06	0.06
18.167	0.06	0.06	0.06	0.06	0.06
18.250	0.06	0.06	0.06	0.06	0.06
18.333	0.06	0.06	0.06	0.06	0.06
18.417	0.06	0.06	0.06	0.06	0.06
18.500	0.06	0.06	0.06	0.06	0.06
18.583	0.06	0.06	0.06	0.06	0.06
18.667	0.06	0.06	0.06	0.06	0.06
18.750	0.06	0.06	0.06	0.06	0.06
18.833	0.06	0.06	0.06	0.06	0.06
18.917	0.06	0.06	0.05	0.05	0.05
19.000	0.05	0.05	0.05	0.05	0.05
19.083	0.05	0.05	0.05	0.05	0.05
19.167	0.05	0.05	0.05	0.05	0.05
19.250	0.05	0.05	0.05	0.05	0.05
19.333	0.05	0.05	0.05	0.05	0.05
19.417	0.05	0.05	0.05	0.05	0.05
19.500	0.05	0.05	0.05	0.05	0.05
19.583	0.05	0.05	0.05	0.05	0.05
19.667	0.05	0.05	0.05	0.05	0.05

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
19.750	0.05	0.05	0.05	0.05	0.05
19.833	0.05	0.05	0.05	0.05	0.05
19.917	0.05	0.05	0.05	0.05	0.05
20.000	0.05	0.05	0.05	0.05	0.05
20.083	0.05	0.05	0.05	0.05	0.05
20.167	0.05	0.05	0.05	0.05	0.05
20.250	0.05	0.05	0.05	0.05	0.05
20.333	0.05	0.05	0.05	0.05	0.05
20.417	0.05	0.05	0.05	0.05	0.05
20.500	0.05	0.05	0.05	0.05	0.05
20.583	0.05	0.05	0.05	0.05	0.05
20.667	0.05	0.05	0.05	0.05	0.05
20.750	0.05	0.05	0.05	0.05	0.05
20.833	0.05	0.05	0.05	0.05	0.05
20.917	0.05	0.05	0.05	0.05	0.05
21.000	0.05	0.05	0.05	0.05	0.05
21.083	0.05	0.05	0.05	0.05	0.05
21.167	0.05	0.05	0.05	0.05	0.05
21.250	0.05	0.05	0.05	0.05	0.05
21.333	0.05	0.05	0.05	0.05	0.05
21.417	0.05	0.05	0.05	0.05	0.05
21.500	0.05	0.05	0.05	0.05	0.05
21.583	0.05	0.05	0.05	0.05	0.05
21.667	0.05	0.05	0.05	0.05	0.05
21.750	0.05	0.05	0.05	0.05	0.05
21.833	0.05	0.05	0.05	0.05	0.05
21.917	0.05	0.05	0.05	0.05	0.05
22.000	0.05	0.05	0.05	0.05	0.05
22.083	0.05	0.05	0.05	0.05	0.05
22.167	0.05	0.05	0.05	0.05	0.05
22.250	0.05	0.05	0.05	0.05	0.05
22.333	0.05	0.05	0.05	0.05	0.05
22.417	0.05	0.05	0.05	0.05	0.05
22.500	0.05	0.05	0.05	0.05	0.05
22.583	0.05	0.05	0.05	0.05	0.05
22.667	0.05	0.05	0.05	0.05	0.05
22.750	0.05	0.05	0.05	0.05	0.05
22.833	0.05	0.05	0.05	0.05	0.05
22.917	0.05	0.05	0.05	0.05	0.05
23.000	0.05	0.05	0.05	0.05	0.05
23.083	0.05	0.05	0.05	0.05	0.05
23.167	0.05	0.05	0.05	0.05	0.05
23.250	0.05	0.05	0.05	0.05	0.05
23.333	0.05	0.05	0.05	0.05	0.05
23.417	0.05	0.05	0.05	0.05	0.05
23.500	0.05	0.05	0.05	0.05	0.05
23.583	0.05	0.05	0.05	0.05	0.05
23.667	0.05	0.05	0.05	0.05	0.05
23.750	0.05	0.05	0.05	0.05	0.05
23.833	0.05	0.05	0.05	0.05	0.05
23.917	0.05	0.05	0.05	0.05	0.05
24.000	0.05	(N/A)	(N/A)	(N/A)	(N/A)



Subsection: Pond Routed Hydrograph (total out)
Label: DB-1 (OUT)

Return Event: 100 years
Storm Event: 100 year

Peak Discharge	1.47 ft ³ /s
Time to Peak	12.183 hours
Hydrograph Volume	0.192 ac-ft

HYDROGRAPH ORDINATES (ft³/s)

Output Time Increment = 0.017 hours

Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
6.350	0.00	0.00	0.00	0.00	0.00
6.433	0.00	0.00	0.00	0.00	0.00
6.517	0.00	0.00	0.00	0.00	0.00
6.600	0.00	0.00	0.00	0.00	0.00
6.683	0.00	0.00	0.00	0.00	0.00
6.767	0.00	0.00	0.00	0.00	0.00
6.850	0.00	0.00	0.00	0.00	0.00
6.933	0.00	0.00	0.00	0.00	0.00
7.017	0.00	0.00	0.00	0.00	0.00
7.100	0.00	0.00	0.00	0.00	0.00
7.183	0.00	0.00	0.00	0.00	0.00
7.267	0.00	0.00	0.00	0.00	0.00
7.350	0.00	0.00	0.00	0.00	0.00
7.433	0.00	0.00	0.00	0.00	0.00
7.517	0.00	0.00	0.00	0.00	0.00
7.600	0.00	0.00	0.00	0.00	0.00
7.683	0.00	0.00	0.00	0.00	0.00
7.767	0.00	0.00	0.00	0.00	0.01
7.850	0.01	0.01	0.01	0.01	0.01
7.933	0.01	0.01	0.01	0.01	0.01
8.017	0.01	0.01	0.01	0.01	0.01
8.100	0.01	0.01	0.01	0.01	0.01
8.183	0.01	0.01	0.01	0.01	0.01
8.267	0.01	0.01	0.01	0.01	0.01
8.350	0.01	0.01	0.01	0.01	0.01
8.433	0.01	0.01	0.01	0.01	0.01
8.517	0.01	0.01	0.01	0.01	0.01
8.600	0.01	0.01	0.01	0.01	0.01
8.683	0.01	0.01	0.01	0.01	0.01
8.767	0.01	0.01	0.01	0.01	0.01
8.850	0.01	0.01	0.01	0.01	0.01
8.933	0.01	0.01	0.01	0.01	0.01
9.017	0.01	0.01	0.01	0.01	0.01
9.100	0.01	0.01	0.01	0.01	0.01
9.183	0.01	0.01	0.01	0.01	0.01
9.267	0.01	0.01	0.01	0.01	0.01
9.350	0.01	0.01	0.01	0.01	0.01
9.433	0.01	0.01	0.01	0.01	0.01
9.517	0.01	0.02	0.02	0.02	0.02
9.600	0.02	0.02	0.02	0.02	0.02
9.683	0.02	0.02	0.02	0.02	0.02
9.767	0.02	0.02	0.02	0.02	0.02
9.850	0.02	0.02	0.02	0.02	0.02
9.933	0.02	0.02	0.02	0.02	0.02
10.017	0.02	0.02	0.02	0.02	0.02
10.100	0.02	0.02	0.02	0.02	0.02
10.183	0.02	0.02	0.02	0.02	0.02
10.267	0.02	0.02	0.02	0.02	0.02

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
10.350	0.02	0.02	0.02	0.02	0.02
10.433	0.02	0.02	0.03	0.03	0.03
10.517	0.03	0.03	0.03	0.03	0.03
10.600	0.03	0.03	0.03	0.03	0.03
10.683	0.03	0.03	0.03	0.03	0.03
10.767	0.03	0.03	0.03	0.03	0.03
10.850	0.03	0.03	0.03	0.03	0.03
10.933	0.03	0.03	0.03	0.03	0.03
11.017	0.03	0.03	0.03	0.03	0.03
11.100	0.03	0.03	0.03	0.03	0.03
11.183	0.03	0.03	0.03	0.03	0.03
11.267	0.03	0.03	0.03	0.03	0.03
11.350	0.04	0.04	0.04	0.04	0.04
11.433	0.04	0.04	0.04	0.04	0.04
11.517	0.04	0.04	0.04	0.04	0.04
11.600	0.04	0.04	0.04	0.04	0.04
11.683	0.04	0.04	0.04	0.04	0.04
11.767	0.05	0.05	0.06	0.09	0.16
11.850	0.26	0.36	0.46	0.58	0.70
11.933	0.83	0.92	0.98	1.05	1.11
12.017	1.18	1.24	1.30	1.34	1.38
12.100	1.40	1.43	1.44	1.46	1.46
12.183	1.47	1.47	1.46	1.45	1.45
12.267	1.43	1.42	1.41	1.40	1.38
12.350	1.37	1.35	1.34	1.32	1.31
12.433	1.28	1.26	1.24	1.22	1.20
12.517	1.18	1.15	1.13	1.11	1.09
12.600	1.07	1.05	1.03	1.01	0.99
12.683	0.97	0.95	0.94	0.92	0.90
12.767	0.88	0.85	0.82	0.79	0.76
12.850	0.73	0.70	0.67	0.65	0.63
12.933	0.60	0.58	0.56	0.54	0.53
13.017	0.51	0.49	0.48	0.46	0.45
13.100	0.44	0.42	0.41	0.40	0.39
13.183	0.38	0.37	0.36	0.35	0.34
13.267	0.33	0.33	0.32	0.31	0.30
13.350	0.30	0.29	0.29	0.28	0.28
13.433	0.27	0.27	0.26	0.26	0.25
13.517	0.25	0.24	0.24	0.24	0.23
13.600	0.23	0.22	0.22	0.22	0.22
13.683	0.21	0.21	0.21	0.20	0.20
13.767	0.20	0.20	0.19	0.19	0.19
13.850	0.19	0.19	0.18	0.18	0.18
13.933	0.18	0.18	0.17	0.17	0.17
14.017	0.17	0.17	0.17	0.16	0.16
14.100	0.16	0.16	0.16	0.16	0.15
14.183	0.15	0.15	0.15	0.15	0.15
14.267	0.15	0.15	0.14	0.14	0.14
14.350	0.14	0.14	0.14	0.14	0.14
14.433	0.14	0.14	0.14	0.14	0.13
14.517	0.13	0.13	0.13	0.13	0.13
14.600	0.13	0.13	0.13	0.13	0.13

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
14.683	0.13	0.13	0.13	0.13	0.13
14.767	0.12	0.12	0.12	0.12	0.12
14.850	0.12	0.12	0.12	0.12	0.12
14.933	0.12	0.12	0.12	0.12	0.12
15.017	0.12	0.12	0.12	0.12	0.12
15.100	0.12	0.11	0.11	0.11	0.11
15.183	0.11	0.11	0.11	0.11	0.11
15.267	0.11	0.11	0.11	0.11	0.11
15.350	0.11	0.11	0.11	0.11	0.11
15.433	0.11	0.11	0.11	0.11	0.11
15.517	0.10	0.10	0.10	0.10	0.10
15.600	0.10	0.10	0.10	0.10	0.10
15.683	0.10	0.10	0.10	0.10	0.10
15.767	0.10	0.10	0.10	0.10	0.10
15.850	0.10	0.10	0.10	0.10	0.09
15.933	0.09	0.09	0.09	0.09	0.09
16.017	0.09	0.09	0.09	0.09	0.09
16.100	0.09	0.09	0.09	0.09	0.09
16.183	0.09	0.09	0.09	0.09	0.09
16.267	0.09	0.09	0.09	0.09	0.09
16.350	0.09	0.09	0.09	0.09	0.09
16.433	0.09	0.09	0.09	0.09	0.09
16.517	0.09	0.09	0.09	0.09	0.09
16.600	0.09	0.09	0.09	0.09	0.09
16.683	0.09	0.09	0.09	0.09	0.08
16.767	0.08	0.08	0.08	0.08	0.08
16.850	0.08	0.08	0.08	0.08	0.08
16.933	0.08	0.08	0.08	0.08	0.08
17.017	0.08	0.08	0.08	0.08	0.08
17.100	0.08	0.08	0.08	0.08	0.08
17.183	0.08	0.08	0.08	0.08	0.08
17.267	0.08	0.08	0.08	0.08	0.08
17.350	0.08	0.08	0.08	0.08	0.08
17.433	0.08	0.08	0.08	0.08	0.08
17.517	0.08	0.08	0.08	0.08	0.08
17.600	0.08	0.08	0.08	0.08	0.08
17.683	0.08	0.08	0.08	0.08	0.08
17.767	0.08	0.08	0.08	0.08	0.08
17.850	0.08	0.07	0.07	0.07	0.07
17.933	0.07	0.07	0.07	0.07	0.07
18.017	0.07	0.07	0.07	0.07	0.07
18.100	0.07	0.07	0.07	0.07	0.07
18.183	0.07	0.07	0.07	0.07	0.07
18.267	0.07	0.07	0.07	0.07	0.07
18.350	0.07	0.07	0.07	0.07	0.07
18.433	0.07	0.07	0.07	0.07	0.07
18.517	0.07	0.07	0.07	0.07	0.07
18.600	0.07	0.07	0.07	0.07	0.07
18.683	0.07	0.07	0.07	0.07	0.07
18.767	0.07	0.07	0.07	0.07	0.07
18.850	0.07	0.07	0.07	0.07	0.07
18.933	0.07	0.07	0.07	0.06	0.06

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.


Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
19.017	0.06	0.06	0.06	0.06	0.06
19.100	0.06	0.06	0.06	0.06	0.06
19.183	0.06	0.06	0.06	0.06	0.06
19.267	0.06	0.06	0.06	0.06	0.06
19.350	0.06	0.06	0.06	0.06	0.06
19.433	0.06	0.06	0.06	0.06	0.06
19.517	0.06	0.06	0.06	0.06	0.06
19.600	0.06	0.06	0.06	0.06	0.06
19.683	0.06	0.06	0.06	0.06	0.06
19.767	0.06	0.06	0.06	0.06	0.06
19.850	0.06	0.06	0.06	0.06	0.06
19.933	0.06	0.06	0.06	0.06	0.06
20.017	0.06	0.06	0.06	0.06	0.06
20.100	0.06	0.05	0.05	0.05	0.05
20.183	0.05	0.05	0.05	0.05	0.05
20.267	0.05	0.05	0.05	0.05	0.05
20.350	0.05	0.05	0.05	0.05	0.05
20.433	0.05	0.05	0.05	0.05	0.05
20.517	0.05	0.05	0.05	0.05	0.05
20.600	0.05	0.05	0.05	0.05	0.05
20.683	0.05	0.05	0.05	0.05	0.05
20.767	0.05	0.05	0.05	0.05	0.05
20.850	0.05	0.05	0.05	0.05	0.05
20.933	0.05	0.05	0.05	0.05	0.05
21.017	0.05	0.05	0.05	0.05	0.05
21.100	0.05	0.05	0.05	0.05	0.05
21.183	0.05	0.05	0.05	0.05	0.05
21.267	0.05	0.05	0.05	0.05	0.05
21.350	0.05	0.05	0.05	0.05	0.05
21.433	0.05	0.05	0.05	0.05	0.05
21.517	0.05	0.05	0.05	0.05	0.05
21.600	0.05	0.05	0.05	0.05	0.05
21.683	0.05	0.05	0.05	0.05	0.05
21.767	0.05	0.05	0.05	0.05	0.05
21.850	0.05	0.05	0.05	0.05	0.05
21.933	0.05	0.05	0.05	0.05	0.05
22.017	0.05	0.05	0.05	0.05	0.05
22.100	0.05	0.05	0.05	0.05	0.05
22.183	0.05	0.05	0.05	0.05	0.05
22.267	0.05	0.05	0.05	0.05	0.05
22.350	0.05	0.05	0.05	0.05	0.05
22.433	0.05	0.05	0.05	0.05	0.05
22.517	0.05	0.05	0.05	0.05	0.05
22.600	0.05	0.05	0.05	0.05	0.05
22.683	0.05	0.05	0.05	0.05	0.05
22.767	0.05	0.05	0.05	0.05	0.05
22.850	0.05	0.05	0.05	0.05	0.05
22.933	0.05	0.05	0.05	0.05	0.05
23.017	0.05	0.05	0.05	0.05	0.05
23.100	0.05	0.05	0.05	0.05	0.05
23.183	0.05	0.05	0.05	0.05	0.05
23.267	0.05	0.05	0.05	0.05	0.05

Subsection: Pond Routed Hydrograph (total out)
Label: DB-1 (OUT)

Return Event: 100 years
Storm Event: 100 year

HYDROGRAPH ORDINATES (ft³/s)
Output Time Increment = 0.017 hours
Time on left represents time for first value in each row.

Time (hours)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)	Flow (ft ³ /s)
23.350	0.05	0.05	0.05	0.05	0.05
23.433	0.05	0.05	0.05	0.05	0.05
23.517	0.05	0.05	0.05	0.05	0.05
23.600	0.05	0.05	0.05	0.05	0.05
23.683	0.05	0.05	0.05	0.05	0.05
23.767	0.05	0.05	0.05	0.05	0.05
23.850	0.05	0.05	0.05	0.05	0.05
23.933	0.05	0.05	0.05	0.05	0.05



Index

B

Bethlehem NH (Time-Depth Curve, 10 years)...4, 5
Bethlehem NH (Time-Depth Curve, 100 years)...6, 7
Bethlehem NH (Time-Depth Curve, 2 years)...8, 9
Bethlehem NH (Time-Depth Curve, 50 years)...10, 11

C

Composite Outlet Structure - 1 (Outlet Input Data, 2 years)...106, 107

D

DB-1 (Elevation-Area Volume Curve, 2 years)...105
DB-1 (IN) (Level Pool Pond Routing Summary, 10 years)...109
DB-1 (IN) (Level Pool Pond Routing Summary, 100 years)...111
DB-1 (IN) (Level Pool Pond Routing Summary, 2 years)...108
DB-1 (IN) (Level Pool Pond Routing Summary, 50 years)...110
DB-1 (OUT) (Pond Routed Hydrograph (total out), 10 years)...117, 118, 119, 120, 121
DB-1 (OUT) (Pond Routed Hydrograph (total out), 100 years)...127, 128, 129, 130, 131, 132
DB-1 (OUT) (Pond Routed Hydrograph (total out), 2 years)...112, 113, 114, 115, 116
DB-1 (OUT) (Pond Routed Hydrograph (total out), 50 years)...122, 123, 124, 125, 126

M

Master Network Summary...2, 3

O

O-1 (POST) (Addition Summary, 10 years)...98
O-1 (POST) (Addition Summary, 100 years)...100
O-1 (POST) (Addition Summary, 2 years)...97
O-1 (POST) (Addition Summary, 50 years)...99
O-1 (PRE) (Addition Summary, 10 years)...102
O-1 (PRE) (Addition Summary, 100 years)...104
O-1 (PRE) (Addition Summary, 2 years)...101
O-1 (PRE) (Addition Summary, 50 years)...103

P

POST-1 (Runoff CN-Area, 2 years)...19
POST-1 (Time of Concentration Calculations, 2 years)...12, 13
POST-1 (Unit Hydrograph (Hydrograph Table), 10 years)...29, 30, 31, 32, 33
POST-1 (Unit Hydrograph (Hydrograph Table), 100 years)...42, 43, 44, 45, 46, 47
POST-1 (Unit Hydrograph (Hydrograph Table), 2 years)...23, 24, 25, 26, 27
POST-1 (Unit Hydrograph (Hydrograph Table), 50 years)...35, 36, 37, 38, 39, 40
POST-1 (Unit Hydrograph Summary, 10 years)...28

POST-1 (Unit Hydrograph Summary, 100 years)...41

POST-1 (Unit Hydrograph Summary, 2 years)...22

POST-1 (Unit Hydrograph Summary, 50 years)...34

POST-2 (Runoff CN-Area, 2 years)...20

POST-2 (Time of Concentration Calculations, 2 years)...14, 15, 16

POST-2 (Unit Hydrograph (Hydrograph Table), 10 years)...55, 56, 57, 58, 59

POST-2 (Unit Hydrograph (Hydrograph Table), 100 years)...67, 68, 69, 70, 71, 72

POST-2 (Unit Hydrograph (Hydrograph Table), 2 years)...49, 50, 51, 52, 53

POST-2 (Unit Hydrograph (Hydrograph Table), 50 years)...61, 62, 63, 64, 65

POST-2 (Unit Hydrograph Summary, 10 years)...54

POST-2 (Unit Hydrograph Summary, 100 years)...66

POST-2 (Unit Hydrograph Summary, 2 years)...48

POST-2 (Unit Hydrograph Summary, 50 years)...60

PRE-1 (Runoff CN-Area, 2 years)...21

PRE-1 (Time of Concentration Calculations, 2 years)...17, 18

PRE-1 (Unit Hydrograph (Hydrograph Table), 10 years)...80, 81, 82, 83, 84

PRE-1 (Unit Hydrograph (Hydrograph Table), 100 years)...92, 93, 94, 95, 96

PRE-1 (Unit Hydrograph (Hydrograph Table), 2 years)...74, 75, 76, 77, 78

PRE-1 (Unit Hydrograph (Hydrograph Table), 50 years)...86, 87, 88, 89, 90

PRE-1 (Unit Hydrograph Summary, 10 years)...79

PRE-1 (Unit Hydrograph Summary, 100 years)...91

PRE-1 (Unit Hydrograph Summary, 2 years)...73

PRE-1 (Unit Hydrograph Summary, 50 years)...85

APPENDIX C – HYDRAULIC AND STABILITY CALCULATIONS

Worksheet for Drainage Line P1_10YR

Project Description

Friction Method Manning Formula
Solve For Normal Depth

Input Data

Roughness Coefficient 0.012
Channel Slope 0.02500 ft/ft
Diameter 1.00 ft
Discharge 1.68 ft³/s

Results

Normal Depth 0.36 ft
Flow Area 0.25 ft²
Wetted Perimeter 1.28 ft
Hydraulic Radius 0.20 ft
Top Width 0.96 ft
Critical Depth 0.55 ft
Percent Full 35.9 %
Critical Slope 0.00549 ft/ft
Velocity 6.63 ft/s
Velocity Head 0.68 ft
Specific Energy 1.04 ft
Froude Number 2.28
Maximum Discharge 6.56 ft³/s
Discharge Full 6.10 ft³/s
Slope Full 0.00189 ft/ft
Flow Type SuperCritical

GVF Input Data

Downstream Depth 0.00 ft
Length 0.00 ft
Number Of Steps 0

GVF Output Data

Upstream Depth 0.00 ft
Profile Description
Profile Headloss 0.00 ft
Average End Depth Over Rise 0.00 %
Normal Depth Over Rise 35.87 %
Downstream Velocity Infinity ft/s
Upstream Velocity Infinity ft/s
Normal Depth 0.36 ft
Critical Depth 0.55 ft
Channel Slope 0.02500 ft/ft
Critical Slope 0.00549 ft/ft

Worksheet for Drainage Line P1_25YR

Project Description

Friction Method Manning Formula
Solve For Normal Depth

Input Data

Roughness Coefficient 0.012
Channel Slope 0.02500 ft/ft
Diameter 1.00 ft
Discharge 2.27 ft³/s

Results

Normal Depth 0.42 ft
Flow Area 0.32 ft²
Wetted Perimeter 1.42 ft
Hydraulic Radius 0.22 ft
Top Width 0.99 ft
Critical Depth 0.64 ft
Percent Full 42.3 %
Critical Slope 0.00619 ft/ft
Velocity 7.19 ft/s
Velocity Head 0.80 ft
Specific Energy 1.23 ft
Froude Number 2.24
Maximum Discharge 6.56 ft³/s
Discharge Full 6.10 ft³/s
Slope Full 0.00346 ft/ft
Flow Type SuperCritical

GVF Input Data

Downstream Depth 0.00 ft
Length 0.00 ft
Number Of Steps 0

GVF Output Data

Upstream Depth 0.00 ft
Profile Description
Profile Headloss 0.00 ft
Average End Depth Over Rise 0.00 %
Normal Depth Over Rise 42.26 %
Downstream Velocity Infinity ft/s
Upstream Velocity Infinity ft/s
Normal Depth 0.42 ft
Critical Depth 0.64 ft
Channel Slope 0.02500 ft/ft
Critical Slope 0.00619 ft/ft

Worksheet for Drainage Line P1_100YR

Project Description

Friction Method Manning Formula
Solve For Normal Depth

Input Data

Roughness Coefficient 0.012
Channel Slope 0.02500 ft/ft
Diameter 1.00 ft
Discharge 3.44 ft³/s

Results

Normal Depth 0.54 ft
Flow Area 0.43 ft²
Wetted Perimeter 1.65 ft
Hydraulic Radius 0.26 ft
Top Width 1.00 ft
Critical Depth 0.79 ft
Percent Full 53.7 %
Critical Slope 0.00846 ft/ft
Velocity 8.00 ft/s
Velocity Head 1.00 ft
Specific Energy 1.53 ft
Froude Number 2.15
Maximum Discharge 6.56 ft³/s
Discharge Full 6.10 ft³/s
Slope Full 0.00794 ft/ft
Flow Type SuperCritical

GVF Input Data

Downstream Depth 0.00 ft
Length 0.00 ft
Number Of Steps 0

GVF Output Data

Upstream Depth 0.00 ft
Profile Description
Profile Headloss 0.00 ft
Average End Depth Over Rise 0.00 %
Normal Depth Over Rise 53.72 %
Downstream Velocity Infinity ft/s
Upstream Velocity Infinity ft/s
Normal Depth 0.54 ft
Critical Depth 0.79 ft
Channel Slope 0.02500 ft/ft
Critical Slope 0.00846 ft/ft

Worksheet for Drainage Line P2_WQF

Project Description

Friction Method Manning Formula
Solve For Normal Depth

Input Data

Roughness Coefficient 0.010
Channel Slope 0.04000 ft/ft
Diameter 0.17 ft
Discharge 0.07 ft³/s

Results

Normal Depth 0.12 ft
Flow Area 0.02 ft²
Wetted Perimeter 0.33 ft
Hydraulic Radius 0.05 ft
Top Width 0.15 ft
Critical Depth 0.16 ft
Percent Full 69.5 %
Critical Slope 0.02382 ft/ft
Velocity 4.00 ft/s
Velocity Head 0.25 ft
Specific Energy 0.36 ft
Froude Number 2.17
Maximum Discharge 0.08 ft³/s
Discharge Full 0.08 ft³/s
Slope Full 0.02754 ft/ft
Flow Type SuperCritical

GVF Input Data

Downstream Depth 0.00 ft
Length 0.00 ft
Number Of Steps 0

GVF Output Data

Upstream Depth 0.00 ft
Profile Description
Profile Headloss 0.00 ft
Average End Depth Over Rise 0.00 %
Normal Depth Over Rise 69.54 %
Downstream Velocity Infinity ft/s
Upstream Velocity Infinity ft/s
Normal Depth 0.12 ft
Critical Depth 0.16 ft
Channel Slope 0.04000 ft/ft
Critical Slope 0.02382 ft/ft

Worksheet for Drainage Line P3_10YR

Project Description

Friction Method Manning Formula
Solve For Normal Depth

Input Data

Roughness Coefficient 0.012
Channel Slope 0.04400 ft/ft
Diameter 1.00 ft
Discharge 1.68 ft³/s

Results

Normal Depth 0.31 ft
Flow Area 0.21 ft²
Wetted Perimeter 1.18 ft
Hydraulic Radius 0.18 ft
Top Width 0.92 ft
Critical Depth 0.55 ft
Percent Full 30.9 %
Critical Slope 0.00549 ft/ft
Velocity 8.13 ft/s
Velocity Head 1.03 ft
Specific Energy 1.34 ft
Froude Number 3.03
Maximum Discharge 8.71 ft³/s
Discharge Full 8.10 ft³/s
Slope Full 0.00189 ft/ft
Flow Type SuperCritical

GVF Input Data

Downstream Depth 0.00 ft
Length 0.00 ft
Number Of Steps 0

GVF Output Data

Upstream Depth 0.00 ft
Profile Description
Profile Headloss 0.00 ft
Average End Depth Over Rise 0.00 %
Normal Depth Over Rise 30.91 %
Downstream Velocity Infinity ft/s
Upstream Velocity Infinity ft/s
Normal Depth 0.31 ft
Critical Depth 0.55 ft
Channel Slope 0.04400 ft/ft
Critical Slope 0.00549 ft/ft

Worksheet for Drainage Line P3_25YR

Project Description

Friction Method	Manning Formula
Solve For	Normal Depth

Input Data

Roughness Coefficient	0.012	
Channel Slope	0.04400	ft/ft
Diameter	1.00	ft
Discharge	2.27	ft³/s

Results

Normal Depth	0.36	ft
Flow Area	0.26	ft²
Wetted Perimeter	1.29	ft
Hydraulic Radius	0.20	ft
Top Width	0.96	ft
Critical Depth	0.64	ft
Percent Full	36.2	%
Critical Slope	0.00619	ft/ft
Velocity	8.84	ft/s
Velocity Head	1.22	ft
Specific Energy	1.58	ft
Froude Number	3.02	
Maximum Discharge	8.71	ft³/s
Discharge Full	8.10	ft³/s
Slope Full	0.00346	ft/ft
Flow Type	SuperCritical	

GVF Input Data

Downstream Depth	0.00	ft
Length	0.00	ft
Number Of Steps	0	

GVF Output Data

Upstream Depth	0.00	ft
Profile Description		
Profile Headloss	0.00	ft
Average End Depth Over Rise	0.00	%
Normal Depth Over Rise	36.23	%
Downstream Velocity	Infinity	ft/s
Upstream Velocity	Infinity	ft/s
Normal Depth	0.36	ft
Critical Depth	0.64	ft
Channel Slope	0.04400	ft/ft
Critical Slope	0.00619	ft/ft

Worksheet for Drainage Line P3_100YR

Project Description

Friction Method Manning Formula
Solve For Normal Depth

Input Data

Roughness Coefficient 0.012
Channel Slope 0.04400 ft/ft
Diameter 1.00 ft
Discharge 3.44 ft³/s

Results

Normal Depth 0.45 ft
Flow Area 0.35 ft²
Wetted Perimeter 1.48 ft
Hydraulic Radius 0.23 ft
Top Width 1.00 ft
Critical Depth 0.79 ft
Percent Full 45.5 %
Critical Slope 0.00846 ft/ft
Velocity 9.89 ft/s
Velocity Head 1.52 ft
Specific Energy 1.98 ft
Froude Number 2.95
Maximum Discharge 8.71 ft³/s
Discharge Full 8.10 ft³/s
Slope Full 0.00794 ft/ft
Flow Type SuperCritical

GVF Input Data

Downstream Depth 0.00 ft
Length 0.00 ft
Number Of Steps 0

GVF Output Data

Upstream Depth 0.00 ft
Profile Description
Profile Headloss 0.00 ft
Average End Depth Over Rise 0.00 %
Normal Depth Over Rise 45.49 %
Downstream Velocity Infinity ft/s
Upstream Velocity Infinity ft/s
Normal Depth 0.45 ft
Critical Depth 0.79 ft
Channel Slope 0.04400 ft/ft
Critical Slope 0.00846 ft/ft

Worksheet for Drainage Line P4_WQF

Project Description

Friction Method	Manning Formula
Solve For	Normal Depth

Input Data

Roughness Coefficient	0.010	
Channel Slope	0.04600	ft/ft
Diameter	0.67	ft
Discharge	0.07	ft³/s

Results

Normal Depth	0.06	ft
Flow Area	0.02	ft²
Wetted Perimeter	0.42	ft
Hydraulic Radius	0.04	ft
Top Width	0.39	ft
Critical Depth	0.12	ft
Percent Full	9.7	%
Critical Slope	0.00399	ft/ft
Velocity	3.77	ft/s
Velocity Head	0.22	ft
Specific Energy	0.28	ft
Froude Number	3.17	
Maximum Discharge	3.63	ft³/s
Discharge Full	3.37	ft³/s
Slope Full	0.00002	ft/ft
Flow Type	SuperCritical	

GVF Input Data

Downstream Depth	0.00	ft
Length	0.00	ft
Number Of Steps	0	

GVF Output Data

Upstream Depth	0.00	ft
Profile Description		
Profile Headloss	0.00	ft
Average End Depth Over Rise	0.00	%
Normal Depth Over Rise	9.65	%
Downstream Velocity	Infinity	ft/s
Upstream Velocity	Infinity	ft/s
Normal Depth	0.06	ft
Critical Depth	0.12	ft
Channel Slope	0.04600	ft/ft
Critical Slope	0.00399	ft/ft

Worksheet for Drainage Line P5_10YR

Project Description

Friction Method Manning Formula
Solve For Normal Depth

Input Data

Roughness Coefficient	0.012	
Channel Slope	0.02500	ft/ft
Diameter	1.00	ft
Discharge	1.68	ft³/s

Results

Normal Depth	0.36	ft
Flow Area	0.25	ft²
Wetted Perimeter	1.28	ft
Hydraulic Radius	0.20	ft
Top Width	0.96	ft
Critical Depth	0.55	ft
Percent Full	35.9	%
Critical Slope	0.00549	ft/ft
Velocity	6.63	ft/s
Velocity Head	0.68	ft
Specific Energy	1.04	ft
Froude Number	2.28	
Maximum Discharge	6.56	ft³/s
Discharge Full	6.10	ft³/s
Slope Full	0.00189	ft/ft
Flow Type	SuperCritical	

GVF Input Data

Downstream Depth	0.00	ft
Length	0.00	ft
Number Of Steps	0	

GVF Output Data

Upstream Depth	0.00	ft
Profile Description		
Profile Headloss	0.00	ft
Average End Depth Over Rise	0.00	%
Normal Depth Over Rise	35.87	%
Downstream Velocity	Infinity	ft/s
Upstream Velocity	Infinity	ft/s
Normal Depth	0.36	ft
Critical Depth	0.55	ft
Channel Slope	0.02500	ft/ft
Critical Slope	0.00549	ft/ft

Worksheet for Drainage Line P5_25YR

Project Description

Friction Method Manning Formula
Solve For Normal Depth

Input Data

Roughness Coefficient	0.012	
Channel Slope	0.02500	ft/ft
Diameter	1.00	ft
Discharge	2.27	ft³/s

Results

Normal Depth	0.42	ft
Flow Area	0.32	ft²
Wetted Perimeter	1.42	ft
Hydraulic Radius	0.22	ft
Top Width	0.99	ft
Critical Depth	0.64	ft
Percent Full	42.3	%
Critical Slope	0.00619	ft/ft
Velocity	7.19	ft/s
Velocity Head	0.80	ft
Specific Energy	1.23	ft
Froude Number	2.24	
Maximum Discharge	6.56	ft³/s
Discharge Full	6.10	ft³/s
Slope Full	0.00346	ft/ft
Flow Type	SuperCritical	

GVF Input Data

Downstream Depth	0.00	ft
Length	0.00	ft
Number Of Steps	0	

GVF Output Data

Upstream Depth	0.00	ft
Profile Description		
Profile Headloss	0.00	ft
Average End Depth Over Rise	0.00	%
Normal Depth Over Rise	42.26	%
Downstream Velocity	Infinity	ft/s
Upstream Velocity	Infinity	ft/s
Normal Depth	0.42	ft
Critical Depth	0.64	ft
Channel Slope	0.02500	ft/ft
Critical Slope	0.00619	ft/ft

Worksheet for Drainage Line P5_100YR

Project Description

Friction Method Manning Formula
Solve For Normal Depth

Input Data

Roughness Coefficient 0.012
Channel Slope 0.02500 ft/ft
Diameter 1.00 ft
Discharge 3.44 ft³/s

Results

Normal Depth 0.54 ft
Flow Area 0.43 ft²
Wetted Perimeter 1.65 ft
Hydraulic Radius 0.26 ft
Top Width 1.00 ft
Critical Depth 0.79 ft
Percent Full 53.7 %
Critical Slope 0.00846 ft/ft
Velocity 8.00 ft/s
Velocity Head 1.00 ft
Specific Energy 1.53 ft
Froude Number 2.15
Maximum Discharge 6.56 ft³/s
Discharge Full 6.10 ft³/s
Slope Full 0.00794 ft/ft
Flow Type SuperCritical

GVF Input Data

Downstream Depth 0.00 ft
Length 0.00 ft
Number Of Steps 0

GVF Output Data

Upstream Depth 0.00 ft
Profile Description
Profile Headloss 0.00 ft
Average End Depth Over Rise 0.00 %
Normal Depth Over Rise 53.72 %
Downstream Velocity Infinity ft/s
Upstream Velocity Infinity ft/s
Normal Depth 0.54 ft
Critical Depth 0.79 ft
Channel Slope 0.02500 ft/ft
Critical Slope 0.00846 ft/ft

Worksheet for Drainage Line P6_10YR

Project Description

Friction Method Manning Formula
Solve For Normal Depth

Input Data

Roughness Coefficient 0.013
Channel Slope 0.05000 ft/ft
Diameter 1.00 ft
Discharge 0.57 ft³/s

Results

Normal Depth 0.18 ft
Flow Area 0.10 ft²
Wetted Perimeter 0.88 ft
Hydraulic Radius 0.11 ft
Top Width 0.77 ft
Critical Depth 0.31 ft
Percent Full 18.1 %
Critical Slope 0.00563 ft/ft
Velocity 5.88 ft/s
Velocity Head 0.54 ft
Specific Energy 0.72 ft
Froude Number 2.92
Maximum Discharge 8.57 ft³/s
Discharge Full 7.97 ft³/s
Slope Full 0.00026 ft/ft
Flow Type SuperCritical

GVF Input Data

Downstream Depth 0.00 ft
Length 0.00 ft
Number Of Steps 0

GVF Output Data

Upstream Depth 0.00 ft
Profile Description
Profile Headloss 0.00 ft
Average End Depth Over Rise 0.00 %
Normal Depth Over Rise 18.11 %
Downstream Velocity Infinity ft/s
Upstream Velocity Infinity ft/s
Normal Depth 0.18 ft
Critical Depth 0.31 ft
Channel Slope 0.05000 ft/ft
Critical Slope 0.00563 ft/ft

Worksheet for Drainage Line P6_25YR

Project Description

Friction Method Manning Formula
Solve For Normal Depth

Input Data

Roughness Coefficient	0.013	
Channel Slope	0.05000	ft/ft
Diameter	1.00	ft
Discharge	1.09	ft³/s

Results

Normal Depth	0.25	ft
Flow Area	0.15	ft²
Wetted Perimeter	1.05	ft
Hydraulic Radius	0.15	ft
Top Width	0.87	ft
Critical Depth	0.44	ft
Percent Full	25.0	%
Critical Slope	0.00586	ft/ft
Velocity	7.10	ft/s
Velocity Head	0.78	ft
Specific Energy	1.03	ft
Froude Number	2.98	
Maximum Discharge	8.57	ft³/s
Discharge Full	7.97	ft³/s
Slope Full	0.00094	ft/ft
Flow Type	SuperCritical	

GVF Input Data

Downstream Depth	0.00	ft
Length	0.00	ft
Number Of Steps	0	

GVF Output Data

Upstream Depth	0.00	ft
Profile Description		
Profile Headloss	0.00	ft
Average End Depth Over Rise	0.00	%
Normal Depth Over Rise	24.99	%
Downstream Velocity	Infinity	ft/s
Upstream Velocity	Infinity	ft/s
Normal Depth	0.25	ft
Critical Depth	0.44	ft
Channel Slope	0.05000	ft/ft
Critical Slope	0.00586	ft/ft

Worksheet for Drainage Line P6_100YR

Project Description

Friction Method	Manning Formula
Solve For	Normal Depth

Input Data

Roughness Coefficient	0.013	
Channel Slope	0.05000	ft/ft
Diameter	1.00	ft
Discharge	1.75	ft³/s

Results

Normal Depth	0.32	ft
Flow Area	0.22	ft²
Wetted Perimeter	1.20	ft
Hydraulic Radius	0.18	ft
Top Width	0.93	ft
Critical Depth	0.56	ft
Percent Full	31.8	%
Critical Slope	0.00654	ft/ft
Velocity	8.13	ft/s
Velocity Head	1.03	ft
Specific Energy	1.35	ft
Froude Number	2.98	
Maximum Discharge	8.57	ft³/s
Discharge Full	7.97	ft³/s
Slope Full	0.00241	ft/ft
Flow Type	SuperCritical	

GVF Input Data

Downstream Depth	0.00	ft
Length	0.00	ft
Number Of Steps	0	

GVF Output Data

Upstream Depth	0.00	ft
Profile Description		
Profile Headloss	0.00	ft
Average End Depth Over Rise	0.00	%
Normal Depth Over Rise	31.85	%
Downstream Velocity	Infinity	ft/s
Upstream Velocity	Infinity	ft/s
Normal Depth	0.32	ft
Critical Depth	0.56	ft
Channel Slope	0.05000	ft/ft
Critical Slope	0.00654	ft/ft

Worksheet for Drainage Line P7_10YR

Project Description

Friction Method Manning Formula
Solve For Normal Depth

Input Data

Roughness Coefficient 0.013
Channel Slope 0.05000 ft/ft
Diameter 1.00 ft
Discharge 0.57 ft³/s

Results

Normal Depth 0.18 ft
Flow Area 0.10 ft²
Wetted Perimeter 0.88 ft
Hydraulic Radius 0.11 ft
Top Width 0.77 ft
Critical Depth 0.31 ft
Percent Full 18.1 %
Critical Slope 0.00563 ft/ft
Velocity 5.88 ft/s
Velocity Head 0.54 ft
Specific Energy 0.72 ft
Froude Number 2.92
Maximum Discharge 8.57 ft³/s
Discharge Full 7.97 ft³/s
Slope Full 0.00026 ft/ft
Flow Type SuperCritical

GVF Input Data

Downstream Depth 0.00 ft
Length 0.00 ft
Number Of Steps 0

GVF Output Data

Upstream Depth 0.00 ft
Profile Description
Profile Headloss 0.00 ft
Average End Depth Over Rise 0.00 %
Normal Depth Over Rise 18.11 %
Downstream Velocity Infinity ft/s
Upstream Velocity Infinity ft/s
Normal Depth 0.18 ft
Critical Depth 0.31 ft
Channel Slope 0.05000 ft/ft
Critical Slope 0.00563 ft/ft

Burns McDonnell

Worksheet for Drainage Line P7_25YR

Project Description

Friction Method	Manning Formula
Solve For	Normal Depth

Input Data

Roughness Coefficient	0.013	
Channel Slope	0.05000	ft/ft
Diameter	1.00	ft
Discharge	1.09	ft³/s

Results

Normal Depth	0.25	ft
Flow Area	0.15	ft²
Wetted Perimeter	1.05	ft
Hydraulic Radius	0.15	ft
Top Width	0.87	ft
Critical Depth	0.44	ft
Percent Full	25.0	%
Critical Slope	0.00586	ft/ft
Velocity	7.10	ft/s
Velocity Head	0.78	ft
Specific Energy	1.03	ft
Froude Number	2.98	
Maximum Discharge	8.57	ft³/s
Discharge Full	7.97	ft³/s
Slope Full	0.00094	ft/ft
Flow Type	SuperCritical	

GVF Input Data

Downstream Depth	0.00	ft
Length	0.00	ft
Number Of Steps	0	

GVF Output Data

Upstream Depth	0.00	ft
Profile Description		
Profile Headloss	0.00	ft
Average End Depth Over Rise	0.00	%
Normal Depth Over Rise	24.99	%
Downstream Velocity	Infinity	ft/s
Upstream Velocity	Infinity	ft/s
Normal Depth	0.25	ft
Critical Depth	0.44	ft
Channel Slope	0.05000	ft/ft
Critical Slope	0.00586	ft/ft

Worksheet for Drainage Line P7_100YR

Project Description

Friction Method Manning Formula
Solve For Normal Depth

Input Data

Roughness Coefficient 0.013
Channel Slope 0.05000 ft/ft
Diameter 1.00 ft
Discharge 1.75 ft³/s

Results

Normal Depth 0.32 ft
Flow Area 0.22 ft²
Wetted Perimeter 1.20 ft
Hydraulic Radius 0.18 ft
Top Width 0.93 ft
Critical Depth 0.56 ft
Percent Full 31.8 %
Critical Slope 0.00654 ft/ft
Velocity 8.13 ft/s
Velocity Head 1.03 ft
Specific Energy 1.35 ft
Froude Number 2.98
Maximum Discharge 8.57 ft³/s
Discharge Full 7.97 ft³/s
Slope Full 0.00241 ft/ft
Flow Type SuperCritical

GVF Input Data

Downstream Depth 0.00 ft
Length 0.00 ft
Number Of Steps 0

GVF Output Data

Upstream Depth 0.00 ft
Profile Description
Profile Headloss 0.00 ft
Average End Depth Over Rise 0.00 %
Normal Depth Over Rise 31.85 %
Downstream Velocity Infinity ft/s
Upstream Velocity Infinity ft/s
Normal Depth 0.32 ft
Critical Depth 0.56 ft
Channel Slope 0.05000 ft/ft
Critical Slope 0.00654 ft/ft

Worksheet for Emergency Spillway Weir-100YR

Project Description

Solve For Headwater Elevation

Input Data

Discharge	1.47	ft³/s
Crest Elevation	1079.00	ft
Tailwater Elevation	0.00	ft
Crest Surface Type	Gravel	
Crest Breadth	6.00	ft
Crest Length	5.00	ft

Results

Headwater Elevation	1079.23	ft
Headwater Height Above Crest	0.23	ft
Tailwater Height Above Crest	-1079.00	ft
Weir Coefficient	2.60	US
Submergence Factor	1.00	
Adjusted Weir Coefficient	2.60	US
Flow Area	1.17	ft²
Velocity	1.26	ft/s
Wetted Perimeter	5.47	ft
Top Width	5.00	ft

Worksheet for Emergency Spillway Channel-100YR

Project Description

Friction Method	Manning Formula
Solve For	Normal Depth

Input Data

Roughness Coefficient	0.078	
Channel Slope	0.50000	ft/ft
Left Side Slope	3.00	ft/ft (H:V)
Right Side Slope	3.00	ft/ft (H:V)
Bottom Width	5.00	ft
Discharge	1.47	ft³/s

Results

Normal Depth	0.10	ft
Flow Area	0.53	ft²
Wetted Perimeter	5.63	ft
Hydraulic Radius	0.09	ft
Top Width	5.60	ft
Critical Depth	0.14	ft
Critical Slope	0.17866	ft/ft
Velocity	2.79	ft/s
Velocity Head	0.12	ft
Specific Energy	0.22	ft
Froude Number	1.60	
Flow Type	Supercritical	

GVF Input Data

Downstream Depth	0.00	ft
Length	0.00	ft
Number Of Steps	0	

GVF Output Data

Upstream Depth	0.00	ft
Profile Description		
Profile Headloss	0.00	ft
Downstream Velocity	Infinity	ft/s
Upstream Velocity	Infinity	ft/s
Normal Depth	0.10	ft
Critical Depth	0.14	ft
Channel Slope	0.50000	ft/ft
Critical Slope	0.17866	ft/ft

Shear Stress Calculation for Basin Spillway

	* 100 Year	100-YR Flow depth (ft)	Channel Slope (ft/ft)	Channel Lining	Allowable Shear Stress (lb/ft)	Calculated** Shear Stress (lb/ft)
Basin	Flow (cfs)					
DB-1	1.47	0.1	0.5	12" RipRap	4.8	3.12


* Values taken from Flowmaster Results - 100 year storm event used for detention basins

** Shear stress = 62.4 lb/cf x (flow depth) x (channel slope)

*** Allowable shear Stress are taken from table 2.3 of FHA HEC 15, Third Edition

Source:

New Hampshire Stormwater Manual, Volume 2
Post-Construction Best Management Practices
Selection & Design, Dec 2008, Section 4.6.6



Apron Width at Outlet: Width = 3 x Pipe Dia. (or width of channel)

Apron Length: Length = $(1.8 \times Q) / (\text{Dia.}^{1.5}) + 7 \times \text{Dia.}$ if Tw depth is < 1/2 dia.
Length = $(3.0 \times Q) / (\text{Dia.}^{1.5}) + 7 \times \text{Dia.}$ if Tw depth is $\geq 1/2$ dia.

Apron Width at End: Width = 3 x Dia + Apron Length if Tw depth is < 1/2 dia.
Width = 3 x Dia + 0.4 x Apron Length if Tw depth is $\geq 1/2$ dia.
or apron width = channel width if a well defined channel exists

Rock Riprap: Median Diameter = $(0.2 \times Q^{4/3}) / \text{Tw} \times \text{Dia}$
Depth = 18" or 1.5 x largest stone dia.

Design Element	FES-1	FES-2
Design Storm (YR)	25-YR	25-YR
Defined Channel (yes/no)	No	No
Channel Width (ft)	N/A	N/A
Pipe Dia (in)	12	12
Tail Water (ft)	0.88	0.22
	TW $\geq 0.5D$	TW<0.5D
Flow (Q), cfs	2.27	1.09
Apron Width (outlet) ft	3	3
Apron Length, ft	13.81	8.96
Apron Width (end) ft	8.52	11.96
Apron Width, (channel), ft	N/A	N/A
Median Stone dia. (D50), inches	6	6
Apron Depth, inches	18	18

APPENDIX D – NH DES WORKSHEETS

FILTRATION PRACTICE DESIGN CRITERIA (Env-Wq 1508.06)

Type/Node Name:

Underground Sand Filter SF-1

Enter the type of filtration practice (e.g., bioretention system) and the node name in the drainage analysis, if applicable

Yes		Have you reviewed the restrictions on unlined systems outlined in Env-Wq 1508.06(b)?	
0.68	ac	A = Area draining to the practice ¹	
0.05	ac	A_I = Impervious area draining to the practice	
0.07	decimal	I = percent impervious area draining to the practice, in decimal form	
0.12	unitless	R_v = Runoff coefficient = $0.05 + (0.9 \times I)$	
0.08	ac-in	$WQV = 1'' \times R_v \times A$	
287	cf	WQV conversion (ac-in $\times 43,560$ sf/ac $\times 1$ ft/12")	
72	cf	25% $\times WQV$ (check calc for sediment forebay volume)	
215	cf	75% $\times WQV$ (check calc for surface sand filter volume)	
Deep Sump Catch Basin Method of Pretreatment? (not required for clean or roof runoff)			
262	cf	V_{SED} = sediment forebay volume, if used for pretreatment	$\leftarrow \geq 25\%WQV$
85	sf	A_{SA} = surface area of the practice	
1.75	iph	I_{DESIGN} = design infiltration rate ²	
Yes	Yes/No	If I_{DESIGN} is < 0.50 iph, has an underdrain been provided?	
23.3	hours	T_{DRAIN} = drain time = $V / (A_{SA} \times I_{DESIGN})$	$\leftarrow \leq 72$ -hrs
1,087.65	feet	E_{FC} = elevation of the bottom of the filter course material	
1,086.65	feet	E_{UD} = invert elevation of the underdrain (UD), if applicable	
1,086.65	feet	E_{BTM} = elevation of the bottom of the practice (i.e., bottom of the stone reservoir).	
1,082.50	feet	E_{SHWT} = elevation of SHWT (if none found, enter the lowest elevation of the test pit)	
1,063.50	feet	E_{ROCK} = elevation of bedrock (if none found, enter the lowest elevation of the test pit)	
1.00	feet	$D_{FC \text{ to } UD}$ = depth to UD from the bottom of the filter course ³	$\leftarrow \geq 1'$
24.15	feet	$D_{FC \text{ to } ROCK}$ = depth to bedrock from the bottom of the filter course ³	$\leftarrow \geq 1'$
5.15	feet	$D_{FC \text{ to } SHWT}$ = depth to SHWT from the bottom of the filter course ³	$\leftarrow \geq 1'$
4.15	feet	$D_{BTM \text{ to } SHWT}$ = depth to SHWT from the bottom of the practice ³	$\leftarrow \geq 2'$
1,091.75	ft	Peak elevation of the 10-year storm event (infiltration can be used in analysis)	
1,093.65	ft	Elevation of the top of the practice	
YES		10 peak elevation \leq Elevation of the top of the practice	\leftarrow yes

If a surface sand filter is proposed:

YES	ac	Drainage Area check.	$\leftarrow < 10$ ac
	cf	V = volume of storage ^{4,5} (attach a stage-storage table)	$\leftarrow \geq 75\%WQV$
	inches	D_{FC} = filter course thickness	$\leftarrow 18''$
Sheet		Note what sheet in the plan set contains the filter course specification	
Yes/No		Access grate provided?	\leftarrow yes
		The filter shall not be covered in grass. What is covering the filter?	

If an underground sand filter is proposed:

YES	ac	Drainage Area check.	$\leftarrow < 10$ ac
477	cf	V = volume of storage ^{4,5} (attach a stage-storage table)	$\leftarrow \geq 75\%WQV$
24.0	inches	D_{FC} = filter course thickness	$\leftarrow 24''$
Sheet		Note what sheet in the plan set contains the filter course specification	
Yes	Yes/No	Access grate provided?	\leftarrow yes

If a bioretention area is proposed:

YES	ac	Drainage Area no larger than 5 ac?	← yes
	cf	V = volume of storage ^{4,5} (attach a stage-storage table)	← ≥ WQV
	inches	D _{FC} = filter course thickness	← 18"
Sheet		Note what sheet in the plan set contains the filter course specification	
	:1	Pond side slopes	← ≥2:1
Sheet		Note what sheet in the plan set contains the planting plans and surface cover	

If porous pavement is proposed:

		Type of pavement proposed (concrete? Asphalt? Pavers? Etc)	
	acres	A _{SA} = surface area of the pervious pavement	
-	:1	ratio of the contributing area to the pervious surface area	← 5:1
3.0	inches	D _{FC} = filter course thickness	← 12"
Sheet		Note what sheet in the plan set contains the filter course spec.	← 304.1 sand

1. If the practice is a tree box filter, the drainage area shall be < 0.1 acre
2. Rate of the limiting layer (either the filter course or the underlying soil). See Vol. 2 of the NH Stormwater Manual, Ch. 2-4, for guidance on determining the infiltration rate.
3. If not within a GPA or WSIPA: SHWT/Bedrock must be at least 1 foot below the filter course material (or an underdrain must drain the SHWT to at least one foot below the filter course material). If within a GPA or WSIPA: SHWT must be at least two feet below the bottom of the practice OR the filter course material must be at least twice as thick as required and the SHWT must be at least one foot below the filter course material.
4. Volume without depending on infiltration. The storage above the filter media shall not include the volume above the outlet structure, if any.
5. The volume includes the storage above the filter but below the invert of the outlet structure (if any), the filter media voids, and the pretreatment area.

Designer's Notes:

1. Assumed the limiting layer is the sand layer which has a permeability rate (K) of 3.5 ft/day (1.75 in/hr).

2. A waterproof coating will be applied to the exterior walls of the concrete chamber.

Client EversourcePage 1 of Project Northern PassDate Made By Transition Station #5Checked By Impervious Area SummaryPreliminary Final BMP: Underground Sand Filter A_i = Impervious area draining to the practice = 0.05 ac

(Contributing watersheds: Post-Area 1)

0.01 ac Station (roof tops and concrete foundation)

0.02 ac Asphalt Pavement

0.02 ac Retaining Wall

0.05 ac TOTAL Impervious Area Contributing to BMP: Underground Sand Filter

Groundwater Recharge Volume (GRV) Calculation

-	ac	Area of HSG A soil that was replaced by impervious cover	0.40"
(0.04)	ac	Area of HSG B soil that was replaced by impervious cover	0.25"
	ac	Area of HSG C soil that was replaced by impervious cover	0.10"
0.02	ac	Area of HSG D soil or impervious cover that was replaced by impervious cover	0.0"
0.40 inches		Rd = weighted groundwater recharge depth	
-0.01 ac-in		GRV = AI * Rd	
(36) cf		GRV conversion (ac-in x 43,560 sf/ac x 1ft/12")	

Provide calculations below showing that the project meets the groundwater recharge requirements (Env-Wq 1507.04):

Groundwater Recharge is not required

General Calculations - WQV and WQF (optional worksheet)

This worksheet may be useful when designing a BMP that does not fit into one of the specific worksheets already provided. For example, if proposing a new technology, which is not a stormwater wetland, infiltration practice, etc., then this worksheet may be useful.

Water Quality Volume (WQV)

0.68	ac	A = Area draining to the practice
0.05	ac	A _I = Impervious area draining to the practice
0.07	decimal	I = percent impervious area draining to the practice, in decimal form
0.12	unitless	R _v = Runoff coefficient = 0.05 + (0.9 x I)
0.08	ac-in	WQV = 1" x R _v x A
287	cf	WQV conversion (ac-in x 43,560 sf/ac x 1ft/12")


Water Quality Flow (WQF)

1	inches	P = amount of rainfall. For WQF in NH, P = 1"
0.12	inches	Q = water quality depth. $Q = WQV/A$
82	unitless	CN = unit peak discharge curve number. $CN = 1000 / (10 + 5P + 10Q - 10 * [Q^2 + 1.25 * Q * P]^{0.5})$
2.2	inches	S = potential maximum retention. $S = (1000/CN) - 10$
0.436	inches	Ia = initial abstraction. Ia = 0.2S
12.1	minutes	T _c = Time of Concentration
525.0	cfs/mi ² /in	qu is the unit peak discharge. Obtain this value from TR-55 exhibits 4-II and 4-III
0.065	cfs	WQF = q _u x WQV. Conversion: to convert "cfs/mi ² /in * ac-in" to "cfs" multiply by 1mi ² /640ac

Designer's Notes:

NHDES Alteration of Terrain

Last Revised: August 2013

Exhibit 4-II Unit peak discharge (q_u) for NRCS (SCS) type II rainfall distribution



Client Eversource Page of
Project Northern Pass Date 08/28/15 Made By L. Guerin
Bethlehem - Transition Station 5a Checked By
Sand Filter - Stage-Storage Tables Preliminary Final x

Stage/Storage Table

Volume Within Filter Bed

ELEV (FT.)	AREA (S.F.)	AREA (Ac)	DIFFERENCE IN ELEVATION (FT.)	STORAGE VOLUME (Conic Method)			
				INCREMENTAL	x 0.40 *	TOTAL (CF)	Total Ac-Ft
1086.65	84.5	0.002		0	0	0	0
1087	84.5	0.002	0.35	29.57	11.83	11.83	0.000
1088	84.5	0.002	1	84.50	33.80	45.63	0.001
1089	84.5	0.002	1	84.50	33.80	79.43	0.002
1089.9	84.5	0.002	0.9	76.05	30.42	109.85	0.003

* 0.4 = Void factor of filter material

Volume Above filter bed

ELEV (FT.)	AREA (S.F.)	AREA (Ac)	DIFFERENCE IN ELEVATION (FT.)	STORAGE VOLUME (Conic Method)		
				INCREMENTAL	TOTAL (CF)	Total Ac-Ft
1089.9	84.5	0.002	0	0	0	0
1090	84.5	0.002	0.1	8.45	8.45	0.000
1091	84.5	0.002	1	84.50	92.95	0.002
1091.15	84.5	0.002	0.15	12.68	105.63	0.002

WQV = 287 CF

Volume provided in filter chamber = 109.85 CF + 105.63 CF = 215.48 CF > 75% WQV (215.25 CF)

Volume provided in Sediment Chamber


ELEV (FT.)	AREA (S.F.)	AREA (Ac)	DIFFERENCE IN ELEVATION (FT.)	STORAGE VOLUME (Conic Method)		
				INCREMENTAL	TOTAL (CF)	Total Ac-Ft
1086.65	65	0.001		0	0	0
1087	65	0.001	0.35	22.75	22.75	0.001
1088	65	0.001	1	65.00	87.75	0.002
1088.65	65	0.001	0.65	42.25	130.00	0.003
1089	52	0.001	0.35	20.43	150.43	0.003
1090	52	0.001	1	52.00	202.43	0.005
1091	52	0.001	1	52.00	254.43	0.006
1091.15	52	0.001	0.15	7.80	262.23	0.006

Volume in Sediment Chamber is 262.23 > 25% of WQV (71.75 CF)

Total Volume Provided in Sand filter = 215.48 CF + 262.23 CF = 477.71 CF SAY 477.00 CF

Underground Sand Filter Design: TS-4					
Filter Parameters		Preliminary Dimensions	Design Dimensions	Units	Notes
Water Quality Flow	WQF	0.065	0.07	cfs	Design flow is based on 2" PVC inflow capacity
Water Quality Volume	WQV	287	287	cf	
Total Area	A	0.68	0.68	ac	Total area draining to practice
Impervious Area	A _i	0.05	0.05	ac	Total impervious area draining to practice
Sand Bed Depth (including top layer of gravel)	d _f	27	27	inches	Sand Bed is 24 inches. Top layer is 3 inches
Depth pea gravel + underdrain	d _g	12	12	inches	Underdrain is 6" topped with 6" of gravel.
Total Filter Bed Depth	d _m	39	39	inches	d _f + d _g
Average ponding depth on the filter	h	0.63	0.63	ft	h = (4.5 - d _m)/2 . Assume a maximum depth of 4.5 ft (54") from the bottom of the structure to the overflow elevation.
Maximum possible ponding depth	2h	1.25	1.25	ft	distance between discharge from overflow to top of the filter
Permeability coefficient for sand bed	k	3.5	3.5	(ft/day)	
Time for flow to pass through filter bed	t	24.2	23.3	hours	
Sand and gravel media porosity	n	40%	40%		
Surface area on the sand filter media	A _f	63.64	84.50	ft ²	(WQV*d _f)/[k*(h+d _f)*t]
Width of filter bed	W _f	5.64	6.50	ft	sqrt(A _f /2)
Length of filter bed	L _f	11.28	13.00	ft	2*W _f
Filter Volume					
Max available storage volume on the surface of the filter	V _{Tf}	79.6	105.6	cf	A _f * 2h
Storage volume in the void space of gravel and sand media	V _v	82.74	109.85	cf	n x A _f x d _m
Volume of inflow that passes through the filter media while the total WQV is accumulating in the BMP	V _Q	9.50	12.61	cf	[k*A _f (d _f +h)]/d _f
TOTAL FILTER VOLUME*	V _{total}	171.79	228.08	cf	V _{Tf} + V _v + V _Q (Required 75% WQV = 215.25)
Volume of water that must be stored awaiting filtration in the sedimentation chamber	V _{st}	115.21	71.75	cf	WQV - V _{Tf} - V _v - V _Q (Required 25% WQV = 71.75)
Sedimentation Chamber					
Permanent Pool Length	L _p	17.00	9.00	ft	V _{st} / (2h x W _f) - rounded up to the nearest foot
Sedimentation Chamber Length	L _s	9.00	8.00	ft	(0.2 x WQV)/(2h x W _f) - rounded up to the nearest foot

*Minimum total volume required for the filter is equal to 75% of WQV (215.25 cf). Design dimensions adjust the surface area, length and width of the filter bed (while maintaining the filter media depth calculations), to provide a total filter volume greater than or equal to the minimum total volume required.



TS4 Underground Sand Filter Dimensions Summary				
Filter Bed Length, L_f (ft)	Filter Bed Width, W_f (ft)	Total Filter Bed Depth, d_m (ft)	Sedimentation Chamber Length, L_s (ft)	Permanent Pool Length, L_p (ft)*
13.00	6.50	3.25	8.00	10.00

According to the VDOT BMP Design Manual, if the computed length of the permanent pool is less than the length of the sedimentation chamber plus 2 feet, the permanent pool length should be increased to dimensions of L_s plus 2 feet.

Calculate Weir Height and Orifice Size for By-Pass Structure

Known Data:

Water Quality Peak Flow

WQF = 0.065 cfs

Reference:

NH DES

BMP Worksheet

WQF = Water Quality Flow to be diverted through a diversion structure

Size the Low flow orifice to pass the Water Quality Peak Flow

Orifice Flow: $Q = CA(2gh)^{1/2}$

where:

C= 0.6

A= orifice area ft

g= acceleration due to gravity = 32.2 ft/sec²

h= head ft

Let H = 0.5 ft (The height of the bypass/overflow orifice)

solve for the area of the orifice (A)

$A = Q / C (2gh)^{1/2}$

$A = 0.065 \text{ cfs} / (0.6 \times (2 \times 32.2 \text{ ft/sec}^2 \times 0.5 \text{ ft})^{1/2})$

A= 0.019 SF

Solve for the Diameter of the Orifice

$D = (4 \times A / 3.14)^{1/2}$

$D = (4 \times 0.019 \text{ sf} / 3.14)^{1/2}$

D= 0.16 ft

D= 1.87 inch ---> Say 2 Inches

Let D = 2.0 inches

Calculate Capacity of 2 inch Orifice

$A = \pi D^2 / 4$

$A = (3.14 \times (2 \text{ in} / 12 \text{ in/ft})^2) / 4$

A= 0.022 SF

$Q = CA(2gh)^{1/2}$

$Q = (0.6) \times (2 \text{ SF}) \times 2 \times 32.2 \text{ ft/sec}^2 \times 0.5 \text{ ft}^{1/2}$

Q= 0.07 CFS

APPENDIX E – OPERATIONS AND MAINTENANCE PLAN

**Northern Pass Transmission Project
Transition Station #5****Stormwater System Operations and Maintenance Plan****General Overview**

Eversource has established an operations and maintenance (O&M) plan for the station post-construction stormwater management system in accordance with the New Hampshire Department of Environmental Services Stormwater Manual (2008) and will be implemented upon completion of construction as outlined below. Any required post construction stormwater management permits will be obtained and implemented by Eversource.

The station is located on Eversource owned property on Main Street (US Highway 302), Bethlehem, NH 03574

Purpose & Goals

The purpose of this O&M Plan is to provide guidance for the implementation and documentation process of the station site stormwater management system to help conform with the corresponding regulatory agency approvals and permits. The guidance provided herein is the minimum required. The primary goal is to inform all the property managers about how the system operates and what maintenance items are necessary to protect the downstream storm drain system and waters. The secondary goal is to provide a practical, efficient means of maintenance planning and record keeping to verify permit compliance.

Responsible Parties

Eversource will be responsible for implementing the O&M Plan.

Eversource
13 Legends Drive
Hooksett, NH 03106

Maintenance Logs and Checklists

Eversource will keep a record of all maintenance procedures performed, date of inspection/cleanings, etc. Copies of inspection reports and maintenance records shall be kept on site.

Forms

The following forms will be developed for annual maintenance. Copies of the forms will be kept on-site as part of the Post-Construction Stormwater Management Plan.

- Annual Checklist
- Quarterly Checklist
- Monthly Checklist

Training

Responsible operations and maintenance workers and contractors will be trained with a basic description of the purpose and function of the onsite stormwater management system as well as safety protocol and procedures, with annual up-dates, to provide that the workers tasked with maintaining the station site do so in accordance with the approved permit conditions. All workers that have maintenance duties will be adequately informed of their responsibilities. All sub-contractors (Vactor, landscaping, snowplowing, etc.) will be informed of special requirements and responsibilities.

Stormwater Management System

The onsite stormwater management system has several components that are shown on the Site Development Plans and they perform various functions in conveying and treating stormwater runoff. Refer to the Site Development Plans for locations and details for each of the stormwater system components. Regular operations and maintenance is critical to the long term success of the stormwater management system components. The stormwater system components are:

Storm Drainage System:

Onsite storm drainage system including conveyance pipes and flared end sections convey stormwater. The following is recommended for regular maintenance twice annually unless otherwise noted:

- Remove any accumulated sediment or debris at the outfalls.
- Inspect and repair any damage and deterioration to the conveyance pipes, catch basins, and riprap outlet protection.

Outfalls:

Storm drainage outfalls are the point stormwater discharges from pipe outlets and consist of a flared end section and riprap outlet protection. The following is recommended for regular maintenance twice annually unless otherwise noted:

- Remove any accumulated sediment or debris at the outfalls.
- Inspect and repair any damage and deterioration to riprap outlet protection.

Detention Basin:

The detention basin attenuates stormwater, and consists of numerous components including an outlet control structure, trash rack, outlet pipe, emergency spillway, anti-seep collar, etc. The following is recommended for regular maintenance twice annually unless otherwise noted:

- Remove any trash and debris.
- Periodic mowing of embankments.
- Removal of woody vegetation from embankments.
- Removal of debris from outlet structures. Removal of accumulated sediment.
- Inspection and repair of embankments, outlet structures, and appurtenances.

- Inspect for erosion, sediment accumulation, vegetation loss, and presence of invasive species
- Inspection of pretreatment measures at least twice annually and removal of accumulated sediment as warranted by inspection, but no less than once annually.

Underground Sand Filter:

The underground sand filter provides water quality and consists of numerous components including a flow splitter, sedimentation chamber, filter chamber, filter media, underdrains etc. The following is recommended for regular maintenance twice annually unless otherwise noted:

- Remove any trash or debris from any pretreatment devices, flow splitter and sedimentation chamber and filter chamber.
- Sand filter media and or devices should be cleaned or repaired when drawdown times within the chamber exceed 72 hours. Repair may include replacement of the filter material with new materials conforming to the original specifications.
- Sediment should be removed from the sedimentation chamber when it accumulates to a depth of six inches. Material may be removed by a vacuum pump and disposed of at an approved permitted site.
- Oil on the surface should be removed separately and disposed of properly in accordance with local, state and federal regulations.
- Structural components shall be checked for deterioration and evidence of spalling or cracking of concrete.
- Outlets shall be checked for evidence of clogging, downstream erosion and piping failure.

Station Yard Stone:

The station yard stone within the station yard can become compacted and eroded over time. The following is recommended for regular maintenance twice annually unless otherwise noted:

- Inspect for and repair any erosion in the yard, on access roads, and at the perimeter of the gravel areas.
- As the gravel areas become compacted, scrape off top layer to subgrade elevation and install new gravel surfacing layer at design elevation and pitch.

Spill Control

Eversource will have a spill control program. That program will be updated annually and incorporated into the employee-training program.

Disposal:

For all removed sediment, debris, trash, etc. from the stormwater management system during operations and maintenance shall be disposed of properly and legally by a New Hampshire Licensed hauler. Road sand may be reused for winter sanding, but may not be stored on-site.

Pesticides:

Northern Pass anticipates that vegetation management activities will be performed by Eversource. Work will be performed in accordance with Eversource's vegetation management program, which

currently employs only mechanical means for controlling vegetation within the Eversource rights of way. Eversource does not currently plan to use herbicides as part of its vegetation management program, and as indicated in the Northern Pass application for a Presidential Permit (at page 52), all vegetation management and maintenance will be carried out in accordance with the New Hampshire Division of Forest and Lands Best Management Practice for utility maintenance. Herbicides will not be used before or during construction of the Northern Pass.

* * * * *

APPENDIX F – FEMA FLOOD INSURANCE RATE MAP



61°00'00\"/>

71°43'07.5\"/>



MAP SCALE 1" = 500'

50 0 500 1000
FEET

METER

NFIP

NATIONAL FLOOD INSURANCE PROGRAM

PANEL 0136E

FIRM

FLOOD INSURANCE RATE MAP

GRAFTON COUNTY,
NEW HAMPSHIRE
(ALL JURISDICTIONS)

PANEL 136 OF 1185

(SEE MAP INDEX FOR FIRM PANEL LAYOUT)

CONTAINS:

COMMUNITY	NUMBER	PANEL	SUFFIX
BETHLEHEM, TOWN OF	330045	0136	E
LITTLETON, TOWN OF	330064	0136	E

Notice to User: The Map Number shown below should be used when placing map orders; the Community Number shown above should be used on insurance applications for the subject community.



MAP NUMBER
33009C0136E


EFFECTIVE DATE
FEBRUARY 20, 2008

Federal Emergency Management Agency

This is an official copy of a portion of the above referenced flood map. It was extracted using F-MIT On-Line. This map does not reflect changes or amendments which may have been made subsequent to the date on the title block. For the latest product information about National Flood Insurance Program flood maps check the FEMA Flood Map Store at www.msc.fema.gov


APPENDIX G – SOIL SURVEY REPORTS (BY OTHERS)

Hydrologic Soil Group—Grafton County, New Hampshire



MAP LEGEND

Area of Interest (AOI)









 Area of Interest (AOI)

Soils

Soil Rating Polygons





 A
 A/D
 B
 B/D
 C
 C/D
 D
 Not rated or not available

Soil Rating Lines

 A
 A/D
 B
 B/D
 C
 C/D
 D
 Not rated or not available

Soil Rating Points






 A
 A/D
 B
 B/D

 C
 C/D
 D
 Not rated or not available

Water Features

 Streams and Canals

Transportation

 Rails
 Interstate Highways
 US Routes
 Major Roads
 Local Roads

Background

 Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:24,000.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL: <http://websoilsurvey.nrcs.usda.gov>
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Grafton County, New Hampshire
 Survey Area Data: Version 17, Sep 12, 2014

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Aug 19, 2010—Jul 16, 2011

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Hydrologic Soil Group

Hydrologic Soil Group— Summary by Map Unit — Grafton County, New Hampshire (NH009)				
Map unit symbol	Map unit name	Rating	Acres in AOI	Percent of AOI
59B	Waumbek loamy sand, 3 to 8 percent slopes, very stony	B	0.4	19.7%
255B	Monadnock and Hermon soils, 3 to 8 percent, very stony	B	0.5	24.1%
255E	Monadnock and Hermon soils, 25 to 35 percent slopes, very stony	B	1.1	50.6%
731	Peacham and ossipee soils, very stony	A/D	0.1	5.6%
Totals for Area of Interest			2.1	100.0%

Description

Hydrologic soil groups are based on estimates of runoff potential. Soils are assigned to one of four groups according to the rate of water infiltration when the soils are not protected by vegetation, are thoroughly wet, and receive precipitation from long-duration storms.

The soils in the United States are assigned to four groups (A, B, C, and D) and three dual classes (A/D, B/D, and C/D). The groups are defined as follows:

Group A. Soils having a high infiltration rate (low runoff potential) when thoroughly wet. These consist mainly of deep, well drained to excessively drained sands or gravelly sands. These soils have a high rate of water transmission.

Group B. Soils having a moderate infiltration rate when thoroughly wet. These consist chiefly of moderately deep or deep, moderately well drained or well drained soils that have moderately fine texture to moderately coarse texture. These soils have a moderate rate of water transmission.

Group C. Soils having a slow infiltration rate when thoroughly wet. These consist chiefly of soils having a layer that impedes the downward movement of water or soils of moderately fine texture or fine texture. These soils have a slow rate of water transmission.

Group D. Soils having a very slow infiltration rate (high runoff potential) when thoroughly wet. These consist chiefly of clays that have a high shrink-swell potential, soils that have a high water table, soils that have a claypan or clay layer at or near the surface, and soils that are shallow over nearly impervious material. These soils have a very slow rate of water transmission.

If a soil is assigned to a dual hydrologic group (A/D, B/D, or C/D), the first letter is for drained areas and the second is for undrained areas. Only the soils that in their natural condition are in group D are assigned to dual classes.

Rating Options

Aggregation Method: Dominant Condition

Component Percent Cutoff: None Specified

Tie-break Rule: Higher



Northern Pass Transmission Project

Site-Specific Soil Survey Report for the Bethlehem Transition Station (T5A)

Prepared For:
Northern Pass Transmission, LLC

Submitted On:
August 14, 2015

Prepared By:
Normandeau Associates, Inc.
25 Nashua Road
Bedford, NH 03110

www.normandeau.com

Table of Contents

	Page
1.0 INTRODUCTION.....	1
2.0 PURPOSE	3
3.0 METHODOLOGY	3
3.1 FIELD PROCEDURES.....	3
3.2 SOIL MAP UNITS.....	4
3.3 HYDRIC SOILS	5
4.0 SUMMARY OF FINDINGS.....	5
4.1 BETHLEHEM LL 3140.....	5
5.0 REFERENCES	8
APPENDICES	
Appendix A: Map Unit Descriptions	
Appendix B: Soil Test Pit Logs	
Appendix C: NRCS Soil Series Descriptions	
Appendix D: Soil Survey Map	

List of Figures

	Page
Figure 1. Site Location Transition Station	2


List of Tables

	Page
Table 3-1. Slope Class	4
Table 4-1. Bethlehem Transition Site - Summary of Soil Physical Characteristics	6
Table 4-1A. Bethlehem Transition Site - Characteristics Summary of Disturbed Soil Map Units (Estimated Physical Characteristics)	7



1.0 Introduction

Normandeau Associates, Inc. (Normandeau) has reviewed and mapped the soils at an area under consideration for a proposed Transition Station (LL 3140) located in Bethlehem, NH (Figure 1) associated with the Northern Pass Transmission (NPT) Project. This report summarizes the soil survey completed at this site located at 1071 Main St. in Bethlehem, NH.

This site was previously surveyed for wetlands by a Normandeau wetland scientist this year. Information obtained during the soil surveys indicates that wetland boundaries were consistent with hydric soil boundaries.



TS5a: Bethlehem



Data Provided By: Cornerstone Energy Inc.
ESRI & GRANIT

TS5a SOIL SURVEY SITE LOCATION

Bethlehem, NH



EVERSOURCE
ENERGY

NORMANDEAU ASSOCIATES
Environmental Consultants

2.0 Purpose

The purpose of the soil survey is to provide a soil map of each site showing limitations to development, including hydric soil boundaries where observed, for inclusion in an Alteration of Terrain Permit application that is anticipated to be filed for the Project. This survey is appropriate for use in planning site design for stormwater runoff and erosion control. Information is also provided regarding limitations to the potential for site development including roads, shallow excavations, and stormwater detention. It is important to note that soils considered appropriate (non-limiting) for one use may be considered limiting for another use. Soil map units described in this report have been influenced by the intended use of the soil map; consequently, the information provided may not be adequate for uses other than for those for which the soil map was originally developed.

This soil narrative and accompanying soil survey map have been completed in accordance with the *Site Specific Standards for New Hampshire and Vermont* (SSSNNE 2011). No other warranty, expressed or implied, is made. This map product is within the technical standards of the National Cooperative Soil Survey. It is a special purpose product, intended for the assessment of site limitations to development of the site. It was produced by professional soil scientists, and is not the product of the USDA Natural Resources Conservation Service (NRCS). There are maps for each site that accompany this report.

Data provided on soil series are based on interpretation of published information by the NRCS. Due to the complexity of the glaciated landscape in New Hampshire, variations in subsurface conditions may exist that were not evident during the Project review. Should significant variations in subsurface conditions become evident during site development, re-evaluation of site conditions may be warranted based on the present findings of this report.

3.0 Methodology

3.1 Field Procedures

Certified Soil Scientists conducted the field reviews at the various sites. Ian Broadwater, a Maine-Certified Soil Scientist, with reciprocity to practice in New Hampshire, completed the fieldwork. Field observations were made using borings advanced by hand with a Dutch auger and test pits dug with an excavator. Soil observations were made to 60 inches, where feasible.

The general field procedures used to make this soil map follow those of the National Cooperative Soil Survey (Schoeneberger et al. 1998). The soils mapped are either established soil series used in the State of New Hampshire by the NRCS (USDA NRCS 2011) or are classified according to the NRCS classification system described in the *Disturbed Soil Mapping Unit Supplement for New Hampshire, DES AoT Site Specific Soil Maps* (SSSNNE 2011). Map unit descriptions are provided in Appendix A.

Soil test pit logs were completed for each test pit excavation and are provided in Appendix B. Test pits were located with a Trimble® GPS, which is capable of submeter accuracy. Soil map unit boundaries are approximate, as their placement is based on a combination of field observations and surveyed site topography.

3.2 Soil Map Units

The soil map units used for this survey are either consociations or complexes. Consociations are dominated by a single soil series and similar soils. Complexes consist of two or more dissimilar components that cannot be mapped separately and the named components are sufficiently different in either morphology or behavior that the unit cannot be considered a consociation. Map unit symbols in this survey are from the State Numerical Legend along with the soil series name. Slope phases are designated as a letter in the map unit symbol - A, B, C, D, and E - refers to slope class (Table 3-1).

Table 3-1. Slope Class

Slope Symbol	Standard Range
A	0-3%
B	3-8%
C	8-15%
D	15-25%
E	25-50%

The soil interpretations provided are based on information in the soil series descriptions and technical information provided by the NRCS web soil survey (Soil Survey Staff 2014a). All limitations and constraints invoked by the NRCS for such interpretations also apply to this soil survey.

The map units observed are described in Appendix A. These descriptions are within the NRCS range for each official Soil Series Description; however, they provide more detail as they are based on site-specific observations. Each map unit description includes information on soil taxonomic classification, general description, morphology, physical characteristics, inclusions, use, and management. The taxonomic classification follows Keys to Soil Taxonomy (Soil Survey Staff 2014a). Information on soil morphology and physical characteristics were obtained from the NRCS (Soil Survey Staff 2014b). It should be noted that Ossipee and Peacham soils are mapped together in New Hampshire as one map unit because management and limitations of these soils are similar.

Disturbed soil map units were classified according to the New Hampshire State-Wide Numerical Soils Legend (USDA NRCS 2011). Additional information on each map unit is provided according to criteria outlined in the disturbed soil supplement created by SSSNNE (2011), which utilizes the definition of disturbed land, including excavated and filled land, as defined by RSA 485 485-A:6, VIII; RSA 485-A: 17; and NHDES Env-Wq 1500. The map symbol for disturbed soil consists of two parts separated by a forward slash (/). The first part consists of the NRCS Disturbed Map Unit symbol (NRCS 2011) and a capital letter designating slope. The second part consists of symbols of the Disturbed Soil Supplement (SSSNNE 2011) and is composed of 5 lower case letters, which describe drainage class, parent material, restrictive/impervious layers, estimated Ksat, and estimated hydrologic soil group.

Consociation map units, in accordance with the standards, will have a minimum of 75% of the named soil or similar soils within that unit. The named soil will be the most common of all

similar soils. The total number of dissimilar soils in any one mapping unit for either consociations or complexes should not exceed 25% of the map unit of which no more than 15% is limiting. Similar soils are alike in most properties and share similar limitations such as depth to water table or content of organic matter. Dissimilar soils do not share limits of some important diagnostic properties of the named soil and may have different use or management requirements for a particular land use. It is important to note that some dissimilar soils are more limiting in their use than the named soil. For instance, an inclusion of somewhat poorly drained soils can occur within a well-drained soil map unit. A summary of potential inclusions of similar and dissimilar soils is provided for each map unit.

The hydrologic group identifies soils having the same runoff potential under similar storm conditions. Soil properties that influence runoff are those that influence the minimum rate of infiltration for a bare soil after prolonged wetting and when not frozen. Infiltration rate is the rate at which water enters the soil at the surface and is controlled by surface conditions. Transmission rate is the rate at which water moves in the soil and is controlled by soil properties.

Saturated hydraulic conductivity (Ksat) refers to the ease with which pores in a saturated soil transmit water. Ksat values are based on soil characteristics in the field, particularly structure, consistence, porosity and texture (SSSNNE 2009). The Ksat values provided are from the typical pedon from the county that best reflected the soil and/or had the most acres of that soil. The data represents the range within the B and C horizons (SSSNNE 2009).

3.3 Hydric Soils

Hydric soils refer to those soil series the NRCS considers to be either poorly or very poorly drained. The NRCS (Soil Survey Staff, 2014b) defines hydric soil as "a soil that is saturated, flooded, or ponded long enough during the growing season to develop anaerobic conditions in the upper part". The hydric soil boundary corresponds with the wetland boundary in the areas observed for this Project. The hydric soil boundary was located with a Trimble® GPS unit and post processed for submeter accuracy. Impacts to wetlands come under the jurisdiction of the U.S. Army Corps of Engineers and New Hampshire Department of Environmental Services.

4.0 Summary of Findings

The following summarizes the results of the soil surveys at the Bethlehem transition station site (T-5a). Soil map unit descriptions are provided in Appendix A; representative soil logs in Appendix B; NRCS soil series descriptions in Appendix C, and soil maps in Appendix D.

4.1 Bethlehem LL 3140

Overview

The proposed Bethlehem transition station site (T-5a) is located off Route 302 aka Main St. in Bethlehem, NH. A majority of the site is a developed residential lot with a house and detached garage with woods along the perimeter. West of the site is an existing electrical transmission right-of-way (ROW).

The site slopes from the high points along Route 302 to the north. Slopes range from moderately steep (15% to 25%) to nearly level in front and behind the house. No bedrock was noted in any of the explorations within 48 inches from the soil surface. Wetlands were noted in the northern half of the parcel beginning at the base of a topographic slope.

Soil Mapping Results

Normandeau conducted a field review of the Bethlehem site on May 12, 2015 and May 21, 2015. The final survey area was 0.92 acres. Two soil type map units were identified within the site. Both the natural soils mapped on site have glacial-fluvial parent material. Table 4-1 summarizes the map units and their physical characteristics that were identified within the Project site. Slope phases are not provided in Table 4-1 but are included in the site-specific soil maps in Appendix D.

A total of 4 test pits were distributed across the site and located with a Trimble® GPS. The wetland boundary had been previously flagged and located in the field by Normandeau Associates, Inc.

Table 4-1. Bethlehem Transition Site - Summary of Soil Physical Characteristics

Map Unit	Hydrologic Group	Seasonal Water Table (SWT) Depth ¹ (Inches)	Depth to Bedrock (Inches)	Drainage Class ²	Ksat (in/hr) ⁵	Limitations
549-Peacham, very stony mucky peat	D	0	>60	VP	0.6-2.0	Hydric soil ⁴
123B-Telos, very stony	C	<15	>60	SP	0.6-2.0	Seasonal high water <15" inches below ground surface ⁴
299-Udorthents, smoothed	A/B (Variable)	16-40+	>60	SE, W, MW	NM/NR	Seasonal high water 17" and 42" inches below ground surface in MW drained condition ⁴

1. Seasonal water table ranges are provided from the NRCS. On-site conditions are expected to fall within these ranges based on test pit observations.
2. Drainage Classes:
P- poorly drained; SP- somewhat poorly drained; MW- moderately well drained
W- well drained; SE- somewhat excessively drained.
3. NM-not measured; NR-not reported.
4. See the summary at the end of this section for additional information.
5. As reported for the B horizon.

Peacham and Ossipee soils, and Telos units mapped on-site were derived from glacio-fluvial deposits. Peacham and Ossipee mucky peat is very poorly drained soil and was found north of the Udorthent unit that makes up the area around the house. Telos was found north of the Peacham map unit in the northwest corner of the parcel.

A majority of the lawn area of the parcel as well as the associated driveway were mapped as a sandy Udorthent in a moderately well to well drained condition. A fill layer measuring up to

19 inches over native soil was observed on the west side of the house. On the east side, it appears that some of the native soil was removed and/or reworked. Depths of fill were shallower on the east side, measuring 16 inches at the maximum depth observed. The soil adjacent and north of the house, also mapped as a Udorthent, smoothed, consisted of excavated soil resulting from the house construction.

The Udorthent map unit characteristics on the parcel are summarized in Table 4-1A.

Table 4-1A. Bethlehem Transition Station Site – Characteristics Summary of Disturbed Soil Map Units (Estimated Physical Characteristics¹)

Characteristic	299B/dbcde and 299C/dbcde
Drainage Class	d- estimated to be moderately well drained (or drier).
Parent Material	b-glacial-fluvial deposits
Restrictive/Impervious layer	c- mineral restrictive layer present in the soil profile less than 40 inches
Estimated ksat	d- not determined
Hydrologic Group	e- not determined (Likely A/B)

1. Society of Soil Scientists of Northern New England. 2011.

Beyond the northern edge of the Udorthent Map Unit, there is a steep topographic drop of approximately 2 to 4 feet. At the base of the drop is a Peacham and Ossipee Soils Map Unit that was observed in the wetland in this location. These soils are both organic in nature, very poorly drained, and rated as hydric. Organic matter up to 18 inches was observed in this map unit. The rise in topography along the northern boundary of the parcel contains Telos soils in a somewhat poorly drained condition.

Summary

Limitations to development within the site consist of moderately steep slope leading to a wetland to the north of the house. Course fragments within the C horizon can make the upland soils (the Udorthent) difficult to excavate without a properly sized machine. Hydric soils, consistent with wetlands, mapped as Peacham mucky peat, are also present on the north half of the parcel and present constraints to development. Filling these soils likely requires a permit from the New Hampshire Department of Environmental Services and the U.S. Army Corps of Engineers. Fill soils may need to be removed for proper foundation construction.

5.0 References

- Schoeneberger, P.J., Wysocki, D.A., Benham, E.C., and Broderson, W.D. 1998. Field book for describing and sampling soils. Natural Resources Conservation Service, USDA, National Soil Survey Center, Lincoln, NE.
- Society of Soil Scientists of Northern New England. 2009. Ksat Values for New Hampshire Soils. SSSNNE Special Publication No. 5. September, 2009. Durham, NH.
- Society of Soil Scientists of Northern New England. 2011. Site-Specific Soil Mapping Standards for New Hampshire and Vermont. Version 4.0. SSSNNNE Special Publication No. 3. Durham, NH.
- Soil Survey Staff. 2014a. Keys to Soil Taxonomy, 12th ed. USDA-Natural Resources Conservation Service, Washington, DC.
- Soil Survey Staff. 2014b. Natural Resources Conservation Service, United States Department of Agriculture. Web Soil Survey. Accessed July and August 2014. Available online at <http://websoilsurvey.nrcs.usda.gov/app/HomePage.htm>.
- USDA Natural Resources Conservation Service. 2011. New Hampshire State-Wide Numerical Soils Legend. Issue #10. Durham, NH.

Appendix A

Map Unit Descriptions

731A-Peacham and Ossipee soils, very stony

These very deep, very poorly drained soils are on level to nearly level glaciated uplands. The Peacham soils typically are in depressions and along drainageways. The Ossipee soils typically are in ponded depressions. The areas of the unit are irregular in shape and range from 5 to 75 acres in size. Slopes range from 0 to 2 percent. Stones on the Peacham soils are generally 5 to 30 feet apart and cover from less than 1 percent to 3 percent of the surface. Some areas of the unit are dominantly Peacham soils, some areas are dominantly Ossipee soils, and some are both soils. The Peacham and Ossipee soils were mapped together because they have no major differences in use and management. The total acreage of the unit is about 40 percent Peacham soils, 40 percent Ossipee soils, and 20 percent other soils.

The typical sequence, depth, and composition of the layers of the Peacham soil are as follows—

Surface layer:

0 to 7 inches, very dark grayish brown muck

Subsoil:

7 to 15 inches, dark grayish brown gravelly fine sandy loam

15 to 30 inches, dark grayish brown gravelly sandy loam

Substratum:

30 to 65 inches, dark grayish brown, firm sandy loam

The typical sequence, depth, and composition of the layers of the Ossipee soil are as follows—

Surface layer:

0 to 6 inches, black slightly decomposed herbaceous and woody materials

Subsurface layer:

6 to 25 inches, dark reddish brown partially decomposed herbaceous and woody materials

25 to 41 inches, black partially decomposed herbaceous and woody materials

Substratum:

41 to 46 inches, dark grayish brown silt loam

46 to 65 inches, greenish gray silt loam

Telos-see Appendix D for official NRCS description

Disturbed Soil Map Units¹

299- Udorthents, smoothed

299- Udorthents, smoothed: land that has been cut and filled to create large level or nearly level areas such as building lots and roads. Soil material making up this area are generally from the surrounding area.

1 USDA Natural Resources Conservation Service. 2011. New Hampshire State-Wide Numerical Soils Legend. Issue #10. Durham, NH.

Appendix B

Soil Test Pit Logs

Soil Observation Logs

Abbreviations

Abbreviation	Soil Texture	Consistence	Miscellaneous
S	Sandy		
FS	Fine Sand		
FSL	Fine Sandy Loam		
VFSL	Very Fine Sandy Loam		
CS	Coarse Sand		
GRY	Gravelly		
L	Loam		
SL	Sandy Loam		
FR		Friable	
EOE			Extent of Excavation

Town, City, Plantation <u>Bethlehem</u>	Street, Road, Subdivision <u>1071 main St (RT 302)</u>	Owner or Applicant Name <u>E. Resource</u>
SOIL PROFILE DESCRIPTION AND CLASSIFICATION (Location of Observation Holes Shown Above)		

Observation Hole # 1 ☒ Test Pit ☐ Boring

0 " Depth of organic horizon above mineral soil

Texture	Consistency	Color	Mottling
0	F.S.L.	10YR 3/2	none (fill)
6	SoLo	10YR 4/3	woody debris in profile (fill)
12	5% c.f.s. as boulders		no nodules
18	F.S.L.	10YR 4/4	90% nodules
24	F.S.L.	7.5YR 5/6	none (3% nodules)
30			
36	A.S.L.	2.5Y 5/6	none
42	F.S.L.	2.5Y 5/6	5% c.f.s. as boulders
48			

Soil Profile	Classification	Slope	Limiting Factor	<input type="checkbox"/> Groundwater
	<u>Well</u>	<u>B</u>	<u>412"</u>	<input checked="" type="checkbox"/> Restrictive Layer
Profile	Condition	Percent	Depth	<input type="checkbox"/> Bedrock

Soil Series Name Udorthent 249 Hydrologic Group B

Observation Hole # 2 ☒ Test Pit ☐ Boring

17 " Depth of organic horizon above mineral soil

Texture	Consistency	Color	Mottling
0	mucky part	30% clay, 70% rubbery	10YR 4/2
6		massive	none saturated
12	mucky part	massive 10% after rubbery	10YR 2/2
18			
24	mucky silt 30% c.f.	massive dense	10YR 4/2
30	as boulders		saturated
36			
42	medium sand 5% c.f.s.	dense massive	10YR 5/1
48	as gravel, rubbery, boulders		

Soil Profile	Classification	Slope	Limiting Factor	<input checked="" type="checkbox"/> Groundwater
		<u>2</u>	<u>0"</u>	<input type="checkbox"/> Restrictive Layer
Profile	Condition	Percent	Depth	<input type="checkbox"/> Bedrock

Soil Series Name Kachan Hydrologic Group D

Observation Hole # 3 ☒ Test Pit ☐ Boring

0 " Depth of organic horizon above mineral soil

Texture	Consistency	Color	Mottling
0	A.S.L.	10YR 4/2	none (fill)
6	SoLo		
12	SoLo	7.5YR 4/6	none
18	5% c.f.s. as fine gravel		
24	A.S.L.	10YR 4/4	none
30	SoLo		few
36	SoLo	2.5Y 4/2	few
42	10% c.f.s. as boulders (rounded)		
48			

Soil Profile	Classification	Slope	Limiting Factor	<input type="checkbox"/> Groundwater
			<u>26"</u>	<input checked="" type="checkbox"/> Restrictive Layer
Profile	Condition	Percent	Depth	<input type="checkbox"/> Bedrock

Soil Series Name Udorthent Hydrologic Group B

Observation Hole # 4 ☒ Test Pit ☐ Boring

0 " Depth of organic horizon above mineral soil

Texture	Consistency	Color	Mottling
0	A.S.L.	10YR 4/2	none
6	SoLo	2.5Y 4/2	none
12	5% c.f.s. as fine gravel		
18	S.L.	2.5Y 5/2	few
24			
30			
36			
42			
48			

Soil Profile	Classification	Slope	Limiting Factor	<input type="checkbox"/> Groundwater
		<u>12</u>	<u>16"</u>	<input checked="" type="checkbox"/> Restrictive Layer
Profile	Condition	Percent	Depth	<input type="checkbox"/> Bedrock

Soil Series Name Udorthent Hydrologic Group B

Soil Scientist/Site Evaluator Signature

CSS/LSE#

Date

7/31/15

Appendix C

NRCS Soil Series Descriptions

LOCATION TELOS

ME

Established Series
Rev. KJL-LRF-MJK
07/2014

TELOS SERIES

The Telos series consists of somewhat poorly drained soils on till plains, hills, and ridges. They are shallow to dense lodgement till and very deep to bedrock. These soils formed in till. Saturated hydraulic conductivity is moderately high or high in the solum and low to moderately high in the substratum. Slope ranges from 0 to 25 percent. Mean annual temperature is about 4.4 degrees C, and mean annual precipitation is about 97 centimeters at the type location.

TAXONOMIC CLASS: Loamy, isotic, frigid, shallow Aquic Haplorthods

TYPICAL PEDON: Telos silt loam, on a 3 percent slope in a very stony forested area, at an elevation of about 500 meters. (Colors are for moist soil.)

Oi -- 0 to 5 centimeters; dark brown (7.5YR 3/4) slightly decomposed plant material; weak medium granular structure; very friable; common very fine and fine roots throughout; extremely acid; abrupt wavy boundary.

Oe -- 5 to 8 centimeters; black (10YR 2/1) moderately decomposed plant material; weak medium granular structure; very friable; few very fine roots throughout; extremely acid; abrupt wavy boundary. (Combined thickness of the O horizons is 5 to 18 centimeters.)

E -- 8 to 13 centimeters; light brownish gray (10YR 6/2) silt loam; weak medium subangular blocky structure; friable, common fine roots throughout; 5 percent gravel; extremely acid; abrupt wavy boundary. (0 to 15 centimeters thick.)

Bs -- 13 to 33 centimeters; brown (7.5YR 5/4) loam; weak medium subangular blocky structure; friable; common very fine to medium roots throughout; 5 percent gravels and 5 percent channers; very strongly acid; clear wavy boundary. (10 to 30 centimeters thick.)

BC -- 33 to 48 centimeters; light olive brown (2.5Y 5/4) loam; weak fine subangular blocky structure; friable; few very fine and fine roots throughout; 1 percent fine faint light yellowish brown (2.5Y 6/3), moist, areas of iron depletion throughout and 10 percent fine prominent strong brown (7.5YR 5/6), moist, masses of oxidized iron throughout; 5 percent gravels; strongly acid; clear wavy boundary. (0 to 18 centimeters thick.)

Cd -- 48 to 152 centimeters; olive (5Y 5/3) loam; structureless massive; firm; 1 percent fine prominent brownish yellow (10YR 6/8), moist, masses of oxidized iron throughout and 10 percent fine distinct light brownish gray (10YR 6/2), moist, areas of iron depletion throughout; 5 percent gravels and 5 percent channers; strongly acid.

TYPE LOCATION: Somerset County, Maine; Township 5, Range 15; 6.0 miles east of Ragmuff Road

on the Bean Pot Road; USGS Bean Pot Pond, ME topographic quadrangle; Latitude 46 degrees, 5 minutes, 37.2 seconds N. and Longitude 69 degrees, 39 minutes, 30.9 seconds W., NAD 1927.

RANGE IN CHARACTERISTICS: Thickness of the solum ranges from 33 to 50 centimeters. Thickness of the mineral soil over the dense till ranges from 25 to 50 centimeters. Depth to bedrock is more than 152 centimeters. Texture of the fine-earth fraction in the solum is silt loam, loam, very fine sandy loam, and fine sandy loam. The weighted average of clay in the particle-size control section is 10 to 18 percent. Texture in the Cd layer is silt loam and loam in the fine-earth fraction. Rock fragment content ranges from 5 to 35 percent in the E or A horizons where present, and from 5 to 25 percent in the underlying material. Rock fragments are mainly channers and pebbles, but in the A and E horizons of some pedons they are mainly cobbles. Stones and boulders cover from 0 to 25 percent of the surface. Reaction ranges from extremely acid to moderately acid in the solum, and from strongly acid to slightly acid in the substratum.

The O horizon has a hue of 2.5YR to 10YR, value of 2 to 3, and chroma of 1 or 4.

Some areas have an Ap horizon with hue of 10YR and value and chroma of 3 or 4.

The E horizon has hue of 5YR to 10YR, value of 5 to 7, and chroma of 1 or 2. Consistence is very friable or friable.

The Bhs horizon has hue of 2.5YR or 5YR, with value and chroma of 2.5 or 3. The Bh horizon, where present, has hue of 7.5YR to 10YR, value of 2 to 3, and chroma of 2 or 3.

The Bs horizon has hue of 5YR to 10YR, value of 3 to 5, and chroma of 4 to 8. Consistence is very friable or friable.

The BC horizon has hue of 2.5Y or 5Y, value of 4 to 6, and chroma of 3 or 4. Consistence is friable or firm.

Some pedons have an E' horizon with hue of 2.5Y or 5Y, value of 5 or 6, and chroma of 2. Consistence is friable or firm.

The Cd layer has hue of 2.5Y or 5Y, value of 3 to 5, and chroma of 1 to 4. It is massive or it has strong very coarse prisms which may part to weak to strong, thin to very thick plates, or moderate or strong, fine to coarse angular blocks. Arrangement of soil particles into structural aggregates is considered to be inherited from the parent material. Consistence is firm or very firm.

COMPETING SERIES: [Colonel](#) is the only other series in the same family. Colonel soils have less than 10 percent clay content in the particle-size control section.

[Chesuncook](#), [Daigle](#), [Dixfield](#), [Dixmont](#), [Howland](#), [Peru](#), [Skerry](#), and [Sunapee](#) series are in related families. Chesuncook soils are moderately deep to dense till, moderately well drained, and do not have redox depletions within 16 inches from the mineral soil surface. Daigle soils from 18 to 27 percent clay content in the particle-size control section. Dixfield, Dixmont, Howland, Peru, Skerry, and Sunapee soils have less than 10 percent clay in the particle-size control section.

GEOGRAPHIC SETTING: Telos soils are on upland till plains, hills, and ridges. Slope ranges from 0 to 25 percent. The soils formed in dense glacial till derived mainly from slate and other dark colored sedimentary and metamorphic rocks. The climate is humid and cool temperate. The mean annual

temperature ranges from 2 to 7 degrees C and mean annual precipitation ranges from 86 to 117 centimeters. The frost-free season ranges from 80 to 130 days. Elevation ranges from 100 to 840 meters above mean sea level.

GEOGRAPHICALLY ASSOCIATED SOILS: These are the [Burnham](#), [Chesuncook](#), [Elliottsville](#), [Monarda](#), [Monson](#), [Ragmuff](#), and [Thorndike](#) soils. The Burnham and Monarda soils occur in lower positions on the landscape and are wetter. Chesuncook soils are better drained and are in higher positions on the landscape. Elliottsville, Monson, Ragmuff, and Thorndike soils are shallower to bedrock and occur in higher positions on the landscape.

DRAINAGE AND SATURATED HYDRAULIC CONDUCTIVITY: Somewhat poorly drained. Saturated hydraulic conductivity is moderately high or high in the mineral solum and low to moderately high in the substratum.

USE AND VEGETATION: Mostly forest. Common tree species include red spruce, white spruce, balsam fir, yellow birch, paper birch, and red maple.

DISTRIBUTION AND EXTENT: Maine. MLRA 143, 144B, and 146. The series is of moderate extent.

MLRA SOIL SURVEY REGIONAL OFFICE (MO) RESPONSIBLE: Amherst, Massachusetts.

SERIES ESTABLISHED: Soil survey of Franklin County Area and Part of Somerset County, Maine, 1992.

REMARKS: Series classification was revised 11/05 from Coarse-loamy, isotic, frigid, shallow Aquic Haplorthods to Loamy, isotic, frigid, shallow Aquic Haplorthods to reflect shallow characteristic. Competing series section revised 5/06 to reflect classification.

Diagnostic horizons and features recognized in this pedon include:

- a. Albic horizon - the zone from 8 to 13 centimeters (E horizon).
- b. Spodic horizon - the zone from 13 to 33 centimeters (Bhs and Bs1 horizons).
- c. Cambic horizon - the zone from 33 to 48 centimeters (BC horizon).
- c. Densic materials - firm, dense lodgement till at a depth of 48 centimeters.
- d. Aquic conditions - redoximorphic features at 25 centimeters below the mineral soil surface.

Additional Data: This pedon is characterized by the National Soil Survey Laboratory in Lincoln Nebraska, reference pedon 09N0166. Climate data are from US official station #171472 Clayton Lake, Maine. Source of data used in establishing taxonomic class and range in characteristics is Maine Agricultural and Forest Experiment Station, Technical Bulletin 155, 1994; NRCS Characterization Data; and composite data from the Field Appraisal of Resource Management Systems compiled by Dr. Paul R. Hepler, of the Department of Plant and Soil Sciences, University of Maine, Orono, Maine.

National Cooperative Soil Survey
U.S.A.

LOCATION PEACHAM

VT+MA ME NH

Established Series
Rev. SHG-RFL-DHZ
05/2015

PEACHAM SERIES

The Peacham series consists of very deep, very poorly drained soils that formed in organic material over loamy lodgment till in glaciated uplands and lowlands. They are shallow to a dense substratum and very deep to bedrock. Estimated saturated hydraulic conductivity is moderately high or high in the solum and moderately low or low in the dense substratum. Slope ranges from 0 to 8 percent. Mean annual precipitation is about 1180 mm, and mean annual temperature is about 6 degrees C.

TAXONOMIC CLASS: Loamy, mixed, superactive, nonacid, frigid, shallow Histic Humaquepts

TYPICAL PEDON: Peacham mucky peat, on a 3 percent slope in a very stony pasture. (Colors are for moist soil.)

²
Oe--0 to 3 cm; black (N 2.5/) mucky peat; massive; very friable; many fine roots; neutral (pH 7.3); abrupt wavy boundary.

^{2"-10"}
Oa--5 to 25 cm; black (N 2.5/) muck; massive; very friable; many fine roots; neutral (pH 6.7); abrupt smooth boundary. (O horizon is 20 to 40 cm thick.)

^{10"-13"}
Bg--25 to 38 cm; dark greenish gray (5GY 4/1) fine sandy loam; weak fine and medium subangular blocky structure; friable; many fine roots; common medium prominent yellowish brown (10YR 5/8) masses of iron accumulation; 7 percent rock fragments; neutral (pH 6.8); abrupt wavy boundary. (11 to 50 cm thick)

Cdg1--38 to 79 cm; dark grayish brown (2.5Y 4/2) fine sandy loam; massive; firm; many coarse prominent yellowish brown (10YR 5/8) masses of iron accumulation and many medium faint gray (5Y 5/1) iron depletions; 10 percent rock fragments; slightly acid (pH 6.4); clear wavy boundary.

Cdg2--79 to 165 cm; dark olive gray (5Y 3/2) sandy loam; massive; firm; many medium prominent yellowish brown (10YR 5/8) masses of iron accumulation and many medium faint gray (5Y 5/1) iron depletions; 10 percent rock fragments; neutral (pH 6.8).

TYPE LOCATION: Caledonia County, Vermont; Town of Burke; located about 1.8 km south of the Sutton River, and 430 meters east of the Sutton town line; USGS Burke Mountain, VT topographic quadrangle; latitude 44 degrees, 37 minutes, and 29 seconds N. and longitude 71 degrees 59 minutes, and 02 seconds W., NAD 1983.

RANGE IN CHARACTERISTICS: The thickness of the mineral solum ranges from 11 to 50 cm. Depth to bedrock is greater than 165 cm. Texture is sandy loam, fine sandy loam, very fine sandy loam, loam, or silt loam in the fine-earth fraction. The weighted average of clay in the particle-size control section is 1 to 10 percent. Rock fragments are mostly gravel and cobbles and range from 5 to 30 percent

in the mineral horizons. Reaction ranges from very strongly acid to neutral throughout the soil.

The O horizon is neutral or has hue of 5YR to 10YR, value of 2 to 3, and chroma of 0 to 2. It is mucky peat or muck.

Some pedons have an Oi horizon that consists of peat.

Some pedons have an A horizon that has hue of 10YR to 5Y, value of 2 to 4, and chroma of 1 or 2. Mucky mineral texture modifiers are common.

The Bg horizon, and Eg horizon where present, is neutral or has hue of 10YR to 5GY, value of 4 to 6, and chroma of 0 to 2.

The Cd_g horizon is neutral or has hue of 2.5Y to 5B, value of 3 to 6, and chroma of 0 to 2. It is massive or has plates of geogenic origin. Consistence is firm or very firm.

Some pedons have thin sandy lenses in the Bg and Cd_g horizons.

Some pedons have a thin, friable C_g horizon above the Cd_g horizon.

COMPETING SERIES: The [Burnham](#) series is in the same family. Burnham soils have more than 10 percent clay in the particle-size control section.

GEOGRAPHIC SETTING: Peacham soils are on nearly level to gently sloping areas in glaciated uplands and lowlands. They are typically in open and closed depressions on footslopes and toeslopes. The soils formed in organic material 20 to 40 cm thick and the underlying loamy lodgment till. The till is Wisconsin-aged and derived mainly from granite, gneiss, schist, and phyllite. Slope ranges from 0 to 8 percent. The mean annual precipitation is 790 to 1640 mm, and the mean annual temperature is 2 to 7 degrees C. The frost-free period ranges from 70 to 135 days. Elevation ranges from about 100 to 800 meters above sea level.

GEOGRAPHICALLY ASSOCIATED SOILS: These are the [Brayton](#), [Buckland](#), [Cabot](#), [Colonel](#), [Marlow](#), [Peru](#), [Pillsbury](#), [Tunbridge](#), [Vershire](#), and [Wonsqueak](#) soils. Peacham soils are in a drainage sequence with the well drained Marlow soils, moderately well drained Buckland and Peru soils, somewhat poorly drained Colonel soils, and poorly drained Brayton, Cabot, and Pillsbury soils. Tunbridge and Vershire soils are on higher positions in the landscape and are well drained and moderately deep to bedrock. Wonsqueak soils formed in thicker deposits of organic material over mineral soil material.

DRAINAGE AND SATURATED HYDRAULIC CONDUCTIVITY: Very poorly drained. Estimated saturated hydraulic conductivity is moderately high or high in the solum and moderately low or low in the dense substratum.

USE AND VEGETATION: Most areas are forested. The common trees are balsam fir, red spruce, black spruce, red maple, yellow birch, tamarack, black ash, eastern white pine, and northern white cedar. A few areas cleared of stones are used mainly for hay and pasture.

DISTRIBUTION AND EXTENT: Vermont, Maine, Massachusetts, and New Hampshire; MLRAs 143 and 144B. These soils are extensive with about 160,000 acres of the series mapped.

MLRA SOIL SURVEY REGIONAL OFFICE (MO) RESPONSIBLE: Amherst, Massachusetts.

SERIES ESTABLISHED: Franklin County, Vermont, 1948.

REMARKS: Diagnostic horizons and features recognized in this pedon are:

Histic epipedon - the zone from 0 to 25 cm (Oe and Oa horizons).

Cambic horizon - the zone from 25 to 38 cm (Bg horizon).

Aquic conditions- masses of iron accumulation in the matrix and an iron depleted matrix from 25 to 38 cm (Bg horizon).

Densic materials - the zone from 38 to 165 cm (Cdg1 and Cdg2 horizons).

ADDITIONAL DATA: Characterization data for Peacham and similar soils is available through the National Cooperative Soil Survey Soil Characterization Database:

<http://ncsslabsdatamart.sc.egov.usda.gov/>

National Cooperative Soil Survey
U.S.A.

LOCATION OSSIPEE

NH+ME NY VT

Established Series
Rev. SALP-HRM
01/2000

OSSIPEE SERIES

The Ossipee series consists of very deep, very poorly drained soils formed in organic accumulations. They are underlain by loamy sediments on outwash plains, lake plains, and glacial till uplands. Slopes range from 0 to 2 percent. Mean annual precipitation is about 42 inches, and mean annual temperature is about 43 degrees F.

TAXONOMIC CLASS: Loamy, mixed, dysic, frigid Terric Haplohemists

TYPICAL PEDON: Ossipee mucky peat, on a nearly level undisturbed bog. (Colors are for moist soil unless otherwise stated.)

0e1--0 to 12 inches; dark reddish brown (5YR 2/2), broken face and rubbed, hemic material; about 60 percent fibers, 35 percent rubbed; moderate medium and coarse granular structure; nonsticky; 2 percent coarse fragments; extremely acid; clear smooth boundary. (4 to 16 inches thick)

0e2--12 to 18 inches; dark reddish brown (5YR 2/2), broken face and rubbed, hemic material; about 60 percent fibers, 30 percent rubbed; moderate very coarse granular structure; nonsticky; 2 percent coarse fragments; extremely acid; clear smooth boundary. (4 to 20 inches thick)

0e3--18 to 25 inches; dark brown (7.5YR 3/2), broken face and rubbed, hemic material; about 50 percent fibers, 25 percent rubbed; massive; nonsticky; 8 percent coarse fragments; extremely acid; abrupt smooth boundary. (0 to 20 inches thick)

Cg1--25 to 36 inches; gray (5Y 6/1) silt loam; massive; firm; strongly acid; clear smooth boundary. (0 to 15 inches thick)

Cg2--36 to 65 inches; gray (5Y 6/1) very fine sandy loam; massive; firm; moderately acid.

TYPE LOCATION: Carroll County, New Hampshire; Town of Conway, about 700 feet east of the Brewster Morrill access road to Conway Lake and about 1.25 miles south of Rt. 113. USGS Ossipee Lake, NH-ME; 15 feet Quadrangle; 43 degrees 58 feet 44 inches N and 71 degrees 4 feet 21 inches W.

RANGE IN CHARACTERISTICS: Thickness of the organic soil layers ranges from 16 to 50 inches. The organic materials are comprised of herbaceous and woody materials. Slightly decomposed woody fragments comprise 2 to 15 percent by volume of the organic materials. Thin layers of live sphagnum moss up to 4 inches in thickness commonly occur on the surface. The organic soil layers are neutral or have hue of 5YR through 10YR, value of 1 through 4, and chroma of 0 through 2. The value and/or chroma may increase 1 or 2 units when exposed to air. Reaction is extremely acid.

The surface tier, exclusive of loose surface litter or moss, is comprised of hemic or fibric material with an unrubbed fiber content that ranges from 35 to 95 percent of the organic volume; rubbed fiber content

ranges from 15 to 90 percent. It has weak to moderate, medium to coarse granular structure.

The subsurface tier is dominated by hemic material. The unrubbed fiber content ranges from 35 to 80 percent; the rubbed fiber content ranges from 10 to 40 percent. It is dominantly massive, but ranges to include granular structure.

The organic bottom tier, where present, has the same range as the subsurface tier.

The C horizon is neutral or has hue of 10YR through 5GY, value of 4 through 6, and chroma of 0 through 4. It is sandy loam, fine sandy loam, very fine sandy loam, loam, silt loam, clay loam, or silty clay loam. Reaction ranges from very strongly acid through slightly acid.

COMPETING SERIES: These are the [Merwin](#) series in the same family and the [Cathro](#), [Chocorua](#), and [Greenwood](#) series in related families. The Merwin soils have a thin buried soil in the upper part of the mineral substratum. Cathro soils are dominantly of sapric material and are less acid. Chocorua soils have a coarser textured mineral substratum. Greenwood soils have organic materials thicker than 51 inches.

GEOGRAPHIC SETTING: Ossipee soils occur in depressional areas within outwash and lake plains and on glacial till uplands. The average size of these soil areas ranges from about 5 to 75 acres. Slopes are less than 2 percent. The climate is humid and cool temperate. The mean annual temperature ranges from 40 to 45 degrees F., and the mean annual precipitation ranges from 35 to 50 inches.

GEOGRAPHICALLY ASSOCIATED SOILS: The competing [Chocorua](#) and [Greenwood](#) soils occupy similar landscapes. The [Adams](#), [Au Gres](#), [Boothbay](#), [Naumburg](#), [Pillsbury](#), and [Raynham](#) mineral soils commonly occur near the edges of bogs above the Ossipee soils.

DRAINAGE AND PERMEABILITY: Very poorly drained; surface runoff is ponded. Permeability is moderate to moderately rapid in the organic portion and moderately slow to moderate in the mineral substratum.

USE AND VEGETATION: These soils are primarily in native vegetation consisting of shrubs, reeds, sedges, and commonly with a tree canopy. The trees include tamarack, black spruce, balsam fir, yellow birch, and black ash.

DISTRIBUTION AND EXTENT: Maine, New Hampshire, and New York. The series is of moderate extent.

MLRA SOIL SURVEY REGIONAL OFFICE (MO) RESPONSIBLE: Amherst, Massachusetts

SERIES ESTABLISHED: Carroll County, New Hampshire, 1974.





REMARKS: 1. The Ossipee soils were formerly included with areas designated as Muck and Peat.
2. Diagnostic horizons and features recognized in this pedon are:


- a. Organic materials feature - the zone from 0 to 25 inches (Oe horizon).
- b. Terric feature - the zone from 25 to 65 inches (2Cg horizon).
- c. Dysic feature - the pH is less than 4.5 in .01 molar calcium chloride in all parts of the organic materials in the control section (Oe1, Oe2, and Oe3 horizons).

Appendix D

Soil Survey Map

Site Features



-  Test Pits
-  Soil Boundaries
-  Building
-  Parcel Boundary



NOTES

1. This detailed Site-Specific Soil Map conforms to the standards of SSSNNE Publication No. 3, as amended, "Site-Specific Soil Mapping Standards for NH and VT".
2. This map has been prepared to comply with soil mapping requirements of RSA 485 A: 17 and NHDES Env-Wq 1500, Alteration of Terrain.
3. See accompanying narrative report for methodology, map symbol legend, and interpretations.

Map Symbol	Name	Slope (%)	Hydrologic Group
123B	Telos silt loam	3-8	C
299B/dbcde	Udorthents, smoothed	3-8	A/B
299C/dbcde	Udorthents, smoothed	8-15	C/A/D
731A	Peacham and Ossipee mucky peat	0-3	D



TS5a SOIL SURVEY OVERVIEW

Bethlehem, NH



EVERSOURCE
ENERGY

NORMANDEAU ASSOCIATES
Environmental Consultants

APPENDIX H – GEOTECHNICAL REPORT (BY OTHERS)

Geotechnical Engineering Report

Transition Station #5 Project Northern Pass Transmission Line Bethlehem, New Hampshire

December 23, 2016
QS Project No. 16004

Prepared for:

PAR Electrical Contractors, Inc.
60 Fuller Road
Chicopee, Massachusetts 01020

Prepared by:

Quanta Subsurface
307 W. Main Street
Radford, Virginia 24141





December 23, 2016

PAR Electrical Contractors, Inc.
60 Fuller Road
Chicopee, Massachusetts 01020

Attention: Ms. Stephanie Labbe
Project Manager

Re: Geotechnical Engineering Report
Transition Station #5 Project – Northern Pass Transmission Line
Bethlehem, New Hampshire
QS Project No. 16004


Dear Ms. Labbe,

The purpose of this report is to present the results of the subsurface exploration program and geotechnical engineering analyses undertaken by Quanta Subsurface (QS) associated with the above referenced project. Our services were provided in general accordance with QS's proposal dated August 22, 2016 as approved by PAR Electrical Contractors' (PAR) Limited Notice to Proceed (LNTP) #4 dated August 26, 2016. The attached report presents our understanding of the project, the findings of the subsurface exploration program, and our geotechnical conclusions and recommendations.

Sincerely,

Quanta Subsurface

Sean Kearney, P.G.
Project Engineering Geologist



12/23/16

J.T. McGinnis, P.E.
Geotechnical Department Manager

TABLE OF CONTENTS

1.0	PROJECT INFORMATION	1
2.0	PROVIDED DOCUMENTS AND PREVIOUS EXPLORATION DATA	1
3.0	PURPOSE AND SCOPE OF SERVICE	2
4.0	EXPLORATION AND TESTING PROCEDURES	3
4.1	SUBSURFACE EXPLORATION	3
4.2	LABORATORY TESTING	4
4.3	FIELD INFILTRATION TESTING	4
5.0	GEOLOGY AND SUBSURFACE CONDITIONS	5
5.1	GENERAL	5
5.2	REGIONAL GEOLOGY	5
5.3	SITE SUBSURFACE CONDITIONS	5
6.0	DESIGN AND CONSTRUCTION RECOMMENDATIONS	7
6.1	GENERAL	7
6.2	SITE PREPARATION	7
6.3	CONTROLLED STRUCTURAL FILL	8
6.4	SLOPE STABILITY	9
6.4.1	General	9
6.4.2	New Slope Stability	9
6.5	GROUNDWATER CONDITIONS	9
6.5.1	General	9
6.5.2	Basin Estimated Seasonal High Water Table (ESHWT)	10
6.6	GEOTECHNICAL DESIGN STRENGTH PARAMETERS	11
6.7	BUS SUPPORT STRUCTURE/POLE FOUNDATION DESIGN AND CONSTRUCTION	11
6.7.1	General	11
6.7.2	Drilled Shaft Foundations	11
6.7.3	Drilled Shaft Construction	13
6.8	SHALLOW FOUNDATION DESIGN AND CONSTRUCTION	13
6.8.1	Transformer Pad	13
6.8.2	Single-Story Equipment Structures	14
6.8.3	Shrink-Swell and Frost Depth Considerations	14
6.8.4	Shallow Foundation Construction	14
6.9	MECHANICALLY STABILIZED EARTH RETAINING WALLS	15
6.10	EARTHQUAKE CONSIDERATIONS	17
6.10.1	Seismic Site Class Definition	17
6.10.2	Liquefaction	17
6.11	KARST GEOLOGY	17
6.12	CORROSION CONSIDERATIONS	17
7.0	LIMITATIONS	18
8.0	REFERENCES	18

FIGURES

Figure 1	Site Vicinity Map
Figure 2	Site Location Map
Figure 3	Boring Location Plan
Figure 4	Surficial Geologic Map

APPENDICES

Appendix A	Boring Logs
Appendix B	Laboratory Test Results
Appendix C	Infiltration Test Results
Appendix D	Summary Geotechnical Design Parameters

EXECUTIVE SUMMARY

This Executive Summary is provided as a brief overview of our geotechnical engineering conclusions and recommendations for the project and is not intended to replace more detailed information contained elsewhere in this report. As an overview, this summary inherently omits details that could be very important to the proper application of the provided geotechnical design recommendations. This report should be read in its entirety.

- QS's geotechnical field exploration program consisted of eight (8) Standard Penetration Test (SPT) borings, drilled to a maximum depth of approximately 52 feet.
- Two infiltration (INF) test borings were conducted to characterize the subsurface conditions to a depth of approximately 2 to 6 feet below the planned basin bottom. Following completion of each INF test boring, field infiltration tests were performed at each location.
- The subsurface conditions encountered at the site generally included a layer of topsoil, meltwater channel deposits, and till.
- Bedrock was not encountered in the test borings.
- Groundwater is anticipated to exist at a depth of about 13 feet in the area of borings BH 801 and BH 802 and within 5 feet of the existing ground surface at all other locations. It should be noted that borings BH 803 through BH 806 (including INF 801 and INF 802) were located in a low lying area of the site where wetland conditions existed at the surface (including areas of standing water).
- In general, the subsurface conditions encountered at the site are suitable for the proposed construction with considerations presented herein.
- Due to encountering very dense/hard channel deposits and till containing boulders and cobbles at relatively shallow depths in the area of the planned structures, drilled shafts are recommended for support of the bus support/pole structures.
- Controlled structural fill and/or the onsite soils (meltwater channel deposits) will provide suitable support for the transformer pad designed to transmit an approximate uniform bearing pressure of up to 500 psf and structures supported by shallow foundation designed with a maximum allowable bearing pressure of 3,000 psf.
- The onsite soils will generally have a low shrink-swell potential. Accordingly, no design modifications relative to the potential for shrink-swell soils are recommended.
- Frost depth should be anticipated to be 4 feet below the lowest adjacent grade.
- A Seismic Site Class Definition of "D" is recommended for design.
- Laboratory corrosivity testing performed on samples collected from the site indicated that onsite soils will exhibit "aggressive" corrosion potential.
- We anticipate that the retaining walls planned to develop planned finished grades will consist of a mechanically stabilized earth (MSE) walls. Subgrade conditions at the site are suitable to support MSE walls.

1.0 PROJECT INFORMATION

The Northern Pass project consists of a 192-mile long transmission line that will convey 1,090 megawatts of energy from hydroelectric facilities in Canada to New England via a corridor that traverses north-to-south through New Hampshire (see Site Vicinity Map – Figure 1). In addition to construction of new transmission line, the project also includes the construction of three (3) new substations and six (6) new transition stations along the corridor. In general, the new transition stations (designated Transition Stations #1 through #6) are located along the northern and central portions of the corridor while the three new substations (designated Franklin Converter Station, Deerfield Substation, and Scobie Pond Substation) are located along the southern portion of the corridor. The information presented herein is for the Transition Station #5 located approximately 1 mile west of Bethlehem, New Hampshire (see Site Location Map - Figure 2).

The Transition Station #5 site is partially developed (existing residential dwelling) and partially wooded. Within the transition station pad footprint, existing ground surface elevations range from approximately 1078 feet to 1101 feet. Placement of up to 21 feet of fill will be required to develop the planned finished grade elevations of 1098 feet to 1100 feet. Development will include a detention basin to the north of the transition station that will be constructed with cut and fill slopes less than 5 feet in height and a gravel-covered access road that will provide access to the station from Highway 302. An approximate 600-foot long retaining wall with a maximum height of about 21 feet is planned along the east, west, and north perimeter of the transition station pad. Due to the height and length of the planned wall, QS has assumed that a Mechanically Stabilized Earth (MSE) retaining wall system will be utilized for design and construction of the wall.

New structures within the transition station footprint are anticipated to consist of a transformer pad, a bus support structure, an MSE retaining wall, and possibly single-story structures designed to house electrical equipment. Quanta Subsurface (QS) has assumed the following regarding loading and foundation support of the new structures: 1) the bus structure will require deep foundation support to resist shear and overturning loads, 2) the transformer pad will consist of slab-on-grade support designed for a maximum bearing pressure of 500 psf, 3) the MSE retaining wall will utilize shallow foundation support, and 4) single-story structures designed to house equipment will be lightly loaded with shallow foundation support.

2.0 PROVIDED DOCUMENTS AND PREVIOUS EXPLORATION DATA

Multiple documents were provided to QS by PAR Electrical Contractors (PAR) for consideration during our geotechnical exploration and engineering evaluation. The provided geotechnical report documents were developed by others and presented information at various locations along the transmission line corridor. Upon review of the provided data, one document provided GIS information containing general surficial and bedrock geology information in the area of the Transition Station #5 site. The specific document included as reference by QS herein is listed below.

- Terracon Consultants, Inc.; *Report of Expected Geotechnical Conditions*: Northern Pass Project; July 10, 2015.

Although data from this report was not specifically used in development of the recommendations presented in Section 6.0 of this report, selected information was used as reference in support of the site specific data obtained by QS. Specific citations are noted below.

3.0 PURPOSE AND SCOPE OF SERVICE

QS's scope of work was developed based on information provided by PAR that included requested field investigations for civil works from Burns & McDonnell (*Subsurface Exploration and Geotechnical Engineering Report: Technical Guidelines*; Northern Pass Transmission Stations, New Hampshire, provided to QS on July 11, 2016) as well as requested investigations for planned structures from others. The purposes of our involvement on Transition Station #5 phase of the project were as follows: 1) provide general descriptions of the subsurface conditions encountered at the transition station site; 2) provide geotechnical design parameters for use by others in analysis and design of site grading and permanent slopes; 3) provide geotechnical foundation design recommendations for support of the transition station structures; and 4) comment on geotechnical aspects of the proposed construction. In order to accomplish the above objectives, QS undertook the following scope of services:

- 1) reviewed available subsurface and geologic information relative to the project site;
- 2) supervised a subsurface exploration program consisting of eight (8) geotechnical borings within the area of the proposed transition station;
- 3) performed field infiltration testing services at two (2) locations within the proposed basin area;
- 4) supervised a laboratory testing program on selected soil samples obtained during the drilling program;
- 5) evaluated the findings of the test borings and laboratory tests relative to foundation support of planned structures and other geotechnical aspects of the project;
- 6) and prepared this written report summarizing our services for the project, providing descriptions of the subsurface conditions encountered, laboratory test results, and design recommendations, as well as geotechnical considerations for construction. Copies of the boring logs, laboratory test results, infiltration test results, and summary of geotechnical design parameters are provided in Appendices A through D.

QS's scope of services did not include a survey of boring locations and elevations, quantity estimates, preparation of plans or specifications, pavement design, infiltration/retention basin design, blasting recommendations, identification of environmental impacts or aspects related to the project and/or site, or other services not specified above.

4.0 EXPLORATION AND TESTING PROCEDURES

4.1 SUBSURFACE EXPLORATION

QS's geotechnical field exploration program consisted of eight (8) Standard Penetration Test (SPT) borings performed at the approximate locations shown on the attached Boring Location Plan (see Figure 3) and summarized in Table 1 below. The test boring locations were staked in the field by others using surveying methods; ground surface elevations at the boring locations were derived from topographic data included within an ACAD site plan document (labeled *NPTT804-C101-Geotech.dwg*) using latitude and longitude data provided by PAR.

Table 1 - As-Drilled SPT Borehole Depths and Coordinates

Boring Designation	Total Depth (ft)	Ground Surface Elevation (ft)	Latitude	Longitude
BH 801	50.9	1101.1	44.28227222	-71.72596944
BH 802	40.8	1100.0	44.28209722	-71.72533056
BH 803	50.4	1083.2	44.28241389	-71.72576111
BH 804	52	1079.1	44.28261667	-71.72582778
BH 805	51	1082.5	44.28248333	-71.72518611
BH 806	51.4	1077.5	44.28264722	-71.72545833
INF 801	10	1080.1	44.28257222	-71.72543611
INF 802	8	1082.0	44.28256111	-71.72530556

Note: Elevation information is NAVD88

Test borings were performed by S.W. Cole Engineering, Inc. (S.W. Cole) utilizing a CME 850 drill rig equipped with a 140-lb automatic drop hammer falling 30 inches. The drilling methods utilized for this investigation consisted of solid stem augers, hollow stem augers, and rotary drive and wash (wet rotary). Standard penetration testing was performed in general accordance with ASTM D1586 and at approximate 2-foot intervals to a depth of 10 feet and at 5-foot intervals thereafter. The number of hammer blows required to advance the sample for successive 6-inch intervals is recorded, and the total number of blows required to drive the sampler from 6 to 18 inches is referred to as the SPT "N-value". The N-value provides a general indication of in-situ soil density/consistency and has been correlated with certain engineering properties of soils. Soil samples were collected with a standard split-spoon sampler (2-in OD) and in bulk samples from auger cuttings for laboratory testing.

In some soils it is not always practical to drive a split-spoon sampler the full four consecutive 6-inch increments. Whenever more than 50 blows are required to drive the sampler over a 6-inch increment, or the sampler is observed not to penetrate after 50 blows, the condition is referred to as split-spoon refusal. The SPT N-value for split-spoon refusal conditions is typically estimated as greater than 100 blows per foot (bpf). Where the sampler is observed not to penetrate after 50 blows, the N-value is reported as 50/0. Otherwise, the depth of penetration after 50 blows is reported in inches (i.e. 50/5, 50/2, etc.). The test borings were extended to the planned termination depth or auger refusal, whichever was encountered first.

The subsurface materials encountered at each boring location were visually classified by QS personnel in the field. Soil samples were visually classified in accordance with ASTM D2488. In addition to visual classification of the materials in the field, the boring logs incorporate both driller and field inspector observations and comments as well as modifications based on laboratory test results. QS's boring logs are presented in Appendix A. SPT samples were collected in Ziploc bags and bulk samples were collected in 5-gallon buckets.

4.2 LABORATORY TESTING

QS selected various bulk and SPT samples for laboratory testing. Laboratory testing on soil samples was performed by S.W. Cole in their Londonderry and Manchester (New Hampshire) laboratories or via subcontract with Absolute Resource Associates (sulfate and chloride testing). Table 2 provides a summary of the laboratory testing performed for the Transition Station #5 site. A summary of the laboratory testing results and accompanying laboratory test data reports are provided in Appendix B.

Table 2 – Laboratory Test Summary

Test	ASTM/AASHTO	No. of Test Performed
Moisture Content	D2216	17
Sieve Analysis	D422	2
Percent Passing No. 200 Sieve	D1140	8
Atterberg Limits	D4318	1
Modified Proctor	D1557	1
pH of Soil	G51	1
Soluble Chloride	--	1
Soluble Sulfate	--	1
Resistivity	T188	1

4.3 FIELD INFILTRATION TESTING

Two infiltration (INF) test borings were conducted (designated INF 801 and INF 802) to characterize the subsurface conditions to a depth of approximately 2 to 6 feet below the planned basin bottom. Each boring was sampled continuously (every 2 feet) from ground surface to its termination depth. Following completion of each INF test boring, an offset borehole was drilled and PVC casing was installed to the approximate planned bottom of the basin for field infiltration testing. At some time following completion of drilling, field infiltration tests were performed by Quanta Subsurface. The results of the field infiltration tests are provided in Appendix C. The installation, preparation, and testing procedures followed were in general accordance with Table 2-3 of the *New Hampshire Department of Environmental Services Stormwater Manual*, Volume 2 (2008).

5.0 GEOLOGY AND SUBSURFACE CONDITIONS

5.1 GENERAL

The overburden soils at the project site are derived from several episodes of advancing and retreating glacial ice. Subsurface materials encountered within the borings are consistent with the geologic setting of the area. The following sections describe the regional geology and site specific subsurface conditions.

5.2 REGIONAL GEOLOGY

The surficial geology of the White Mountains in New Hampshire is derived from the erosional and depositional processes of the continental and mountain glaciers of the Wisconsin Glacial Episode during the late Pleistocene Epoch. The dominant glacial soils that are found in this region are glacial till, glaciofluvial/outwash deposits, and glacio-lacustrine deposits. Younger post glacial deposits formed from the numerous rivers, streams, and lakes that dominate the landscape; these include alluvium and stream terrace deposits. The surficial soil in the area of the Transition Station #5 site is mapped as till as shown in Figure 4 (Surficial Geologic Map) with alluvial materials shown in the immediate vicinity.

Bedrock in the White Mountains are comprised of folded and faulted Paleozoic sedimentary and volcanic rocks that have been regionally metamorphosed and intruded by large and small bodies of plutonic rocks. The grade of metamorphism ranges from the chlorite zone at one extreme to the sillimanite zone at the other (Billings, 1980). The majority of the rocks mapped in this region consist of schist, phyllites, limestone, and quartzite. Based on Terracon Exhibit A2-2 (Bedrock Geology Map), the bedrock underlying the Transition Station #5 site is mapped as granite.

5.3 SITE SUBSURFACE CONDITIONS

The subsurface conditions encountered in the test borings generally included a layer of topsoil, channel deposits/alluvium, and till. A summary of the subsurface materials encountered in the exploration described herein is provided below and in Table 3, and specific data are shown on the boring logs provided in Appendix A.

Topsoil

Material described as topsoil was encountered at the ground surface in each of the test borings. The thickness of the topsoil ranged from 0.5 to 2.5 feet. The sampled topsoil was described as SILT with sand (ML), sandy SILT (ML), or silty SAND (SM) with trace amounts of organic. Laboratory testing was not performed to determine the organic content or horticultural properties of the topsoil. Therefore, the term “topsoil” is not intended to indicate suitability for landscaping and/or other purposes.

Meltwater Channel Deposits/Alluvium

Channel deposits are alluvial material formed by intermittent episodes of meltwater from glacial ice travelling through drainage channels in a high energy environment. The channel deposits are often variable in both particle size and layer thickness. Channel deposits were encountered in each test boring and were generally described as poorly graded SAND with silt (SP-SM), silty SAND (SM), or sandy SILT (ML) with varying amounts of gravel. Boulders and cobbles are

commonly present within channel deposits. The thickness of this unit ranged from 4 to 17 feet. Field N-values ranged from 5 bpf to 50 blows per 2 inches of penetration with a typical N-value of greater than 15 bpf.

Glacial Till

Glacial till was encountered below channel deposits at six (6) of the boring locations: BH 801, BH 802, BH 803, BH 804, BH 805, and BH 806. Glacial till was not encountered in the two (2) infiltration test borings due their shallow termination depth (i.e. 10 feet). Glacial till deposits consist of material that has been transported and deposited by glacial ice. The glacial till encountered was characterized as ablation till (melt-out till) indicating the material was carried on or near the surface of the glacier. Boulders of varying size are common within till deposits. Sampled till was generally described as poorly graded SAND with silt (SP-SM), silty SAND (SM), or sandy SILT (ML) with varying amounts of gravel. Field N-values obtained within the till material ranged from 40 bpf to 50 blows per 3 inches of penetration with a typical N-value of greater than 50 bpf.

Groundwater

Groundwater levels were measured using a tape measure in each boring. With the exception of borings BH 802, BH 806, and INF 801, groundwater was encountered in each of the borings. Where encountered, groundwater depths ranged from 0 (i.e. at the ground surface) to 13 feet below the existing ground surface. Due to the presence of existing wetland and a nearby pond (approximately 100 feet away from the site), the groundwater table is expected to be within 5 feet of the existing ground surface in the vicinity of borings BH 803 through 806. Fluctuations in water levels and soil moisture should be anticipated with changes in precipitation, run-off, and moisture.

Table 3 – Encountered Subsurface Conditions Summary

Boring No.	Ground Elevation (ft)	Depth to Groundwater ¹ (ft)	Boring Termination Condition	Depth (ft)	Material Origin	Encountered Material	Field N-Value ²
BH 801	1101.1	13.0	BT	0 - 1.5	Topsoil	ML	3
				1.5 - 6	Channel Deposits	SM	15 - 22
				6 - 8		SM	67
				8 - 50.9	Till	SM	78 - 50/4"
BH 802	1100.0	N.E.	BT	0 - 1.5	Topsoil	ML	4
				1.5 - 6	Channel Deposits	SM	18 - 21
				6 - 40.8	Till	SM	50/6" - 50/3"
BH 803	1083.2	0.0	BT	0 - 2.5	Topsoil	ML	1
				2.5 - 19	Channel Deposits	SM, ML	19 - 35
				19 - 50.4	Till	SM, ML	46 - 50/5"

Table 3 – Encountered Subsurface Conditions Summary (cont)

BH 804	1079.1	1.5	BT	0 - 1.5	Topsoil	ML	11
				1.5 - 6	Channel Deposits	SM, ML	12 - 30
				6 - 8		SM	56
				8 - 25	Till	SM	50/6"
				25 - 35		SM	45 - 60
				35 - 52		SM, SP-SM	71 - 50/3"
BH 805	1082.5	0.5	BT	0 - 1	Topsoil	ML	-
				1 - 2	Channel Deposits	SP-SM, SM	6
				2 - 13		SM	24 - 48
				13 - 51	Till	SM	60 - 50/4"
BH 806	1077.5	N.E.	BT	0 - 1	Topsoil	ML	-
				1 - 2	Channel Deposits	SM	5
				2 - 10		SM	32 - 81
				10 - 51.4	Till	SM	40 - 50/5"
INF 801	1080.1	N.E.	BT	0 - 1.5	Topsoil	ML	7
				1.5 - 6	Channel Deposits	SM, ML	18 - 37
				6 - 8		SM	50/2"
				8 - 10		SM	31
INF 802	1082.0	7.8	BT	0 - 1.5	Topsoil	SM	2
				1.5 - 8	Channel Deposits	SM, ML, SP-SM	14 - 25

¹ Reported groundwater levels were measured at the time of drilling.

² Field N-Value is an uncorrected blow count value measured in the field.

BT = Boring Termination (at or near the planned depth)

6.0 DESIGN AND CONSTRUCTION RECOMMENDATIONS

6.1 GENERAL

The following sections present our geotechnical recommendations for design and construction of the transition station. In general, the subsurface conditions encountered at the site are suitable for the proposed construction with considerations presented in the following subsections.

6.2 SITE PREPARATION

Before proceeding with construction, any topsoil, roots, foundation remnants, pavements, and any other deleterious non-soil materials should be stripped or removed from the proposed construction area. During the clearing and stripping operations, positive surface drainage should be maintained to prevent the accumulation of water. It should be noted that areas of standing surface water and small streams of flowing water were observed at the surface in multiple areas within the project site.

After stripping, areas intended to support new fill, gravel roadways, slabs, and foundations should be carefully evaluated by an experienced geotechnical engineer or engineering geologist. Based on the boring data across the project site, the top 2 feet of existing material (topsoil and loose soil) should be removed and replaced with controlled structural fill prior to at-grade construction.

Where noted on the borings logs and where located within 3 to 4 feet of new fill, roadways, slabs, and foundations, soils that exhibit SPT N-values of 6 bpf or less should be removed and replaced with controlled structural fill placed in accordance with recommendations presented in Section 6.3. The geotechnical engineer/geologist may also require scarification and compaction (per Section 6.3) of the upper 6 inches of the exposed surface and/or proofrolling of the subgrade with a 20- to 30-ton loaded dump truck or other pneumatic tired vehicle of similar size and weight. Proofrolling should be performed during a time of good weather and not while the site is wet, frozen, or severely desiccated. The purpose of the proofrolling is to locate soft, weak, or excessively wet soils present at the time of construction and provide an opportunity for the geotechnical engineer/geologist to locate inconsistencies intermediate of the boring locations.

Depending on how the near surface materials respond during proofrolling operations, some in-place densification, undercutting, or in-place stabilization may be required. The extent of densification, undercutting and/or in-place stabilization required across the site can best be determined by a geotechnical engineer/geologist at the time of construction. Once the site has been properly prepared, at-grade construction may proceed.

6.3 CONTROLLED STRUCTURAL FILL

Where required, controlled structural fill may consist of the non-organic, on-site soils (including channel deposits). However, development of the project site will predominately require fill to achieve the planned finished grades. Therefore, structural fill material originating from an offsite source is expected. Based on laboratory testing on bulk samples obtained from other transition station and substation sites along the transmission line corridor, we anticipate that off-site borrow material will consist of sandy silt, silty sand, or sand with a USCS classification of ML, SM, or SP. Other materials may be suitable for use as controlled structural fill and should be individually evaluated by the geotechnical engineer; in general, the structural fill should have a USCS classification of CL, ML, SM, or SC. Backfill requirements specific to MSE retaining walls expected on the project are provided in Section 6.9. Controlled structural fill should be free of boulders, organic matter, debris, or other deleterious materials and should have a maximum particle size no greater than 3 inches.

Fill materials should be placed in horizontal lifts with a maximum height of 8 inches loose measure. New fill should be adequately keyed into stripped and scarified subgrade soils and should, where applicable, be benched into the existing slopes. During fill operations, positive surface drainage should be maintained to prevent the accumulation of water. We recommend that structural fill (soil and crushed stone) be compacted to a minimum of 95 percent of the maximum dry density and within two (2) percentage points of the optimum moisture content determined by the modified Proctor density test (ASTM D1557). In confined areas such as utility trenches, portable compaction equipment and thin lifts of 3 to 4 inches may be required to achieve specified degrees of compaction. Each lift of fill should be tested in order to confirm that the recommended degree of compaction is attained.

6.4 SLOPE STABILITY

6.4.1 General

We recommend that cut and fill slopes have a minimum factor of safety of 1.3 for global stability. Proposed structures on the Transition Station #5 site should be located a minimum distance of 10 feet and 15 feet from the crest and toe of slopes, respectively. In addition, we recommend that roadways be designed with a minimum setback of 5 feet from both the crest and toe of slopes.

Drainage from nearby structures and/or surface runoff should be directed away from the crest and toe of both planned cut and fill slopes. We note that diversion of surface water away from the slope crest and face is critical to reducing the potential of surface erosion and shallow failures. For erosion protection, a protective cover of grass or other vegetation should be established on permanent soil slopes as soon as possible.

6.4.2 New Slope Stability

The planned finished grade of the transition station pad will be developed using retaining walls; new slopes on the project will be limited to those required to construct the planned detention basin. New detention basin slopes will predominately consist of cut slopes with a configuration of 3(H) to 1(V). A small fill slope with a 2(H) to 1(V) configuration and a rip-rap face is planned as part of the basin as well. All slopes will be less than 5 feet in height. We anticipate that the planned cut and fill slopes will exhibit a factor of safety (FoS) of 1.3 or greater for global stability if constructed in accordance with the recommendations presented herein.

We recommend that protective rip-rap layers have a minimum thickness of 1.5 feet, be underlain by a separation geotextile to minimum soil intrusion into the rip-rap, and be keyed into the subgrade at the slope's toe a minimum of 1.5 feet. The separation geotextile fabric used should have an equivalent opening size of equal to or greater than the US No 50 sieve, a minimum tensile strength at 20 percent strain of 30 pounds/linear inch, and a minimum puncture strength of 80 pounds.

6.5 GROUNDWATER CONDITIONS

6.5.1 General

Based on the data obtained during our exploration program and the site's proximity to a nearby pond, we anticipate that groundwater will be encountered during expected earthwork at the site. Considering the groundwater depths encountered and reported in the test borings, we anticipate that groundwater will exist at a depth of about 13 feet in the area of borings BH 801 and BH 802 and within 5 feet of the existing ground surface at all other locations. It should be noted that borings BH 803 through BH 806 (including INF 801 and INF 802) were located in a low lying area of the site where wetland conditions existed at the surface (including areas of standing water). Fluctuation of the groundwater surface due to seasonal precipitation and immediately after precipitation events should be expected.

6.5.2 Basin Estimated Seasonal High Water Table (ESHWT)

Borings INF 801 and INF 802 were performed to characterize the subsurface conditions to a depth of approximately 2 to 6 feet below the planned basin bottom and provide information necessary to estimate the seasonal high water table within the basin footprint. Subsurface data recorded in the infiltration test borings are shown on the respective logs included in Appendix A, and the results of infiltration tests performed immediately adjacent to each boring are provided in Appendix C. Table 4 below presents a summary of the interpreted ESHWT at each boring location as well as pertinent information required for design of the basins.

Table 4 – Infiltration Basin Summary Information

Description	Boring INF 801	Boring INF 802
Infiltration Planned Bottom Elev. (ft)	1076	1076
Encountered Very Dense/Very Hard Soil Elev. (ft)	N.E.	N.E.
Encountered Bedrock Elev. (ft)	N.E.	N.E.
Encountered Groundwater Elev. (ft)	N.E.	1074
Highest Elevation of Observed Redox Features	N.E.	1078
USDA Textural Class (with 5 ft of Basin Bottom)	Loam	Loam
Estimated Seasonal High Water Table (ESHWT) Elev. (ft)	1078	1078
Infiltration Test Elevation (ft)	1074	1078
Average Infiltration Rate at Test Elevation (in/hr)	0.0	0.0

Notes:

- 1) Borings generally extended below the planned depth of the basin unless where refusal and/or bedrock was encountered.
- 2) N.E. = Not Encountered
- 3) Very Dense/Very Hard Soil is defined as material exhibiting an SPT N-Value of greater than 50 blows per foot (bpf).
- 4) Very dense material encountered in INF 801 at 6.5 feet was due to cobbles and thus not reported on the table.
- 5) Noted elevations are estimates and should be considered approximate.
- 6) The average infiltration rate presented is based on field measurements; a factor of safety has not been applied.
- 7) Drilling contractor flushed the infiltration test boreholes with water following test casing installation. The water level measurements obtained at INF 801 and INF 802 at the time of the infiltration testing is not anticipated to represent the stabilized groundwater level. See the INF 801 and 802 boring logs for the appropriate groundwater level.

6.6 GEOTECHNICAL DESIGN STRENGTH PARAMETERS

Recommended geotechnical strength parameters are provided for the subsurface conditions encountered in each test boring (not including infiltration test borings) in Appendix D. The recommended soil strength parameters were developed with consideration of lab test results and established correlations with SPT data. Bedrock was not encountered at the site.

6.7 BUS SUPPORT STRUCTURE/POLE FOUNDATION DESIGN AND CONSTRUCTION

6.7.1 General

Foundation support for the bus support structure (including ancillary pole structures) is anticipated to require deep foundations to resist shear and overturning loads. Driven pile, helical pile, and drilled shaft foundation options were considered for support of the bus structure. We anticipate that very dense/hard channel deposits and till containing boulders and cobbles will be encountered within 10 feet of the planned finished grade in areas within the substation pad. Therefore, some amount of pre-drilling would be expected to facilitate installation of driven and helical piles. We recommend that support for the bus support/pole structures consist of drilled shafts at the Transition Station #5 site.

6.7.2 Drilled Shaft Foundations

Based on the subsurface conditions encountered in the area of borings BH 801 and BH 803, a top of finished grade elevation of about 1100 feet, and the general site preparation recommendations presented in previous sections of this report, we recommend the allowable axial values and the associated LPILE (lateral) parameters shown in Tables 5 through 8 be used for design of drilled shaft foundations. Tables 5 and 6 are applicable to foundations on the north side of the bus structure (where deep controlled fill will be placed to develop the planned finished grade) and Tables 7 and 8 are applicable to foundations on the south side where less than 5 feet of new controlled fill is expected. Total settlement of drilled shaft foundations designed per the recommendations provided below is estimated to be less than 1 inch.

Table 5 – Recommended Drilled Shaft Axial Design Parameters (North Side–BH 803)

Sublayer Description	Sublayer Depth (ft)		Material USCS Description	Allowable Skin Friction (Comp.) (psf)	Allowable Skin Friction (Uplift) (psf)	Allowable End Bearing (psf)
	Top	Bottom				
Structural Fill	0	5	SM/ML	IGNORE		
	5	20	SM/ML	250	210	-
Channel Deposits	20	24	SM	850	700	7,500
	24	26	ML	600	500	7,500
	26	43	SM	1,200	1,000	17,500
Till	43+	-	SM	2,300	1,925	20,000

Notes:

- 1) Approximately 18 feet of fill soil will be added in the area of BH 803. Including the recommended 2 feet of undercut and replace of existing topsoil/loose material, the total new fill depth was estimated to be about 20 feet.
- 2) Ultimate skin friction and end bearing capacities determined per methods prescribed in FHWA GEC 10: *Drilled Shaft: Construction Procedures and LRFD Design Methods* (2010).
- 3) Allowable capacities for skin (comp), skin (uplift), and end-bearing determined by applying a factor of safety of 2.5, 3.0 and 3.0, respectively.

Table 6 – Recommended Drilled Shaft Lateral (LPILE) Design Parameters (North Side–BH 803)

Sublayer Description	Sublayer Depth (ft)		Material USCS Description	Effective Unit Weight (pcf)	Effective Friction Angle (deg)	Soil Modulus Constant (k) (pci)	Unconfined Comp. Strength (psi)	m_i	Poisson's Ratio	Geologic Strength Index (GSI)	Rock Mass Modulus (psi)
	Top	Bot.									
Structural Fill	0	20	SM/ML	125	30	48	-	-	-	-	-
Channel Deposits	20	24	SM	63	35	86	-	-	-	-	-
	24	26	ML	53	29	24	-	-	-	-	-
	26	43	SM	63	37	108	-	-	-	-	-
Till	43+	-	SM	78	43	192	-	-	-	-	-

Note:

- 1) Use of the Reese (Sand) constitutive model is recommended for each sublayer.

Table 7 – Recommended Drilled Shaft Axial Design Parameters (South Side–BH 801)

Sublayer Description	Sublayer Depth (ft)		Material USCS Description	Allowable Skin Friction (Comp.) (psf)	Allowable Skin Friction (Uplift) (psf)	Allowable End Bearing (psf)
	Top	Bottom				
Structural Fill	0	5	SM/ML	IGNORE		
	5	7	SM/ML	250	210	-
Channel Deposits	7	11	SM	490	400	-
	11	13	SM	1,450	1,200	20,000
Till	13	18	SM	1,750	1,450	20,000
	18+	-	SM	1,900	1,575	20,000

Notes:

- 1) Approximately 5 feet of fill soil will be added in the south portion of the bus structure (approximate area of BH 801). Including the recommended 2 feet of undercut and replace of existing topsoil/loose material, the total new fill depth was estimated to be about 7 feet.
- 2) Ultimate skin friction and end bearing capacities determined per methods prescribed in FHWA GEC 10: *Drilled Shaft: Construction Procedures and LRFD Design Methods* (2010).
- 3) Allowable capacities for skin (comp), skin (uplift), and end-bearing determined by applying a factor of safety of 2.5, 3.0 and 3.0, respectively.

Table 8 – Recommended Drilled Shaft Lateral (LPILE) Design Parameters (South Side–BH 801)

Sublayer Description	Sublayer Depth (ft)		Material USCS Description	Effective Unit Weight (pcf)	Effective Friction Angle (deg)	Soil Modulus Constant (k) (pci)	Unconfined Comp. Strength (psi)	m_i	Poisson's Ratio	Geologic Strength Index (GSI)	Rock Mass Modulus (psi)
	Top	Bot.									
Structural Fill	0	7	SM/ML	125	30	48	-	-	-	-	-
Channel Deposits	7	11	SM	120	33	102	-	-	-	-	-
	11	13	SM	135	42	310	-	-	-	-	-
Till	13	18	SM	140	43	338	-	-	-	-	-
	18+	-	SM	78	43	192	-	-	-	-	-

Note:

- 2) Use of the Reese (Sand) constitutive model is recommended for each sublayer.

Additional Drilled Shaft Design Recommendations

- Due to strain incompatibilities, drilled shaft design based entirely on skin friction or end bearing is recommended.
- A minimum shaft length (below the ground surface) of 20 feet is recommended to adequately resist uplift created due to adfreeze forces within the frost zone.
- A minimum shaft diameter of 30 inches is recommended.
- Should multiple shaft foundations be required, the minimum center-to-center spacing should be three (3) times the shaft diameter.
- Based on groundwater depths encountered and reported in QS test borings, we anticipate that groundwater will exist near the bottom of the new fill and existing ground surface interface.

6.7.3 Drilled Shaft Construction

Temporary wall support through the use of temporary casing may be required to prevent loss of sidewall support. The use of slurry for side wall support is not recommended. We recommend that the proposed drilled shaft construction equipment, methods, procedures, and planned quality control testing and inspection during construction be reviewed by a qualified geotechnical engineer prior to the start of shaft construction.

The ability of a drilled shaft to provide the end bearing resistances and associated settlements described herein is directly related to the construction methods and procedures used to provide a clean shaft bottom condition. Drilled shaft excavation and clean out methods shall result in bases/bottoms that are free of loose, soft, or disturbed material. Cleaning of the shaft excavations shall result in a maximum of 1 inch of loose, soft, or disturbed material on the shaft bottom at the time of concrete placement. Should concrete placement within the shaft not occur immediately following excavation and clean out, the condition of the excavation bottom shall be verified to confirm that no more than 1 inch of loose, soft, or disturbed material is present in the bottom of the excavation prior to concrete placement. Inspection of the installation methods and materials by an individual qualified and experienced in drilled shaft construction is recommended.

Placement of concrete via free-fall methods is acceptable assuming placement is directed vertically downward avoiding impact with reinforcement and that the height of groundwater on the bottom of the shaft does not exceed 3 inches at the time of placement. Should the level of water at the bottom of the excavation not be maintained at less than 3 inches, concrete placement via tremmie methods will be required.

6.8 SHALLOW FOUNDATION DESIGN AND CONSTRUCTION

6.8.1 Transformer Pad

Where planned (vicinity of BH 803), we anticipate 18 to 20 feet of fill will be required to develop the planned finished grade in the area of the transformer pad. Therefore, we expect the transformer pad to be supported on newly placed, controlled structural fill. The source of the new fill was unknown at the time this report was prepared; however, testing on materials from other transition/substation locations indicate that the fill material will likely consist of sandy silt, silty sand, and/or sand with a USCS classification of ML, SM, or SP. Support on these materials

placed in accordance with recommendations provided herein is acceptable if the transformer pad is not susceptible to frost action. If the transformer equipment and ancillary connections are susceptible to vertical movement resulting from frost action, then the material 4 feet below the transformer pad (and to a distance of 2 feet laterally beyond the pad edges) should be removed and replaced with a clean sand or gravel meeting the requirements of NHDOT Standard Specification Section 209.

Controlled structural fill material placed in accordance with recommendations provided in herein will provide suitable support for transformer pads designed to impart an approximate uniform bearing pressure of up to 500 pounds per square foot (psf). The soils encountered at the site should react elastically to structure loads; settlements induced by foundation loads should occur soon after the load is applied. Maximum total settlement induced by the transformer slab loads are anticipated to be about ½ inch.

6.8.2 Single-Story Equipment Structures

Should single-story buildings be required to house equipment operated at the transition station, they may be supported on shallow foundations bearing on approved channel deposit silty sands or newly placed controlled structural fill material placed in accordance with recommendations provided herein. We recommend that building foundations be designed for a maximum allowable bearing pressure of 3,000 psf for foundations bearing on approved subgrades. To reduce the possibility of localized shear failures, spread and strip footings should be a minimum of 3 feet and 1.5 feet wide, respectively.

For single-story structures designed for a maximum allowable bearing pressure of 3,000 psf on approved channel deposit soils or newly controlled structural fill, total settlements of about ½ inch with differential settlements of 1/2 to 2/3 the total estimated settlement are anticipated. As stated previously, settlements induced by foundation loads should occur soon after the load is applied.

6.8.3 Shrink-Swell and Frost Depth Considerations

Based on the soil materials observed in the test boring samples and the laboratory test results, the on-site soils will generally have a low shrink-swell potential. Accordingly, we do not recommend any foundation design modifications relative to the potential for shrink-swell soils.

Frost depth should be anticipated to be 4 feet below the lowest adjacent grade. Therefore, utilities that are susceptible to frost action and building foundations should bear a minimum of 4 feet below adjacent grades.

6.8.4 Shallow Foundation Construction

All foundation subgrades should be observed, evaluated, and verified for the design bearing pressure by a representative of the geotechnical engineer after excavation and prior to reinforcement steel placement. If low density/consistency soils are encountered at the foundation subgrade during construction, localized undercutting and/or in-place stabilization of foundation subgrades may be required. The actual need for, and extent of, undercutting or in-place stabilization should be based on field observations made by a representative of the geotechnical engineer at the time of construction.

Excavations for footings should be made in such a way as to provide bearing surfaces that are firm and free of loose, soft, wet, or otherwise disturbed soils. Foundation concrete should not be placed on frozen or saturated subgrades. If such materials are allowed to remain below foundations, settlements will increase. Foundation excavations should be concreted as soon as practical after they are excavated. If an excavation is left open for an extended period, a thin mat of lean concrete should be placed over the bottom of the excavation to minimize damage to the bearing surface from weather or construction activities. Water should not be allowed to pond in any excavation.

6.9 MECHANICALLY STABILIZED EARTH RETAINING WALLS

Mechanically Stabilized Earth (MSE) walls typically consist of alternating horizontal layers of tensile reinforcement and compacted fill material creating a “block” of stabilized earth. Several types of reinforcement have been historically used in MSE wall construction; however, synthetically manufactured geogrids are common in current practice. The reinforcement is commonly fixed to a modular block facing or other type of permanent wall facing.

Assuming a maximum height of about 20 feet, we anticipate that the walls will exert a maximum bearing pressure of approximately 2500 psf on the underlying subgrade. Considering the conditions encountered in the test borings, subgrades consisting of controlled structural fill and/or undisturbed channel deposits prepared in accordance with recommendations presented herein will provide suitable MSE wall bearing support (with an FoS of 3 against bearing failure). We estimate that total settlement of the underlying subgrade along the MSE wall will be less than 1 inch, with differential settlements of less than ½ inch in 100 feet of wall.

As stated in Section 6.2 (Site Preparation), we recommend that the top 2 feet of existing material (topsoil and loose soil) be removed and replaced with controlled structural fill across the project site and prior to commencement of MSE wall construction. Structural fill (soil and/or crushed stone) used within and behind the reinforced zone of the wall shall be placed in horizontal lifts with a maximum height of 8 inches loose measure; the fill shall be compacted to a minimum of 95 percent of the maximum dry density and within two (2) percentage points of the optimum moisture content determined by the modified Proctor density test (ASTM D1557). Heavy equipment should not be operated within 3 feet of the MSE wall facing. Lighter compaction equipment and thinner lifts (i.e. 3 to 4 inches thick) shall be used adjacent to the wall face to prevent buildup of high lateral pressures on the wall facing material.

The source of backfill material planned for use in the reinforced zone of the MSE walls was not known at the time this report was prepared. We recommend that a granular fill material conforming to the requirements presented in Table 9 be used within the reinforced zone of the MSE walls. The granular fill should be well graded in accordance with the UCSC in ASTM D2487 and free of organic matter and deleterious substances/materials. A geotechnical engineer experienced in MSE wall design should review and approve the material planned for use in the reinforced zone. Following review and approval of the reinforced zone backfill material, appropriate strength properties can be selected for design of the wall's reinforced zone.

Depending on the source and type of granular material selected, additional laboratory testing (such as direct shear testing – ASTM D3080 and other physical property testing) may be required to establish the appropriate strength properties for use in design. Additional recommendations for MSE wall design and construction are provided following Table 9.

Table 9 – MSE Wall Granular Reinforced Fill Requirements

Gradation	U.S. Sieve Size	Percent Passing
	2 in (50.8 mm)	100
	No. 40 (0.425 mm)	0 – 60
	No. 200 (0.075 mm)	0 – 15
Plasticity Index (PI)	PI ≤ 6	
Electrochemical	Property	Criteria
	Resistivity	>3000 ohm-cm
	pH	> 5 and <10
	Chlorides	< 100 ppm
	Sulfates	< 200 ppm

Additional MSE Wall Design and Construction Recommendations

- The following strength and unit weight properties of the retained backfill (i.e. unreinforced fill material behind the reinforced zone) shall be assumed: friction angle = 30 degrees; and effective unit weight = 125 pcf.
- For design calculations of resistance to wall sliding, a value of 0.58 should be used as the ultimate coefficient of friction at the interface of the reinforced zone and the underlying subgrade.
- Backfill material used to construct the reinforced zone of the wall shall extend a minimum of 1 foot beyond the reinforcement length.
- A functioning drainage system shall be installed to prevent buildup of hydrostatic pressures within the wall system.
- Hydrostatic pressures should be incorporated into the wall design where an adjacent detention basin is planned. The water level assumed in the design should correspond to the maximum level for which the basin is design to hold.
- The reinforcing within the reinforced zone shall not be penetrated by foundations and/or utilities.
- Design and construction of MSE walls shall be in general accordance with recommendations provided in *FHWA-NHI-10-024: Design and Construction of Mechanically Stabilized Earth Walls and Reinforced Slopes* (2009).

6.10 EARTHQUAKE CONSIDERATIONS

6.10.1 Seismic Site Class Definition

The following recommendations are based Chapter 20 of the ASCE 7-10. ASCE 7-10 provides a methodology for interpretation of SPT resistance values (N-values) to determine a Site Class Definition; however, this method requires averaging N-values over the top 100 feet of the subsurface profile. We note that the test borings for this project were extended to a maximum depth of about 50 feet below existing site grades.

The available subsurface data from our exploration indicates an N-value range of about 3 to greater than 100 bpf within the upper 50 feet below existing site grades. In general accordance with ASCE 7-10 and considering the boring data and planned grading, we recommend that a Site Class Definition “D” be used for design.

6.10.2 Liquefaction

Liquefaction of saturated, loose to medium dense, fine grained sands, and silty sands is not anticipated to be a design concern for the Transition Station #5 site.

6.11 KARST GEOLOGY

Karst topography occurs from the dissolution of soluble bedrock (such as limestone, dolomite, or gypsum) which creates karst features (sinkholes and caves) within the subsurface. Karst conditions were not encountered during the exploration reported herein. Karst features/conditions are not anticipated to be a design or construction concern for the Transition Station #5 site.

6.12 CORROSION CONSIDERATIONS

A bulk sample obtained in boring INF 802 was tested in the laboratory to determine pH, water soluble sulfate and chloride, and resistivity. The results of the lab tests are summarized in Table 7 below.

Table 7 – Laboratory Corrosivity Test Results

Boring No.	Sample Type & Depth (ft)	pH	Chloride (ug/g)	Sulfate (ug/g)	Electrical Resistivity (ohm-cm)
INF 802	BULK (1 - 6)	5.9	140	< 6.3	1,500

Based on the results of the laboratory tests on material collected from INF 802, the soils at the Transition Station #5 site should be considered as having “aggressive” corrosion potential. As a result, we recommend that cut material originating from the INF 802 area should be used in locations onsite or on the transition corridor where underground utilities, foundations, and walls are not planned. New fill used to develop the transition station finished grades (originating offsite) should be tested prior to placement to confirm that they exhibit “non-aggressive” corrosion potential as defined by FWHA.

7.0 LIMITATIONS

This report has been prepared for the exclusive use of PAR Electrical Contractors, Inc. or their agent, for specific application to the Transition Station #5 project near Bethlehem, New Hampshire. The conclusions and recommendations presented herein are based on design information furnished to us, the data obtained from the previously described subsurface exploration programs, and generally accepted geotechnical engineering practice. The conclusions and recommendations do not reflect variations in subsurface conditions which could exist intermediate of the boring locations or in unexplored areas of the site. Should such variations become apparent during construction, it will be necessary to re-evaluate our conclusions and recommendations based upon on-site observations of the conditions.

The soil and rock descriptions/classifications and the strata breaks shown on the boring logs attached to this report are based primarily on visual observation and should be considered approximate. Regardless of the thoroughness of a subsurface exploration, there is the possibility that conditions between borings will differ from those at the boring locations, that conditions are not as anticipated by the designers, or that the construction process has altered the soil conditions. Therefore, experienced geotechnical engineers or engineering geologists should evaluate earthwork and foundation construction to verify that the conditions anticipated in design actually exist.

In the event that changes are made in the design or location of the project, the recommendations presented in the report shall not be considered valid unless the changes are reviewed by Quanta Subsurface and conclusions of this report modified and/or verified in writing. If this report is copied or transmitted to a third party, it must be copied or transmitted in its entirety, including text, attachments, and enclosures. Interpretations based on only a part of this report may not be valid.

8.0 REFERENCES

- American Society of Civil Engineers: *Minimum Design Loads for Buildings and Other Structures*; ASCE/SEI 7-10; 2010.
- New Hampshire Department of Environmental Services: *New Hampshire Stormwater Manual; Post-Construction Best Management Practices Selection & Design*; Volume 2; December 2008.
- New Hampshire Department of Resources and Economic Development: *Surficial Geologic Map of the Bethlehem West 7.5' Quadraingle, Coos and Grafton Counties, New Hampshire*, 2000.
- New Hampshire Department of Transportation: *Standard Specifications for Road and Bridge Construction*; Section 209 Granular Backfill; 2016
- Terracon Consultants' Inc.; *Report of Expected Geotechnical Conditions*: Northern Pass Project; July 10, 2015.
- U.S Department of Transportation Federal Highway Administration (FHWA): *Design and Construction of Mechanically Stabilized Earth Walls and Reinforced Soil Slopes – Volumes I and II*; FHWA-NHI-10-024; November 2010.

- U.S Department of Transportation Federal Highway Administration (FHWA): *Drilled Shafts: Construction Procedures and LRFD Design Methods*; FHWA-NHI-10-016; May 2010.
- McGregor, J and J.M. Duncan; Virginia Polytechnic Institute and State University - Center for Geotechnical Practice and Research: *Performance and Use of the Standard Penetration Test in Geotechnical Engineering Practice*; October 1998.

Figures






Figure 1
Site Vicinity Map



Base Map: Google Earth, 2016.

Figure 2
Site Location Map



Base Map: Transition Station #5: NPTT804-C101-Geotech.dwg




-  Quanta Subsurface Boring Location, August/September 2016
-  Quanta Subsurface Infiltration Location, August/September 2016

Figure 3
QS Boring Location Plan



Base Map: New Hampshire Department of Resources and Economic Development, *Surficial Geologic Map of the Bethlehem West 7.5' Quadrangle, Coos and Grafton Counties, New Hampshire (2000)*

Legend:

af	Artificial Fill	Qst	Stream-Terrace Deposits
Qal	Stream Alluvium	Qt	Till
Qs	Swamp Deposit		

Temporary Meltwater Flow Channel
Showing Direction of Flow

Figure 4
Surficial Geologic Map

Appendix A Boring Logs



Quanta Subsurface

BORING NUMBER BH 801

PAGE 1 OF 3

CLIENT PAR Electrical ContractorsPROJECT NAME Northern Pass TL - Transition Station #5PROJECT NUMBER 16004PROJECT LOCATION Bethlehem, New HampshireDATE STARTED 11/18/16COMPLETED 11/18/16GROUND ELEVATION 1101.1 ftHOLE SIZE 6"DRILLING CONTRACTOR SW ColeLATITUDE 44.28227222LONGITUDE -71.72596944DRILLING METHOD Solid Stem Auger/Wet RotaryDRILLING EQUIPMENT CME 850SPT HAMMER AutomaticLOGGED BY S. LaingCHECKED BY J.T. McGinnis

GROUND WATER LEVEL:

NOTES

▽ AT TIME OF DRILLING 13.0ft / Elev 1088.1ft

GEOTECH BH COLUMNS - DF STD US LAB E-M.GDT - 12/22/16 09:31 - C:\USERS\JUNION\DOCUMENTS\16004\16004 NORTHERN PASS TRANSITION 5.GPJ

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)	REMARKS
									LIQUID LIMIT	PLASTICITY INDEX		
	0											
1100		SPT 1	54	1-2-1-9 (3)			TOPSOIL: SILT with sand (ML), trace organics, moderate brown, moist, soft, fine grained sand					
		SPT 2	63	7-7-8-9 (15)			CHANNEL DEPOSITS: Silty SAND with gravel (SM), moderate yellowish brown, moist, medium dense, fine to coarse grained gravel, fine to medium grained sand, subangular					
5		SPT 3	67	4-7-15-23 (22)			- very dense from 6 to 8 feet	5.2			43.7	
1095		SPT 4	71	24-28-39- 37 (67)			TILL: Silty SAND with gravel (SM), moderate yellowish brown, moist, medium dense, fine to coarse grained gravel, fine to medium grained sand, subangular					
		SPT 5	73	50/6"			- boulders and cobbles were encountered from 8 to 10 feet					Boulder encountered at 8 feet. Boring offset 2 feet and continued drilling using wet rotary (roller bit) below 10 feet.
10												
1090												
15												
1085		SPT 6	71	18-36-42- 34 (78)			- wet from 15 to 23 feet	10.7				
20		SPT 7	67	50/5"			- cobbles were encountered from 20 to 20.4 feet					

(Continued Next Page)



Quanta Subsurface

BORING NUMBER BH 801

PAGE 2 OF 3





CLIENT PAR Electrical Contractors

PROJECT NAME Northern Pass TL - Transition Station #5

PROJECT NUMBER 16004

PROJECT LOCATION Bethlehem, New Hampshire

GEOTECH BH COLUMNS - DF STD US LAB E-M.GDT - 12/22/16 09:31 - C:\USERS\MR\UNION\DOCUMENTS\16004\16004 NORTHERN PASS TRANSITION 5.GPJ

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)	REMARKS
									LIQUID LIMIT	PLASTICITY INDEX		
1080							TILL: Silty SAND with gravel (SM), moderate yellowish brown, moist, medium dense, fine to coarse grained gravel, fine to medium grained sand, subangular (<i>continued</i>)					
	25						Silty SAND (SM), trace fine gravel, light olive gray, moist, very dense, fine grained sand, subangular					
1075		 SPT 8	92	36-50/6"								
	30						Silty SAND with gravel (SM), light olive gray, moist, very dense, fine to coarse grained gravel, fine grained sand, subangular					
		 SPT 9	100	50/4"			- a boulder was encountered from 30.5 to 34.5 feet					
1070												
	35											
		 SPT 10	68	50/6"								
1065												
	40											
		 SPT 11	95	25-42-50/6"								
1060												
	45						Silty SAND (SM), little fine gravel, light olive gray, moist, very dense, fine grained sand, subangular					

(Continued Next Page)



Quanta Subsurface

BORING NUMBER BH 801

PAGE 3 OF 3

CLIENT PAR Electrical Contractors

PROJECT NAME Northern Pass TL - Transition Station #5

PROJECT NUMBER 16004

PROJECT LOCATION Bethlehem, New Hampshire

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)	REMARKS
									LIQUID LIMIT	PLASTICITY INDEX		
1055	45	SPT 12	84	21-42- 50/6"			Silty SAND (SM), little fine gravel, light olive gray, moist, very dense, fine grained sand, subangular <i>(continued)</i>					
							Silty SAND with gravel (SM), light olive gray, moist, very dense, fine to coarse grained gravel, fine grained sand, subangular					
	50	SPT 13	55	33-50/5"								

Bottom of Borehole at 50.9 feet



Quanta Subsurface

BORING NUMBER BH 802

PAGE 1 OF 2

CLIENT PAR Electrical ContractorsPROJECT NAME Northern Pass TL - Transition Station #5PROJECT NUMBER 16004PROJECT LOCATION Bethlehem, New HampshireDATE STARTED 11/18/16COMPLETED 11/18/16GROUND ELEVATION 1100.0 ftHOLE SIZE 6"DRILLING CONTRACTOR SW ColeLATITUDE 44.28209722LONGITUDE -71.72533056DRILLING METHOD Solid Stem Auger/Wet RotaryDRILLING EQUIPMENT CME 850SPT HAMMER AutomaticLOGGED BY S. LaingCHECKED BY J.T. McGinnis

GROUND WATER LEVEL:

NOTES

▽ AT TIME OF DRILLING Not encountered

GEOTECH BH COLUMNS - DF STD US LAB E-M GDT - 12/22/16 09:31 - C:\USERS\IMR\UNION\DOCUMENTS\16004\16004 NORTHERN PASS TRANSITION 5.GPJ

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)	REMARKS
									LIQUID LIMIT	PLASTICITY INDEX		
1100	0						TOPSOIL: Sandy SILT (ML), trace organics, moderate brown, moist, soft, fine grained sand					
		SPT 1	50	1-1-3-13 (4)								
		SPT 2	63	9-10-11-21 (21)			CHANNEL DEPOSITS: Silty SAND with gravel (SM), pale yellowish brown, moist, medium dense, fine to coarse grained gravel, fine to medium grained sand, subangular	6.9			26.4	
1095	5	SPT 3	0	4-6-12-15 (18)				7.5				
		SPT 4	0	17-50/5"			TILL: Silty SAND with gravel (SM), pale yellowish brown, moist, very dense, fine to coarse grained gravel, fine to medium grained sand, subangular, -zones of oxidation, light olive gray from 28 to 40.8 feet					
		SPT 5	0	21-50/5"								
1090	10											
							- wet from 13 to 40.8 feet					
1085	15	SPT 6	60	44-50/4"								
							- dusky yellow from 18 to 28 feet					
1080	20	SPT 7	85	50/6"								

(Continued Next Page)



Quanta Subsurface

BORING NUMBER BH 802





PAGE 2 OF 2

CLIENT PAR Electrical Contractors

PROJECT NAME Northern Pass TL - Transition Station #5

PROJECT NUMBER 16004

PROJECT LOCATION Bethlehem, New Hampshire

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)	REMARKS
									LIQUID LIMIT	PLASTICITY INDEX		
1075	25	 SPT 8	73	29-50/5"			TILL: Silty SAND with gravel (SM), pale yellowish brown, wet, very dense, fine to coarse grained gravel, fine to medium grained sand, subangular, - zones of oxidation, light olive gray from 28 to 40.8 feet (continued) - light olive gray from 28 to 40.8 feet					
1070	30	 SPT 9	41	16-42- 50/5"								
1065	35	 SPT 10	0	27-50/3"								
1060	40	 SPT 11	80	45-50/4"								

Bottom of Borehole at 40.8 feet

GEOTECH BH COLUMNS - DF STD US LAB E-M.GDT - 12/22/16 09:31 - C:\USERS\IMR\UNION\DOCUMENTS\16004\16004 NORTHERN PASS TRANSITION 5.GPJ



Quanta Subsurface

BORING NUMBER BH 803

PAGE 1 OF 3

CLIENT PAR Electrical ContractorsPROJECT NAME Northern Pass TL - Transition Station #5PROJECT NUMBER 16004PROJECT LOCATION Bethlehem, New HampshireDATE STARTED 11/18/16COMPLETED 11/18/16GROUND ELEVATION 1083.2 ftHOLE SIZE 6"DRILLING CONTRACTOR SW ColeLATITUDE 44.28241389LONGITUDE -71.72576111DRILLING METHOD Solid Stem Auger/Wet RotaryDRILLING EQUIPMENT CME 850SPT HAMMER AutomaticLOGGED BY S. LaingCHECKED BY J.T. McGinnis

GROUND WATER LEVEL:

NOTES Boring performed within a wetland area.▽ AT TIME OF DRILLING 0.0ft / Elev 1083.2ft

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)	REMARKS
									LIQUID LIMIT	PLASTICITY INDEX		
	0						▽					
		SPT 1	4	0-0-1-1 (1)			TOPSOIL: Sandy SILT (ML), moderate brown, wet, soft, fine grained sand					
1080		SPT 2	63	9-15-13-11 (28)			CHANNEL DEPOSITS: Silty SAND (SM), moderate yellowish brown, wet, medium dense, fine to medium grained sand, subangular	12.7				
5		SPT 3	63	11-10-9-6 (19)			Sandy SILT (ML), little fine to coarse gravel, moderate yellowish brown, wet, stiff, fine grained sand, subangular					
		SPT 4	58	7-7-8-10 (15)				15.9			58.8	
1075		SPT 5	50	12-16-19-19 (35)			Silty SAND (SM), little fine to coarse gravel, moderate yellowish brown, dense, fine grained sand, subangular					
10												
1070							- boulders were encountered from 13 to 19 feet					
15												
1065												
20							TILL: Silty SAND (SM), little fine to coarse gravel, light olive gray, wet, very dense, fine grained sand, subangular					

Wet rotary (roller bit) drilling method used below 10 feet. Roller bit refusal was encountered at 17 feet on a boulder; rock coring used from 17 to 22 feet.

(Continued Next Page)



Quanta Subsurface

BORING NUMBER BH 803

PAGE 2 OF 3










CLIENT PAR Electrical Contractors

PROJECT NAME Northern Pass TL - Transition Station #5

PROJECT NUMBER 16004

PROJECT LOCATION Bethlehem, New Hampshire

GEOTECH BH COLUMNS - DF STD US LAB E-M.GDT - 12/22/16 09:31 - C:\USERS\IMR\UNION\DOCUMENTS\16004\16004 NORTHERN PASS TRANSITION 5.GPJ

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)	REMARKS
									LIQUID LIMIT	PLASTICITY INDEX		
1060	25	 SPT 6	59	26-50/6"			TILL: Silty SAND (SM), little fine to coarse gravel, light olive gray, wet, very dense, fine grained sand, subangular (continued)					
1055	30	 SPT 7	67	24-50/6"								
1050	35	 SPT 8	79	12-18-28- 43 (46)								
1045	40	 SPT 9	73	18-42- 50/6"								
1040	45											

(Continued Next Page)



Quanta Subsurface

BORING NUMBER BH 803

PAGE 3 OF 3

CLIENT PAR Electrical Contractors

PROJECT NAME Northern Pass TL - Transition Station #5

PROJECT NUMBER 16004

PROJECT LOCATION Bethlehem, New Hampshire

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)	REMARKS
									LIQUID LIMIT	PLASTICITY INDEX		
45		SPT 10	82	30-50/5"			TILL: Silty SAND (SM), little fine to coarse gravel, light olive gray, wet, very dense, fine grained sand, subangular (<i>continued</i>)					
1035												
50		SPT 11	63	50/5"								

Bottom of Borehole at 50.4 feet



Quanta Subsurface

BORING NUMBER BH 804

PAGE 1 OF 3

CLIENT PAR Electrical Contractors	PROJECT NAME Northern Pass TL - Transition Station #5
PROJECT NUMBER 16004	PROJECT LOCATION Bethlehem, New Hampshire
DATE STARTED 11/18/16	COMPLETED 11/18/16
GROUND ELEVATION 1079.1 ft	HOLE SIZE 6"
DRILLING CONTRACTOR SW Cole	LATITUDE 44.28261667
DRILLING METHOD Solid Stem Auger/Wet Rotary	LONGITUDE -71.72582778
DRILLING EQUIPMENT CME 850	SPT HAMMER Automatic
LOGGED BY S. Laing	CHECKED BY J.T. McGinnis
GROUND WATER LEVEL:	
▽ AT TIME OF DRILLING 1.5ft / Elev 1077.6ft	

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)
									LIQUID LIMIT	PLASTICITY INDEX	
	0										
		SPT 1	17	1-1-10-4 (11)			TOPSOIL: Sandy SILT (ML), little organics, moderate brown, wet, medium stiff, fine grained sand				
		SPT 2	0	11-20-10-8 (30)			CHANNEL DEPOSITS: Silty SAND with gravel (SM), dark yellowish orange, wet, medium dense, fine to coarse grained gravel, fine grained sand				
1075											
	5	SPT 3	75	4-5-7-11 (12)			SILT (ML), little fine sand, dark yellowish orange, wet, stiff	27.3			94.6
		SPT 4	63	15-22-34- 27 (56)			Silty SAND with gravel (SM), moderate yellowish brown, wet, very dense, fine to coarse grained gravel, fine grained sand				
1070		SPT 5	100	13-39- 50/6"			TILL: Silty SAND with gravel (SM), light olive gray, wet, very dense, fine to coarse grained gravel, fine grained sand				
	10										
1065											
	15	SPT 6	85	50/6"							
1060											
	20	SPT	84	25-41-							

GEOTECH BH COLUMNS - DF STD US LAB E-M.GDT - 12/22/16 09:31 - C:\USERS\IMR\UNION\DOCUMENTS\16004\16004 NORTHERN PASS TRANSITION 5.GPJ

(Continued Next Page)



Quanta Subsurface

BORING NUMBER BH 804

PAGE 2 OF 3

CLIENT PAR Electrical Contractors

PROJECT NAME Northern Pass TL - Transition Station #5

PROJECT NUMBER 16004

PROJECT LOCATION Bethlehem, New Hampshire

GEOTECH BH COLUMNS - DF STD US LAB E-M.GDT - 12/22/16 09:31 - C:\USERS\MR\UNION\DOCUMENTS\16004\16004 NORTHERN PASS TRANSITION 5.GPJ

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)
									LIQUID LIMIT	PLASTICITY INDEX	
		7		50/6"			TILL: Silty SAND with gravel (SM), light olive gray, wet, very dense, fine to coarse grained gravel, fine grained sand (continued)				
1055	25	SPT 8	92	14-21-24-30 (45)							
1050	30	SPT 9	83	13-20-40-32 (60)							
1045	35	SPT 10	100	50/5"							
1040	40	SPT 11	75	50/4"			Poorly Graded SAND with silt and gravel (SP-SM), light olive gray, wet, very dense, fine to coarse grained gravel, fine to medium grained sand				
1035	45										

(Continued Next Page)



Quanta Subsurface

BORING NUMBER BH 804

PAGE 3 OF 3

CLIENT PAR Electrical Contractors

PROJECT NAME Northern Pass TL - Transition Station #5

PROJECT NUMBER 16004

PROJECT LOCATION Bethlehem, New Hampshire

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)
									LIQUID LIMIT	PLASTICITY INDEX	
45		SPT 12	73	43-50- 50/3"			Poorly Graded SAND with silt and gravel (SP-SM), light olive gray, wet, very dense, fine to coarse grained gravel, fine to medium grained sand (continued)				
1030											
50		SPT 13	13	18-31-40- 46 (71)							

Bottom of Borehole at 52.0 feet



Quanta Subsurface

BORING NUMBER BH 805

PAGE 1 OF 3

CLIENT PAR Electrical ContractorsPROJECT NAME Northern Pass TL - Transition Station #5PROJECT NUMBER 16004PROJECT LOCATION Bethlehem, New HampshireDATE STARTED 11/18/16COMPLETED 11/18/16GROUND ELEVATION 1082.5 ftHOLE SIZE 6"DRILLING CONTRACTOR SW ColeLATITUDE 44.28248333LONGITUDE -71.72518611DRILLING METHOD Solid Stem Auger/Wet RotaryDRILLING EQUIPMENT CME 850SPT HAMMER AutomaticLOGGED BY S. LaingCHECKED BY J.T. McGinnis

GROUND WATER LEVEL:

NOTES

▽ AT TIME OF DRILLING 0.5ft / Elev 1082.0ft

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)	REMARKS
									LIQUID LIMIT	PLASTICITY INDEX		
	0											
		SPT 1	25	6-2-3-4 (5)			TOPSOIL: SILT with sand (ML), little organics, moderate brown, wet, medium stiff, fine grained sand					
1080		SPT 2	46	8-10-16-20 (26)			CHANNEL DEPOSITS: Poorly Graded SAND with silt and gravel (SP-SM), dark yellowish orange, wet, loose to medium dense, fine grained gravel, fine grained sand, subangular	15.3				
	5	SPT 3	54	12-12-12-11 (24)			Silty SAND with gravel (SM), dusky yellow, wet, medium dense to dense, fine to coarse grained gravel, fine grained sand, subrounded					
1075		SPT 4	58	14-16-19-21 (35)				10.1			45.8	
	10	SPT 5	71	23-24-24-39 (48)								
1070												
	15	SPT 6	13	23-41-50/4"			TILL: Silty SAND with gravel (SM), dusky yellow, wet, very dense, fine to coarse grained gravel, fine grained sand, subrounded					
							- cobbles were encountered from 16 to 19 feet					
1065												
	20						- a boulder was encountered from 19 to 21 feet					

Wet rotary (roller bit) drilling method used below 10 feet. Roller bit refusal was encountered at 17 feet on a boulder; rock coring used from 19 to 24 feet.

(Continued Next Page)



Quanta Subsurface

BORING NUMBER BH 805

PAGE 2 OF 3





CLIENT PAR Electrical Contractors

PROJECT NAME Northern Pass TL - Transition Station #5

PROJECT NUMBER 16004

PROJECT LOCATION Bethlehem, New Hampshire

GEOTECH BH COLUMNS - DF STD US LAB E-M.GDT - 12/22/16 09:31 - C:\USERS\JUNION\DOCUMENTS\16004\16004 NORTHERN PASS TRANSITION 5.GPJ

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)	REMARKS
									LIQUID LIMIT	PLASTICITY INDEX		
1060							TILL: Silty SAND with gravel (SM), dusky yellow, wet, very dense, fine to coarse grained gravel, fine grained sand, subrounded (<i>continued</i>)					
	25	 SPT 7	67	12-23-37-40 (60)			Silty SAND with gravel (SM), pale yellowish brown and light olive gray, wet, very dense, fine to coarse grained gravel, fine to medium grained sand, subangular	9.7				
1055												
	30	 SPT 8	88	13-28-35-36 (63)								
1050												
	35	 SPT 9	55	37-50/5"								
1045												
	40	 SPT 10	89	23-31-50 (81)								
1040												
	45											

(Continued Next Page)



Quanta Subsurface

BORING NUMBER BH 805

PAGE 3 OF 3

CLIENT PAR Electrical Contractors

PROJECT NAME Northern Pass TL - Transition Station #5

PROJECT NUMBER 16004

PROJECT LOCATION Bethlehem, New Hampshire

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)	REMARKS
									LIQUID LIMIT	PLASTICITY INDEX		
45		SPT 11	55	27-50/5"			Silty SAND with gravel (SM), pale yellowish brown and light olive gray, wet, very dense, fine to coarse grained gravel, fine to medium grained sand, subangular (continued)					
1035												
50		SPT 12	34	32-50/6"								

Bottom of Borehole at 51.0 feet



Quanta Subsurface

BORING NUMBER BH 806

PAGE 1 OF 3

CLIENT PAR Electrical ContractorsPROJECT NAME Northern Pass TL - Transition Station #5PROJECT NUMBER 16004PROJECT LOCATION Bethlehem, New HampshireDATE STARTED 11/18/16COMPLETED 11/18/16GROUND ELEVATION 1077.5 ftHOLE SIZE 6"DRILLING CONTRACTOR SW ColeLATITUDE 44.28264722LONGITUDE -71.72545833DRILLING METHOD Solid Stem Auger/Wet RotaryDRILLING EQUIPMENT CME 850SPT HAMMER AutomaticLOGGED BY S. LaingCHECKED BY J.T. McGinnis

GROUND WATER LEVEL:

NOTES

AT END OF DRILLING Not Encountered

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)
									LIQUID LIMIT	PLASTICITY INDEX	
	0						TOPSOIL: SILT with sand (ML), trace organics, moderate brown, moist, soft, fine grained sand				
		SPT 1	58	1-2-3-28 (5)			CHANNEL DEPOSITS: Silty SAND with gravel (SM), moderate yellowish brown, moist to wet, dense, fine to coarse grained gravel, fine grained sand, subrounded, with cobbles	10.0			37.9
	1075	SPT 2	67	11-20-32- 19 (52)			- no cobbles encountered from 3.5 to 6 feet				
	5	SPT 3	100	10-17-15- 17 (32)			- very dense from 6 to 18 feet and cobbles from 6 to 13 feet	10.8			
		SPT 4	67	10-39-42- 40 (81)							
	1070	SPT 5	94	11-20-50 (70)							
	10						TILL: Silty SAND with gravel (SM), moderate yellowish brown, moist, dense, fine to coarse grained gravel, fine grained sand, subrounded				
	1065										
	15	SPT 6	75	15-21-19- 26 (40)				10.2			49.9
	1060										
	20	SPT		10-20-22-							

(Continued Next Page)



Quanta Subsurface

BORING NUMBER BH 806

PAGE 2 OF 3

CLIENT PAR Electrical Contractors

PROJECT NAME Northern Pass TL - Transition Station #5

PROJECT NUMBER 16004

PROJECT LOCATION Bethlehem, New Hampshire

GEOTECH BH COLUMNS - DF STD US LAB E-M.GDT - 12/22/16 09:31 - C:\USERS\JUNION\DOCUMENTS\16004\16004 NORTHERN PASS TRANSITION 5.GPJ

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)
									LIQUID LIMIT	PLASTICITY INDEX	
1055		7	75	25 (42)			TILL: Silty SAND with gravel (SM), moderate yellowish brown, moist, dense, fine to coarse grained gravel, fine grained sand, subrounded <i>(continued)</i>	9.6			
							Silty SAND with gravel (SM), light olive gray, wet, very dense, fine grained sand, subrounded				
25		SPT 8	83	12-20-22- 21 (42)							
1050											
30		SPT 9	75	19-28-38- 49 (66)							
1045											
35		SPT 10	79	41-43-32- 50 (75)							
1040											
40		SPT 11	82	30-50/5"							
1035											
45											

(Continued Next Page)



Quanta Subsurface

BORING NUMBER BH 806

PAGE 3 OF 3

CLIENT PAR Electrical Contractors

PROJECT NAME Northern Pass TL - Transition Station #5

PROJECT NUMBER 16004

PROJECT LOCATION Bethlehem, New Hampshire

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)
									LIQUID LIMIT	PLASTICITY INDEX	
45		SPT 12	78	31-39-50 (89)			Silty SAND with gravel (SM), light olive gray, wet, very dense, fine grained sand, subrounded (<i>continued</i>)				
1030											
50		SPT 13	47	20-32- 50/5"							

Bottom of Borehole at 51.4 feet



Quanta Subsurface

BORING NUMBER INF 801

PAGE 1 OF 1

CLIENT PAR Electrical ContractorsPROJECT NAME Northern Pass TL - Transition Station #5PROJECT NUMBER 16004PROJECT LOCATION Bethlehem, New HampshireDATE STARTED 11/18/16COMPLETED 11/18/16GROUND ELEVATION 1080.1 ftHOLE SIZE 6"DRILLING CONTRACTOR SW ColeLATITUDE 44.28257222LONGITUDE -71.72543611DRILLING METHOD Hollow Stem AugerDRILLING EQUIPMENT CME 850SPT HAMMER AutomaticLOGGED BY S. LaingCHECKED BY J.T. McGinnis

GROUND WATER LEVEL:

NOTES

AT END OF DRILLING Not Encountered

GEOTECH BH COLUMNS -DF STD US LAB E-M.GDT - 12/22/16 09:31 - C:\USERS\IMR\UNION\DOCUMENTS\16004\16004 NORTHERN PASS TRANSITION 5.GPJ

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)	REMARKS
									LIQUID LIMIT	PLASTICITY INDEX		
1080	0						TOPSOIL: SILT with sand (ML), trace organics, moderate brown, moist, medium stiff, fine grained sand					Infiltration test casing installed in an adjacent borehole to a depth of approximately 6 feet. The ESHWT is at an approximate depth of 2 feet
		SPT 1	33	1-5-2-2 (7)			CHANNEL DEPOSITS: Silty SAND with gravel (SM), moderate yellowish brown, wet, medium dense, fine grained gravel, fine grained sand, subrounded					
		SPT 2	75	8-8-10-8 (18)			Sandy SILT (ML), trace fine gravel, moderate yellowish brown, wet, very stiff to hard, fine grained sand, subrounded, laminations of sand and silt					
1075	5	SPT 3	83	6-7-30-24 (37)				13.7			65.4	
		SPT 4	63	14-50/2"			Silty SAND with gravel (SM), moderate yellowish brown, very dense, fine grained gravel, fine grained sand, subrounded, with cobbles					
		SPT 5	71	11-15-16-31 (31)			Silty SAND with gravel (SM), moderate yellowish brown, wet, dense, fine grained gravel, fine grained sand, subrounded, laminations of sand and silt					
	10											

Bottom of Borehole at 10.0 feet



Quanta Subsurface

BORING NUMBER INF 802

PAGE 1 OF 1

CLIENT PAR Electrical Contractors

PROJECT NAME Northern Pass TL - Transition Station #5

PROJECT NUMBER 16004

PROJECT LOCATION Bethlehem, New Hampshire

DATE STARTED 11/18/16

COMPLETED 11/18/16

GROUND ELEVATION 1082.0 ft

HOLE SIZE 6"

DRILLING CONTRACTOR SW Cole

LATITUDE 44.28256111

LONGITUDE -71.72530556

DRILLING METHOD Hollow Stem Auger

DRILLING EQUIPMENT CME 850

SPT HAMMER Automatic

LOGGED BY S. Laing

CHECKED BY J.T. McGinnis

GROUND WATER LEVEL:

NOTES Boring offset about 6.5 feet to SW of staked location.

▼ AT END OF DRILLING 7.8ft / Elev 1074.2ft

ELEV (ft)	DEPTH (ft)	SAMPLE TYPE NUMBER	RECOVERY % (RQD)	BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	GRAPHIC LOG	MATERIAL DESCRIPTION	MOISTURE CONTENT (%)	ATTERBERG LIMITS		FINES CONTENT (%)	REMARKS
									LIQUID LIMIT	PLASTICITY INDEX		
	0											
1080		SPT 1	50	1-1-1-2 (2)			TOPSOIL: Silty SAND (SM), trace organics, moderate brown, moist, very loose, fine grained sand					Infiltration test casing installed in an adjacent borehole to a depth of approximately 4 feet. A bulk sample was obtained from 1 to 6 feet. w% = 10.8% LL = NP; PI = NP % fines = 33.4% Resistivity = 1,500 ohm-cm pH = 5.9 The ESHWT is at an approximate depth of 4 feet
		SPT 2	46	7-5-9-9 (14)			CHANNEL DEPOSITS: Silty SAND with gravel (SM), moderate yellowish brown, wet, medium dense, coarse grained gravel, fine grained sand, subangular - cobbles encountered at 3 feet					
5		SPT 3	25	8-8-9-10 (17)			Sandy SILT (ML), little fine gravel, moderate yellowish brown, wet, very stiff, fine grained sand, subangular, laminations of oxidation	15.0			59.5	
1075		SPT 4	54	12-14-11-16 (25)			Poorly Graded SAND with silt and gravel (SP-SM), moderate yellowish brown, wet, medium dense, fine grained gravel, fine to medium grained sand, subangular ▼					

Bottom of Borehole at 8.0 feet

Appendix B

Laboratory Test Results



SUMMARY OF LAB TESTING RESULTS
NORTHERN PASS TRANSMISSION LINE PROJECT
TRANSITION STATION #5
PROJECT NO.: 16004

SAMPLE INFORMATION			LAB TEST RESULTS																
BOREHOLE No.	FIELD SAMPLE ID	DEPTH (ft)	MOISTURE CONTENT (ASTM D2216) (%)	ORGANIC CONTENT OF SOIL (ASTM D2794) (%)	Sieve Analysis (ASTM D422)				% PASSING NO. 200 SEIVE (ASTM D1140)	ATTERBERG LIMITS (ASTM D4318)			MODIFIED PROCTOR (ASTM D1557)		UNCONFINED COMPRESSIVE STRENGTH OF ROCK (ASTM D7102) (psi)	SOIL CHEMISTRY			
					% Gravel	% Sand	% Silt	% Clay		LL	PL	PI	Max. Dry Density (pcf)	Optimum Moisture Content (%)		SO ₄ (ASTM D516)	CHLORIDE (ASTM D512)	pH (ASTM G51)	RESISTIVITY (AASHTO T288) (ohm-cm)
BH 801	S3	4-6							43.7										
BH 801	S4	6-8	5.2																
BH 801	S6	15-17	10.7																
BH 802	S2	2-4	6.9						26.4										
BH 802	S3	4-6	7.5																
BH 803	S2	2-4	12.7																
BH 803	S4	6-8	15.9						58.8										
BH 804	S3	4-6	27.3						94.6										
BH 805	S2	2-4	15.3																
BH 805	S4	6-8	10.1						45.8										
BH 805	S7	25-27	9.7																
BH 806	S2	2-4	10.0						37.9										
BH 806	S4	6-8	10.8																
BH 806	S6	15-17	10.2						49.9										
BH 806	S8	25-27	9.6																
INF 801	S3	4-6	13.7		4.0	30.6	34.1	31.3											
INF 802	BULK	1-6	10.8						33.4	NP	NP	NP	130.6 ^C	8.7 ^C		< 6.3 ^A	140.0 ^A	5.9 ^A	1,500 ^A
INF 802	S3	4-6	15.0		3.4	37.2	47.9	11.6											

NOTES:
General - Testing performed by S.W. Cole unless otherwise noted.
A - Testing performed by Absolute Resource Associates as a subcontractor to S.W. Cole.
B - Testing performed by GeoTesting.
C - Reported maximum dry density and optimum moisture based on corrected values.

**Report of Moisture Content
of Soil and Rock**

ASTM D2216-10

Project Name: Northern Pass
Project Location: Various, NH
Client: Quanta Subsurface
Material Description: Various
Material Source: Transition Station #5

Project Number: 16-0600
Lab ID: Multiple
Date Received: 11/22/16
Date Completed: 11/28/16
Tested By: MRB

Lab ID	Nominal Maximum Aggregate Size	Material Description	Moisture Content
1641M	3/8"	BH-801, S4, 6'-8'	5.2%
1642M	3/8"	BH-801, S6, 15'-17'	10.7%
1643M	3/8"	BH-802, S2, 2'-4'	6.9%
1644M	3/8"	BH-802, S3, 4'-6'	7.5%
1645M	3/8"	BH-803, S2, 2'-4'	12.7%
1646M	3/8"	BH-803, S4, 6'-8'	15.9%
1647M	3/8"	BH-804, S3, 4'-6'	27.3%
1648M	3/8"	BH-805, S2, 2'-4'	15.3%
1649M	3/8"	BH-805, S4, 6'-8'	10.1%
1650M	3/8"	BH-805, S7, 25'-27'	9.7%

Comments:

Reviewed By: CBM

**Report of Moisture Content
of Soil and Rock**

ASTM D2216-10

Project Name: Northern Pass
Project Location: Various, NH
Client: Quanta Subsurface
Material Description: Various, NH
Material Source: Transition Station #5

Project Number: 16-0600
Lab ID: Multiple
Date Received: 11/22/16
Date Completed: 11/28/16
Tested By: MRB

Lab ID	Nominal Maximum Aggregate Size	Material Description	Moisture Content
1651M	3/8"	B-806, S2, 2'-4'	10.0%
1652M	3/8"	B-806, S4, 6'-8'	10.8%
1653M	3/8"	B-806, S6, 15-17'	10.2%
1654M	3/8"	B806, S8, 25'-27'	9.6%
1655M	3/8"	INF-801, S3, 4'-6'	13.7%
1657M	3/8"	INF-802, S3, 4'-6'	15.0%
1656M	3/8"	INF-802, BULK 1'-6'	10.8%

Comments:

Reviewed By: CBM



Percent Finer than No. 200 ASTM D1140

Project Number: 16-0600
Project Name: Northern Pass Transmission - Transition Station #5

Sample ID: 1643M
Sample Source: BH-802, S-2, 2'-4'
Client Sample Description: SM

% Passing # 200: 26.4

Sample ID: 1646M
Sample Source: BH-803, S4, 6'-8'
Client Sample Description: ML

% Passing # 200: 58.8

Sample ID: 1647M
Sample Source: BH-804, S3, 4'-6'
Client Sample Description: ML

% Passing # 200: 94.6

Sample ID: 1649M
Sample Source: BH-805, S4, 6'-8'
Client Sample Description: SM

% Passing # 200: 45.8

Sample ID: 1651M
Sample Source: BH-806, S2, 2'-4'
Client Sample Description: SM

% Passing # 200: 37.9



Percent Finer than No. 200 ASTM D1140

Project Number: 16-0600
Project Name: Northern Pass Transmission - Transition Station #5

Sample ID: 15371
Sample Source: BH-801, S3, 4-6'
Client Sample Description: SM

% Passing # 200: 43.7

Sample ID: 1653M
Sample Source: BH-806, S6, 15'-17'
Client Sample Description: SM

% Passing # 200: 49.9

Sample ID: 1656M
Sample Source: INF-802, BULK, 1'-6'
Client Sample Description: ML

% Passing # 200: 33.4


Report of Hydrometer

ASTM D422-63 (07)

Project Name: Northern Pass
Project Location: Transition Station #5
Client: Quanta Subsurface
Material Description: ML
Material Source: INF-801, S3, 4'-6'

Project Number: 16-0600
Lab ID: 1655M
Date Received: 11/22/2016
Date Completed: 11/29/2016
Tested By: CRW

Sieve Analysis				Hydrometer Analysis		
Sieve Size	Standard Designation (mm)	Amount Passing (%)	Specification (name)	Particle Size (mm)	Amount	Passing (%)
3"	76	100		0.05092	60.3	
2"	50	100		0.03752	56.7	
1½"	38.1	100		0.02739	52.9	
1"	25	100		0.02739	52.9	
¾"	19	100		0.01996	49.1	
½"	12.5	100		0.01475	44.2	
¼"	6.3	97		0.01111	40.9	
No. 4	4.75	96		0.00805	36.2	
No. 10	2	88		0.00575	34.4	
No. 20	0.85	84		0.00427	27.2	
No. 40	0.425	81		0.00312	22.4	
No. 60	0.25	77		0.00225	19.6	
No. 100	0.15	73		0.00130	15.6	
No. 200	0.075	65.4				



Particle Distribution: Gravel (3" - No. 4) **4.0%** Fines (0.074 - 0.005) **34.1%**
 Sand (No. 4 - No. 200) **30.6%** Clay (<0.005) **31.3%**

Comments:

CBM

Reviewed By

13 Delta Drive, Unit 8, Londonderry, NH 03053 • P: (603) 716.2111 • F: (603) 716.2112 • E: infomanchester@swcole.com


Report of Hydrometer

ASTM D422-63 (07)

Project Name: Northern Pass
Project Location: Transition Station #5
Client: Quanta Subsurface
Material Description: ML
Material Source: INF-802, S3, 4'-6'

Project Number: 16-0600
Lab ID: 1657M
Date Received: 11/22/2016
Date Completed: 11/29/2016
Tested By: CRW

Sieve Analysis				Hydrometer Analysis		
Sieve Size	Standard Designation (mm)	Amount Passing (%)	Specification (name)	Particle Size (mm)	Amount	Passing (%)
3"	76	100		0.05995		50.0
2"	50	100		0.04410		44.0
1½"	38.1	100		0.03192		40.1
1"	25	100		0.03192		40.1
¾"	19	100		0.02338		32.8
½"	12.5	100		0.01688		29.0
¼"	6.3	99		0.01262		23.4
No. 4	4.75	97		0.00920		18.2
No. 10	2	91		0.00655		15.2
No. 20	0.85	86		0.00471		10.7
No. 40	0.425	81		0.00340		8.2
No. 60	0.25	77		0.00241		6.2
No. 100	0.15	72		0.00136		5.4
No. 200	0.075	59.5				



Particle Distribution: Gravel (3" - No. 4) **3.4%** Fines (0.074 - 0.005) **47.9%**
 Sand (No. 4 - No. 200) **37.2%** Clay (<0.005) **11.6%**

Comments:

CBM

Reviewed By

13 Delta Drive, Unit 8, Londonderry, NH 03053 • P: (603) 716.2111 • F: (603) 716.2112 • E: infomanchester@swcole.com

Report of Moisture-Density

Method ASTM D-1557 MODIFIED

Procedure A

 Project Name VARIOUS NH - NORTHERN PASS TRANSMISSION LINE -
 LABORATORY TESTING SERVICES

Project Number 16-0600

Client SWCOLE EXPLORATIONS, LLC

Lab ID 1656M

Material Type ML


Date Received 11/22/2016

Material Source INF-802, BULK, 1'-6'

Date Completed 12/2/2016

Tested By MARK BENNETT

Moisture-Density Relationship Curve




Maximum Dry Density (pcf) 129.5

Optimum Moisture Content (%) 9

Percent Oversized 4.7%

Corrected Dry Density (pcf) **130.6**
Corrected Moisture Content (%) **8.7**

Comments

 CBM



Report of Atterberg Limits

ASTM D4318-10 - Method A

Project Name: Northern Pass Transmission Line
Project Location: Various, NH
Client: SWCOLE Explorations, LLC
Material Description: ML
Material Source: INF-802, BULK, 1-6'


Project Number: 16-0600
Lab ID: 15372S
Date Received: 11/22/16
Date Completed: 12/12/16
Tested By: BLG

Liquid Limit

Plastic Limit

Plasticity Index

Non-Plastic



Material Retained On the No. 40 Sieve: N/A

As-received Moisture Content: N/A

Comments:

Reviewed By: CBM



Report of Soil Resistivity


AASHTO T288

Project Name: Northern Pass Transmission Line
Project Location: Various, NH
Client: SWCOLE Explorations, LLC
Material Description: ML
Material Source: INF-802, BULK, 1-6'

Project Number: 16-0600
Lab ID: 15372S
Date Received: 11/22/16
Date Completed: 12/12/16
Tested By: BLG

Minimum Soil Resistivity 1,500 ohm-cm

Soil Temperature 20.5 °C



Comments:

Reviewed By: CBM

Laboratory Report



Absolute Resource *associates*

124 Heritage Avenue Portsmouth NH 03801

Chad Michaud
S.W. Cole Engineering Inc.
10 Centre Road
Somersworth, NH 03878-2926

PO Number: None
Job ID: 38616
Date Received: 11/22/16

Project: None

Attached please find results for the analysis of the samples received on the date referenced above.

Unless otherwise noted in the attached report, the analyses performed met the requirements of Absolute Resource Associates' Quality Assurance Plan. The Standard Operating Procedures are based upon USEPA SW-846, USEPA Methods for Chemical Analysis of Water and Wastewater, Standard Methods for the Examination of Water and Wastewater and other recognized methodologies. The results contained in this report pertain only to the samples as indicated on the chain of custody.

Absolute Resource Associates maintains certification with the agencies listed below.

We appreciate the opportunity to provide laboratory services. If you have any questions regarding the enclosed report, please contact the laboratory and we will be glad to assist you.

Sincerely,
Absolute Resource Associates

A handwritten signature in black ink, appearing to read "Sue Sylvester (for)".

Sue Sylvester
Principal, General Manager

Date of Approval: 12/8/2016
Total number of pages: 3

Absolute Resource Associates Certifications

New Hampshire 1732
Maine NH903

Massachusetts M-NH902

Project ID: None
Job ID: 38616

Sample#: 38616-002
Sample ID: INF-802, Bulk, 1-6'
Matrix: Solid Percent Dry: 79.5% Results expressed on a dry weight basis.
Sampled: 11/22/16 9:30

Parameter	Result	Reporting Limit	Units	Instr Dil'n Factor	Analyst	Prep Date	Batch	Analysis Date	Time	Reference
Chloride	140	6.3	ug/g	1	JZL		1603363	12/2/16	18:29	E300.0A
Sulfate	< 6.3	6.3	ug/g	1	JZL		1603363	12/2/16	18:29	E300.0A
pH	5.9		pH	1	APA		1603274	11/29/16	4:40	SW9045C

[illegible]

Appendix C

Infiltration Field Test Results



FIELD INFILTRATION TEST RESULTS

Project Name: Northern Pass TL - Transition Station #5
 Project Number: 16004
 Client: PAR Electrical Contractors
 Test Location: Infiltration Boring INF 801

Test Date: 11/19-11/20/2016
 Tested By: L. Gschwind
 Reviewed By: J.T. McGinnis

FIELD TEST DATA

Run #1	Date: 11/19 Time: 07:41	Run #2	Date: 11/19 Time: 08:45	Run #3	Date: 11/20 Time: 12:45	Run #4	Date: 11/20 Time: 13:50
Time Elapsed (min)	Depth to Water (ft)	Time Elapsed (min)	Depth to Water (ft)	Time Elapsed (min)	Depth to Water (ft)	Time Elapsed (min)	Depth to Water (ft)
0	0.76	0	0.76	0	0.77	0	0.77
1	0.76	1	0.76	1	0.77	1	0.77
2	0.76	2	0.76	2	0.77	2	0.77
3	0.76	3	0.76	3		3	
4	0.76	4	0.76	4		4	
5	0.76	5	0.76	5		5	
6	0.76	6		6		6	
7	0.76	7		7		7	
8	0.76	8		8		8	
9	0.76	9		9		9	
10	0.76	10		10		10	
15	0.76	15	0.76	15		15	
20	0.76	20		20		20	
25	0.76	25		25		25	
30	0.76	30	0.76	30	0.77	30	0.77
45	0.76	45		45		45	
60	0.76	60	0.76	60	0.77	60	0.77
(ft/hr)	0.00	(ft/hr)	0.00	(ft/hr)	0.00	(ft/hr)	0.00
(in/hr)	0.00	(in/hr)	0.00	(in/hr)	0.00	(in/hr)	0.00

TEST SUMMARY

Average Infiltration Rate (in/hr)	0.00
Pre-Soak Performed on 11/18/2016 at 09:31	
Hole Depth from Top of Casing (ft)	7.6
Casing Stickup from Ground Surface (ft)	1.6
Pre-Infiltration Test Water Depth from Top of Casing (ft)	2.7 (See Notes 3 and 4 below)

Notes:

- 1) Testing was performed in accordance with guidelines presented in the New Hampshire Stormwater Manual (Vol 2; Table 2-3).
- 2) The Average Infiltration Rate (in/hr) presented is based on field measurements obtained; a safety factor has not been applied.
- 3) The high water level measurement resulted from the drill crew flushing hole out immediately following casing installation; see the INF 801 boring log for the appropriate groundwater level.
- 4) Surface water was running adjacent to test hole casing.



FIELD INFILTRATION TEST RESULTS

Project Name: Northern Pass TL - Transition Station #5
 Project Number: 16004
 Client: PAR Electrical Contractors
 Test Location: Infiltration Boring INF 802

Test Date: 11/19-11/20/2016
 Tested By: L. Gschwind
 Reviewed By: J.T. McGinnis

FIELD TEST DATA

Run #1	Date: 11/19 Time: 07:41	Run #2	Date: 11/19 Time: 08:45	Run #3	Date: 11/20 Time: 12:45	Run #4	Date: 11/20 Time: 13:50
Time Elapsed (min)	Depth to Water (ft)	Time Elapsed (min)		Time Elapsed (min)	Depth to Water (ft)	Time Elapsed (min)	Depth to Water (ft)
0	0.08	0	0.08	0	.10	0	.10
1	0.08	1	0.08	1	.10	1	.10
2	0.08	2	0.08	2	.10	2	.10
3	0.08	3	0.08	3		3	
4	0.08	4	0.08	4		4	
5	0.08	5	0.08	5		5	
6	0.08	6		6		6	
7	0.08	7		7		7	
8	0.08	8		8		8	
9	0.08	9		9		9	
10	0.08	10		10		10	
15	0.08	15	0.08	15		15	
20	0.08	20		20		20	
25	0.08	25		25		25	
30	0.08	30	0.08	30	.10	30	.10
45	0.08	45	0.08	45	.10	45	
60	0.08	60	0.08	60	.10	60	.10
(ft/hr)	0.00	(ft/hr)	0.00	(ft/hr)	0.00	(ft/hr)	0.00
(in/hr)	0.00	(in/hr)	0.00	(in/hr)	0.00	(in/hr)	0.00

TEST SUMMARY

Average Infiltration Rate (in/hr)	0.00
Pre-Soak Performed on 11/18/2016 at 09:31	
Hole Depth from Top of Casing (ft)	5.4
Casing Stickup from Ground Surface (ft)	1.4
Pre-Infiltration Test Water Depth from Top of Casing (ft)	0.1 (See Note 3 below)

Notes:

- 1) Testing was performed in accordance with guidelines presented in the New Hampshire Stormwater Manual (Vol 2; Table 2-3).
- 2) The Average Infiltration Rate (in/hr) presented is based on field measurements obtained; a safety factor has not been applied.
- 3) The high water level measurement resulted from the drill crew flushing hole out immediately following casing installation; see the INF 802 boring log for the appropriate groundwater level.

Appendix D

Summary of Geotechnical Design Parameters

Summary of Geotechnical Design Parameters Transition Station #5

Boring BH 801

Sublayer Description	Sublayer Depth (ft)		Material Description	Average N ₆₀	Effective Unit Weight (pcf)	Soil Friction Angle (deg)	Soil Undrained Strength (psf)	Bedrock (Rock Mass Equivalent Mohr-Coulomb Fit)	
	Top	Bot.						Friction Angle (deg)	Cohesion (psf)
Topsoil	0	2	REMOVE AND REPLACE WITH CONTROLLED STRUCTURAL FILL						
Channel Deposits	2	6	SM	24	120	33	-	-	-
	6	8	SM	84	135	42	-	-	-
Till	8	13	SM	100+	140	43	-	-	-
	13	51	SM	100+	78	43	-	-	-

Boring BH 802

Sublayer Description	Sublayer Depth (ft)		Material Description	Average N ₆₀	Effective Unit Weight (pcf)	Soil Friction Angle (deg)	Soil Undrained Strength (psf)	Bedrock (Rock Mass Equivalent Mohr-Coulomb Fit)	
	Top	Bot.						Friction Angle (deg)	Cohesion (psf)
Topsoil	0	2	REMOVE AND REPLACE WITH CONTROLLED STRUCTURAL FILL						
Channel Deposits	2	6	SM	25	120	33	-	-	-
Till	6	12	SM	100+	140	43	-	-	-
	12	13	SM	100+	78	43	-	-	-

Boring BH 803

Sublayer Description	Sublayer Depth (ft)		Material Description	Average N ₆₀	Effective Unit Weight (pcf)	Soil Friction Angle (deg)	Soil Undrained Strength (psf)	Bedrock (Rock Mass Equivalent Mohr-Coulomb Fit)	
	Top	Bot.						Friction Angle (deg)	Cohesion (psf)
Topsoil	0	2	REMOVE AND REPLACE WITH CONTROLLED STRUCTURAL FILL						
Channel Deposits	2	6	SM	30	63	35	-	-	-
	6	8	ML	19	53	29	-	-	-
	8	25	SM	44	63	37	-	-	-
Till	25	50	SM	100+	78	43	-	-	-

Summary of Geotechnical Design Parameters (cont)

Transition Station #5

Boring BH 804

Sublayer Description	Sublayer Depth (ft)		Material Description	Average N ₆₀	Effective Unit Weight (pcf)	Soil Friction Angle (deg)	Soil Undrained Strength (psf)	Bedrock (Rock Mass Equivalent Mohr-Coulomb Fit)	
	Top	Bot.						Friction Angle (deg)	Cohesion (psf)
Topsoil	0	2	REMOVE AND REPLACE WITH CONTROLLED STRUCTURAL FILL						
Channel Deposits	2	4	SM	38	63	36	-	-	-
	4	6	ML	15	48	28	-	-	-
	6	8	SM	70	73	42	-	-	-
Till	8	52	SM/SP-SM	100+	78	43	-	-	-

Boring BH 805

Sublayer Description	Sublayer Depth (ft)		Material Description	Average N ₆₀	Effective Unit Weight (pcf)	Soil Friction Angle (deg)	Soil Undrained Strength (psf)	Bedrock (Rock Mass Equivalent Mohr-Coulomb Fit)	
	Top	Bot.						Friction Angle (deg)	Cohesion (psf)
Topsoil	0	1	REMOVE AND REPLACE WITH CONTROLLED STRUCTURAL FILL						
Channel Deposits	1	2							
	2	6	SP-SM/SM	36	63	36	-	-	-
	6	13	SM	52	68	38	-	-	-
Till	13	33	SM	85	73	42	-	-	-
	33	51	SM	100+	78	43	-	-	-

Boring BH 806

Sublayer Description	Sublayer Depth (ft)		Material Description	Average N ₆₀	Effective Unit Weight (pcf)	Soil Friction Angle (deg)	Soil Undrained Strength (psf)	Bedrock (Rock Mass Equivalent Mohr-Coulomb Fit)	
	Top	Bot.						Friction Angle (deg)	Cohesion (psf)
Topsoil	0	1	REMOVE AND REPLACE WITH CONTROLLED STRUCTURAL FILL						
Channel Deposits	1	2							
	2	6	SM	53	68	39	-	-	-
	6	18	SM	100+	78	43	-	-	-
Till	18	30	SM	52	68	38	-	-	-
	35	51	SM	95	78	43	-	-	-

Summary of Geotechnical Design Parameters (cont)
Transition Station #5

Controlled Structural Fill

Sublayer Description	Sublayer Depth (ft)		Material Description	Average N ₆₀	Effective Unit Weight (pcf)	Friction Angle (deg)	Undrained Strength (psf)	Bedrock (Rock Mass Equivalent Mohr-Coulomb Fit)	
	Top	Bot.						Friction Angle (deg)	Cohesion (psf)
Structural Fill	-	-	SM/ML	-	125	30	-	-	-

APPENDIX I – WETLAND DELINEATION REPORT (BY OTHERS)

WETLANDS REPORT INFORMATION INCLUDED UNDER SEPARATE COVER

APPENDIX J – POLLUTANT LOADING CALCULATIONS

Condition	Point of Analysis (PoA) Number	Sub-Area Number	Area Description	Land Use	BMP	Is the Impervious Area Disconnected in accordance with Chapter 6, Volume 1 of the NH Stormwater Manual or is the BMP an Infiltration BMP designed in accordance with Alteration of Terrain regulations (Env-Wq 1500)?	Pervious Undisturbed (i.e, forest, meadow, etc.)	Pervious Disturbed (i.e. lawn or other area that will be fertilized regularly)	Pervious Pavement that filters and infiltrates all stormwater (no underdrains)	Pervious Disturbed Other	Description of Pervious Disturbed Other	Pervious Total	Pervious Pavement that filters but does not infiltrate all stormwater (has underdrains)	Impervious Roof	Impervious Road	Impervious Parking and Drives	Impervious Sidewalks	Impervious Surface Water	Impervious Other	Description of Impervious Other	Impervious Total (prior to Disconnection or Infiltration BMP Credit)	Total Area	Composite % Impervious (without disconnection or Infiltration credit)	Composite % Impervious (with disconnection or Infiltration credit)
							Acres	Acres	Acres	Acres		Acres	Acres	Acres	Acres	Acres	Acres	Acres	Acres		Acres	Acres		
Pre-Development	Pre-1	Pre-1	Pre-Dev Watershed Map Area 1	Residential (general)		NO	0.33	0.63	0.00	0.00		0.96	0.00	0.06	0.13	0.07	0.00	0.00	0.02	shed, walk, wall, pad	0.27	1.23	22.01%	22.01%
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00		
Pre-Development						NO	0.00	0.00	0.00	0.00														

Condition	Point of Analysis (PoA) Number	Sub-Area Number	Area Description	Land Use	BMP	Is the Impervious Area Disconnected in accordance with Chapter 6, Volume 1 of the NH Stormwater Manual or is the BMP an Infiltration BMP designed in accordance with Alteration of Terrain regulations (Env-Wq 1500)?	Pervious Undisturbed (i.e., forest, meadow, etc.)	Pervious Disturbed (i.e. lawn or other area that will be fertilized annually)	Pervious Pavement that filters and infiltrates all stormwater (no underdrains)	Pervious Disturbed Other	Description of Pervious Disturbed Other	Pervious Total	Pervious Pavement that filters but does not infiltrate all stormwater (has underdrains)	Impervious Roof	Impervious Road	Impervious Parking and Drives	Impervious Sidewalks	Impervious Surface Water	Impervious Other	Description of Impervious Other	Impervious Total (Prior to Disconnection or Infiltration BMP Credit)	Total Area	Composite % Impervious (without disconnection or Infiltration credit)	Composite % Impervious (with disconnection or Infiltration credit)	Percent that is Pervious Disturbed (i.e. lawn or other area that will be fertilized annually)
							Acres	Acres	Acres	Acres		Acres	Acres	Acres	Acres	Acres	Acres	Acres	Acres		Acres	Acres			%
Post-Development	Post-1	Post-1	Post-Dev Watershed Map Area 1	Residential (general)	Underground Sand Filter with Underdrain	NO	0.00	0.00	0.55	0.08	grass, not fertilized	0.64	0.00	0.01	0.02	0.00	0.00	0.00	0.02	Retaining Wall	0.05	0.68	7.02%	7.02%	0.0%
Post-Development	Post-2	Post-2	Post-Dev Watershed Map Area 2	Residential (general)		NO	0.07	0.00	0.02	0.24	grass, not fertilized	0.33	0.00	0.00	0.17	0.00	0.00	0.05	0.00		0.22	0.55	40.00%	40.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00	0.00	100.00%	100.00%	0.0%
Post-Development						NO	0.00	0.00	0.0																

Date (MM/DD/YYYY):
Project Name:
Town/City:
Impacted Surface Waters:
Applicant:
DES File #:

1/12/2017

Bethlehem Substation

Bethlehem, Grafton County

Bakers Brook/Upper Connecticut River

Northern Pass Transmission, LLC.

Average Annual Precipitation P
Fraction of Annual Runoff events that produce runoff

45.90
0.90

inches
(usually 0.9)

ONLY INPUT VALUES IN BLUE SHADED CELLS

Credit for Using Low Nutrient Fertilizer: If there are managed turf areas under post development conditions that are to be fertilized annually, reductions in post development nutrient (TP and TN) loadings can be realized by by providing enforceable documents (i.e., deed restrictions) requiring land owners to use low nutrient fertilizer. To get low nutrient fertilizer pollutant reductions input the proposed reduced fertilizer application rates for post development development for TP and TN in the table below. Low nutrient fertilizers must have application rates less than the standard fertilizer application rate shown in the table. Then input the percent of each land use in each post development sub-area that is managed turf that is fertilized annually.

Fertilizer Reduction Calculator	
TP	TN
15.0	150.0
0.0	44.0
100.0%	70.7%
50%	50%
10%	10%
5.0%	3.5%
0.11	1.74

Used to reduce EMCs for Post TP and Post TN for each land use in each Sub Area depending on percent of area that is managed turf that is fertilized annually

PRE-DEVELOPMENT CONDITIONS

	Area	Impervious Area
Total Area (All Sub-Areas) (acres)	1.23	0.27

POST-DEVELOPMENT CONDITIONS

	Area	Impervious Area	Area Fertilized Annually
	1.23	0.27	0.00

Insert information for 1st sub-area below

Sub_Area_ID
Point of Analysis (PoA) Number
Total Area for Sub-Area (acres)

Pre-1
Pre-1
1.23

0.27

Sub_Area_ID
Point of Analysis (PoA) Number
Total Area in Sub-Area (acres)

Post-1
Post-1
0.68

0.05

0.00

Land Use	Area	Ia
	(acres)	(% Impervious)
From HWG		
Residential Roof	0.00	0.00%
Commercial Roof	0.00	0.00%
Commercial/Res Parking	0.00	0.00%
Residential Street	0.00	0.00%
Urban Highway	0.00	0.00%
Lawns	0.00	0.00%
Driveway	0.00	0.00%
Residential (general)	1.23	22.01%
Commercial (general)	0.00	0.00%
Industrial (general)	0.00	0.00%
From CDM		
Agriculture and Pasture	0.00	0.00%
Commercial	0.00	0.00%
Forest/Rural Open	0.00	0.00%
Highway	0.00	0.00%
Industrial	0.00	0.00%
Medium Density Residential	0.00	0.00%
Urban Open	0.00	0.00%
Water/Wetland	0.00	0.00%

Land Use	Total Area for each Land Use	Ia	Percent of Area that is managed turf (i.e., fertilized annually)	Post-TP EMC	Post-TN EMC
	(acres)	(% Impervious)	%	mg/L	mg/L
From HWG					
Residential Roof	0.00	0.00%	0.0%	0.11	1.50
Commercial Roof	0.00	0.00%	0.0%	0.14	2.10
Commercial/Res Parking	0.00	0.00%	0.0%	0.15	1.90
Residential Street	0.00	0.00%	0.0%	0.55	1.40
Urban Highway	0.00	0.00%	0.0%	0.32	3.00
Lawns	0.00	0.00%	0.0%	2.10	9.10
Driveway	0.00	0.00%	0.0%	0.56	2.10
Residential (general)	0.68	7.02%	0.0%	0.40	2.20
Commercial (general)	0.00	0.00%	0.0%	0.20	2.00
Industrial (general)	0.00	0.00%	0.0%	0.40	2.50
From CDM					
Agriculture and Pasture	0.00	0.00%	0.0%	0.37	5.98
Commercial	0.00	0.00%	0.0%	0.33	2.97
Forest/Rural Open	0.00	0.00%	0.0%	0.11	1.74
Highway	0.00	0.00%	0.0%	0.43	2.65
Industrial	0.00	0.00%	0.0%	0.32	3.97
Medium Density Residential	0.00	0.00%	0.0%	0.52	5.15
Urban Open	0.00	0.00%	0.0%	0.11	1.74
Water/Wetland	0.00	0.00%	0.0%	0.08	1.38

Insert information for 2nd sub-area below									
Sub_Area_ID			Sub_Area_ID	Post-2					
Point of Analysis (PoA) Number			Point of Analysis (PoA) Number	Post-2					
Total Area for Sub-Area (acres)	0.00	0.00	Total Area in Sub-Area (acres)	0.55	0.22	0.00			
						Percent of Area that is managed turf (i.e., fertilized annually)	Post-TP EMC	Post-TN EMC	
Land Use	Area (acres)	Ia (% Impervious)	Land Use	Area (acres)	Ia (% Impervious)	%	mg/L	mg/L	
From HWG			From HWG						
Residential Roof	0.00	0.00%	Residential Roof	0.00	0.00%	0.0%	0.11	1.50	
Commercial Roof	0.00	0.00%	Commercial Roof	0.00	0.00%	0.0%	0.14	2.10	
Commercial/Res Parking	0.00	0.00%	Commercial/Res Parking	0.00	0.00%	0.0%	0.15	1.90	
Residential Street	0.00	0.00%	Residential Street	0.00	0.00%	0.0%	0.55	1.40	
Urban Highway	0.00	0.00%	Urban Highway	0.00	0.00%	0.0%	0.32	3.00	
Lawns	0.00	0.00%	Lawns	0.00	0.00%	0.0%	2.10	9.10	
Driveway	0.00	0.00%	Driveway	0.00	0.00%	0.0%	0.56	2.10	
Residential (general)	0.00	0.00%	Residential (general)	0.55	40.00%	0.0%	0.40	2.20	
Commercial (general)	0.00	0.00%	Commercial (general)	0.00	0.00%	0.0%	0.20	2.00	
Industrial (general)	0.00	0.00%	Industrial (general)	0.00	0.00%	0.0%	0.40	2.50	
From CDM			From CDM						
Agriculture and Pasture	0.00	0.00%	Agriculture and Pasture	0.00	0.00%	0.0%	0.37	5.98	
Commercial	0.00	0.00%	Commercial	0.00	0.00%	0.0%	0.33	2.97	
Forest/Rural Open	0.00	100.00%	Forest/Rural Open	0.00	0.00%	0.0%	0.11	1.74	
Highway	0.00	0.00%	Highway	0.00	0.00%	0.0%	0.43	2.65	
Industrial	0.00	0.00%	Industrial	0.00	0.00%	0.0%	0.32	3.97	
Medium Density Residential	0.00	0.00%	Medium Density Residential	0.00	0.00%	0.0%	0.52	5.15	
Urban Open	0.00	0.00%	Urban Open	0.00	0.00%	0.0%	0.11	1.74	
Water/Wetland	0.00	0.00%	Water/Wetland	0.00	0.00%	0.0%	0.08	1.38	
Insert information for 3rd sub-area below									
Sub_Area_ID			Sub_Area_ID						
Point of Analysis (PoA) Number	Post--		Point of Analysis (PoA) Number						
Total Area for Sub-Area (acres)	0.00	0.00	Total Area in Sub-Area (acres)	0.00	0.00	0.00			
						Percent of Area that is managed turf (i.e., fertilized annually)	Post-TP EMC	Post-TN EMC	
Land Use	Area (acres)	Ia (% Impervious)	Land Use	Area (acres)	Ia (% Impervious)	%	mg/L	mg/L	
From HWG			From HWG						
Residential Roof	0.00	0.00%	Residential Roof	0.00	0.00%	0.0%	0.11	1.50	
Commercial Roof	0.00	0.00%	Commercial Roof	0.00	0.00%	0.0%	0.14	2.10	
Commercial/Res Parking	0.00	0.00%	Commercial/Res Parking	0.00	0.00%	0.0%	0.15	1.90	
Residential Street	0.00	0.00%	Residential Street	0.00	0.00%	0.0%	0.55	1.40	
Urban Highway	0.00	0.00%	Urban Highway	0.00	0.00%	0.0%	0.32	3.00	
Lawns	0.00	0.00%	Lawns	0.00	0.00%	0.0%	2.10	9.10	
Driveway	0.00	0.00%	Driveway	0.00	0.00%	0.0%	0.56	2.10	
Residential (general)	0.00	0.00%	Residential (general)	0.00	0.00%	0.0%	0.40	2.20	
Commercial (general)	0.00	0.00%	Commercial (general)	0.00	0.00%	0.0%	0.20	2.00	
Industrial (general)	0.00	0.00%	Industrial (general)	0.00	0.00%	0.0%	0.40	2.50	
From CDM			From CDM						
Agriculture and Pasture	0.00	0.00%	Agriculture and Pasture	0.00	0.00%	0.0%	0.37	5.98	
Commercial	0.00	0.00%	Commercial	0.00	0.00%	0.0%	0.33	2.97	
Forest/Rural Open	0.00	0.00%	Forest/Rural Open	0.00	100.00%	0.0%	0.11	1.74	
Highway	0.00	0.00%	Highway	0.00	0.00%	0.0%	0.43	2.65	
Industrial	0.00	0.00%	Industrial	0.00	0.00%	0.0%	0.32	3.97	
Medium Density Residential	0.00	0.00%	Medium Density Residential	0.00	0.00%	0.0%	0.52	5.15	
Urban Open	0.00	0.00%	Urban Open	0.00	0.00%	0.0%	0.11	1.74	
Water/Wetland	0.00	0.00%	Water/Wetland	0.00	0.00%	0.0%	0.08	1.38	

ONLY CHANGE VALUES SHADED IN BLUE

[illegible]

Bethlehem TS#5a Simple Method_01122017.xls
OVERALL SUMMARY

1/12/2017

Date (MM/DD/YYYY): 1/12/2017
Project Name: Bethlehem Substation
Town/City: Bethlehem, Grafton County
Impacted Surface Waters: Bakers Brook/Upper Connecticut River
Applicant: Northern Pass Transmission, LLC.
DES File #:

TOTAL PRE -DEVELOPMENT (PRE-DEV) AREA (ACRES) =	1.23
TOTAL PRE-DEV EFFECTIVE IMPERVIOUS AREA (ACRES) =	0.27
TOTAL PRE-DEV PERCENT EFFECTIVE IMPERVIOUS (%) =	22.0%
TOTAL POST DEVELOPMENT (POST-DEV) AREA (ACRES) =	1.23
TOTAL POST-DEV EFFECTIVE IMPERVIOUS AREA (ACRES) =	0.27
TOTAL POST-DEV PERCENT EFFECTIVE IMPERVIOUS (%) =	21.7%
TOTAL POST-DEV AREA THAT IS FERTILIZED ANNUALLY (ACRES) =	0.00
TOTAL POST-DEV PERCENT OF AREA THAT IS FERTILIZED ANNUALLY (%) =	0.0%

	TSS (LBS/YR)	TP (LBS/YR)	TN (LBS/YR)
PRE DEVELOPMENT LOADS (NO BMPS)	285.2	1.1	6.3
PRE DEVELOPMENT LOADS (WITH BMPS)	285.2	1.1	6.3
PRE DEVELOPMENT LOAD REDUCTION DUE TO BMPS	0.0	0.0	0.0
PROPOSED PERCENT REDUCTION IN FERTILIZER APPLICATION RATE	NA	5.0%	3.5%
POST DEVELOPMENT LOADS (NO BMPS)	282.8	1.1	6.2
POST DEVELOPMENT LOADS (WITH BMPS)	245.9	1.0	6.1
POST DEVELOPMENT LOAD REDUCTION DUE TO BMPS	36.9	0.1	0.2
POST DEVELOPMENT - PRE DEVELOPMENT (SHOULD BE 0 OR NEGATIVE)	-39.2	-0.1	-0.2
% DIFFERENCE FROM PRE DEVELOPMENT LOADS (SHOULD BE 0 OR NEGATIVE)	-13.8%	-9.2%	-3.4%
TOTAL REMOVAL EFFICIENCY NEEDED TO MEET PRE-DEVELOPMENT LOAD	-0.8%	-0.8%	-0.8%

TOTAL POST DEVELOPMENT - PRE DEVELOPMENT (SHOULD BE 0 OR NEGATIVE) (lbs/yr)	-39.2
% DIFFERENCE FROM PRE DEVELOPMENT LOADS (SHOULD BE 0 OR NEGATIVE)	-13.8%
TOTAL REMOVAL EFFICIENCY NEEDED TO MEET PRE-DEVELOPMENT LOAD	-0.8%
CURRENTLY PROPOSED REMOVAL EFFICIENCY	13.0%
REMAINING REMOVAL EFFICIENCY NECESSARY TO MEET PRE-DEVELOPMENT LOAD	-13.9%

[illegible]

TOTAL POST DEVELOPMENT - PRE DEVELOPMENT (SHOULD BE 0 OR NEGATIVE) (lbs/yr)	-39.2
% DIFFERENCE FROM PRE DEVELOPMENT LOADS (SHOULD BE 0 OR NEGATIVE)	-13.8%
TOTAL REMOVAL EFFICIENCY NEEDED TO MEET PRE-DEVELOPMENT LOAD	-0.8%
CURRENTLY PROPOSED REMOVAL EFFICIENCY	13.0%
REMAINING REMOVAL EFFICIENCY NECESSARY TO MEET PRE-DEVELOPMENT LOAD	-13.9%

[illegible]

TOTAL POST DEVELOPMENT - PRE DEVELOPMENT (SHOULD BE 0 OR NEGATIVE) (lbs/yr)	-0.1
% DIFFERENCE FROM PRE DEVELOPMENT LOADS (SHOULD BE 0 OR NEGATIVE)	-9.2%
TOTAL REMOVAL EFFICIENCY NEEDED TO MEET PRE-DEVELOPMENT LOAD	-0.8%
CURRENTLY PROPOSED REMOVAL EFFICIENCY	8.4%
REMAINING REMOVAL EFFICIENCY NECESSARY TO MEET PRE-DEVELOPMENT LOAD	-9.3%

[illegible]

POST-DEVELOPMENT

PRE OR POST - DEV	SUB-AREA	POINT OF ANALYSIS NUMBER	AREA (acres)	Effective Impervious Area (acres)	Area Fertilized Annually (acres)	POLLUTANT	PERCENT REDUCTION IN FERTILIZER APPLICATION RATE	BMPs	LOAD (NO BMPs) (lbs/yr)	LOAD (WITH BMPs) (lbs/yr)	LOAD REDUCTION DUE TO BMPs (lbs/yr)	PERCENT REMOVAL
POST	Post-1	Post-1	0.68	0.05	0.00	TP	5.0%	Underground Sand Filter with Underdrain	0.3	0.2	0.1	33.0%
POST	Post-2	Post-2	0.55	0.22	0.00	TP	5.0%		0.8	0.8	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
POST	0.00		0.00	0.00	0.00	TP	5.0%		0.0	0.0	0.0	0.0%
TOTAL		TOTAL	1.23	0.27	0.00			TOTAL	1.1	1.0	0.1	8.4%

1/12/2017
Bethlehem Substation
Bethlehem, Grafton County
Bakers Brook/Upper Connecticut River
Northern Pass Transmission, LLC.

TOTAL POST DEVELOPMENT - PRE DEVELOPMENT (SHOULD BE 0 OR NEGATIVE) (lbs/yr)	-0.2
% DIFFERENCE FROM PRE DEVELOPMENT LOADS (SHOULD BE 0 OR NEGATIVE)	-3.4%
TOTAL REMOVAL EFFICIENCY NEEDED TO MEET PRE-DEVELOPMENT LOAD	-0.8%
CURRENTLY PROPOSED REMOVAL EFFICIENCY	2.6%
REMAINING REMOVAL EFFICIENCY NECESSARY TO MEET PRE-DEVELOPMENT LOAD	-3.4%

PRE-DEVELOPMENT

[illegible]

1/12/2017
Bethlehem Substation
Bethlehem, Grafton County
Bakers Brook/Upper Connecticut River
Northern Pass Transmission, LLC.

[illegible]

http://ofmpub.epa.gov/waters10/attains_waterbody.control?p_list_id=NHRIV801030403-09&p_report_type=T&p_cycle=2008

Last updated on 9/1/2015



Watershed Assessment, Tracking & Environmental

Results: [EPA Home](#) [Water](#) [WATERS](#) [Water Quality Assessment and TMDL Information](#)
Waterbody Quality Assessment Report

[Return to home page](#)

Features

On This Page

- [Causes of Impairment](#)
- [TMDLs That Apply to This Waterbody](#)
- [Previous Causes of Impairment Now Attaining All Uses](#)

State: [New Hampshire](#)
Waterbody ID: NHRIV801030403-09
Location: 010801030403, Baker Brook, Unknown Fishery
State Waterbody Type: River
EPA Waterbody Type: Rivers and Streams
Water Size: 2.63
Units: miles
Watershed Name: [Waits](#)

[Waterbody History Report](#)

Data are also available for these years: [2010](#) [2006](#) [2004](#) [2002](#)

2008 Waterbody Report for Baker Brook



Click on the waterbody for an interactive map

Click on the waterbody for an interactive map

- [About This Database \(Integrated Report\)](#)
- [Assessing Water Quality \(Questions and Answers\)](#)
- [Integrated Reporting Guidance](#)
- [Previous National Water Quality Reports](#)
- [EnviroMapper for Water](#)
- [AskWATERS](#)
- [EPA WATERS Homepage](#)
- [Exchange Network](#)
- [Assessment Database](#)
- [Statewide Statistical Surveys](#)
- [How's My Waterway Local Search tool](#)
- [Pollution Categories Summary Document](#)
- [Nitrogen and Phosphorus Pollution Data Access Tool \(NPDAT\)](#)

Causes of Impairment for Reporting Year 2008

[Description of this table](#)

Cause of Impairment	Cause of Impairment Group	State TMDL Development Status
Fish Bioassessments	Cause Unknown - Impaired Biota	TMDL needed
Mercury	Mercury	TMDL completed

TMDLs That Apply to this waterbody[Description of this table](#)

TMDL Document Name	TMDL Date	TMDL Pollutant Description	TMDL Pollutant Source Type	Cause(s) of Impairment Addressed
Ne Regional Mercury Tmdl	Dec-20-2007	Mercury	Nonpoint Source	Mercury

Previous Causes of Impairments Now Attaining All Uses

No causes of impairment are recorded as attaining all uses for this waterbody.



Burns & McDonnell
New England Office
108 Leigus Road
Wallingford, CT 06492
Phone: 203-284-8590
Fax: 203-284-3693
www.burnsmcd.com

Burns & McDonnell: Making our clients successful for more than 100 years